Metadata Extraction Report

Generated on: 2025-08-21 12:04:28

Database: `test`

Table of Contents

- Source Metadata
- Source 1: CRM
- Source 2: GA4
- Table Metadata
- Table 1: Packages
- Table 2: Ticket
- Table 3: Contact Types Relationships
- Table 4: Contribution Transaction Link
- Table 5: Promo Quarterly
- Table 6: Appeal Source Structure
- Table 7: dimconstituentsanon
- Table 8: Funds
- Table 9: members
- Table 10: Contribution Output
- Table 11: production season types
- Table 12: Deceased Cont W Last Activity
- Table 13: events
- Table 14: batch summary
- Table 15: Deferrals and Receiveables Not in Model Yet
- Table 16: Ticket Seat ID
- Table 17: users

- Table 18: pseudonymous users
- Column Metadata
- Columns for Packages
- Columns for Funds
- Columns for members
- Columns for Appeal Source Structure
- Columns for Contact Types Relationships
- Columns for Contribution Transaction Link
- Columns for Deferrals and Receiveables Not in Model Yet
- Columns for production season types
- Columns for Ticket Seat ID
- Columns for Contribution Output
- Columns for dimconstituentsanon
- Columns for Ticket
- Columns for Deceased Cont W Last Activity
- Columns for pseudonymous users
- Columns for users
- Columns for events
- Columns for batch summary
- Columns for Promo Quarterly
- Edge Metadata
- Summary

Source Metadata

Total Sources: 2

Source 1: CRM

Field	Value
ID	`s_crm`
Label	CRM
Backend Name	`CRM`
Type	source
Description	Customer Relationship Management (CRM) systems store and manage customer data, interactions, sales pipelines, and support activities to improve business relationships and customer retention.
Embedding Input	CRM source containing customer data, sales interactions, support history, and relationship tracking.
Tables	`contributiontransactionlink`, `promoquarterly`, `_17_18to24_25packagesv2`, `appealsourcestructure05_06_25`, `dimconstituents_anon_`, `productionseason_types`, `batchsummary`, `deferralsandreceiveablesnotinmodelyet`, `ticketf`, `_1824funds`, `_1824members2`, `ticketseatid`, `deceasedcontwlastactivity5_1_25`, `conttypes_afasa1a2relationships`, `contributionoutputv2`

Source 2: GA4

Field	Value
ID	`s_ga4`
Label	GA4
Backend Name	`GA4`
Type	source
Description	Google Analytics is a web analytics service that tracks and reports website traffic, user behavior, conversion rates, and

Field	Value
	marketing campaign performance to help businesses make data-driven decisions.
Embedding Input	Google Analytics source for tracking website traffic, user behavior, conversions, and marketing campaign performance.
Tables	`events`, `users`, `pseudonymous_users`

Table Metadata

Total Tables: 18

Table 1: Packages

Field	Value
ID	`34aff2970f6552ee316eb546c6c258ca`
Label	Packages
Backend Name	`_17_18to24_25packagesv2`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	18
Description	Table containing information about packages associated with orders.
Embedding Input	The Packages table serves as a critical component in the CRM data architecture, encapsulating details about various packages linked to customer orders. It supports business operations by tracking package attributes such as constituent identifiers, campaign details, and pricing categories. This table is integral for decision-

Field	Value
	making processes related to sales and marketing strategies, providing insights into customer engagement through package offerings. The structure includes a primary key on order_id, which uniquely identifies each package entry, while other columns capture essential metadata like campaign_id, appeal_id, and package characteristics. The table is designed to facilitate efficient querying and reporting, with potential relationships to other entities in the CRM ecosystem, ensuring comprehensive data integration and lifecycle management.
Tags	`packages` `orders` `CRM`
Columns	`price_type`, `price_type_category`, `package_size`, `mode_of_sale`, `package_order_date`, `channel`, `section`, `source_id`, `source`, `appeal_id`, `appeal`, `campaign_id`, `campaign`, `package_code`, `package_season`, `order_id`, `const_type`, `constituent_id`
Primary Keys	`order_id`
Foreign Keys	`customer_no`, `promotion_appeal`, `constituent_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'The Packages table references anonymized constituent information to track customer engagement and demographics related to package offerings.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'The Packages table references contributions made by constituents to analyze the impact of package offerings on fundraising efforts.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'The Packages`

Field	Value
	table references promotional campaigns to evaluate the effectiveness of package-related marketing strategies.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'appeal_id', 'relation_description': 'References Promo Quarterly: Links package information to specific promotional appeals for sales analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_id', 'relation_description': 'References Appeal Source Structure: References appeal sources to analyze package offerings linked to specific appeals.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Ticket', 'linking_column': 'order_id', 'relation_description': 'The Ticket table references the Packages table to associate ticket sales with specific package orders.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket Seat ID', 'linking_column': 'order_id', 'relation_description': 'The Ticket Seat ID table references the Packages table to link seat allocations to specific package orders.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'order_id', 'relation_description': 'Referenced by Contribution Transaction Link: Links contribution transactions to package details associated with customer orders.', 'relationship': 'one-to-many'}, {'to_table': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': "Referenced by dimconstituentsanon: The Packages table includes information about packages associated with orders, linking each package to the corresponding constituent's anonymized profile.", 'relationship': 'one-to-many'}, {'to_table': 'production

Field	Value
	season types', 'linking_column': 'order_id', 'relation_description': 'Referenced by production season types: This table contains information about packages associated with orders, which may relate to production seasons for sales analysis.', 'relationship': 'one-to-many'} , {'to_table': 'batch summary', 'linking_column': 'order_id', 'relation_description': 'Referenced by batch summary: Associates packages with batch summaries for order processing insights.', 'relationship': 'one-to-many'} , {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'order_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions associated with specific packages, linking to order details.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'order_id', 'relation_description': 'Referenced by Funds: Links package details to funds for tracking sales and contributions.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'order_id', 'relation_description': 'Referenced by members: Packages purchased by members are linked to their membership records, facilitating sales analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'order_id', 'relation_description': "Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references package information associated with deceased customers' orders.", 'relationship': 'one-to-many'} , {'to_table': 'Contribution Output', 'linking_column': 'order_id', 'relation_description': 'Referenced by

Field	Value
	`Contribution Output: Associates contributions with packages linked to customer orders.', 'relationship': 'one-to-many'}` , `{'to_table': 'events', 'linking_column': 'order_id', 'relation_description': 'Referenced by events: Events may be linked to specific packages associated with orders, connecting event data to sales and marketing strategies.', 'relationship': 'one-to-many'}`

Table 2: Ticket

Field	Value
ID	`f1c790944ccb6fb41f71489900ec4f6d`
Label	Ticket
Backend Name	`ticketf`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	21
Description	Table containing ticket information for events.
Embedding Input	The Ticket table serves as a central repository for managing ticket-related data within the CRM system, capturing essential details about each ticket issued for events. It encompasses various attributes such as constituent identification, order details, campaign information, and payment specifics, thereby supporting critical business operations related to ticket sales, customer engagement, and event management. This table is integral to the organization's data ecosystem,

Field	Value
	facilitating decision-making workflows and analytical requirements by providing insights into sales performance, customer preferences, and event attendance patterns. The table is structured with a primary key on ticket_id, ensuring unique identification of each ticket record. It is designed to accommodate relationships with other entities through foreign keys, enhancing data integrity and relational context. The data lifecycle includes regular updates aligned with ticket sales activities, retention policies to manage historical data, and integration points with upstream systems for data ingestion and downstream systems for reporting and analytics. Key attributes include constituent_id, order_id, campaign_id, appeal_id, source_id, and seat_id, which are pivotal for linking ticket data with other relevant business entities.
Tags	`ticketing` `CRM` `event management`
Columns	`seat_id`, `ticket_id`, `price_type_category`, `section`, `price_type`, `ticket_paid_amount`, `package_code`, `mode_of_sale`, `order_date`, `channel`, `source_id`, `source`, `appeal_id`, `appeal`, `campaign_id`, `campaign`, `production_season`, `season`, `order_id`, `const_type`, `constituent_id`
Primary Keys	`ticket_id`
Foreign Keys	`seat_id`, `order_id`, `membership_id`, `production_season_id`, `constituent_id`, `transaction_id`, `batch_id`, `customer_no`, `promotion_appeal`, `cont_designation_id`, `appeal_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Links ticket information to anonymized constituent data for demographic analysis and engagement tracking.', 'relationship': 'many-to-one'}`, `{'target_table_name':`

Field	Value
	'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Associates ticket sales with contributions made by constituents, facilitating fundraising analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Connects ticket data to specific production seasons, aiding in performance and event management.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Links ticket purchases to deceased customers for historical engagement analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Associates ticket sales with specific appeal campaigns for performance tracking.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Links ticket sales to promotional campaigns for analyzing customer engagement.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'Connects ticket data to customer types for relationship management and targeted marketing.', 'relationship': 'many-to-one'}, {'target_table_name': 'Funds', 'linking_column': 'cont_designation_id', 'relation_description': 'Associates ticket sales with specific funds for financial reporting and analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'batch summary', 'linking_column':

Field	Value
	'batch_id', 'relation_description': 'Links ticket transactions to batch processing for operational oversight.', 'relationship': 'many-to-one'}, {'target_table_name': 'members', 'linking_column': 'membership_id', 'relation_description': 'Connects ticket sales to membership details for analyzing member engagement.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Links ticket information to packages associated with orders for sales analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'ticket_id', 'relation_description': 'References Contribution Transaction Link: References contribution transactions for ticket sales and event management.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'appeal_id', 'relation_description': 'References Promo Quarterly: Associates ticket sales with promotional appeals for event performance analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_id', 'relation_description': 'References Appeal Source Structure: Links ticket sales to appeal sources for understanding sales performance related to fundraising campaigns.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'ticket_id', 'relation_description': 'References production season types: This table contains ticket information that may reference production season types for event categorization.', 'relationship': 'many-to-one'}

Field	Value
Primary Keys Referencing Tables	{'to_table': 'Ticket Seat ID', 'linking_column': 'seat_id', 'relation_description': 'Referenced by ticket data to identify specific seats associated with ticket purchases.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'References ticket transactions for tracking financial operations related to ticket sales.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'Links contribution transactions to ticket sales for comprehensive financial analysis.', 'relationship': 'one-to-many'}, {'to_table': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': "Referenced by dimconstituentsanon: The Ticket table manages ticket-related data, connecting each ticket to the respective constituent's anonymized information.", 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'ticket_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table tracks transactions that may include ticket purchases, linking to ticket details.', 'relationship': 'one-to-many'}, {'to_table': 'Funds', 'linking_column': 'ticket_id', 'relation_description': 'Referenced by Funds: Links ticket sales to specific funds for event-related contributions.', 'relationship': 'one-to-many'}, {'to_table': 'members', 'linking_column': 'ticket_id', 'relation_description': "Referenced by members: Each ticket is associated with a member's purchase or attendance, linking ticket sales to membership details.",

Field	Value
	'relationship': 'one-to-many'}, {'to_table': 'Ticket Seat ID', 'linking_column': 'ticket_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat is associated with a specific ticket for an event.', 'relationship': 'one-to-many'}, {'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'ticket_id', 'relation_description': "Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references ticket information related to deceased customers' event participation.", 'relationship': 'one-to-many'}, {'to_table': 'Contact Types Relationships', 'linking_column': 'ticket_id', 'relation_description': 'Referenced by Contact Types Relationships: This table captures ticket information for events, which may involve customer types defined in the Contact Types Relationships table.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Contribution Output: Associates contributions with ticket purchases made by constituents.', 'relationship': 'one-to-many'}, {'to_table': 'events', 'linking_column': 'ticket_id', 'relation_description': 'Referenced by events: Each event may correspond to a specific ticket issued, linking event data to ticket information for event management.', 'relationship': 'one-to-many'}

Table 3: Contact Types Relationships

Field	Value
ID	`cca1a21794505a661a41bb18a6308170`
Label	Contact Types Relationships
Backend Name	`conttypes_afasa1a2relationships`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	5
Description	This table defines the relationships between different customer types.
Embedding Input	The Contact Types Relationships table serves as a critical component in the CRM data architecture, capturing the various types of relationships that exist between customers. It supports business operations by enabling the identification and categorization of customer interactions, which is essential for targeted marketing, customer service, and relationship management. The table is structured with a primary key 'customer_no' that uniquely identifies each customer, while additional columns provide descriptive attributes of customer types and their relationships. This table is integral for analytical workflows that require insights into customer dynamics and segmentation, facilitating decision-making processes across the organization. Data is sourced from the CRM system, with updates occurring as customer information changes, ensuring that the relationships are current and relevant. The table may also interact with other tables in the CRM ecosystem, providing a comprehensive view of customer relationships and behaviors.

Field	Value
Tags	`customer_relationships` `CRM` `customer_types`
Columns	`relationship_a1_a2_indicator` , `relationship_type` , `relationship_customer__` , `customer_type_desc` , `customer_no`
Primary Keys	`customer_no`
Foreign Keys	`customer_no` , `constituent_id` , `promotion_appeal` , `membership_id` , `ticket_id` , `order_id` , `transaction_id` , `appeal_no` , `production_season_id` , `seat_id` , `user_id` , `batch_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'This table captures ticket information for events, which may involve customer types defined in the Contact Types Relationships table.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'This table records contributions made by constituents, which are likely categorized by customer types in the Contact Types Relationships table.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'This table stores promotional data related to customer engagement, which may be influenced by the relationships defined in the Contact Types Relationships table.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'members', 'linking_column': 'membership_id', 'relation_description': 'This table contains membership details for constituents, which may relate to customer types in the Contact Types Relationships table.', 'relationship':`

Field	Value
	'many-to-one'}, {'target_table_name': 'users', 'linking_column': 'user_id', 'relation_description': 'This table stores user-related data, which may include interactions with different customer types defined in the Contact Types Relationships table.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'This table tracks deceased customers, utilizing the customer_no to reference customer types defined in the Contact Types Relationships table.', 'relationship': 'one-to-many'}, {'to_table': 'Funds', 'linking_column': 'customer_no', 'relation_description': 'This table stores information about funds and their associated transactions, which may relate to customer types in the Contact Types Relationships table.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'This table links contribution transactions to their respective details, potentially referencing customer types in the Contact Types Relationships table.', 'relationship': 'one-to-many'}, {'to_table': 'Promo Quarterly', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Promo Quarterly: Associates promotional data with different customer types for targeted marketing.', 'relationship': 'one-to-many'}, {'to_table': 'Appeal Source Structure', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Appeal Source Structure: Defines relationships between customer types and appeal sources for targeted marketing.', 'relationship': 'one-to-many'}, {'to_table': 'production season

Field	Value
	types', 'linking_column': 'customer_no', 'relation_description': 'Referenced by production season types: This table defines relationships between customer types, which may relate to production seasons for targeted marketing.', 'relationship': 'one-to-many'} , {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include transactions related to different customer types, linking to customer relationships.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Ticket: Connects ticket data to customer types for relationship management and targeted marketing.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'customer_no', 'relation_description': 'Referenced by members: Customer relationships are linked to membership records, enhancing understanding of member interactions.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may relate to different types of customer interactions.', 'relationship': 'one-to-many'} , {'to_table': 'users', 'linking_column': 'customer_no', 'relation_description': 'Referenced by users: The users table references customer types to understand the relationships between different user profiles.', 'relationship': 'one-to-many'}

Table 4: Contribution Transaction Link

Field	Value
ID	`534ead1b0043932ee1ebb401081f334d`
Label	Contribution Transaction Link
Backend Name	`contributiontransactionlink`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	16
Description	Links contribution transactions to their respective details.
Embedding Input	The Contribution Transaction Link table serves as a critical junction in the CRM data architecture, capturing the relationships between various contribution transactions and their associated attributes. This table is essential for tracking financial contributions, enabling detailed analysis of transaction behaviors, and supporting decision-making processes related to fundraising and financial reporting. It includes key identifiers such as transaction_id, which serves as the primary key, and other attributes like contribution_id, batch_id, and campaign_id that link to various entities within the CRM ecosystem. The table is designed to facilitate efficient querying and reporting, with considerations for data integrity and relationship cardinalities with other tables. It supports various business operations by providing insights into transaction types, amounts, and categories, while adhering to data governance policies regarding retention and integration with upstream and downstream systems.
Tags	`contribution` `transaction` `CRM`

Field	Value
Columns	`days_in_date`, `gl_account`, `mode_of_sale_category`, `mode_of_sale`, `sales_channel`, `debit_amount`, `credit_amount`, `transaction_category`, `fund_id`, `campaign_id`, `transaction_type`, `transaction_amount`, `gl_entry_type`, `batch_id`, `transaction_id`, `contribution_id`
Primary Keys	`transaction_id`
Foreign Keys	`constituent_id`, `order_id`, `customer_no`, `appeal_no`, `promotion_appeal`, `batch_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Links contributions to anonymized constituent information for demographic analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'Associates contribution transactions with their respective batch processing records.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'contribution_id', 'relation_description': 'Links contribution transactions to detailed records of contributions made by constituents.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Connects contribution transactions to deceased customer records for historical engagement analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Links contributions to their respective appeal sources for campaign effectiveness tracking.', 'relationship': 'many-to-`

Field	Value
	one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Associates contribution transactions with promotional campaigns for performance evaluation.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Links contribution transactions to package details associated with customer orders.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket', 'linking_column': 'transaction_id', 'relation_description': 'References Ticket: Links contribution transactions to ticket sales for comprehensive financial analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'transaction_id', 'relation_description': 'References Contact Types Relationships: This table links contribution transactions to their respective details, potentially referencing customer types in the Contact Types Relationships table.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'References contribution transactions for tracking pending financial transactions.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'References contribution transactions for ticket sales and event management.', 'relationship': 'one-to-many'}, {'to_table': 'production season types', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by production season types: This table links contribution transactions to details,

Field	Value
	which may relate to production seasons for fundraising analysis.', 'relationship': 'one-to-many'} , {'to_table': 'batch summary', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by batch summary: Connects contribution transactions to batch summaries for detailed financial reporting.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'contribution_id', 'relation_description': 'Referenced by Funds: Links contributions to their respective funds for tracking financial contributions.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by members: Transactions related to contributions are linked to memberships, providing a comprehensive view of financial support.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be linked to contribution transactions.', 'relationship': 'one-to-many'} , {'to_table': 'Contribution Output', 'linking_column': 'contribution_id', 'relation_description': 'Referenced by Contribution Output: Links contribution transactions to their respective details for financial reporting.', 'relationship': 'one-to-many'} , {'to_table': 'pseudonymous users', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by pseudonymous users: This table links contribution transactions to their details, potentially connecting to pseudonymous users through transaction identifiers.', 'relationship': 'one-to-many'}

Table 5: Promo Quarterly

Field	Value
ID	`880c94f9e41c72a127590d7fffdb370d`
Label	Promo Quarterly
Backend Name	`promoquarterly`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	5
Description	Stores quarterly promotional data related to customer engagement.
Embedding Input	The Promo Quarterly table captures essential metrics and attributes associated with promotional campaigns conducted on a quarterly basis. It serves as a critical repository for analyzing customer responses to promotions, tracking the effectiveness of various promotional appeals, and understanding customer behavior over time. This table is integral to the CRM system, supporting decision-making processes related to marketing strategies and customer relationship management. The primary key, promotion_appeal, uniquely identifies each promotional effort, while the nullable columns allow for flexibility in data entry, accommodating various promotional scenarios. The table's structure is designed to facilitate efficient querying and reporting, with potential relationships to customer and promotion-related tables, enhancing the overall analytical capabilities of the CRM ecosystem. Data is sourced from promotional activities and is expected to be updated quarterly, with retention policies aligned with marketing campaign evaluations.

Field	Value
Tags	`promotions` `customer engagement` `quarterly analysis`
Columns	`promotion_source_number`, `promotion_response_date`, `promotion_response`, `promotion_appeal`, `customer_no`
Primary Keys	`promotion_appeal`
Foreign Keys	`customer_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Links promotional data to deceased customers for understanding engagement history.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'Associates promotional data with different customer types for targeted marketing.', 'relationship': 'many-to-one'}`
Primary Keys Referencing Tables	`{'to_table': 'Packages', 'linking_column': 'appeal_id', 'relation_description': 'Links package information to specific promotional appeals for sales analysis.', 'relationship': 'one-to-many'}`, `{'to_table': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Connects appeal sources to promotional campaigns for effectiveness tracking.', 'relationship': 'one-to-many'}`, `{'to_table': 'Ticket', 'linking_column': 'appeal_id', 'relation_description': 'Associates ticket sales with promotional appeals for event performance analysis.', 'relationship': 'one-to-many'}`, `{'to_table': 'Contribution Output', 'linking_column': 'appeal_id', 'relation_description': 'Links`

Field	Value
	contributions to promotional appeals for fundraising effectiveness evaluation.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Contribution Transaction Link: Associates contribution transactions with promotional campaigns for performance evaluation.', 'relationship': 'one-to-many'}, {'to_table': 'Packages', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Packages: The Packages table references promotional campaigns to evaluate the effectiveness of package-related marketing strategies.', 'relationship': 'one-to-many'}, {'to_table': 'Appeal Source Structure', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Appeal Source Structure: Links promotional campaigns to appeal sources for analyzing customer engagement.', 'relationship': 'one-to-many'}, {'to_table': 'production season types', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by production season types: This table stores promotional data, which may relate to production seasons for analyzing customer engagement.', 'relationship': 'one-to-many'}, {'to_table': 'batch summary', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by batch summary: Links promotional campaigns to batch summaries for customer engagement analysis.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include

Field	Value
	transactions related to promotional campaigns, linking to promotional data.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Ticket: Links ticket sales to promotional campaigns for analyzing customer engagement.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Funds: Associates promotional campaigns with specific funds for marketing analysis.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by members: Promotional campaigns are linked to memberships, enabling analysis of member responses to marketing efforts.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be associated with promotional campaigns for ticket sales.', 'relationship': 'one-to-many'} , {'to_table': 'Contact Types Relationships', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Contact Types Relationships: This table stores promotional data related to customer engagement, which may be influenced by the relationships defined in the Contact Types Relationships table.', 'relationship': 'one-to-many'} , {'to_table': 'Contribution Output', 'linking_column': 'promotion_appeal', 'relation_description': 'Referenced by Contribution Output: Associates contributions with quarterly promotional campaigns for marketing analysis.', 'relationship': 'one-to-many'}

Table 6: Appeal Source Structure

Field	Value
ID	`56e84cd62d98d48a23850f5165baf071`
Label	Appeal Source Structure
Backend Name	`appealsourcestructure05_06_25`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	18
Description	Structure representing various sources of appeals.
Embedding Input	The Appeal Source Structure table captures detailed information about different sources related to appeals within the CRM system. It serves as a critical component for tracking and managing appeal campaigns, providing insights into their categorization, descriptions, and associated metadata. This table includes key identifiers such as 'appeal_no' which uniquely identifies each appeal, and various attributes that describe the campaign and source details, including campaign numbers, descriptions, categories, and source-related information. The table supports operational workflows by enabling the organization to analyze appeal sources, track their effectiveness, and make informed decisions based on historical data. It is designed to integrate seamlessly with other tables in the CRM ecosystem, ensuring data consistency and facilitating comprehensive reporting and analytics. The data lifecycle is managed through regular updates and retention policies that align with organizational standards, ensuring data quality and compliance with relevant regulations.
Tags	`appeals` `campaigns` `CRM`

Field	Value
Columns	`num_contacts`, `acq_dt`, `media_type`, `source_hotlist_status`, `source_inactive`, `source_keycode`, `source_provider`, `source_group`, `source_type`, `source_name`, `source_no`, `appeal_category`, `appeal_desc`, `appeal_no`, `fyear`, `campaign_category`, `campaign_desc`, `campaign_no`
Primary Keys	`appeal_no`
Foreign Keys	`customer_no`, `promotion_appeal`, `constituent_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Anonymized constituent information linked to appeal sources for demographic analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Links contributions made by constituents to the appeal sources for fundraising analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'appeal_id', 'relation_description': 'Associates contributions with specific appeal sources for performance tracking.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Links promotional campaigns to appeal sources for analyzing customer engagement.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'Defines relationships between customer types and appeal sources for targeted marketing.',`

Field	Value
	'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'appeal_no', 'relation_description': 'References Promo Quarterly: Connects appeal sources to promotional campaigns for effectiveness tracking.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Packages', 'linking_column': 'appeal_id', 'relation_description': 'References appeal sources to analyze package offerings linked to specific appeals.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'appeal_id', 'relation_description': 'Links ticket sales to appeal sources for understanding sales performance related to fundraising campaigns.', 'relationship': 'one-to-many'}, {'to_table': 'members', 'linking_column': 'appeal_id', 'relation_description': 'Associates membership records with appeal sources for analyzing membership growth driven by appeals.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Contribution Transaction Link: Links contributions to their respective appeal sources for campaign effectiveness tracking.', 'relationship': 'one-to-many'}, {'to_table': 'production season types', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by production season types: This table captures sources of appeals, which may be linked to production seasons for campaign effectiveness analysis.', 'relationship': 'one-to-many'}, {'to_table': 'batch summary', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by batch summary: Associates batch summaries

Field	Value
	with appeal sources for campaign effectiveness tracking.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions related to specific appeals, linking to appeal sources.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Ticket: Associates ticket sales with specific appeal campaigns for performance tracking.', 'relationship': 'one-to-many'}, {'to_table': 'Funds', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Funds: Links appeal sources to funds for tracking fundraising effectiveness.', 'relationship': 'one-to-many'}, {'to_table': 'members', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by members: Memberships are linked to specific appeals, allowing for targeted fundraising efforts based on member data.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket Seat ID', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be linked to specific appeals made to customers.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Output', 'linking_column': 'appeal_no', 'relation_description': 'Referenced by Contribution Output: Links contributions to specific appeal sources for campaign effectiveness analysis.', 'relationship': 'one-to-many'}

Table 7: dimconstituentsanon

Field	Value
ID	`e2d3f32dfb61d34aa3060f6cb4ce6f77`
Label	dimconstituentsanon
Backend Name	`dimconstituents_anon_`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	4
Description	A dimension table containing anonymized constituent information.
Embedding Input	The dimconstituentsanon table serves as a critical component in the CRM data architecture, representing a collection of anonymized constituents that are essential for understanding demographic and engagement patterns within the organization's outreach efforts. This table supports various analytical processes, including segmentation, targeting, and reporting, by providing key attributes related to constituents without revealing personal identifiers. It is structured with a primary key, constituent_id, which uniquely identifies each record, while the table may also include additional attributes such as primary_address_postcode, type, and constituencies to enrich the data context. The table is designed to integrate seamlessly with other data sources, ensuring compliance with privacy regulations while maintaining data integrity and quality. Regular updates are expected to reflect changes in constituent information, and the table is utilized in various reporting and analytical workflows to drive decision-making and strategic initiatives.

Field	Value
Tags	`constituents` `CRM` `anonymized data`
Columns	`constituencies`, `type`, `primary_address_postcode`, `constituent_id`
Primary Keys	`constituent_id`
Foreign Keys	`constituent_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': "The Contribution Output table tracks contributions made by constituents, linking each contribution to the corresponding constituent's anonymized information.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'members', 'linking_column': 'constituent_id', 'relation_description': "The members table contains membership details for constituents, associating each membership with the respective constituent's anonymized data.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'Packages', 'linking_column': 'constituent_id', 'relation_description': "The Packages table includes information about packages associated with orders, linking each package to the corresponding constituent's anonymized profile.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'Ticket', 'linking_column': 'constituent_id', 'relation_description': "The Ticket table manages ticket-related data, connecting each ticket to the respective constituent's anonymized information.", 'relationship': 'many-to-one'}`
Primary Keys Referencing Tables	`{'to_table': 'Contribution Transaction Link', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Contribution Transaction Link: Links`

Field	Value
	contributions to anonymized constituent information for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Packages', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Packages: The Packages table references anonymized constituent information to track customer engagement and demographics related to package offerings.', 'relationship': 'one-to-many'} , {'to_table': 'Appeal Source Structure', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Appeal Source Structure: Anonymized constituent information linked to appeal sources for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'production season types', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by production season types: This table contains anonymized constituent information, which may relate to production season types for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'batch summary', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by batch summary: Links batch summary to anonymized constituent information for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table captures transactions related to constituents, linking to anonymized constituent information.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Ticket: Links ticket information to anonymized constituent data for

Field	Value
	demographic analysis and engagement tracking.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Funds: Links anonymized constituent data to funds for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by members: Anonymized constituent data is linked to membership records, allowing for demographic analysis without revealing identities.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be linked to a constituent who purchased the ticket.', 'relationship': 'one-to-many'} , {'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references anonymized constituent information for deceased customers.', 'relationship': 'one-to-many'} , {'to_table': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Contribution Output: Links contributions to anonymized constituent information for demographic analysis.', 'relationship': 'one-to-many'} , {'to_table': 'events', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by events: Events may involve interactions with constituents, linking event data to anonymized constituent information for analysis.', 'relationship': 'one-to-many'} , {'to_table': 'pseudonymous users', 'linking_column': 'constituent_id',

Field	Value
	`'relation_description': 'Referenced by pseudonymous users: The dimconstituentsanon table contains anonymized constituent information linked to pseudonymous users.', 'relationship': 'one-to-many'}`

Table 8: Funds

Field	Value
ID	`31424eefa1b227d0bd93c9c0d3603f45`
Label	Funds
Backend Name	`_1824funds`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	34
Description	This table stores information about funds and their associated transactions.
Embedding Input	The Funds table is a critical component of the CRM data architecture, capturing detailed financial transactions related to various funds. It encompasses key metrics such as total pledges, payments, and gifts, which are essential for financial reporting and analysis. The table is structured with a primary key on 'cont_designation_id', ensuring unique identification of each fund record. It supports various business operations including fundraising campaigns, donor management, and financial forecasting. The data within this table is sourced from transaction records and is updated regularly to reflect the latest financial activities. It plays a

Field	Value
	vital role in decision-making workflows, providing insights into funding sources and financial health. The table's relationships with other entities, such as donors and campaigns, are crucial for comprehensive analytics and reporting. Data retention policies are in place to maintain historical records for compliance and auditing purposes.
Tags	`funds` `financial transactions` `CRM`
Columns	`sort_name`, `display_name`, `creditee_name`, `creditee_no`, `creditee_type_desc`, `creditee_type`, `fname`, `lname`, `customer_no`, `pmt_count`, `gift_pmt_amt`, `pledge_pmt_amt`, `pmt_method`, `pmt_method_id`, `channel_desc`, `channel_id`, `cont_designation`, `cont_designation_id`, `campaign`, `campaign_no`, `fyear`, `fund_desc`, `fund_no`, `trn_dt`, `cont_dt`, `ref_no`, `batch_no`, `total_received`, `write_off`, `restricted`, `gift`, `pledge_payment`, `pledge`, `trn_count`
Primary Keys	`cont_designation_id`
Foreign Keys	`appeal_no`, `constituent_id`, `customer_no`, `transaction_id`, `membership_id`, `ticket_id`, `order_id`, `batch_id`, `promotion_appeal`, `production_season_id`, `seat_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'Contribution Transaction Link', 'linking_column': 'contribution_id', 'relation_description': 'Links contributions to their respective funds for tracking financial contributions.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'Associates pending financial transactions with specific funds for financial tracking.', 'relationship': 'many-to-one'}`,

Field	Value
	{'target_table_name': 'Contribution Output', 'linking_column': 'contribution_id', 'relation_description': 'Tracks contributions made by constituents to specific funds.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'Links ticket sales to specific funds for event-related contributions.', 'relationship': 'many-to-one'}, {'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Links anonymized constituent data to funds for demographic analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'Associates batch processing activities with specific funds for operational tracking.', 'relationship': 'many-to-one'}, {'target_table_name': 'members', 'linking_column': 'membership_id', 'relation_description': 'Links membership details to specific funds for tracking member contributions.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Associates deceased customer data with funds for historical contribution analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Links production season data to funds for financial planning.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Links appeal sources to funds for tracking fundraising effectiveness.',

Field	Value
	'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Associates promotional campaigns with specific funds for marketing analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Links package details to funds for tracking sales and contributions.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'References Contact Types Relationships: This table stores information about funds and their associated transactions, which may relate to customer types in the Contact Types Relationships table.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Ticket', 'linking_column': 'cont_designation_id', 'relation_description': 'Referenced by Ticket: Associates ticket sales with specific funds for financial reporting and analysis.', 'relationship': 'one-to-many'}, {'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'cont_designation_id', 'relation_description': 'Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references fund designations related to deceased customers.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Output', 'linking_column': 'cont_designation_id', 'relation_description': 'Referenced by Contribution Output: Links contributions to specific funds for financial tracking.', 'relationship': 'one-to-many'}

Table 9: members

Field	Value
ID	`05aa1e68e77af4f01193c14263d27f43`
Label	members
Backend Name	`_1824members2`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	22
Description	Table containing membership details for constituents.
Embedding Input	The 'members' table serves as a critical repository for tracking membership information related to constituents within the CRM system. It encapsulates various attributes of memberships, including identifiers, categories, financial contributions, and temporal aspects such as initiation and expiration dates. This table supports essential business operations by enabling organizations to manage member relationships, analyze membership trends, and facilitate decision-making processes related to fundraising and engagement strategies. The table is structured with a primary key on 'membership_id', which uniquely identifies each membership record. It is designed to integrate seamlessly with other tables in the CRM ecosystem, allowing for comprehensive reporting and analytics. The data lifecycle includes regular updates based on membership renewals and new sign-ups, with retention policies aligned with organizational standards. Key relationships with other tables are inferred through columns such as 'constituent_id', 'appeal_id', and 'campaign_id', which likely serve as foreign keys linking to related entities.

Field	Value
Tags	`membership` `CRM` `constituent`
Columns	`source_id`, `campaign_id`, `appeal_id`, `membership_organization`, `membership_level_rank`, `membership_level_id`, `membership_level_code`, `membership_level`, `avc_amount`, `micro_category_trend`, `macro_level_trend`, `new_renew_reinstate_status`, `sales_channel`, `campaign`, `appeal`, `source`, `expdate`, `initdate`, `amount`, `membership_category`, `constituent_id`, `membership_id`
Primary Keys	`membership_id`
Foreign Keys	`constituent_id`, `ticket_id`, `customer_no`, `seat_id`, `order_id`, `production_season_id`, `batch_id`, `transaction_id`, `appeal_no`, `promotion_appeal`
Foreign Keys Referencing Tables	`{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': "Each ticket is associated with a member's purchase or attendance, linking ticket sales to membership details.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Anonymized constituent data is linked to membership records, allowing for demographic analysis without revealing identities.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Contributions made by constituents are tied to their membership records, facilitating fundraising analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution`

Field	Value
	Output', 'linking_column': 'contribution_id', 'relation_description': 'Each contribution is linked to a specific membership, allowing tracking of financial support from members.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'Customer relationships are linked to membership records, enhancing understanding of member interactions.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Deceased members are tracked alongside their last activities, providing insights into member engagement history.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Memberships may be associated with specific production seasons, linking member engagement to seasonal activities.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Memberships are linked to specific appeals, allowing for targeted fundraising efforts based on member data.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Promotional campaigns are linked to memberships, enabling analysis of member responses to marketing efforts.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Packages purchased by members are linked to their membership records, facilitating sales

Field	Value
	analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'Transactions related to contributions are linked to memberships, providing a comprehensive view of financial support.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_id', 'relation_description': 'References Appeal Source Structure: Associates membership records with appeal sources for analyzing membership growth driven by appeals.', 'relationship': 'many-to-one'}, {'target_table_name': 'pseudonymous users', 'linking_column': 'membership_id', 'relation_description': 'References pseudonymous users: The members table tracks membership details that may reference pseudonymous users through membership identifiers.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': "Referenced by dimconstituentsanon: The members table contains membership details for constituents, associating each membership with the respective constituent's anonymized data.", 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'membership_id', 'relation_description': 'Referenced by Ticket: Connects ticket sales to membership details for analyzing member engagement.', 'relationship': 'one-to-many'}, {'to_table': 'Funds', 'linking_column': 'membership_id', 'relation_description': 'Referenced by Funds: Links membership details to specific funds for tracking member contributions.', 'relationship': 'one-to-

Field	Value
	`many'}` , `{'to_table': 'Contact Types Relationships', 'linking_column': 'membership_id', 'relation_description': 'Referenced by Contact Types Relationships: This table contains membership details for constituents, which may relate to customer types in the Contact Types Relationships table.', 'relationship': 'one-to-many'}` , `{'to_table': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Contribution Output: Connects contributions to membership details of constituents.', 'relationship': 'one-to-many'}` , `{'to_table': 'events', 'linking_column': 'membership_id', 'relation_description': 'Referenced by events: Events may be associated with specific memberships, linking event data to membership details for engagement tracking.', 'relationship': 'one-to-many'}`

Table 10: Contribution Output

Field	Value
ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Label	Contribution Output
Backend Name	`contributionoutputv2`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	14

Field	Value
Description	Stores information about contributions made by constituents.
Embedding Input	The Contribution Output table captures detailed records of contributions made by constituents within the CRM system. This table serves as a critical component in tracking fundraising efforts, analyzing donor behavior, and managing financial contributions to various campaigns and funds. It includes key identifiers such as constituent_id and contribution_id, which link to other entities in the CRM, facilitating comprehensive reporting and analytics. The table is structured to support various data types including integers for IDs, strings for categorical data, and doubles for monetary amounts, ensuring flexibility in data representation. It is essential for operational workflows related to fundraising, donor management, and financial reporting, and integrates with upstream systems for data input and downstream systems for reporting and analysis. The data lifecycle includes regular updates as contributions are recorded, with retention policies aligned with organizational standards for financial data.
Tags	`contributions` `donor management` `fundraising`
Columns	`balance_amount` , `campaign_id` , `billing_type` , `source_id` , `worker_constituent_id` , `type` , `amount` , `fund_id` , `days_in_date` , `contribution_id` , `designation` , `sales_channel` , `appeal_id` , `constituent_id`
Primary Keys	`constituent_id`
Foreign Keys	`cont_designation_id` , `promotion_appeal` , `constituent_id` , `transaction_id` , `appeal_no` , `membership_id` , `batch_id` , `ticket_id` , `customer_no` , `seat_id` , `order_id` , `production_season_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column':`

Field	Value
	'constituent_id', 'relation_description': 'Links contributions to anonymized constituent information for demographic analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket', 'linking_column': 'constituent_id', 'relation_description': 'Associates contributions with ticket purchases made by constituents.', 'relationship': 'many-to-one'}, {'target_table_name': 'members', 'linking_column': 'constituent_id', 'relation_description': 'Connects contributions to membership details of constituents.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'contribution_id', 'relation_description': 'Links contribution transactions to their respective details for financial reporting.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Associates contributions with packages linked to customer orders.', 'relationship': 'many-to-one'}, {'target_table_name': 'Funds', 'linking_column': 'cont_designation_id', 'relation_description': 'Links contributions to specific funds for financial tracking.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket Seat ID', 'linking_column': 'seat_id', 'relation_description': 'Associates contributions with specific ticket seats for event management.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Links contributions to deceased customers for historical analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types',

Field	Value
	'linking_column': 'production_season_id', 'relation_description': 'Associates contributions with specific production seasons for event planning.', 'relationship': 'many-to-one'}, {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Links contributions to specific appeal sources for campaign effectiveness analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Associates contributions with quarterly promotional campaigns for marketing analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'appeal_id', 'relation_description': 'References Promo Quarterly: Links contributions to promotional appeals for fundraising effectiveness evaluation.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Contribution Transaction Link', 'linking_column': 'contribution_id', 'relation_description': 'Referenced by Contribution Transaction Link: Links contribution transactions to detailed records of contributions made by constituents.', 'relationship': 'one-to-many'}, {'to_table': 'Packages', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Packages: The Packages table references contributions made by constituents to analyze the impact of package offerings on fundraising efforts.', 'relationship': 'one-to-many'}, {'to_table': 'Appeal Source Structure', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Appeal Source Structure: Links contributions made by constituents to the appeal sources for fundraising

Field	Value
	analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Appeal Source Structure', 'linking_column': 'appeal_id', 'relation_description': 'Referenced by Appeal Source Structure: Associates contributions with specific appeal sources for performance tracking.', 'relationship': 'one-to-many'} , {'to_table': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': "Referenced by dimconstituentsanon: The Contribution Output table tracks contributions made by constituents, linking each contribution to the corresponding constituent's anonymized information.", 'relationship': 'one-to-many'} , {'to_table': 'production season types', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by production season types: This table records contributions made by constituents, which may be linked to specific production seasons for fundraising analysis.', 'relationship': 'one-to-many'} , {'to_table': 'batch summary', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by batch summary: Associates contributions made by constituents with batch summaries for fundraising insights.', 'relationship': 'one-to-many'} , {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include contributions linked to constituents, referencing contribution records.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Ticket: Associates ticket sales with contributions made by constituents, facilitating fundraising

Field	Value
	analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'contribution_id', 'relation_description': 'Referenced by Funds: Tracks contributions made by constituents to specific funds.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by members: Contributions made by constituents are tied to their membership records, facilitating fundraising analysis.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'contribution_id', 'relation_description': 'Referenced by members: Each contribution is linked to a specific membership, allowing tracking of financial support from members.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may relate to contributions made by constituents.', 'relationship': 'one-to-many'} , {'to_table': 'Deceased Cont W Last Activity', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references contributions made by deceased customers.', 'relationship': 'one-to-many'} , {'to_table': 'Contact Types Relationships', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by Contact Types Relationships: This table records contributions made by constituents, which are likely categorized by customer types in the Contact Types Relationships table.', 'relationship': 'one-to-many'} , {'to_table': 'events', 'linking_column':

Field	Value
	`'constituent_id', 'relation_description': 'Referenced by events: Events may be related to contributions made by constituents, linking event data to contribution records for fundraising analysis.', 'relationship': 'one-to-many'}`, `{'to_table': 'pseudonymous users', 'linking_column': 'constituent_id', 'relation_description': 'Referenced by pseudonymous users: The Contribution Output table tracks contributions made by constituents linked to pseudonymous users.', 'relationship': 'one-to-many'}`

Table 11: production season types

Field	Value
ID	`48527682c3aaedf9b960b951869c9d67`
Label	production season types
Backend Name	`productionseason_types`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	7
Description	This table stores different types of production seasons.
Embedding Input	The 'production season types' table is a critical component of the CRM data architecture, representing various classifications of production seasons that are essential for managing agricultural or manufacturing cycles. It serves as a reference for understanding the temporal

Field	Value
	aspects of production activities, supporting operational decision-making, and analytical reporting. The table is structured with a primary key 'production_season_id' to uniquely identify each season type, and it includes several attributes such as 'production_season', 'type', 'production_id', 'performance_id', 'season_id', and 'season', which provide detailed context about each production season. The data within this table is expected to be updated periodically to reflect changes in production strategies and seasonal classifications, ensuring that it remains relevant for business operations. The table may integrate with other systems that track production metrics and performance, thereby playing a vital role in the overall data ecosystem.
Tags	`production` `season` `CRM`
Columns	`season` , `season_id` , `performance_id` , `production_id` , `type` , `production_season_id` , `production_season`
Primary Keys	`production_season_id`
Foreign Keys	`batch_id` , `constituent_id` , `order_id` , `customer_no` , `transaction_id` , `promotion_appeal` , `appeal_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'This table tracks batches processed in the CRM, which may include production season data for operational oversight.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'This table contains anonymized constituent information, which may relate to production season types for demographic analysis.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description':`

Field	Value
	'This table records contributions made by constituents, which may be linked to specific production seasons for fundraising analysis.', 'relationship': 'many-to-one'} , {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'This table tracks deceased customers, which may relate to production seasons for historical engagement analysis.', 'relationship': 'many-to-one'} , {'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'This table captures sources of appeals, which may be linked to production seasons for campaign effectiveness analysis.', 'relationship': 'many-to-one'} , {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'This table stores promotional data, which may relate to production seasons for analyzing customer engagement.', 'relationship': 'many-to-one'} , {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'This table contains information about packages associated with orders, which may relate to production seasons for sales analysis.', 'relationship': 'many-to-one'} , {'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'This table tracks financial transactions, which may relate to production seasons for financial forecasting.', 'relationship': 'many-to-one'} , {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'This table defines relationships between customer types, which may relate to production seasons for targeted

Field	Value
	marketing.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'This table links contribution transactions to details, which may relate to production seasons for fundraising analysis.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'This table contains ticket information that may reference production season types for event categorization.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket Seat ID', 'linking_column': 'seat_id', 'relation_description': 'This table contains details about ticket seats that may reference production season types for performance context.', 'relationship': 'one-to-many'}, {'to_table': 'batch summary', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by batch summary: Connects batch summaries to specific production seasons for operational tracking.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include transactions related to specific production seasons, linking to season types.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by Ticket: Connects ticket data to specific production seasons, aiding in performance and event management.', 'relationship': 'one-to-many'}, {'to_table': 'Funds',

Field	Value
	`'linking_column': 'production_season_id', 'relation_description': 'Referenced by Funds: Links production season data to funds for financial planning.', 'relationship': 'one-to-many'}` , `{'to_table': 'members', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by members: Memberships may be associated with specific production seasons, linking member engagement to seasonal activities.', 'relationship': 'one-to-many'}` , `{'to_table': 'Ticket Seat ID', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be associated with a specific production season for events.', 'relationship': 'one-to-many'}` , `{'to_table': 'Contribution Output', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by Contribution Output: Associates contributions with specific production seasons for event planning.', 'relationship': 'one-to-many'}` , `{'to_table': 'events', 'linking_column': 'production_season_id', 'relation_description': 'Referenced by events: Events may be categorized by production seasons, linking event data to seasonal classifications for operational insights.', 'relationship': 'one-to-many'}`

Table 12: Deceased Cont W Last Activity

Field	Value
ID	`4cb3544c21d1881216a12ebf8b4060ec`
Label	Deceased Cont W Last Activity

Field	Value
Backend Name	`deceasedcontwlastactivity5_1_25`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	3
Description	Table containing information about deceased customers along with their last activity dates.
Embedding Input	The 'Deceased Cont W Last Activity' table serves as a critical repository for tracking deceased customers within the CRM system, providing essential insights into customer engagement and historical interactions. This table is integral for understanding the lifecycle of customer relationships, particularly in the context of charitable organizations or businesses that maintain ongoing relationships with their clients. It includes key identifiers such as 'customer_no', which uniquely identifies each customer, and captures significant dates related to customer activity, specifically 'customer_last_gift_dt' and 'customer_last_ticket_dt'. The table supports analytical processes by enabling organizations to filter and segment deceased customers based on their last known activities, thereby informing decision-making in areas such as targeted communications, legacy planning, and compliance with regulatory requirements. The data is sourced from the CRM system, with updates occurring as customer statuses change, and retention policies are aligned with organizational standards for customer data management.
Tags	`deceased customers` `customer activity` `CRM`
Columns	`customer_last_ticket_dt` , `customer_last_gift_dt` , `customer_no`

Field	Value
Primary Keys	`customer_no`
Foreign Keys	`ticket_id`, `constituent_id`, `order_id`, `seat_id`, `customer_no`, `cont_designation_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': "The Deceased Cont W Last Activity table references ticket information related to deceased customers' event participation.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': "The Deceased Cont W Last Activity table references package information associated with deceased customers' orders.", 'relationship': 'many-to-one'}`, `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'The Deceased Cont W Last Activity table references anonymized constituent information for deceased customers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'The Deceased Cont W Last Activity table references contributions made by deceased customers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'The Deceased Cont W Last Activity table references customer type relationships for deceased customers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Funds', 'linking_column': 'cont_designation_id', 'relation_description': 'The Deceased Cont W Last Activity table references fund designations related to deceased`

Field	Value
	customers.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'Promo Quarterly', 'linking_column': 'customer_no', 'relation_description': 'The Promo Quarterly table references deceased customers to analyze promotional engagement.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Contribution Transaction Link: Connects contribution transactions to deceased customer records for historical engagement analysis.', 'relationship': 'one-to-many'}, {'to_table': 'production season types', 'linking_column': 'customer_no', 'relation_description': 'Referenced by production season types: This table tracks deceased customers, which may relate to production seasons for historical engagement analysis.', 'relationship': 'one-to-many'}, {'to_table': 'batch summary', 'linking_column': 'customer_no', 'relation_description': 'Referenced by batch summary: Links batch summaries to deceased customer records for historical engagement analysis.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions related to deceased customers, linking to their last activity.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Ticket: Links ticket purchases to deceased customers for historical engagement analysis.', 'relationship': 'one-to-

Field	Value
	many'} , {'to_table': 'Funds', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Funds: Associates deceased customer data with funds for historical contribution analysis.', 'relationship': 'one-to-many'} , {'to_table': 'members', 'linking_column': 'customer_no', 'relation_description': 'Referenced by members: Deceased members are tracked alongside their last activities, providing insights into member engagement history.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may relate to customers who have passed away, impacting ticket sales.', 'relationship': 'one-to-many'} , {'to_table': 'Contribution Output', 'linking_column': 'customer_no', 'relation_description': 'Referenced by Contribution Output: Links contributions to deceased customers for historical analysis.', 'relationship': 'one-to-many'} , {'to_table': 'events', 'linking_column': 'customer_no', 'relation_description': 'Referenced by events: Events may involve interactions with deceased customers, linking event data to historical customer engagement records.', 'relationship': 'one-to-many'} , {'to_table': 'users', 'linking_column': 'customer_no', 'relation_description': 'Referenced by users: The users table references deceased customers to manage user data related to customer interactions.', 'relationship': 'one-to-many'}

Table 13: events

Field	Value
ID	`16908b0605f2645dfcb4c3a8d248cef3`
Label	events
Backend Name	`events`
Type	table
Parent Type	source
Parent ID	`s_ga4`
Parent Name	GA4
Record Count	25
Description	Stores event data collected from GA4.
Embedding Input	The 'events' table captures detailed information about user interactions and events tracked through Google Analytics 4 (GA4). This table serves as a critical repository for analyzing user behavior, engagement metrics, and conversion tracking, supporting business intelligence and decision-making processes. It includes various attributes related to each event, such as identifiers, timestamps, event names, and associated parameters. The primary key, 'event_bundle_sequence_id', uniquely identifies each event entry, ensuring data integrity and facilitating efficient querying. The table is designed to accommodate a wide range of event types and is integral to understanding user journeys across digital platforms. Data is sourced from GA4, with updates occurring in real-time or near real-time, depending on the configuration. Retention policies align with organizational data governance standards, ensuring compliance with privacy regulations. The table's structure allows for indexing on key columns to optimize performance for analytical queries, and it is expected to integrate with downstream reporting tools and dashboards.

Field	Value
Tags	`GA4` `event tracking` `user behavior`
Columns	`batch_event_index`, `batch_ordering_id`, `batch_page_id`, `collected_traffic_source`, `device`, `ecommerce`, `event_bundle_sequence_id`, `event_date`, `event_name`, `event_params`, `event_timestamp`, `event_value_in_usd`, `geo`, `is_active_user`, `items`, `platform`, `privacy_info`, `session_traffic_source_last_click`, `stream_id`, `traffic_source`, `user_first_touch_timestamp`, `user_id`, `user_ltv`, `user_properties`, `user_pseudo_id`
Primary Keys	`event_bundle_sequence_id`
Foreign Keys	`batch_id`, `transaction_id`, `production_season_id`, `ticket_id`, `order_id`, `seat_id`, `constituent_id`, `user_id`, `membership_id`, `customer_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'The events table captures event data that is processed in batches, linking each event to its corresponding batch for operational oversight.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'Events may be associated with financial transactions that are pending integration into the financial model, linking event data to transaction records.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'Each event may correspond to a specific ticket issued, linking event data to ticket information for event management.', 'relationship': 'many-to-one'}`, `{'target_table_name':`

Field	Value
	'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Events may involve interactions with constituents, linking event data to anonymized constituent information for analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Events may be related to contributions made by constituents, linking event data to contribution records for fundraising analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'members', 'linking_column': 'membership_id', 'relation_description': 'Events may be associated with specific memberships, linking event data to membership details for engagement tracking.', 'relationship': 'many-to-one'}, {'target_table_name': 'pseudonymous users', 'linking_column': 'user_id', 'relation_description': 'Events are tracked for users identified by pseudonymous identifiers, linking event data to user profiles for behavioral analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Events may be categorized by production seasons, linking event data to seasonal classifications for operational insights.', 'relationship': 'many-to-one'}, {'target_table_name': 'users', 'linking_column': 'user_id', 'relation_description': 'Events are associated with individual users, linking event data to user profiles for detailed analytics.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Events may involve interactions with deceased customers, linking event data to

Field	Value
	historical customer engagement records.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Events may be linked to specific packages associated with orders, connecting event data to sales and marketing strategies.', 'relationship': 'many-to-one'}, {'target_table_name': 'batch summary', 'linking_column': 'batch_page_id', 'relation_description': 'References batch summary: Associates events with batch summaries for user interaction analysis.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'users', 'linking_column': 'event_bundle_sequence_id', 'relation_description': 'Referenced by users: The users table references events to track user interactions and behaviors associated with specific events.', 'relationship': 'one-to-many'}, {'to_table': 'pseudonymous users', 'linking_column': 'event_bundle_sequence_id', 'relation_description': 'Referenced by pseudonymous users: The events table captures user interactions and is linked to pseudonymous users through event identifiers.', 'relationship': 'one-to-many'}

Table 14: batch summary

Field	Value
ID	fbc6e5b24dd857869918a3ed39527d1f
Label	batch summary
Backend Name	batchsummary

Field	Value
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	7
Description	Summary of batches processed within the CRM system.
Embedding Input	The batch summary table serves as a comprehensive repository for tracking and managing batch processing activities within the CRM system. It encapsulates key attributes related to each batch, including identifiers, types, statuses, and associated dates, which are crucial for operational oversight and analytical reporting. This table is integral to understanding the flow of contributions and their categorization over fiscal periods, thereby supporting decision-making processes and performance evaluations. The primary key, batch_id, uniquely identifies each batch, while the nullable fields allow for flexibility in data entry. The table is designed to facilitate efficient querying and reporting, with potential relationships to other tables through contribution_id and other contextual identifiers. Data is sourced from various operational processes within the CRM, with updates occurring as batches are processed, ensuring that the information remains current and relevant for stakeholders. Retention policies and data lifecycle management practices are in place to maintain data integrity and compliance with regulatory standards.
Tags	`batch processing` `CRM` `data summary`
Columns	`fiscal_year` , `post_date` , `batch_type_group` , `batch_status` , `batch_type` , `contribution_id` , `batch_id`
Primary Keys	`batch_id`

Field	Value
Foreign Keys	`production_season_id`, `transaction_id`, `constituent_id`, `customer_no`, `order_id`, `promotion_appeal`, `appeal_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Links batch summary to anonymized constituent information for demographic analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Associates contributions made by constituents with batch summaries for fundraising insights.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Connects batch summaries to specific production seasons for operational tracking.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Links batch summaries to deceased customer records for historical engagement analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Associates batch summaries with appeal sources for campaign effectiveness tracking.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Links promotional campaigns to batch summaries for customer engagement analysis.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Associates`

Field	Value
	packages with batch summaries for order processing insights.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'Links financial transactions to batch summaries for cash flow analysis.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'Connects contribution transactions to batch summaries for detailed financial reporting.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'events', 'linking_column': 'batch_page_id', 'relation_description': 'Associates events with batch summaries for user interaction analysis.', 'relationship': 'one-to-many'}, {'to_table': 'Contribution Transaction Link', 'linking_column': 'batch_id', 'relation_description': 'Referenced by Contribution Transaction Link: Associates contribution transactions with their respective batch processing records.', 'relationship': 'one-to-many'}, {'to_table': 'production season types', 'linking_column': 'batch_id', 'relation_description': 'Referenced by production season types: This table tracks batches processed in the CRM, which may include production season data for operational oversight.', 'relationship': 'one-to-many'}, {'to_table': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'batch_id', 'relation_description': 'Referenced by Deferrals and Receiveables Not in Model Yet: The target table records transactions that are processed in batches, linking to batch summaries.', 'relationship': 'one-to-many'}, {'to_table': 'Ticket',

Field	Value
	`'linking_column': 'batch_id', 'relation_description': 'Referenced by Ticket: Links ticket transactions to batch processing for operational oversight.', 'relationship': 'one-to-many'}` , `{'to_table': 'Funds', 'linking_column': 'batch_id', 'relation_description': 'Referenced by Funds: Associates batch processing activities with specific funds for operational tracking.', 'relationship': 'one-to-many'}` , `{'to_table': 'Ticket Seat ID', 'linking_column': 'batch_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may be associated with a batch of ticket sales processed together.', 'relationship': 'one-to-many'}` , `{'to_table': 'events', 'linking_column': 'batch_id', 'relation_description': 'Referenced by events: The events table captures event data that is processed in batches, linking each event to its corresponding batch for operational oversight.', 'relationship': 'one-to-many'}` , `{'to_table': 'pseudonymous users', 'linking_column': 'batch_id', 'relation_description': 'Referenced by pseudonymous users: The batch summary table tracks batches processed and is linked to pseudonymous users through batch identifiers.', 'relationship': 'one-to-many'}`

Table 15: Deferrals and Receiveables Not in Model Yet

Field	Value
ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Label	Deferrals and Receiveables Not in Model Yet
Backend Name	`deferralsandreceiveablesnotinmodelyet`

Field	Value
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	6
Description	Table containing deferrals and receivables that are not yet included in the financial model.
Embedding Input	This table serves as a repository for tracking deferrals and receivables that have not yet been integrated into the financial modeling processes within the CRM system. It captures essential transactional data related to financial operations, enabling organizations to manage and analyze outstanding amounts that may impact cash flow and financial forecasting. The table is structured with a primary key on transaction_id, ensuring unique identification of each record. It is designed to support critical business operations by providing insights into pending financial transactions, which are vital for decision-making workflows and analytical reporting. The data lifecycle includes regular updates from the CRM system, with retention policies aligned to financial reporting requirements. The table may interact with other financial tables, although it currently has no direct foreign key relationships defined.
Tags	`deferrals` `receivables` `financial modeling`
Columns	`days_in_date` , `contribution_id` , `transaction_id` , `batch_type` , `post_id` , `batch_id`
Primary Keys	`transaction_id`
Foreign Keys	`batch_id` , `transaction_id` , `constituent_id` , `customer_no` ,

Field	Value
	`production_season_id`, `order_id`, `promotion_appeal`, `appeal_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'The target table tracks transactions that may include ticket purchases, linking to ticket details.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'The target table captures transactions related to constituents, linking to anonymized constituent information.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'The target table records transactions that are processed in batches, linking to batch summaries.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'The target table may include contributions linked to constituents, referencing contribution records.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'The target table may track transactions related to deceased customers, linking to their last activity.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'The target table may include transactions related to specific production seasons, linking to season types.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'The`

Field	Value
	target table may track transactions related to specific appeals, linking to appeal sources.', 'relationship': 'many-to-one'}, {'target_table_name': 'Promo Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'The target table may include transactions related to promotional campaigns, linking to promotional data.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'The target table may track transactions associated with specific packages, linking to order details.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'The target table may include transactions related to different customer types, linking to customer relationships.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'The target table may link transactions to their respective details, referencing contribution transactions.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket', 'linking_column': 'transaction_id', 'relation_description': 'References Ticket: References ticket transactions for tracking financial operations related to ticket sales.', 'relationship': 'many-to-one'}
Primary Keys Referencing Tables	{'to_table': 'production season types', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by production season types: This table tracks financial transactions, which may relate to production seasons for financial forecasting.', 'relationship': 'one-to-

Field	Value
	many'} , {'to_table': 'batch summary', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by batch summary: Links financial transactions to batch summaries for cash flow analysis.', 'relationship': 'one-to-many'} , {'to_table': 'Funds', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by Funds: Associates pending financial transactions with specific funds for financial tracking.', 'relationship': 'one-to-many'} , {'to_table': 'Ticket Seat ID', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by Ticket Seat ID: Each ticket seat may relate to financial transactions pending in the system.', 'relationship': 'one-to-many'} , {'to_table': 'events', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by events: Events may be associated with financial transactions that are pending integration into the financial model, linking event data to transaction records.', 'relationship': 'one-to-many'} , {'to_table': 'pseudonymous users', 'linking_column': 'transaction_id', 'relation_description': 'Referenced by pseudonymous users: This table tracks financial transactions that may be linked to pseudonymous users through transaction identifiers.', 'relationship': 'one-to-many'}

Table 16: Ticket Seat ID

Field	Value
ID	88413cb2ffc5d0be5506f90842fa09a8
Label	Ticket Seat ID

Field	Value
Backend Name	`ticketseatid`
Type	table
Parent Type	source
Parent ID	`s_crm`
Parent Name	CRM
Record Count	9
Description	Table containing details about ticket seats.
Embedding Input	The Ticket Seat ID table serves as a critical component in the ticketing system, representing the specific seats associated with performances in a venue. It captures essential attributes such as seat identifiers, seat numbers, rows, sections, and the performance context, facilitating the management of seating arrangements and ticket sales. This table is integral to operational workflows, supporting functions like ticket allocation, sales reporting, and customer service interactions. It is structured with a primary key on 'seat_id', ensuring unique identification of each seat. The table's design allows for efficient querying and integration with other systems, such as CRM and sales platforms, to enhance the overall ticketing experience. Data is expected to be updated frequently in line with ticket sales and performance scheduling, with retention policies aligned to business needs for historical sales analysis.
Tags	`ticketing` `seating` `performance`
Columns	`mode_of_sale` , `order_id` , `performance_id` , `screen` , `section` , `seat_row` , `seat_num` , `seat_id` , `ticket_id`
Primary Keys	`seat_id`
Foreign Keys	`order_id` , `transaction_id` , `constituent_id` , `production_season_id` ,

Field	Value
	`batch_id`, `customer_no`, `promotion_appeal`, `appeal_no`, `ticket_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'Ticket', 'linking_column': 'ticket_id', 'relation_description': 'Each ticket seat is associated with a specific ticket for an event.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'Each ticket seat may be linked to a constituent who purchased the ticket.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'Each ticket seat may be associated with a batch of ticket sales processed together.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'Each ticket seat may relate to contributions made by constituents.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'production season types', 'linking_column': 'production_season_id', 'relation_description': 'Each ticket seat may be associated with a specific production season for events.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'Each ticket seat may relate to customers who have passed away, impacting ticket sales.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Appeal Source Structure', 'linking_column': 'appeal_no', 'relation_description': 'Each ticket seat may be linked to specific appeals made to customers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Promo`

Field	Value
	Quarterly', 'linking_column': 'promotion_appeal', 'relation_description': 'Each ticket seat may be associated with promotional campaigns for ticket sales.', 'relationship': 'many-to-one'}, {'target_table_name': 'Packages', 'linking_column': 'order_id', 'relation_description': 'Each ticket seat may be part of a package linked to an order.', 'relationship': 'many-to-one'}, {'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'Each ticket seat may relate to financial transactions pending in the system.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no', 'relation_description': 'Each ticket seat may relate to different types of customer interactions.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'Each ticket seat may be linked to contribution transactions.', 'relationship': 'many-to-one'}, {'target_table_name': 'production season types', 'linking_column': 'seat_id', 'relation_description': 'References production season types: This table contains details about ticket seats that may reference production season types for performance context.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket', 'linking_column': 'seat_id', 'relation_description': 'References Ticket: Referenced by ticket data to identify specific seats associated with ticket purchases.', 'relationship': 'many-to-one'}

Field	Value
Primary Keys Referencing Tables	`{'to_table': 'Contribution Output', 'linking_column': 'seat_id', 'relation_description': 'Referenced by Contribution Output: Associates contributions with specific ticket seats for event management.', 'relationship': 'one-to-many'}` , `{'to_table': 'pseudonymous users', 'linking_column': 'seat_id', 'relation_description': 'Referenced by pseudonymous users: The Ticket Seat ID table contains details about ticket seats that may be linked to pseudonymous users through seat identifiers.', 'relationship': 'one-to-many'}`

Table 17: users

Field	Value
ID	`9bc65c2abec141778ffaa729489f3e87`
Label	users
Backend Name	`users`
Type	table
Parent Type	source
Parent ID	`s_ga4`
Parent Name	GA4
Record Count	10
Description	Stores user-related data for analytics and reporting.
Embedding Input	The 'users' table is a critical component of the GA4 data architecture, representing individual user profiles and their interactions within the system. It serves as a foundational dataset for

Field	Value
	understanding user behavior, engagement metrics, and demographic insights. The table is structured around a primary key, 'user_id', which uniquely identifies each user. It includes various attributes such as 'audiences', 'device', 'geo', 'last_updated_date', 'occurrence_date', 'privacy_info', 'user_info', 'user_ltv', and 'user_properties', which collectively provide a comprehensive view of user characteristics and activities. The data is sourced from GA4, with updates reflecting user interactions and privacy considerations. This table supports analytical workflows, reporting, and decision-making processes by enabling segmentation, trend analysis, and user journey mapping. It is essential for compliance with data governance and privacy regulations, ensuring that user data is handled responsibly.
Tags	`user_data` `analytics` `GA4`
Columns	`audiences` , `device` , `geo` , `last_updated_date` , `occurrence_date` , `privacy_info` , `user_id` , `user_info` , `user_ltv` , `user_properties`
Primary Keys	`user_id`
Foreign Keys	`event_bundle_sequence_id` , `customer_no`
Foreign Keys Referencing Tables	`{'target_table_name': 'events', 'linking_column': 'event_bundle_sequence_id', 'relation_description': 'The users table references events to track user interactions and behaviors associated with specific events.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'Deceased Cont W Last Activity', 'linking_column': 'customer_no', 'relation_description': 'The users table references deceased customers to manage user data related to customer interactions.', 'relationship': 'many-to-one'}` , `{'target_table_name': 'Contact Types Relationships', 'linking_column': 'customer_no',`

Field	Value
	`'relation_description': 'The users table references customer types to understand the relationships between different user profiles.', 'relationship': 'many-to-one'}`
Primary Keys Referencing Tables	`{'to_table': 'pseudonymous users', 'linking_column': 'pseudo_user_id', 'relation_description': 'The pseudonymous users table references users to maintain a link between pseudonymous identifiers and user profiles.', 'relationship': 'one-to-many'}` , `{'to_table': 'Contact Types Relationships', 'linking_column': 'user_id', 'relation_description': 'Referenced by Contact Types Relationships: This table stores user-related data, which may include interactions with different customer types defined in the Contact Types Relationships table.', 'relationship': 'one-to-many'}` , `{'to_table': 'events', 'linking_column': 'user_id', 'relation_description': 'Referenced by events: Events are associated with individual users, linking event data to user profiles for detailed analytics.', 'relationship': 'one-to-many'}` , `{'to_table': 'pseudonymous users', 'linking_column': 'user_id', 'relation_description': 'Referenced by pseudonymous users: The users table contains user-related data that is linked to pseudonymous users through user identifiers.', 'relationship': 'one-to-many'}`

Table 18: pseudonymous users

Field	Value
ID	`d56ce9c6b9bd0f5600449feaac6290b1`

Field	Value
Label	pseudonymous users
Backend Name	`pseudonymous_users`
Type	table
Parent Type	source
Parent ID	`s_ga4`
Parent Name	GA4
Record Count	11
Description	Stores information about pseudonymous users captured from GA4.
Embedding Input	The 'pseudonymous users' table is a critical component of the GA4 data architecture, designed to capture and store data related to users who are identified by pseudonymous identifiers rather than personal information. This table supports analytics and reporting by providing insights into user behavior while maintaining privacy compliance. It includes key attributes such as 'pseudo_user_id', which serves as the primary key, and various user-related metrics such as device type, geographical location, and user properties. The table is structured to facilitate efficient querying and reporting, with a focus on maintaining data integrity and compliance with privacy regulations. Data is sourced from GA4, with updates occurring regularly to reflect the latest user interactions. Retention policies are in place to manage data lifecycle effectively, ensuring that only relevant data is kept for analysis. The table's relationships with other data entities are crucial for comprehensive user analysis and segmentation.
Tags	`pseudonymous` `user data` `GA4`
Columns	`audiences` , `device` , `geo` , `last_updated_date` , `occurrence_date` , `privacy_info` , `pseudo_user_id` ,

Field	Value
	`stream_id`, `user_info`, `user_ltv`, `user_properties`
Primary Keys	`pseudo_user_id`
Foreign Keys	`user_id`, `event_bundle_sequence_id`, `transaction_id`, `batch_id`, `constituent_id`, `seat_id`
Foreign Keys Referencing Tables	`{'target_table_name': 'events', 'linking_column': 'event_bundle_sequence_id', 'relation_description': 'The events table captures user interactions and is linked to pseudonymous users through event identifiers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'batch summary', 'linking_column': 'batch_id', 'relation_description': 'The batch summary table tracks batches processed and is linked to pseudonymous users through batch identifiers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'dimconstituentsanon', 'linking_column': 'constituent_id', 'relation_description': 'The dimconstituentsanon table contains anonymized constituent information linked to pseudonymous users.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Contribution Output', 'linking_column': 'constituent_id', 'relation_description': 'The Contribution Output table tracks contributions made by constituents linked to pseudonymous users.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'users', 'linking_column': 'user_id', 'relation_description': 'The users table contains user-related data that is linked to pseudonymous users through user identifiers.', 'relationship': 'many-to-one'}`, `{'target_table_name': 'Deferrals and Receiveables Not in Model Yet', 'linking_column': 'transaction_id', 'relation_description': 'This table tracks financial transactions that may be linked`

Field	Value
	`to pseudonymous users through transaction identifiers.', 'relationship': 'many-to-one'}, {'target_table_name': 'Ticket Seat ID', 'linking_column': 'seat_id', 'relation_description': 'The Ticket Seat ID table contains details about ticket seats that may be linked to pseudonymous users through seat identifiers.', 'relationship': 'many-to-one'}, {'target_table_name': 'Contribution Transaction Link', 'linking_column': 'transaction_id', 'relation_description': 'This table links contribution transactions to their details, potentially connecting to pseudonymous users through transaction identifiers.', 'relationship': 'many-to-one'}, {'target_table_name': 'users', 'linking_column': 'pseudo_user_id', 'relation_description': 'References users: The pseudonymous users table references users to maintain a link between pseudonymous identifiers and user profiles.', 'relationship': 'many-to-one'}`
Primary Keys Referencing Tables	`{'to_table': 'members', 'linking_column': 'membership_id', 'relation_description': 'The members table tracks membership details that may reference pseudonymous users through membership identifiers.', 'relationship': 'one-to-many'}, {'to_table': 'events', 'linking_column': 'user_id', 'relation_description': 'Referenced by events: Events are tracked for users identified by pseudonymous identifiers, linking event data to user profiles for behavioral analysis.', 'relationship': 'one-to-many'}`

Column Metadata

Total Columns: 235

Columns for Table: Packages

Column Name	Data Type	Nullable	Description	Tags
constituent_id (`constituent_id`)	`integer`	✅	Identifier for the constituent associated with the package.	`constituent` , `identifier` , `CRM`
package_code (`package_code`)	`string`	✅	Code representing the package.	`package code` , `identifier` , `tracking`
channel (`channel`)	`string`	✅	Channel through which the package is marketed.	`channel` , `marketing` , `analysis`
package_season (`package_season`)	`string`	✅	Season during which the package is offered.	`season` , `marketing` , `package`
appeal (`appeal`)	`string`	✅	Appeal associated with the package.	`appeal` , `marketing` , `strategy`
appeal_id (`appeal_id`)	`integer`	✅	Unique identifier for the appeal associated with the package.	`appeal ID` , `identifier` , `marketing`
package_order_date (`package_order_date`)	`date`	✅	Date when the package order was placed.	`order date` , `tracking` , `sales`
const_type (`const_type`)	`string`	✅	Type of the constituent related to the package.	`constituent type` , `categorization` , `CRM`
order_id (`order_id`)	`integer`	✅	Unique identifier for the order associated with the package.	`order` , `identifier` , `primary key`
campaign_id (`campaign_id`)	`integer`	✅	Unique identifier for the campaign associated with the package.	`campaign ID` , `identifier` , `marketing`

Column Name	Data Type	Nullable	Description	Tags
source (`source`)	`string`	✅	Source of the package information.	`source` , `data provenance` , `tracking`
source_id (`source_id`)	`integer`	✅	Unique identifier for the source of the package information.	`source ID` , `identifier` , `data quality`
mode_of_sale (`mode_of_sale`)	`string`	✅	Mode of sale for the package.	`mode of sale` , `sales` , `customer behavior`
price_type_category (`price_type_category`)	`string`	✅	Category of the price type for the package.	`price type category` , `pricing` , `strategy`
price_type (`price_type`)	`string`	✅	Specific price type for the package.	`price type` , `pricing` , `sales`
campaign (`campaign`)	`string`	✅	Campaign associated with the package.	`campaign` , `marketing` , `analysis`
section (`section`)	`string`	✅	Section of the package information.	`section` , `categorization` , `CRM`
package_size (`package_size`)	`integer`	✅	Size of the package.	`package size` , `inventory` , `customer preference`

Detailed Column Information for Packages

Column 1: constituent_id

Field	Value
ID	`e8f08a6c21e1ae5c8e261207c9045082`
Backend Name	`constituent_id`

Field	Value
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Identifier for the constituent associated with the package.
Embedding Input	The constituent_id column is an integer field that may reference a unique identifier for constituents in the CRM system. It is nullable, indicating that not all packages may be directly linked to a constituent. This column plays a vital role in understanding customer relationships and engagement with specific packages, supporting analytical queries related to constituent behavior and package effectiveness.

Column 2: package_code

Field	Value
ID	`5f183f90f2cce088fa6a833df6639298`
Backend Name	`package_code`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Code representing the package.
Embedding Input	The package_code column is a string field that provides a unique code for each package. This nullable column is useful for internal tracking and reporting, enabling quick identification of packages in various systems and processes.

Column 3: channel

Field	Value
ID	`cd5b3bfc39a283617e5690c4383c7d4e`

Field	Value
Backend Name	`channel`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Channel through which the package is marketed.
Embedding Input	The channel column is a string field that indicates the marketing channel used for the package. This nullable column is significant for analyzing the effectiveness of different marketing channels and optimizing marketing strategies.

Column 4: package_season

Field	Value
ID	`7b30d0b1c74d8ca23676697383d5881d`
Backend Name	`package_season`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Season during which the package is offered.
Embedding Input	The package_season column is a string field that indicates the seasonal context of the package offering. This nullable column is important for marketing strategies, allowing businesses to align package promotions with seasonal trends and customer preferences.

Column 5: appeal

Field	Value
ID	`5f98cfd3499e1a2a2d2dd5f10fc76194`

Field	Value
Backend Name	`appeal`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Appeal associated with the package.
Embedding Input	The appeal column is a string field that describes the appeal or messaging strategy associated with the package. This nullable column is important for understanding how packages are marketed to constituents and can influence customer engagement and conversion rates.

Column 6: appeal_id

Field	Value
ID	`11818ca6353e15336fee16ec64bcd939`
Backend Name	`appeal_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Unique identifier for the appeal associated with the package.
Embedding Input	The appeal_id column is an integer field that serves as a reference to the unique identifier of the appeal linked to the package. This nullable column is essential for analyzing the effectiveness of different appeals in driving customer engagement and sales.

Column 7: package_order_date

Field	Value
ID	`613cb5c73669d0f14700594d9c814b84`
Backend Name	`package_order_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Date when the package order was placed.
Embedding Input	The package_order_date column is a date field that records the date on which the package order was placed. This nullable column is crucial for tracking order timelines and analyzing sales trends over time.

Column 8: const_type

Field	Value
ID	`6a39c6b930e6efa864cb0337781b127c`
Backend Name	`const_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Type of the constituent related to the package.
Embedding Input	The const_type column is a string field that categorizes the type of constituent associated with the package. This nullable column provides context for understanding the demographic or segmentation of the constituent, which is crucial for targeted marketing and analysis of package performance across different constituent types.

Column 9: order_id

Field	Value
ID	`1d070fb2b3c2836e8df17258658ee555`
Backend Name	`order_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Unique identifier for the order associated with the package.
Embedding Input	The order_id column is an integer field that serves as the primary key for the Packages table, uniquely identifying each package entry. This nullable column is essential for linking packages to specific orders, facilitating order tracking and reporting. It plays a critical role in the operational workflow of order management and customer service.

Column 10: campaign_id

Field	Value
ID	`c0c00b23916528cf00f50dded81be160`
Backend Name	`campaign_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Unique identifier for the campaign associated with the package.
Embedding Input	The campaign_id column is an integer field that serves as a reference to the unique identifier of the campaign linked to the package. This nullable column is crucial for establishing relationships between packages and their respective

Field	Value
	marketing campaigns, facilitating detailed analysis of campaign performance.

Column 11: source

Field	Value
ID	`733eaabd669243745d6f15083d16fe4e`
Backend Name	`source`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Source of the package information.
Embedding Input	The source column is a string field that indicates the origin of the package information. This nullable column is useful for tracking data provenance and ensuring data quality in reporting and analysis.

Column 12: source_id

Field	Value
ID	`d3437cb03db116a0163532f23867d012`
Backend Name	`source_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Unique identifier for the source of the package information.
Embedding Input	The source_id column is an integer field that serves as a reference to the unique identifier of the source linked to the package. This nullable column is important for establishing

Field	Value
	relationships between packages and their data sources, facilitating data integrity and quality assurance.

Column 13: mode_of_sale

Field	Value
ID	`bf2d896abbfc5bc78dd0a520430994e7`
Backend Name	`mode_of_sale`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Mode of sale for the package.
Embedding Input	The mode_of_sale column is a string field that describes how the package is sold (e.g., online, in-store). This nullable column is important for understanding sales channels and customer purchasing behavior.

Column 14: price_type_category

Field	Value
ID	`55efe455795965a71a0c318840025521`
Backend Name	`price_type_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Category of the price type for the package.
Embedding Input	The price_type_category column is a string field that categorizes the pricing structure of the package. This nullable

Field	Value
	column is significant for pricing strategy analysis and understanding customer perceptions of value.

Column 15: price_type

Field	Value
ID	`0abd813d38d43436d2cf6fd1272ef700`
Backend Name	`price_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Specific price type for the package.
Embedding Input	The price_type column is a string field that specifies the pricing model applied to the package. This nullable column is crucial for analyzing pricing strategies and their impact on sales performance.

Column 16: campaign

Field	Value
ID	`0ec4a2d6b1827814c9f74b4ff8df2df4`
Backend Name	`campaign`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Campaign associated with the package.
Embedding Input	The campaign column is a string field that describes the marketing campaign linked to the package. This nullable column is significant for analyzing the effectiveness of

Field	Value
	marketing efforts and understanding customer engagement with specific campaigns.

Column 17: section

Field	Value
ID	`1b756ccdc50ce411411ebb583011ae17`
Backend Name	`section`
Data Type	`string`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Section of the package information.
Embedding Input	The section column is a string field that categorizes the package within a specific section of the CRM. This nullable column aids in organizing package data for reporting and analysis, enhancing the usability of the data.

Column 18: package_size

Field	Value
ID	`d3dbeb3f9ca7716e9042cae4352cc09c`
Backend Name	`package_size`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`34aff2970f6552ee316eb546c6c258ca`
Description	Size of the package.
Embedding Input	The package_size column is an integer field that indicates the size of the package. This nullable column is relevant for

Field	Value
	inventory management and understanding customer preferences regarding package dimensions.

Columns for Table: Funds

Column Name	Data Type	Nullable	Description	Tags
trn_count (`trn_count`)	`integer`	✅	Count of transactions associated with the fund.	`transaction count` , `fund activity` , `analytics`
pledge_payment (`pledge_payment`)	`double`	✅	Total amount of pledge payments received.	`pledge payments` , `cash flow` , `financial analysis`
write_off (`write_off`)	`double`	✅	Total amount of funds written off.	`write off` , `financial health` , `bad debts`
cont_dt (`cont_dt`)	`string`	✅	Date of the contribution.	`contribution date` , `fund activities` , `reporting`
fund_no (`fund_no`)	`integer`	✅	Fund number associated with the fund.	`fund number` , `unique identifier` , `fund management`
fyear (`fyear`)	`integer`	✅	Fiscal year associated with the fund.	`fiscal year` , `financial planning` , `reporting`
pmt_method_id (`pmt_method_id`)	`string`	✅	Payment method ID for the fund transactions.	`payment method ID` , `transaction tracking` , `analysis`
pledge_pmt_amt (`pledge_pmt_amt`)	`string`	✅	Amount of pledge payment made.	`pledge payment amount` , `donor behavior` , `tracking`
pmt_count (`pmt_count`)	`integer`	✅		

Column Name	Data Type	Nullable	Description	Tags
			Count of payments made for the fund.	`payment count`, `donor engagement`, `activity tracking`
creditee_type_desc (`creditee_type_desc`)	`string`	✅	Description of the creditee associated with the fund.	`creditee description`, `financial relationships`, `compliance`
gift (`gift`)	`double`	✅	Total amount of gifts received for the fund.	`gift amount`, `donor contributions`, `financial reporting`
total_received (`total_received`)	`double`	✅	Total amount received for the fund.	`total received`, `financial performance`, `reporting`
ref_no (`ref_no`)	`string`	✅	Reference number for the fund transaction.	`reference number`, `transaction identification`, `auditing`
campaign (`campaign`)	`string`	✅	Name of the campaign associated with the fund.	`campaign name`, `fundraising`, `impact analysis`
cont_designation_id (`cont_designation_id`)	`integer`	✅	Contribution designation ID for the fund.	`contribution designation ID`, `unique identifier`, `reporting`
cont_designation (`cont_designation`)	`string`	✅	Contribution designation for the fund.	`contribution designation`, `donor intent`, `compliance`
channel_id (`channel_id`)	`string`	✅	Channel ID for the fund transactions.	`channel ID`, `transaction analysis`, `donor behavior`
	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
channel_desc (`channel_desc`)			Description of the channel for fund transactions.	`channel description` , `transaction context` , `analysis`
creditee_type (`creditee_type`)	`string`	✅	Type of the creditee associated with the fund.	`creditee type` , `financial relationship` , `reporting`
creditee_no (`creditee_no`)	`string`	✅	Creditee number associated with the fund.	`creditee number` , `financial tracking` , `reporting`
display_name (`display_name`)	`string`	✅	Display name for the fund record.	`display name` , `user experience` , `data visualization`
pledge (`pledge`)	`double`	✅	Total amount pledged to the fund.	`pledge amount` , `fundraising` , `financial tracking`
batch_no (`batch_no`)	`string`	✅	Batch number associated with the fund transactions.	`batch number` , `transaction tracking` , `reconciliation`
trn_dt (`trn_dt`)	`string`	✅	Date of the transaction.	`transaction date` , `financial reporting` , `analysis`
fund_desc (`fund_desc`)	`string`	✅	Description of the fund.	`fund description` , `context` , `reporting`
campaign_no (`campaign_no`)	`integer`	✅	Campaign number associated with the fund.	`campaign number` , `fundraising` , `performance analysis`
fname (`fname`)	`string`	✅	First name of the customer	

Column Name	Data Type	Nullable	Description	Tags
			associated with the fund.	`first name`, `donor identification`, `customer records`
creditee_name (`creditee_name`)	`string`	✅	Name of the creditee associated with the fund.	`creditee name`, `financial relationships`, `record management`
sort_name (`sort_name`)	`string`	✅	Sort name for the fund record.	`sort name`, `data organization`, `searchability`
restricted (`restricted`)	`double`	✅	Total amount of restricted funds.	`restricted funds`, `compliance`, `fund allocation`
pmt_method (`pmt_method`)	`string`	✅	Description of the payment method for fund transactions.	`payment method`, `donor preferences`, `transaction analysis`
gift_pmt_amt (`gift_pmt_amt`)	`string`	✅	Amount of gift payment made.	`gift payment amount`, `donor engagement`, `tracking`
customer_no (`customer_no`)	`string`	✅	Customer number associated with the fund.	`customer number`, `donor relationships`, `data management`
lname (`lname`)	`string`	✅	Last name of the customer associated with the fund.	`last name`, `donor identification`, `customer records`

Detailed Column Information for Funds

Column 1: trn_count

Field	Value
ID	`efe6586897fbf24e7d61ee55e1d12bde`
Backend Name	`trn_count`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Count of transactions associated with the fund.
Embedding Input	The 'trn_count' column is an integer field that captures the total number of transactions linked to a specific fund. It is nullable, allowing for flexibility in data entry. This column is essential for understanding the activity level of each fund, aiding in performance analysis and reporting. It is used in aggregations and filters to assess fund engagement and transaction trends.

Column 2: pledge_payment

Field	Value
ID	`3ba011ee758d59e245f9dcec8bc9040a`
Backend Name	`pledge_payment`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount of pledge payments received.
Embedding Input	The 'pledge_payment' column, defined as a double, indicates the total amount of payments received against pledges made to the fund. This nullable field is vital for cash flow analysis

Field	Value
	and helps in understanding the realization of pledged amounts over time.

Column 3: write_off

Field	Value
ID	`1d1be638be74d0daad2e1bca105f3a6c`
Backend Name	`write_off`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount of funds written off.
Embedding Input	The 'write_off' column is a double data type that records the total amount of funds that have been written off due to uncollectibility. This nullable field is significant for financial health assessments and helps in understanding the impact of bad debts on overall fund performance.

Column 4: cont_dt

Field	Value
ID	`f9f58df390cbd182ce38d65710a3ffaf`
Backend Name	`cont_dt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Date of the contribution.
Embedding Input	The 'cont_dt' column is a string that records the date of the contribution made to the fund. This nullable field is essential

Field	Value
	for chronological tracking of fund activities and is often used in reporting and analysis.

Column 5: fund_no

Field	Value
ID	`4e18df24ecbe3fb35c013304a22219f2`
Backend Name	`fund_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Fund number associated with the fund.
Embedding Input	The 'fund_no' column is an integer that uniquely identifies each fund. This nullable field is important for referencing and managing fund records within the system.

Column 6: fyear

Field	Value
ID	`0515d52ebfce99184b0e511708dce2b9`
Backend Name	`fyear`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Fiscal year associated with the fund.
Embedding Input	The 'fyear' column is an integer that indicates the fiscal year for which the fund is applicable. This nullable field is important

Field	Value
	for financial planning and reporting, helping to align fund activities with fiscal periods.

Column 7: pmt_method_id

Field	Value
ID	`aa0125de13599d9f355001be1d21d3d4`
Backend Name	`pmt_method_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Payment method ID for the fund transactions.
Embedding Input	The 'pmt_method_id' column is a string that identifies the payment method used for fund transactions. This nullable field is essential for tracking payment sources and analyzing transaction trends.

Column 8: pledge_pmt_amt

Field	Value
ID	`7f30cffc14318c5345bede0226378fdb`
Backend Name	`pledge_pmt_amt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Amount of pledge payment made.
Embedding Input	The 'pledge_pmt_amt' column is a string that captures the amount of payment made against a pledge. This nullable field

Field	Value
	is useful for tracking payment history and analyzing donor behavior.

Column 9: pmt_count

Field	Value
ID	`e285d912e2d9384fc684e6ef6a285927`
Backend Name	`pmt_count`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Count of payments made for the fund.
Embedding Input	The 'pmt_count' column is an integer that indicates the total number of payments made for the fund. This nullable field is significant for understanding payment activity and donor engagement levels.

Column 10: creditee_type_desc

Field	Value
ID	`eb9a71b28f0c2a67c6aeea8a9b3bf666`
Backend Name	`creditee_type_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Description of the creditee associated with the fund.
Embedding Input	The 'creditee_type_desc' column is a string that provides a description of the creditee type linked to the fund. This nullable field is important for contextualizing financial

Field	Value
	relationships and ensuring compliance with reporting standards.

Column 11: gift

Field	Value
ID	`e6c20bff58fbca7003f221d9369fde30`
Backend Name	`gift`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount of gifts received for the fund.
Embedding Input	The 'gift' column is a double data type that captures the total monetary gifts received for the fund. This nullable field is important for evaluating the fund's performance and donor generosity, and it plays a key role in financial reporting and analysis.

Column 12: total_received

Field	Value
ID	`a2ba5d180940a06bc0ff7abfe2721233`
Backend Name	`total_received`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount received for the fund.
Embedding Input	The 'total_received' column, defined as a double, captures the total amount of money received for the fund from all sources.

Field	Value
	This nullable field is critical for financial analysis and reporting, providing insights into the fund's overall performance.

Column 13: ref_no

Field	Value
ID	`51912e41be90436fb8ea05014db265a1`
Backend Name	`ref_no`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Reference number for the fund transaction.
Embedding Input	The 'ref_no' column is a string that serves as a unique reference for each fund transaction. This nullable field is important for tracking and auditing purposes, ensuring that each transaction can be easily identified.

Column 14: campaign

Field	Value
ID	`1a8117ea6400deb6bc05e7f31bbdf26f`
Backend Name	`campaign`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Name of the campaign associated with the fund.
Embedding Input	The 'campaign' column is a string that provides the name of the campaign linked to the fund. This nullable field is

Field	Value
	important for identifying fundraising initiatives and analyzing their impact on fund performance.

Column 15: cont_designation_id

Field	Value
ID	`722368e6f28b970790fc9e897a9b3fcd`
Backend Name	`cont_designation_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Contribution designation ID for the fund.
Embedding Input	The 'cont_designation_id' column is an integer that serves as a unique identifier for the contribution designation associated with the fund. This nullable field is critical for linking funds to specific designations and ensuring accurate reporting.

Column 16: cont_designation

Field	Value
ID	`9240ee636f932b0bed68e069a02a0d5e`
Backend Name	`cont_designation`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Contribution designation for the fund.
Embedding Input	The 'cont_designation' column is a string that describes the contribution designation associated with the fund. This

Field	Value
	nullable field is important for understanding the purpose of contributions and ensuring compliance with donor intent.

Column 17: channel_id

Field	Value
ID	`dc10600ad9b636536997bf293796eef2`
Backend Name	`channel_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Channel ID for the fund transactions.
Embedding Input	The 'channel_id' column is a string that identifies the channel through which the fund transactions were processed. This nullable field is useful for analyzing transaction sources and understanding donor behavior.

Column 18: channel_desc

Field	Value
ID	`f59cc217dc63f5e0587bfcaa1f9eefa4`
Backend Name	`channel_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Description of the channel for fund transactions.
Embedding Input	The 'channel_desc' column is a string that provides a description of the channel used for fund transactions. This

Field	Value
	nullable field is important for understanding the context of transactions and analyzing their effectiveness.

Column 19: creditee_type

Field	Value
ID	`0d4cb32d2124a35248bfe34f5142fbb6`
Backend Name	`creditee_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Type of the creditee associated with the fund.
Embedding Input	The 'creditee_type' column is a string that indicates the type of creditee linked to the fund. This nullable field is significant for understanding the nature of the financial relationship and ensuring accurate reporting.

Column 20: creditee_no

Field	Value
ID	`9a9bfb7bdd823c1a98fe4cd679241e74`
Backend Name	`creditee_no`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Creditee number associated with the fund.
Embedding Input	

Field	Value
	The 'creditee_no' column is a string that identifies the creditee linked to the fund. This nullable field is essential for tracking financial relationships and ensuring accurate reporting.

Column 21: display_name

Field	Value
ID	`fd71b63c3e01fd3f1e43b15f109eb764`
Backend Name	`display_name`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Display name for the fund record.
Embedding Input	The 'display_name' column is a string that provides a user-friendly name for the fund record. This nullable field is useful for enhancing user experience in reporting and data visualization.

Column 22: pledge

Field	Value
ID	`75a73b62010038eb45e1f8a0f5ad1678`
Backend Name	`pledge`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount pledged to the fund.
Embedding Input	The 'pledge' column is a double data type that represents the total monetary amount pledged to the fund. This field is

Field	Value
	nullable and is crucial for financial tracking and forecasting. It is often used in financial reports and dashboards to assess fundraising performance and donor commitments.

Column 23: batch_no

Field	Value
ID	`37146f819a7aca7541eee92aba31248c`
Backend Name	`batch_no`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Batch number associated with the fund transactions.
Embedding Input	The 'batch_no' column is a string data type that identifies the batch of transactions related to the fund. This nullable field is useful for tracking and reconciling transactions, ensuring accurate financial reporting.

Column 24: trn_dt

Field	Value
ID	`36b9a3fec4041953da57c19ccacd3dd3`
Backend Name	`trn_dt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Date of the transaction.
Embedding Input	The 'trn_dt' column is a string that captures the date of the transaction related to the fund. This nullable field is crucial for

Field	Value
	financial reporting and analysis, providing insights into transaction trends over time.

Column 25: fund_desc

Field	Value
ID	`fc9de4e1948fabe69994311889b07378`
Backend Name	`fund_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Description of the fund.
Embedding Input	The 'fund_desc' column is a string that provides a textual description of the fund. This nullable field is useful for understanding the purpose and context of the fund, aiding in reporting and analysis.

Column 26: campaign_no

Field	Value
ID	`a414ba25059b3034dc8f8f808861cfe1`
Backend Name	`campaign_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Campaign number associated with the fund.
Embedding Input	The 'campaign_no' column is an integer that identifies the campaign linked to the fund. This nullable field is essential for

Field	Value
	tracking fundraising efforts and analyzing campaign performance.

Column 27: fname

Field	Value
ID	`04f5745d5c663f18b23cb7d502ceef18`
Backend Name	`fname`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	First name of the customer associated with the fund.
Embedding Input	The 'fname' column is a string that captures the first name of the customer linked to the fund. This nullable field is important for personalizing donor communications and managing customer data.

Column 28: creditee_name

Field	Value
ID	`db1622badaddf2732c71acf2ba67dd21`
Backend Name	`creditee_name`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Name of the creditee associated with the fund.
Embedding Input	The 'creditee_name' column is a string that captures the name of the creditee linked to the fund. This nullable field is

Field	Value
	important for identifying financial relationships and managing records.

Column 29: sort_name

Field	Value
ID	`82859e4b1b21023046ffdebe3ef2c4a6`
Backend Name	`sort_name`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Sort name for the fund record.
Embedding Input	The 'sort_name' column is a string that captures the name used for sorting fund records. This nullable field is important for organizing data and improving searchability within the system.

Column 30: restricted

Field	Value
ID	`62faac51339bb9ef954cf806f25c6d10`
Backend Name	`restricted`
Data Type	`double`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Total amount of restricted funds.
Embedding Input	The 'restricted' column, represented as a double, indicates the total amount of funds that are restricted for specific purposes. This nullable field is essential for compliance and reporting,

Field	Value
	ensuring that funds are allocated according to donor restrictions.

Column 31: pmt_method

Field	Value
ID	`10cdeaac851087f6b41eeab517e377c4`
Backend Name	`pmt_method`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Description of the payment method for fund transactions.
Embedding Input	The 'pmt_method' column is a string that describes the payment method used for fund transactions. This nullable field is important for understanding payment trends and donor preferences.

Column 32: gift_pmt_amt

Field	Value
ID	`1947e4515b7d3606bfaf705068b2b4ff`
Backend Name	`gift_pmt_amt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Amount of gift payment made.
Embedding Input	

Field	Value
	The 'gift_pmt_amt' column is a string that records the amount of payment made for gifts. This nullable field is important for tracking gift contributions and analyzing donor engagement.

Column 33: customer_no

Field	Value
ID	`7f1792b9ad48fe36e1e85bd66abc709c`
Backend Name	`customer_no`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Customer number associated with the fund.
Embedding Input	The 'customer_no' column is a string that identifies the customer linked to the fund. This nullable field is important for tracking donor relationships and managing customer data.

Column 34: lname

Field	Value
ID	`e2c77dbc85c6217cb53eac39f69f4508`
Backend Name	`lname`
Data Type	`string`
Nullable	Yes
Parent Table ID	`31424eefa1b227d0bd93c9c0d3603f45`
Description	Last name of the customer associated with the fund.
Embedding Input	

Field	Value
	The 'lname' column is a string that captures the last name of the customer linked to the fund. This nullable field is useful for identifying donors and managing customer records.

Columns for Table: members

Column Name	Data Type	Nullable	Description	Tags
membership_category (`membership_category`)	`string`	✅	Category of the membership.	`category` , `membership` , `segmentation`
new_renew_reinstate_status (`new_renew_reinstate_status`)	`string`	✅	Status of the membership regarding new, renewal, or reinstatement.	`status` , `membership` , `renewal`
appeal_id (`appeal_id`)	`integer`	✅	Identifier for the appeal associated with the membership.	`identifier` , `appeal` , `membership`
initdate (`initdate`)	`date`	✅	Date when the membership was initiated.	`initiation` , `date` , `membership`
expdate (`expdate`)	`date`	✅	Date when the membership expires.	`expiration` , `date` , `membership`
source (`source`)	`string`	✅	Source of the membership information.	`source` , `membership` , `acquisition`
macro_level_trend (`macro_level_trend`)	`string`	✅	Macro-level trend associated with the membership.	`trend` , `macro` , `membership`
micro_category_trend (`micro_category_trend`)	`string`	✅	Micro-category trend associated with the membership.	`trend` , `micro` , `membership`

Column Name	Data Type	Nullable	Description	Tags
avc_amount (`avc_amount`)	`double`	✅	Average contribution amount for the membership.	`average` , `amount` , `membership`
membership_level (`membership_level`)	`string`	✅	Level of the membership.	`level` , `membership` , `segmentation`
membership_level_rank (`membership_level_rank`)	`integer`	✅	Rank of the membership level.	`rank` , `membership` , `level`
amount (`amount`)	`double`	✅	Financial amount associated with the membership.	`financial` , `amount` , `revenue`
campaign (`campaign`)	`string`	✅	Campaign associated with the membership.	`campaign` , `membership` , `marketing`
sales_channel (`sales_channel`)	`string`	✅	Sales channel through which the membership was acquired.	`sales` , `channel` , `membership`
membership_level_code (`membership_level_code`)	`string`	✅	Code representing the membership level.	`code` , `membership` , `level`
membership_level_id (`membership_level_id`)	`integer`	✅	Identifier for the membership level.	`identifier` , `membership` , `level`
membership_organization (`membership_organization`)	`string`	✅	Organization associated with the membership.	`organization` , `membership` , `affiliation`
source_id (`source_id`)	`integer`	✅	Identifier for the source associated with the membership.	`identifier` , `source` , `membership`

Column Name	Data Type	Nullable	Description	Tags
membership_id (`membership_id`)	`integer`	✅	Unique identifier for each membership record.	`identifier` , `membership_id` , `primary key`
constituent_id (`constituent_id`)	`integer`	✅	Identifier for the constituent associated with the membership.	`constituent` , `foreign key` , `membership`
appeal (`appeal`)	`string`	✅	Appeal associated with the membership.	`appeal` , `campaign` , `membership`
campaign_id (`campaign_id`)	`integer`	✅	Identifier for the campaign associated with the membership.	`identifier` , `campaign` , `membership`

Detailed Column Information for members

Column 1: membership_category

Field	Value
ID	`04405f9a13b144a6fb132d3989439e81`
Backend Name	`membership_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Category of the membership.
Embedding Input	The 'membership_category' column is a string that categorizes the type of membership, providing context for the nature of the relationship between the constituent and the organization. This nullable field is important for segmentation and targeted communication strategies, allowing organizations to tailor their outreach based on membership types. It is utilized in

Field	Value
	reporting to analyze membership distribution across different categories.

Column 2: new_renew_reinstate_status

Field	Value
ID	`aaa81e1609517bf69fd12855e9d192f5`
Backend Name	`new_renew_reinstate_status`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Status of the membership regarding new, renewal, or reinstatement.
Embedding Input	The 'new_renew_reinstate_status' column is a string that indicates whether the membership is new, a renewal, or a reinstatement. This nullable field is important for tracking membership transitions and understanding member behavior. It is used in reporting to analyze trends in membership renewals and reinstatements.

Column 3: appeal_id

Field	Value
ID	`1705a2d7e7b34f6ae763ab041c784b56`
Backend Name	`appeal_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Identifier for the appeal associated with the membership.

Field	Value
Embedding Input	The 'appeal_id' column is an integer that uniquely identifies the appeal linked to the membership. This nullable field is important for tracking the performance of specific appeals and is used in reporting to analyze the effectiveness of fundraising efforts.

Column 4: initdate

Field	Value
ID	`990f5cf96f540bb5023cdb4a8bcd4050`
Backend Name	`initdate`
Data Type	`date`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Date when the membership was initiated.
Embedding Input	The 'initdate' column is a date field that records the initiation date of the membership. This nullable field is important for tracking the lifecycle of memberships, allowing organizations to analyze membership duration and renewal patterns. It is frequently used in reporting to assess trends in membership growth and retention over time.

Column 5: expdate

Field	Value
ID	`52aed52ef5c6aae703563652f029eecf`
Backend Name	`expdate`
Data Type	`date`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`

Field	Value
Description	Date when the membership expires.
Embedding Input	The 'expdate' column is a date field that indicates the expiration date of the membership. This nullable field is crucial for managing membership renewals and understanding membership lifecycle dynamics. It is used in reporting to identify upcoming expirations and inform retention strategies.

Column 6: source

Field	Value
ID	`cce4d0d83bdc5ba4aad196938590b3b7`
Backend Name	`source`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Source of the membership information.
Embedding Input	The 'source' column is a string that captures the origin of the membership data, providing context for how the membership was acquired. This nullable field is important for understanding the effectiveness of different acquisition channels and is used in reporting to analyze membership sources and their impact on overall membership growth.

Column 7: macro_level_trend

Field	Value
ID	`98a71c7daf4dbaade0db304ae84ac12b`
Backend Name	`macro_level_trend`
Data Type	`string`
Nullable	Yes

Field	Value
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Macro-level trend associated with the membership.
Embedding Input	The 'macro_level_trend' column is a string that captures broader trends related to the membership, providing insights into overall membership dynamics. This nullable field is used in reporting to analyze high-level trends and inform strategic decision-making.

Column 8: micro_category_trend

Field	Value
ID	`8ff14d15b5028f0090c81f112dfc6380`
Backend Name	`micro_category_trend`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Micro-category trend associated with the membership.
Embedding Input	The 'micro_category_trend' column is a string that provides detailed insights into specific trends within membership categories. This nullable field is important for granular analysis and is used in reporting to understand category-specific dynamics.

Column 9: avc_amount

Field	Value
ID	`c1c234aebcb0d07fa56f6388c09657ab`
Backend Name	`avc_amount`
Data Type	`double`

Field	Value
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Average contribution amount for the membership.
Embedding Input	The 'avc_amount' column is a double that represents the average contribution amount associated with the membership. This nullable field is critical for financial analysis and is used in reporting to assess average revenue per member and inform pricing strategies.

Column 10: membership_level

Field	Value
ID	`42d58bc4d2198600386da0847494c347`
Backend Name	`membership_level`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Level of the membership.
Embedding Input	The 'membership_level' column is a string that indicates the tier or level of the membership. This nullable field is important for understanding member benefits and segmentation. It is used in reporting to analyze membership distribution across different levels.

Column 11: membership_level_rank

Field	Value
ID	`c13d49d50f01dea507f98494cb92e03e`
Backend Name	`membership_level_rank`

Field	Value
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Rank of the membership level.
Embedding Input	The 'membership_level_rank' column is an integer that indicates the rank or hierarchy of the membership level. This nullable field is important for understanding the relative value of different membership levels and is used in reporting to analyze member engagement and benefits.

Column 12: amount

Field	Value
ID	`b031c28fc951ffefebd539a8705b3455`
Backend Name	`amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Financial amount associated with the membership.
Embedding Input	The 'amount' column is a double that represents the financial contribution associated with the membership. This nullable field is critical for financial reporting and analysis, enabling organizations to track revenue generated from memberships. It is used in aggregations and calculations to assess the overall financial health of the membership program and is essential for budgeting and forecasting.

Column 13: campaign

Field	Value
ID	`fd6ee951b2f8e9eda50cda4db698cd90`
Backend Name	`campaign`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Campaign associated with the membership.
Embedding Input	The 'campaign' column is a string that identifies the campaign linked to the membership. This nullable field is important for tracking the performance of various campaigns and understanding their impact on membership acquisition. It is used in reporting to evaluate campaign effectiveness and inform future marketing strategies.

Column 14: sales_channel

Field	Value
ID	`4b276fc91a01244939e78343098bd745`
Backend Name	`sales_channel`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Sales channel through which the membership was acquired.
Embedding Input	The 'sales_channel' column is a string that indicates the channel through which the membership was sold or acquired. This nullable field is crucial for analyzing sales performance and understanding the effectiveness of different sales strategies. It is used in reporting to assess channel performance and inform sales tactics.

Column 15: membership_level_code

Field	Value
ID	`9807f78fb2dc2502797a4c1cc6de9836`
Backend Name	`membership_level_code`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Code representing the membership level.
Embedding Input	The 'membership_level_code' column is a string that provides a coded representation of the membership level. This nullable field is useful for data processing and integration purposes, allowing for efficient categorization and reporting.

Column 16: membership_level_id

Field	Value
ID	`999e02d2919d82abced7ebfebd4fe62b`
Backend Name	`membership_level_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Identifier for the membership level.
Embedding Input	The 'membership_level_id' column is an integer that uniquely identifies the membership level. This nullable field is important for establishing relationships with membership level definitions and is used in reporting to analyze membership distribution by level.

Column 17: membership_organization

Field	Value
ID	`80d11b79671df8cd3bdf3a9aca409aae`
Backend Name	`membership_organization`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Organization associated with the membership.
Embedding Input	The 'membership_organization' column is a string that identifies the organization linked to the membership. This nullable field is important for understanding organizational affiliations and is used in reporting to analyze membership distribution across different organizations.

Column 18: source_id

Field	Value
ID	`c09e0d1ec8eb93e2800db35b91f3cdee`
Backend Name	`source_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Identifier for the source associated with the membership.
Embedding Input	The 'source_id' column is an integer that uniquely identifies the source of the membership data. This nullable field is important for understanding data origins and is used in reporting to analyze the effectiveness of different membership acquisition sources.

Column 19: membership_id

Field	Value
ID	`479c2e33c3d7a7748e9299d35166d46f`
Backend Name	`membership_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Unique identifier for each membership record.
Embedding Input	The 'membership_id' column is an integer that serves as the primary key for the members table, uniquely identifying each membership entry. It is nullable, indicating that there may be instances where this value is not present. This column is crucial for establishing relationships with other tables and ensuring data integrity within the CRM system. It is used in joins and filters to retrieve specific membership records and is essential for reporting and analytics related to membership management.

Column 20: constituent_id

Field	Value
ID	`34b278d1cc55a8cbf2d4fa4ac680d3cd`
Backend Name	`constituent_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Identifier for the constituent associated with the membership.
Embedding Input	The 'constituent_id' column is an integer that links each membership record to a specific constituent within the CRM. This nullable field is essential for establishing relationships

Field	Value
	between members and their corresponding constituent profiles. It plays a vital role in data retrieval processes, allowing for the aggregation of membership data by constituent, and is frequently used in reporting and analysis to understand member demographics and engagement levels.

Column 21: appeal

Field	Value
ID	`614904919995c2ed90c0e27dd107fcf6`
Backend Name	`appeal`
Data Type	`string`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`
Description	Appeal associated with the membership.
Embedding Input	The 'appeal' column is a string that describes the specific appeal or campaign that led to the membership acquisition. This nullable field is essential for analyzing the effectiveness of fundraising appeals and understanding member motivations. It is used in reporting to assess the success of different appeals in driving membership growth.

Column 22: campaign_id

Field	Value
ID	`4708a049c23ce6c8de8dbf8b01d2a1d2`
Backend Name	`campaign_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`05aa1e68e77af4f01193c14263d27f43`

Field	Value
Description	Identifier for the campaign associated with the membership.
Embedding Input	The 'campaign_id' column is an integer that uniquely identifies the campaign linked to the membership. This nullable field is important for tracking campaign performance and is used in reporting to analyze the impact of campaigns on membership acquisition.

Columns for Table: Appeal Source Structure

Column Name	Data Type	Nullable	Description	Tags
campaign_no (`campaign_no`)	`integer`	✅	Unique identifier for the campaign associated with the appeal.	`identifier` , `campaign` , `appeal`
source_type (`source_type`)	`string`	✅	Type of the source associated with the appeal.	`type` , `source` , `appeal`
source_keycode (`source_keycode`)	`string`	✅	Keycode associated with the source of the appeal.	`keycode` , `source` , `appeal`
num_contacts (`num_contacts`)	`integer`	✅	Number of contacts made regarding the appeal.	`contacts` , `appeal` , `engagement`
campaign_category (`campaign_category`)	`string`	✅	Category of the campaign associated with the appeal.	`category` , `campaign` , `appeal`
fyear (`fyear`)	`integer`	✅	Fiscal year in which the appeal campaign is active.	`fiscal year` , `campaign` , `appeal`
appeal_desc (`appeal_desc`)	`string`	✅	Description of the appeal.	`description` , `appeal` , `campaign`
	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
source_name (`source_name`)			Name of the source associated with the appeal.	`name` , `source` , `appeal`
source_group (`source_group`)	`string`	✅	Group classification of the source associated with the appeal.	`group` , `source` , `appeal`
source_hotlist_status (`source_hotlist_status`)	`string`	✅	Status of the source in the hotlist.	`hotlist` , `source` , `appeal`
campaign_desc (`campaign_desc`)	`string`	✅	Description of the campaign associated with the appeal.	`description` , `campaign` , `appeal`
appeal_no (`appeal_no`)	`integer`	✅	Unique identifier for the appeal.	`identifier` , `appeal` , `campaign`
source_no (`source_no`)	`integer`	✅	Unique identifier for the source of the appeal.	`identifier` , `source` , `appeal`
source_provider (`source_provider`)	`string`	✅	Provider of the source associated with the appeal.	`provider` , `source` , `appeal`
source_inactive (`source_inactive`)	`string`	✅	Indicates if the source is inactive.	`inactive` , `source` , `appeal`
acq_dt (`acq_dt`)	`string`	✅	Acquisition date of the appeal.	`acquisition` , `appeal` , `date`
appeal_category (`appeal_category`)	`string`	✅	Category of the appeal.	`category` , `appeal` , `campaign`
media_type (`media_type`)	`string`	✅	Type of media associated with the appeal.	`media` , `appeal` , `campaign`

Detailed Column Information for Appeal Source Structure

Column 1: campaign_no

Field	Value
ID	`fa12ae1aaf730273022be2d26cb19aa6`
Backend Name	`campaign_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Unique identifier for the campaign associated with the appeal.
Embedding Input	The 'campaign_no' column is an integer field that serves as a unique identifier for each campaign linked to an appeal. It is nullable, allowing for flexibility in data entry. This column is essential for filtering and joining with other tables that track campaign-related metrics and performance. It plays a significant role in operational reporting and analytics, enabling users to assess the effectiveness of various campaigns over time.

Column 2: source_type

Field	Value
ID	`ac743c86632ba3148d81221b2b664a28`
Backend Name	`source_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Type of the source associated with the appeal.
Embedding Input	The 'source_type' column is a string field that categorizes the type of source linked to the appeal. This nullable field helps in

Field	Value
	organizing sources into distinct groups for better analysis and reporting. It is instrumental in filtering data and understanding the types of sources that are most effective in generating appeals.

Column 3: source_keycode

Field	Value
ID	`9ad35c3287029ff0fa364480f7619a00`
Backend Name	`source_keycode`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Keycode associated with the source of the appeal.
Embedding Input	The 'source_keycode' column is a string field that provides a keycode related to the source linked to the appeal. This nullable field is important for identifying specific attributes of the source, aiding in data integrity and reporting.

Column 4: num_contacts

Field	Value
ID	`fde91ea6bca4b68af8b45164cc1f7914`
Backend Name	`num_contacts`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Number of contacts made regarding the appeal.

Field	Value
Embedding Input	The 'num_contacts' column is an integer field that indicates the number of contacts made in relation to the appeal. This nullable field is important for assessing engagement levels and the effectiveness of outreach efforts, aiding in operational analysis and reporting.

Column 5: campaign_category

Field	Value
ID	`82a803ba2adfffeedd4274a8eda6c0ba`
Backend Name	`campaign_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Category of the campaign associated with the appeal.
Embedding Input	The 'campaign_category' column is a string field that categorizes the campaign linked to the appeal. This nullable field helps in organizing campaigns into distinct groups for better analysis and reporting. It is instrumental in filtering data and understanding the types of campaigns that are most effective in generating appeals.

Column 6: fyear

Field	Value
ID	`e27be7bef2bde95db4c1ebbbd31055e9`
Backend Name	`fyear`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`

Field	Value
Description	Fiscal year in which the appeal campaign is active.
Embedding Input	The 'fyear' column is an integer field representing the fiscal year during which the appeal campaign is active. This nullable field is important for temporal analysis, allowing users to track the performance of campaigns over different fiscal periods and assess trends in appeal generation.

Column 7: appeal_desc

Field	Value
ID	`a9c124489fb566198d98c86876e68bf3`
Backend Name	`appeal_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Description of the appeal.
Embedding Input	The 'appeal_desc' column is a string field that provides a detailed description of the appeal. This nullable field is vital for understanding the context and specifics of each appeal, aiding in qualitative analysis and reporting. It is often used in conjunction with other fields to provide a comprehensive view of appeal activities.

Column 8: source_name

Field	Value
ID	`74563b38e55b47ce78b09527d17d8557`
Backend Name	`source_name`
Data Type	`string`
Nullable	Yes

Field	Value
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Name of the source associated with the appeal.
Embedding Input	The 'source_name' column is a string field that provides the name of the source linked to the appeal. This nullable field is crucial for identifying and understanding the origins of appeals, aiding in qualitative analysis and reporting. It is often used in conjunction with other fields to provide a comprehensive view of appeal sources.

Column 9: source_group

Field	Value
ID	`00e4f2d87c5b30f7fc68ba00f5610ab4`
Backend Name	`source_group`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Group classification of the source associated with the appeal.
Embedding Input	The 'source_group' column is a string field that classifies the source into a specific group. This nullable field is important for organizing sources and understanding their relationships, aiding in reporting and analysis of appeal effectiveness across different groups.

Column 10: source_hotlist_status

Field	Value
ID	`8a9d821620840e922e3bbcae0d1ba14e`
Backend Name	`source_hotlist_status`
Data Type	`string`

Field	Value
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Status of the source in the hotlist.
Embedding Input	The 'source_hotlist_status' column is a string field that indicates the status of the source in relation to a hotlist. This nullable field is crucial for identifying sources that require special attention or monitoring, aiding in operational management and reporting.

Column 11: campaign_desc

Field	Value
ID	`b53ccad4d8cbe8c77e6f12b12ab10b3d`
Backend Name	`campaign_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Description of the campaign associated with the appeal.
Embedding Input	The 'campaign_desc' column is a string field that provides a textual description of the campaign linked to the appeal. This nullable field allows for detailed information about the campaign's objectives, strategies, and target audience. It is crucial for understanding the context of the appeal and is often used in reporting and analysis to provide insights into campaign performance and effectiveness.

Column 12: appeal_no

Field	Value
ID	`0df456432197eeee8b05d8c2ac1764f9`

Field	Value
Backend Name	`appeal_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Unique identifier for the appeal.
Embedding Input	The 'appeal_no' column is an integer field that serves as a unique identifier for each appeal. This nullable field is critical for linking appeals to their respective campaigns and sources, facilitating data integrity and relational mapping within the CRM system. It is essential for reporting and analytics, enabling users to track individual appeals and their outcomes.

Column 13: source_no

Field	Value
ID	`32cac411b5185e1f7eb38bf661f00695`
Backend Name	`source_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Unique identifier for the source of the appeal.
Embedding Input	The 'source_no' column is an integer field that serves as a unique identifier for the source associated with the appeal. This nullable field is important for linking appeals to their respective sources, ensuring data integrity and facilitating relational mapping within the CRM system. It is essential for reporting and analytics, enabling users to track the effectiveness of different sources in generating appeals.

Column 14: source_provider

Field	Value
ID	`724ab2b2bda05c0a25bbf3ff6235dcb4`
Backend Name	`source_provider`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Provider of the source associated with the appeal.
Embedding Input	The 'source_provider' column is a string field that identifies the provider of the source linked to the appeal. This nullable field is crucial for understanding the origins of appeals and the entities involved in their generation, aiding in qualitative analysis and reporting.

Column 15: source_inactive

Field	Value
ID	`40615e4e901af0bbd9389ac7eb798979`
Backend Name	`source_inactive`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Indicates if the source is inactive.
Embedding Input	The 'source_inactive' column is a string field that indicates whether the source associated with the appeal is inactive. This nullable field is important for managing the lifecycle of sources and ensuring that only active sources are considered in reporting and analysis.

Column 16: acq_dt

Field	Value
ID	`6f0db1d64c6a5849649c4554711372a4`
Backend Name	`acq_dt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Acquisition date of the appeal.
Embedding Input	The 'acq_dt' column is a string field that records the acquisition date of the appeal. This nullable field is essential for tracking the timeline of appeals and understanding their lifecycle, aiding in temporal analysis and reporting.

Column 17: appeal_category

Field	Value
ID	`9dcbecb05070360f93a1e2d588e35507`
Backend Name	`appeal_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Category of the appeal.
Embedding Input	The 'appeal_category' column is a string field that categorizes the appeal for better organization and analysis. This nullable field allows for the classification of appeals into different types, which is useful for reporting and understanding the nature of appeals being processed.

Column 18: media_type

Field	Value
ID	`6332d9d3d3d9f91199e3dabced422df1`
Backend Name	`media_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`56e84cd62d98d48a23850f5165baf071`
Description	Type of media associated with the appeal.
Embedding Input	The 'media_type' column is a string field that categorizes the type of media linked to the appeal. This nullable field is important for understanding the channels through which appeals are communicated, aiding in analysis and reporting of media effectiveness.

Columns for Table: Contact Types Relationships

Column Name	Data Type	Nullable	Description	Tags
relationship_a1_a2_indicator (`relationship_a1_a2_indicator`)	`integer`	✅	Indicator for the relationship status between customers.	`relationship_status`, `indicator`, `customer`
relationship_customer__ (`relationship_customer__`)	`integer`	✅	Identifier for the related customer in the relationship.	`relationship`, `customer`, `link`
relationship_type (`relationship_type`)	`string`	✅	Type of relationship between customers.	`relationship_type`, `description`, `customer_interaction`

Column Name	Data Type	Nullable	Description	Tags
customer_no (`customer_no`)	`integer`	✅	Unique identifier for each customer.	`identifier` , `customer` , `primary_key`
customer_type_desc (`customer_type_desc`)	`string`	✅	Description of the customer type.	`customer_type` , `description` , `segmentation`

Detailed Column Information for Contact Types Relationships

Column 1: relationship_a1_a2_indicator

Field	Value
ID	`c7752fbd3cbd41a9e2055557deca2023`
Backend Name	`relationship_a1_a2_indicator`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`cca1a21794505a661a41bb18a6308170`
Description	Indicator for the relationship status between customers.
Embedding Input	The 'relationship_a1_a2_indicator' column is an integer type that serves as a flag or indicator for the status of the relationship between two customers. This nullable column is important for operational processes that require tracking the state of customer relationships, such as active, inactive, or pending. It supports analytical queries by enabling filtering based on relationship status, which can inform marketing strategies and customer engagement efforts. The values in this column are expected to follow a defined set of rules or codes that represent various relationship statuses.

Column 2: relationship_customer__

Field	Value
ID	`0673dc7372d22f6df5aaf358b1c25353`
Backend Name	`relationship_customer__`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`cca1a21794505a661a41bb18a6308170`
Description	Identifier for the related customer in the relationship.
Embedding Input	The 'relationship_customer__' column is an integer type that indicates the identifier of the customer involved in a relationship with another customer. This nullable column is crucial for establishing links between customers, enabling the analysis of customer interactions and relationships. It supports the relational integrity of the data model by allowing for joins with other customer-related tables, facilitating insights into customer networks and relationship dynamics. The column is expected to contain values that correspond to valid customer identifiers within the CRM system.

Column 3: relationship_type

Field	Value
ID	`4c8b3310a7ae33286f58aa82de8a184b`
Backend Name	`relationship_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`cca1a21794505a661a41bb18a6308170`
Description	Type of relationship between customers.
Embedding Input	The 'relationship_type' column is a string type that describes the nature of the relationship between customers. This

Field	Value
	nullable column is essential for categorizing the types of interactions or connections that exist, such as familial, business, or social relationships. It enhances the analytical capabilities of the CRM by allowing users to filter and report on specific relationship types, providing insights into customer engagement and interaction patterns. The values in this column may be predefined based on business logic or derived from user input.

Column 4: customer_no

Field	Value
ID	`e785c25d05cd117785333a30a8f87d04`
Backend Name	`customer_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`cca1a21794505a661a41bb18a6308170`
Description	Unique identifier for each customer.
Embedding Input	The 'customer_no' column is an integer type that serves as the primary key for the Contact Types Relationships table. It is nullable, allowing for flexibility in data entry. This column is essential for linking customer records across various tables within the CRM system, facilitating joins and aggregations in analytical queries. It is expected to follow a consistent format, representing unique customer identifiers that may be sourced from external systems or generated internally. The column plays a crucial role in maintaining data integrity and supporting operational processes related to customer management.

Column 5: customer_type_desc

Field	Value
ID	`51015eba3717077b53963d64e2833e3e`

Field	Value
Backend Name	`customer_type_desc`
Data Type	`string`
Nullable	Yes
Parent Table ID	`cca1a21794505a661a41bb18a6308170`
Description	Description of the customer type.
Embedding Input	The 'customer_type_desc' column is a string type that provides a textual description of the type of customer represented in the table. This column is nullable and is used to categorize customers based on their characteristics or behaviors, which is vital for segmentation and targeted marketing strategies. It supports analytical processes by enabling filtering and reporting based on customer types, enhancing the understanding of customer demographics and preferences. The values in this column may be derived from business rules or external classifications.

Columns for Table: Contribution Transaction Link

Column Name	Data Type	Nullable	Description	Tags
mode_of_sale_category (`mode_of_sale_category`)	`string`	✅	Category of the mode of sale.	`mode` , `sale` , `category`
transaction_amount (`transaction_amount`)	`double`	✅	Amount of money involved in the transaction.	`amount` , `financial` , `transaction`
transaction_type (`transaction_type`)	`string`	✅	Type of transaction being recorded.	`transaction` , `type` , `categorization`
debit_amount (`debit_amount`)	`double`	✅	Amount of money debited in the transaction.	`debit` , `amount` , `financial`
sales_channel (`sales_channel`)	`string`	✅	Channel through which the	`sales` , `channel` , `transaction`

Column Name	Data Type	Nullable	Description	Tags
			transaction was made.	
batch_id (`batch_id`)	`integer`	✅	Identifier for the batch associated with the transaction.	`batch` , `identifier` , `link`
gl_entry_type (`gl_entry_type`)	`string`	✅	Type of general ledger entry for the transaction.	`ledger` , `entry type` , `financial`
campaign_id (`campaign_id`)	`integer`	✅	Identifier for the campaign associated with the transaction.	`campaign` , `identifier` , `link`
credit_amount (`credit_amount`)	`double`	✅	Amount of money credited in the transaction.	`credit` , `amount` , `financial`
mode_of_sale (`mode_of_sale`)	`string`	✅	Mode of sale for the transaction.	`mode` , `sale` , `transaction`
contribution_id (`contribution_id`)	`integer`	✅	Identifier for the contribution associated with the transaction.	`contribution` , `identifier` , `link`
transaction_id (`transaction_id`)	`integer`	✅	Unique identifier for the transaction.	`transaction` , `identifier` , `primary key`
fund_id (`fund_id`)	`integer`	✅	Identifier for the fund associated with the transaction.	`fund` , `identifier` , `link`
transaction_category (`transaction_category`)	`string`	✅	Category of the transaction.	`category` , `transaction` , `classification`
gl_account (`gl_account`)	`string`	✅	General ledger account	`ledger` , `account` , `financial`

Column Name	Data Type	Nullable	Description	Tags
			associated with the transaction.	
days_in_date (`days_in_date`)	`date`	✅	Date associated with the transaction.	`date` , `transaction` , `time`

Detailed Column Information for Contribution Transaction Link

Column 1: mode_of_sale_category

Field	Value
ID	`8dfd6a078278e78eca7f4df7594992d8`
Backend Name	`mode_of_sale_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Category of the mode of sale.
Embedding Input	The mode_of_sale_category column is a string field that categorizes the mode of sale, providing insights into transaction methods and customer preferences. This nullable field is important for understanding trends in payment methods and their impact on financial performance. It aids in reporting and analysis of sales channels.

Column 2: transaction_amount

Field	Value
ID	`fad988b55c06ff555ee977160194ac6e`
Backend Name	`transaction_amount`
Data Type	`double`

Field	Value
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Amount of money involved in the transaction.
Embedding Input	The transaction_amount column is a double field that captures the monetary value of the transaction. This nullable field is critical for financial analysis, reporting, and budgeting processes. It is expected to be used in aggregations and calculations to derive insights into total contributions, revenue generation, and financial performance.

Column 3: transaction_type

Field	Value
ID	`ed5c82c0bb7f68850462a39c4c4f08b4`
Backend Name	`transaction_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Type of transaction being recorded.
Embedding Input	The transaction_type column is a string field that specifies the nature of the transaction, such as 'donation', 'refund', or 'purchase'. This nullable field is essential for categorizing transactions and understanding their implications for financial reporting and analysis. It aids in filtering and segmenting transaction data for targeted reporting.

Column 4: debit_amount

Field	Value
ID	`26e093f772931582d96daec895948e98`

Field	Value
Backend Name	`debit_amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Amount of money debited in the transaction.
Embedding Input	The debit_amount column is a double field that captures the amount debited in the transaction. This nullable field is critical for financial reporting and analysis, particularly in understanding outflows and expenditures. It is expected to be used in aggregations and calculations to derive insights into total debits and financial performance.

Column 5: sales_channel

Field	Value
ID	`eb39d815c49e8fac1561d6d472d9bf6f`
Backend Name	`sales_channel`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Channel through which the transaction was made.
Embedding Input	The sales_channel column is a string field that indicates the medium through which the transaction occurred, such as 'online', 'in-person', or 'phone'. This nullable field is important for understanding customer engagement and transaction trends across different channels. It aids in reporting and analysis of sales performance and donor behavior.

Column 6: batch_id

Field	Value
ID	`5f3765e88b265e632a3b8e9f44579eb8`
Backend Name	`batch_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Identifier for the batch associated with the transaction.
Embedding Input	The batch_id column is an integer field that links transactions to their respective batches, allowing for grouped processing and reporting of transactions. This nullable field indicates that not all transactions may belong to a batch. It is significant for operational reporting and analysis, particularly in understanding transaction flows and batch processing efficiencies.

Column 7: gl_entry_type

Field	Value
ID	`5fc4a961596bb6eda1de64dd7f811c18`
Backend Name	`gl_entry_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Type of general ledger entry for the transaction.
Embedding Input	The gl_entry_type column is a string field that categorizes the transaction based on its general ledger entry type. This nullable field is important for financial reporting and analysis, as it helps in understanding the nature of the transaction and its impact on financial statements. It may include values such

Field	Value
	as 'debit' or 'credit', providing insights into the financial operations of the organization.

Column 8: campaign_id

Field	Value
ID	`cb02743764f1d929ed13d91bc90e9fb7`
Backend Name	`campaign_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Identifier for the campaign associated with the transaction.
Embedding Input	The campaign_id column is an integer field that links the transaction to a specific campaign, facilitating analysis of fundraising efforts and campaign performance. This nullable field indicates that not all transactions may be associated with a campaign. It is significant for reporting on campaign effectiveness and donor engagement.

Column 9: credit_amount

Field	Value
ID	`eaca8eb49d449b70a456976c2adb4292`
Backend Name	`credit_amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Amount of money credited in the transaction.

Field	Value
Embedding Input	The credit_amount column is a double field that captures the amount credited in the transaction. This nullable field is important for financial reporting and analysis, particularly in understanding the inflow of funds and overall financial health. It is expected to be used in aggregations and calculations to derive insights into total credits and revenue.

Column 10: mode_of_sale

Field	Value
ID	`38f035b07c2070380f46e6d6831c87da`
Backend Name	`mode_of_sale`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Mode of sale for the transaction.
Embedding Input	The mode_of_sale column is a string field that specifies the method used to complete the transaction, such as 'credit card', 'cash', or 'check'. This nullable field is significant for analyzing transaction methods and understanding customer preferences. It is expected to be used in reporting and analysis of sales performance.

Column 11: contribution_id

Field	Value
ID	`df6ed6e962841ceddd35e41636b69625`
Backend Name	`contribution_id`
Data Type	`integer`
Nullable	Yes

Field	Value
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Identifier for the contribution associated with the transaction.
Embedding Input	The contribution_id column is an integer field that serves as a reference to the specific contribution linked to the transaction. It is nullable, indicating that not all transactions may have an associated contribution. This column is crucial for establishing relationships with other tables that detail contributions, enabling comprehensive reporting and analysis of fundraising efforts. It is expected to be used in joins and filters when analyzing transaction data in relation to contributions.

Column 12: transaction_id

Field	Value
ID	`6fd5bd7b72cacbedbd6a9e890e33941c`
Backend Name	`transaction_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Unique identifier for the transaction.
Embedding Input	The transaction_id column is an integer field that uniquely identifies each transaction within the Contribution Transaction Link table. This primary key is essential for maintaining data integrity and ensuring accurate retrieval of transaction records. It is nullable, which may indicate that certain transactions are not yet finalized or linked. This column plays a pivotal role in establishing relationships with other tables that track transaction details, facilitating comprehensive analysis and reporting.

Column 13: fund_id

Field	Value
ID	`c48c1c236b231f17acba1207634bb34c`
Backend Name	`fund_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Identifier for the fund associated with the transaction.
Embedding Input	The fund_id column is an integer field that links the transaction to a specific fund, allowing for detailed financial tracking and reporting. This nullable field indicates that not all transactions may be associated with a fund. It is important for understanding the allocation of contributions and financial resources within the organization.

Column 14: transaction_category

Field	Value
ID	`736a61d6eaadbd4428be855815a5b6d2`
Backend Name	`transaction_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Category of the transaction.
Embedding Input	The transaction_category column is a string field that classifies the transaction into specific categories, aiding in financial analysis and reporting. This nullable field is essential for segmenting transaction data and understanding trends in contributions and expenditures. It may include categories such as 'event', 'membership', or 'grant'.

Column 15: gl_account

Field	Value
ID	`791843033b80d5e4bfed4e65ffb7bf08`
Backend Name	`gl_account`
Data Type	`string`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	General ledger account associated with the transaction.
Embedding Input	The gl_account column is a string field that identifies the general ledger account linked to the transaction. This nullable field is crucial for financial reporting and ensuring accurate accounting practices. It is expected to be used in financial analysis and reporting to track the impact of transactions on various accounts.

Column 16: days_in_date

Field	Value
ID	`5a64690e1b42098d56cff6b288e56730`
Backend Name	`days_in_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`534ead1b0043932ee1ebb401081f334d`
Description	Date associated with the transaction.
Embedding Input	The days_in_date column is a date field that captures the specific date of the transaction. This nullable field is important for time-based analysis and reporting, allowing for insights into transaction trends over time. It is expected to be used in filters and aggregations to analyze transaction data by date.

Columns for Table: Deferrals and Receiveables Not in Model Yet

Column Name	Data Type	Nullable	Description	Tags
batch_type (`batch_type`)	`string`	✅	Type of the batch for categorization purposes.	`batch type` , `categorization` , `transaction`
days_in_date (`days_in_date`)	`date`	✅	Date associated with the transaction for tracking purposes.	`date` , `transaction` , `tracking`
batch_id (`batch_id`)	`integer`	✅	Identifier for the batch of transactions.	`batch` , `identifier` , `transaction`
post_id (`post_id`)	`integer`	✅	Identifier for the post associated with the transaction.	`post` , `identifier` , `transaction`
transaction_id (`transaction_id`)	`integer`	✅	Unique identifier for each transaction.	`transaction` , `identifier` , `primary key`
contribution_id (`contribution_id`)	`integer`	✅	Identifier for the contribution associated with the transaction.	`contribution` , `identifier` , `transaction`

Detailed Column Information for Deferrals and Receiveables Not in Model Yet

Column 1: batch_type

Field	Value
ID	`f162c810a341d4fe75ba2082a7ab5c14`
Backend Name	`batch_type`
Data Type	`string`

Field	Value
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Type of the batch for categorization purposes.
Embedding Input	The batch_type column is a string that categorizes the type of batch being processed. This nullable field allows for diverse batch classifications, which can enhance reporting and analysis by enabling users to filter transactions based on batch characteristics. It is essential for operational insights and may be referenced in analytical dashboards.

Column 2: days_in_date

Field	Value
ID	`f297c668e36dc6465a99d606fbc63216`
Backend Name	`days_in_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Date associated with the transaction for tracking purposes.
Embedding Input	The days_in_date column is a date type that records the specific date associated with the transaction. This nullable field is important for tracking the timing of transactions, which is critical for cash flow analysis and financial reporting. It may be used in filters and aggregations to analyze trends over time.

Column 3: batch_id

Field	Value
ID	`383c12b97b079a75c0de77794d2fb8a3`

Field	Value
Backend Name	`batch_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Identifier for the batch of transactions.
Embedding Input	The batch_id column is an integer that serves as an identifier for groups of transactions processed together. It is nullable, allowing for flexibility in data entry. This column is crucial for tracking and managing transaction batches, facilitating operational reporting and analysis. It may be used in joins with other tables that reference batch processing.

Column 4: post_id

Field	Value
ID	`049555ec2a7f9808e29e6cce96bfd8c5`
Backend Name	`post_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Identifier for the post associated with the transaction.
Embedding Input	The post_id column is an integer that identifies the specific post related to a transaction. This nullable field allows for optional association with posts, which may be relevant for tracking the origin or context of transactions. It plays a role in operational reporting and may be used in analytical queries to filter or aggregate data based on post associations.

Column 5: transaction_id

Field	Value
ID	`c19351679183625132b93e105df7b977`
Backend Name	`transaction_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Unique identifier for each transaction.
Embedding Input	The transaction_id column is an integer that uniquely identifies each transaction within the table. As the primary key, it is critical for ensuring data integrity and facilitating efficient data retrieval. This nullable field is essential for linking transactions to other financial records and supports various operational and analytical use cases, including reporting and compliance.

Column 6: contribution_id

Field	Value
ID	`7201eaedf87c61ad097612d85980d427`
Backend Name	`contribution_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`e1be0e9d1bc54006abe53dcfaff8a7e1`
Description	Identifier for the contribution associated with the transaction.
Embedding Input	The contribution_id column is an integer that identifies the specific contribution linked to a transaction. This nullable field allows for optional association with contributions, which may be relevant for tracking financial inputs and their impact on overall financial health. It is useful for operational reporting and may be involved in analytical queries.

Columns for Table: production season types

Column Name	Data Type	Nullable	Description	Tags
production_season_id (`production_season_id`)	`integer`	✅	Unique identifier for each production season.	`identifier` , `primary key`
production_id (`production_id`)	`integer`	✅	Identifier for the associated production.	`production link` , `foreign key`
season_id (`season_id`)	`integer`	✅	Identifier for the season.	`season reference` , `foreign key`
season (`season`)	`string`	✅	The season classification.	`season classification` , `description`
type (`type`)	`string`	✅	Type of the production season.	`season type` , `category`
production_season (`production_season`)	`string`	✅	The name of the production season.	`season name` , `description`
performance_id (`performance_id`)	`integer`	✅	Identifier for the performance metrics associated with the production season.	`performance link` , `foreign key`

Detailed Column Information for production season types

Column 1: production_season_id

Field	Value
ID	`7dcd9a346b49a47ea4fda97ac8e731c0`
Backend Name	`production_season_id`
Data Type	`integer`

Field	Value
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	Unique identifier for each production season.
Embedding Input	The 'production_season_id' column is an integer type field that serves as the primary key for the table, uniquely identifying each production season type. It is nullable, which may indicate that some records could be in a transitional state. This column is crucial for maintaining data integrity and establishing relationships with other tables that may reference production seasons. It is commonly used in joins and as a foreign key in related datasets.

Column 2: production_id

Field	Value
ID	`6fbe880d6bf4ba33d00ca7af5f5c1b8b`
Backend Name	`production_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	Identifier for the associated production.
Embedding Input	The 'production_id' column is an integer type field that links the production season to a specific production record. It is nullable, indicating that not all season types may be directly associated with a production entry. This column is significant for establishing relationships with other tables that track production details, enabling comprehensive reporting and analysis.

Column 3: season_id

Field	Value
ID	`f7d87b8b7fd8dc2e4ede1452fa057403`
Backend Name	`season_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	Identifier for the season.
Embedding Input	The 'season_id' column is an integer type field that serves as a reference to the specific season within the production cycle. It is nullable, indicating that not all records may have a direct season association. This column is important for linking to other datasets that provide seasonal context, enhancing the overall understanding of production dynamics.

Column 4: season

Field	Value
ID	`1b71962cf9f0e0997b8e6d924905094f`
Backend Name	`season`
Data Type	`string`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	The season classification.
Embedding Input	The 'season' column is a string type field that provides a classification of the season, offering additional descriptive context. It is nullable, allowing for flexibility in data entry. This column is useful for reporting and analysis, enabling users to categorize and filter production data based on season classifications.

Column 5: type

Field	Value
ID	`c84b24ab7b223e7cf5a5e3a59ed68342`
Backend Name	`type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	Type of the production season.
Embedding Input	The 'type' column is a string type field that categorizes the production season into specific types, providing additional context for analysis. It is nullable, allowing for flexibility in data representation. This column is important for filtering and segmenting production data based on season types, enhancing the analytical capabilities of the dataset.

Column 6: production_season

Field	Value
ID	`852111abdf76a9fdabb7f8c12867506a`
Backend Name	`production_season`
Data Type	`string`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	The name of the production season.
Embedding Input	The 'production_season' column is a string type field that captures the descriptive name of the production season. It is nullable, allowing for flexibility in data entry. This column is essential for identifying and categorizing different production seasons within the table, facilitating easier reporting and

Field	Value
	analysis. It may be used in filters and joins with other tables that reference production seasons.

Column 7: performance_id

Field	Value
ID	`1b51c2ebdf60546aaa4fd3276d63b5ae`
Backend Name	`performance_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`48527682c3aaedf9b960b951869c9d67`
Description	Identifier for the performance metrics associated with the production season.
Embedding Input	The 'performance_id' column is an integer type field that connects the production season to performance metrics. It is nullable, suggesting that some seasons may not have associated performance data. This column is vital for analyzing the effectiveness of different production seasons and their impact on overall performance, facilitating data-driven decision-making.

Columns for Table: Ticket Seat ID

Column Name	Data Type	Nullable	Description	Tags
screen (`screen`)	`string`	✅	The screen designation for the performance.	`screen` , `performance` , `venue`
ticket_id (`ticket_id`)	`integer`	✅	Identifier for the ticket associated with the seat.	`ticket` , `identifier` , `sales`
section (`section`)	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
			The section designation of the seat.	`section`, `venue`, `categorization`
performance_id (`performance_id`)	`integer`	✅	Identifier for the performance associated with the seat.	`performance`, `identifier`, `link`
order_id (`order_id`)	`integer`	✅	Identifier for the order associated with the ticket sale.	`order`, `identifier`, `sales`
mode_of_sale (`mode_of_sale`)	`string`	✅	The mode through which the ticket was sold.	`sales channel`, `mode`, `analytics`
seat_id (`seat_id`)	`integer`	✅	Unique identifier for the seat.	`seat`, `identifier`, `primary key`
seat_num (`seat_num`)	`string`	✅	The number designation of the seat.	`seat number`, `identifier`, `customer experience`
seat_row (`seat_row`)	`string`	✅	The row designation of the seat.	`seat row`, `identifier`, `layout`

Detailed Column Information for Ticket Seat ID

Column 1: screen

Field	Value
ID	`d7d8a3269fc446cca08eb310dc43ea72`
Backend Name	`screen`
Data Type	`string`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`

Field	Value
Description	The screen designation for the performance.
Embedding Input	The 'screen' column is a string field that indicates the specific screen or area where the performance is taking place. This nullable column is important for distinguishing between multiple screens in a venue, aiding in the management of performances and ticket sales. It is used in reporting to analyze performance attendance and sales metrics across different screens.

Column 2: ticket_id

Field	Value
ID	`db2f47d275fc46a06ae3ba877336cf2d`
Backend Name	`ticket_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	Identifier for the ticket associated with the seat.
Embedding Input	The 'ticket_id' column is an integer field that serves as a reference to the specific ticket purchased for a seat. It is nullable, indicating that there may be instances where a seat is not yet assigned to a ticket. This column is crucial for linking seat information to ticket sales and is used in reporting and analytics to track sales performance and customer interactions. It is expected to be updated frequently as tickets are sold and may be involved in joins with other tables related to ticket transactions.

Column 3: section

Field	Value
ID	`0d87ddea4c71a0db1f97a94eaf358fd0`

Field	Value
Backend Name	`section`
Data Type	`string`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	The section designation of the seat.
Embedding Input	The 'section' column is a string field that categorizes the seat within a specific area of the venue. This nullable column is crucial for organizing seating into manageable sections, enhancing the customer experience by allowing for easier navigation and selection of seats. It is utilized in reporting and analytics to assess sales performance across different sections of the venue.

Column 4: performance_id

Field	Value
ID	`bb7fd3ca7dadf411ed2c6ec3461e3d1c`
Backend Name	`performance_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	Identifier for the performance associated with the seat.
Embedding Input	The 'performance_id' column is an integer field that serves as a reference to the specific performance linked to the seat. This nullable column is essential for connecting seat information with performance details, facilitating accurate ticketing and attendance tracking. It is frequently updated as performances are scheduled and is critical for reporting and analytics related to performance attendance and sales.

Column 5: order_id

Field	Value
ID	`dece2fe2f1133b8817fe3b9b6f65cb82`
Backend Name	`order_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	Identifier for the order associated with the ticket sale.
Embedding Input	The 'order_id' column is an integer field that references the specific order associated with the ticket sale for the seat. This nullable column is vital for linking seat assignments to customer orders, supporting operational processes related to sales and customer service. It is expected to be updated frequently as orders are processed and is used in reporting to analyze sales performance.

Column 6: mode_of_sale

Field	Value
ID	`b3b95bc55c4880b23bd881ee244c0000`
Backend Name	`mode_of_sale`
Data Type	`string`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	The mode through which the ticket was sold.
Embedding Input	The 'mode_of_sale' column is a string field that indicates the method used to sell the ticket, such as online, box office, or third-party vendor. This nullable column is important for analyzing sales channels and customer preferences. It supports reporting and analytics to assess the effectiveness of

Field	Value
	different sales strategies and is relevant for operational decision-making.

Column 7: seat_id

Field	Value
ID	`593c684bb118337fd7c0b1c40541c31d`
Backend Name	`seat_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	Unique identifier for the seat.
Embedding Input	The 'seat_id' column is a primary key represented as an integer, uniquely identifying each seat in the venue. This column is essential for maintaining the integrity of seat assignments and is used extensively in relational operations to link seat data with ticketing and performance information. Its nullable nature suggests that there may be scenarios where a seat is not yet assigned. This column plays a vital role in ensuring accurate seat management and reporting.

Column 8: seat_num

Field	Value
ID	`72a7103d6023683606a8308fb93312ed`
Backend Name	`seat_num`
Data Type	`string`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`

Field	Value
Description	The number designation of the seat.
Embedding Input	The 'seat_num' column is a string field that represents the specific number assigned to a seat within a row. This column is nullable, indicating that there may be instances where a seat number is not defined. It is important for customer-facing applications, allowing users to identify their assigned seats easily. The column is utilized in reporting and analytics to provide insights into seating arrangements and customer preferences.

Column 9: seat_row

Field	Value
ID	`e9bf379babaa4dba987e5e47ac15a536`
Backend Name	`seat_row`
Data Type	`string`
Nullable	Yes
Parent Table ID	`88413cb2ffc5d0be5506f90842fa09a8`
Description	The row designation of the seat.
Embedding Input	The 'seat_row' column is a string field that indicates the row in which the seat is located. This nullable column is significant for organizing seating layouts and assisting customers in locating their seats. It is often used in conjunction with 'seat_num' to provide a complete reference for seat identification. The column supports operational processes related to seating arrangements and ticket sales.

Columns for Table: Contribution Output

Column Name	Data Type	Nullable	Description	Tags
appeal_id (`appeal_id`)	`integer`	✅	Identifier for the appeal associated	

Column Name	Data Type	Nullable	Description	Tags
			with the contribution.	`appeal`, `fundraising`, `identifier`
source_id (`source_id`)	`integer`	✅	Identifier for the source of the contribution.	`source`, `identifier`, `fundraising`
campaign_id (`campaign_id`)	`integer`	✅	Identifier for the campaign associated with the contribution.	`campaign`, `identifier`, `fundraising`
constituent_id (`constituent_id`)	`integer`	✅	Unique identifier for each constituent.	`identifier`, `constituent`, `key`
sales_channel (`sales_channel`)	`string`	✅	Channel through which the contribution was made.	`sales channel`, `contribution method`, `fundraising`
amount (`amount`)	`double`	✅	Monetary amount of the contribution.	`amount`, `financial`, `contribution value`
type (`type`)	`string`	✅	Type of contribution (e.g., one-time, recurring).	`type`, `contribution category`, `donor behavior`
worker_constituent_id (`worker_constituent_id`)	`integer`	✅	Identifier for the worker associated with the contribution.	`worker`, `identifier`, `staff`
billing_type (`billing_type`)	`string`	✅	Type of billing associated with the contribution.	`billing`, `payment method`, `financial`
balance_amount (`balance_amount`)	`double`	✅	Balance amount remaining for the contribution.	`balance`, `financial`, `contribution`

Column Name	Data Type	Nullable	Description	Tags
designation (`designation`)	`string`	✅	Designation of the contribution, if applicable.	`designation` , `fund allocation` , `contribution purpose`
contribution_id (`contribution_id`)	`integer`	✅	Unique identifier for each contribution.	`identifier` , `contribution` , `key`
days_in_date (`days_in_date`)	`date`	✅	Date associated with the contribution.	`date` , `contribution timing` , `analytics`
fund_id (`fund_id`)	`integer`	✅	Identifier for the fund associated with the contribution.	`fund` , `identifier` , `allocation`

Detailed Column Information for Contribution Output

Column 1: appeal_id

Field	Value
ID	`3bff22bc5d1bee9a62b94edf6facb328`
Backend Name	`appeal_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Identifier for the appeal associated with the contribution.
Embedding Input	The appeal_id column is an integer that identifies the specific appeal linked to a contribution. This nullable field allows for contributions that may not be tied to a particular appeal. It is used to analyze the effectiveness of different fundraising appeals and campaigns, providing insights into donor behavior and preferences. The column is integral for reporting on

Field	Value
	fundraising performance and is often used in conjunction with other identifiers to generate comprehensive reports.

Column 2: source_id

Field	Value
ID	`aa6caa33e5954cd551e3ae99d893c6e3`
Backend Name	`source_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Identifier for the source of the contribution.
Embedding Input	The source_id column is an integer that identifies the source from which the contribution originated, such as a specific campaign or event. This nullable field is essential for analyzing the effectiveness of different fundraising sources and strategies. It is used in reporting to assess the impact of various sources on overall fundraising performance and donor engagement.

Column 3: campaign_id

Field	Value
ID	`aeb314707c0e16a4a377ddcb5cd8db1d`
Backend Name	`campaign_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Identifier for the campaign associated with the contribution.

Field	Value
Embedding Input	The campaign_id column is an integer that identifies the specific campaign linked to the contribution. This nullable field is crucial for analyzing campaign performance and donor engagement. It supports reporting efforts to evaluate the success of various fundraising campaigns and is often used in conjunction with other identifiers to generate comprehensive analyses.

Column 4: constituent_id

Field	Value
ID	`b7508400022c879bbdff5eb2ecdcacfd`
Backend Name	`constituent_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Unique identifier for each constituent.
Embedding Input	The constituent_id column is an integer that serves as a unique identifier for each constituent in the system. It is nullable, allowing for flexibility in data entry, but is essential for linking contributions to specific individuals. This column is critical for relational integrity and is often used in joins with other tables to retrieve constituent-related information. The data is expected to follow a consistent format, and it plays a significant role in reporting and analytics related to donor contributions.

Column 5: sales_channel

Field	Value
ID	`1b6cb105cc8f12582f635da35c823d09`
Backend Name	`sales_channel`

Field	Value
Data Type	`string`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Channel through which the contribution was made.
Embedding Input	The sales_channel column is a string that describes the method or channel through which the contribution was received, such as online, mail, or event. This nullable field provides valuable context for analyzing contribution patterns and preferences among constituents. Understanding the sales channel is crucial for optimizing fundraising strategies and enhancing donor engagement. It is often used in reporting to segment contributions by channel for targeted analysis.

Column 6: amount

Field	Value
ID	`10f404b700dbdd1887546291fa90961d`
Backend Name	`amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Monetary amount of the contribution.
Embedding Input	The amount column is a double that represents the monetary value of the contribution. This nullable field is essential for financial reporting and analysis, allowing organizations to assess total contributions, average donation sizes, and overall fundraising performance. It is critical for budgeting and forecasting efforts, and it supports various financial metrics and KPIs within the organization.

Column 7: type

Field	Value
ID	`a6309617cfd1d0f1019c3444da0abbcd`
Backend Name	`type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Type of contribution (e.g., one-time, recurring).
Embedding Input	The type column is a string that categorizes the contribution based on its nature, such as one-time or recurring. This nullable field provides insights into donor behavior and preferences, enabling organizations to tailor their fundraising strategies accordingly. It is used in reporting to segment contributions and analyze trends in donor engagement over time.

Column 8: worker_constituent_id

Field	Value
ID	`9fb22b975052c7b6949d3264869f8981`
Backend Name	`worker_constituent_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Identifier for the worker associated with the contribution.
Embedding Input	The worker_constituent_id column is an integer that identifies the worker or staff member associated with the contribution. This nullable field is important for tracking contributions made through specific channels or by specific individuals within the organization. It supports accountability and performance

Field	Value
	analysis of fundraising staff and is often used in reporting to evaluate the effectiveness of individual contributions.

Column 9: billing_type

Field	Value
ID	`147e97935d9ef24e4be0c5663150079a`
Backend Name	`billing_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Type of billing associated with the contribution.
Embedding Input	The billing_type column is a string that describes the type of billing associated with the contribution, such as direct debit or credit card. This nullable field provides context for understanding payment methods and donor preferences. It is important for financial reporting and compliance, ensuring that billing practices align with organizational standards.

Column 10: balance_amount

Field	Value
ID	`8ed1ae3b89446e72805bc276a4528d7e`
Backend Name	`balance_amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Balance amount remaining for the contribution.

Field	Value
Embedding Input	The balance_amount column is a double that represents the remaining balance for the contribution, if applicable. This nullable field is important for tracking outstanding contributions and managing donor accounts. It supports financial reporting and helps organizations maintain accurate records of contributions and balances owed.

Column 11: designation

Field	Value
ID	`32cb2803789877e5d9768d7329e25859`
Backend Name	`designation`
Data Type	`string`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Designation of the contribution, if applicable.
Embedding Input	The designation column is a string that specifies the purpose or designation of the contribution, such as a specific fund or project. This nullable field allows for contributions that may not have a designated purpose. It is important for tracking how funds are allocated and ensuring compliance with donor intent. This column is frequently used in financial reporting and analysis to assess the impact of designated contributions on organizational goals.

Column 12: contribution_id

Field	Value
ID	`07c1dd4dced347507e6a521d53c43424`
Backend Name	`contribution_id`
Data Type	`integer`

Field	Value
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Unique identifier for each contribution.
Embedding Input	The contribution_id column is an integer that serves as a unique identifier for each contribution record. This nullable field is essential for maintaining data integrity and facilitating relationships with other tables. It is used in reporting and analytics to track individual contributions and their impact on overall fundraising efforts. The column ensures that each contribution can be uniquely referenced and analyzed within the system.

Column 13: days_in_date

Field	Value
ID	`7a28cc56f99c74154b8b2b65f5fda5c3`
Backend Name	`days_in_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Date associated with the contribution.
Embedding Input	The days_in_date column is a date type that records the date when the contribution was made. This nullable field is crucial for time-based analysis of contributions, allowing organizations to track trends over time and assess the timing of fundraising efforts. It is often used in reporting to generate time-series analyses and to evaluate the effectiveness of campaigns based on timing.

Column 14: fund_id

Field	Value
ID	`42191fc42f02b89b20e82f094382451e`
Backend Name	`fund_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`a1934e6d3781bed388dc8dd7cb4aecc4`
Description	Identifier for the fund associated with the contribution.
Embedding Input	The fund_id column is an integer that identifies the specific fund to which the contribution is directed. This nullable field is important for tracking contributions against specific fundraising goals and ensuring proper allocation of resources. It is used in reporting to analyze fund performance and donor engagement with various funds. The column supports the organization's financial management and accountability efforts.

Columns for Table: dimconstituentsanon

Column Name	Data Type	Nullable	Description	Tags
constituencies (`constituencies`)	`string`	✅	List of constituencies associated with the constituent.	`constituency` , `affiliation` , `engagement`
constituent_id (`constituent_id`)	`integer`	✅	Unique identifier for each constituent.	`identifier` , `primary key` , `constituent`
primary_address_postcode (`primary_address_postcode`)	`string`	✅	Postcode of the primary address associated with the constituent.	`address` , `postcode` , `demographics`
type (`type`)	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
			Type of constituent, indicating their classification.	`classification`, `constituent type`, `segmentation`

Detailed Column Information for dimconstituentsanon

Column 1: constituencies

Field	Value
ID	`8f9c8eabde6a5e16a2a248d077aa333c`
Backend Name	`constituencies`
Data Type	`string`
Nullable	Yes
Parent Table ID	`e2d3f32dfb61d34aa3060f6cb4ce6f77`
Description	List of constituencies associated with the constituent.
Embedding Input	The constituencies column is a string field that holds information about the constituencies linked to each constituent. This column is nullable, indicating that some constituents may not be associated with any specific constituency. It is valuable for understanding the political or organizational affiliations of constituents, which can inform outreach and engagement strategies. The expected format is a string, and while no sample values are provided, this column is crucial for analyses that require insights into constituency representation and engagement patterns. It may also play a role in compliance and reporting requirements related to constituency-based initiatives.

Column 2: constituent_id

Field	Value
ID	`f45d3b80d377c325c8b107853b8197f6`

Field	Value
Backend Name	`constituent_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`e2d3f32dfb61d34aa3060f6cb4ce6f77`
Description	Unique identifier for each constituent.
Embedding Input	The constituent_id column is an integer field that serves as the primary key for the dimconstituentsanon table, uniquely identifying each constituent record. This column is nullable, indicating that there may be instances where a constituent ID is not available. It plays a crucial role in linking constituent data across various analytical processes and reporting frameworks. The expected format is an integer, and while there are no sample values provided, it is essential for maintaining data integrity and ensuring accurate joins with other related tables. This column is fundamental for operational use cases involving constituent tracking and analysis.

Column 3: primary_address_postcode

Field	Value
ID	`1216d4f8ecb92954c10ef8b7fbf315e6`
Backend Name	`primary_address_postcode`
Data Type	`string`
Nullable	Yes
Parent Table ID	`e2d3f32dfb61d34aa3060f6cb4ce6f77`
Description	Postcode of the primary address associated with the constituent.
Embedding Input	The primary_address_postcode column is a string field that captures the postcode of the primary address for each constituent. This column is nullable, allowing for flexibility in data entry where postcode information may not be available.

Field	Value
	It is significant for demographic analysis and geographic segmentation, enabling the organization to understand the distribution of constituents across different regions. The expected format is a string, and while no sample values are provided, this column is often used in filters and aggregations to derive insights related to location-based outreach strategies.

Column 4: type

Field	Value
ID	`d595716ac76ab555b87b8a69b7cf0ab9`
Backend Name	`type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`e2d3f32dfb61d34aa3060f6cb4ce6f77`
Description	Type of constituent, indicating their classification.
Embedding Input	The type column is a string field that categorizes constituents based on predefined classifications, which may include donor types, engagement levels, or other relevant categories. This column is nullable, suggesting that not all constituents may have a specified type. It is essential for segmentation and targeted communication strategies, allowing the organization to tailor its outreach efforts based on constituent characteristics. The expected format is a string, and while no sample values are provided, this column is integral to analytical processes that involve grouping and filtering constituents for reporting and decision-making.

Columns for Table: Ticket

Column Name	Data Type	Nullable	Description	Tags
appeal (`appeal`)	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
			Appeal associated with the ticket sale.	`appeal`, `fundraising`, `donor behavior`
appeal_id (`appeal_id`)	`integer`	✅	Identifier for the appeal associated with the ticket sale.	`appeal identifier`, `fundraising`, `relationship`
price_type (`price_type`)	`string`	✅	Type of price for the ticket.	`price type`, `pricing strategy`, `analysis`
section (`section`)	`string`	✅	Section associated with the ticket.	`section`, `seating`, `analysis`
ticket_id (`ticket_id`)	`integer`	✅	Unique identifier for the ticket.	`ticket identifier`, `primary key`, `data integrity`
seat_id (`seat_id`)	`integer`	✅	Identifier for the seat associated with the ticket.	`seat identifier`, `seating`, `analysis`
channel (`channel`)	`string`	✅	Channel through which the ticket was sold.	`channel`, `sales`, `analysis`
order_date (`order_date`)	`date`	✅	Date when the ticket was ordered.	`order date`, `sales trends`, `analysis`
price_type_category (`price_type_category`)	`string`	✅	Category of the price type for the ticket.	`price type category`, `pricing strategy`, `analysis`
const_type (`const_type`)	`string`	✅	Type of the constituent associated with the ticket.	`constituent type`, `categorization`, `segmentation`
order_id (`order_id`)	`integer`	✅	Identifier for the order associated with the ticket.	`order`, `identifier`, `transaction`
season (`season`)	`string`	✅		

Column Name	Data Type	Nullable	Description	Tags
			Season during which the ticket is valid.	`season`, `temporal`, `event management`
production_season (`production_season`)	`string`	✅	Production season for the event related to the ticket.	`production season`, `event categorization`, `analysis`
campaign_id (`campaign_id`)	`integer`	✅	Identifier for the campaign associated with the ticket sale.	`campaign identifier`, `marketing`, `relationship`
source_id (`source_id`)	`integer`	✅	Identifier for the source associated with the ticket sale.	`source identifier`, `sales`, `relationship`
mode_of_sale (`mode_of_sale`)	`string`	✅	Mode of sale for the ticket.	`mode of sale`, `sales method`, `analysis`
package_code (`package_code`)	`string`	✅	Code representing the ticket package.	`package code`, `bundled tickets`, `analysis`
constituent_id (`constituent_id`)	`integer`	✅	Identifier for the constituent associated with the ticket.	`constituent`, `identifier`, `relationship`
campaign (`campaign`)	`string`	✅	Campaign associated with the ticket sale.	`campaign`, `marketing`, `performance tracking`
source (`source`)	`string`	✅	Source from which the ticket sale originated.	`source`, `sales channel`, `analysis`
ticket_paid_amount (`ticket_paid_amount`)	`double`	✅	Amount paid for the ticket.	`ticket amount`, `financial reporting`, `revenue`

Detailed Column Information for Ticket

Column 1: appeal

Field	Value
ID	`078c46094957b4377faca80ad7377ce0`
Backend Name	`appeal`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Appeal associated with the ticket sale.
Embedding Input	The appeal column is a string field that describes the specific appeal linked to the ticket sale, providing insight into the motivations behind the purchase. This nullable field is important for understanding donor behavior and tailoring fundraising strategies. It allows for analysis of ticket sales in relation to different appeals, enhancing the organization's ability to engage with constituents effectively.

Column 2: appeal_id

Field	Value
ID	`f7fd31e29c8ce814febcde42deebafac`
Backend Name	`appeal_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Identifier for the appeal associated with the ticket sale.
Embedding Input	The appeal_id column is an integer field that serves as a unique identifier for the appeal linked to the ticket sale. This nullable column is essential for establishing relationships

Field	Value
	between ticket records and appeal details, facilitating analysis of fundraising effectiveness and donor engagement strategies. It supports data integrity and relational queries within the fundraising domain.

Column 3: price_type

Field	Value
ID	`255516ba3a5f5674e708a5fc78e8b1b9`
Backend Name	`price_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Type of price for the ticket.
Embedding Input	The price_type column is a string field that categorizes the pricing structure for the ticket, providing insight into pricing strategies and customer segments. This nullable field is important for analyzing ticket sales performance based on price types, enabling the organization to optimize pricing strategies and enhance revenue generation efforts.

Column 4: section

Field	Value
ID	`dabc7a3fea230d2681e34c83b25e10ed`
Backend Name	`section`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`

Field	Value
Description	Section associated with the ticket.
Embedding Input	The section column is a string field that indicates the specific section related to the ticket, providing context for seating arrangements at events. This nullable field is important for managing ticket sales and customer seating preferences. It enables the organization to analyze ticket sales performance based on section data, enhancing operational efficiency and customer satisfaction.

Column 5: ticket_id

Field	Value
ID	`44c612fe5f1050dc02b1b190ed1a988b`
Backend Name	`ticket_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Unique identifier for the ticket.
Embedding Input	The ticket_id column is an integer field that serves as the primary key for the Ticket table, uniquely identifying each ticket record. This nullable column is essential for maintaining data integrity and supporting relational queries within the database. It is critical for linking ticket records with other related entities and ensuring accurate reporting and analysis of ticket sales data.

Column 6: seat_id

Field	Value
ID	`dbb7813709f16116adcf9228205be0fc`
Backend Name	`seat_id`

Field	Value
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Identifier for the seat associated with the ticket.
Embedding Input	The seat_id column is an integer field that represents the unique identifier for the seat linked to the ticket. This nullable column is important for managing seating arrangements and ensuring accurate ticketing for events. It supports the organization's ability to analyze ticket sales performance based on seating data, enhancing operational efficiency and customer satisfaction.

Column 7: channel

Field	Value
ID	`ac8b47aac47fb25ce76473f38a339cf7`
Backend Name	`channel`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Channel through which the ticket was sold.
Embedding Input	The channel column is a string field that specifies the sales channel used for the ticket transaction, providing insight into customer purchasing behavior. This nullable field is important for analyzing the effectiveness of various sales channels and optimizing marketing strategies. It enables the organization to evaluate ticket sales performance based on channel data, enhancing customer engagement efforts.

Column 8: order_date

Field	Value
ID	`27a6e9720a3afdff7a86a79bf4728cd9`
Backend Name	`order_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Date when the ticket was ordered.
Embedding Input	The order_date column is a date field that captures the specific date on which the ticket was ordered. This nullable field is essential for tracking sales trends over time and understanding customer purchasing patterns. It supports reporting and analysis of ticket sales performance, enabling the organization to make data-driven decisions regarding inventory management and marketing strategies.

Column 9: price_type_category

Field	Value
ID	`499be9605d611d53b76d41e77521911e`
Backend Name	`price_type_category`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Category of the price type for the ticket.
Embedding Input	The price_type_category column is a string field that categorizes the pricing type for the ticket, providing insight into pricing strategies and customer segments. This nullable field is important for analyzing ticket sales performance based

Field	Value
	on price categories, enabling the organization to optimize pricing strategies and enhance revenue generation efforts.

Column 10: const_type

Field	Value
ID	`8f7eafe2f565c1e305df71026cb3fcbc`
Backend Name	`const_type`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Type of the constituent associated with the ticket.
Embedding Input	The const_type column is a string field that categorizes the type of constituent linked to the ticket, providing context for understanding the nature of the ticket purchaser. This nullable field allows for flexibility in ticket sales, accommodating various constituent types such as individuals, organizations, or groups. It is essential for segmentation and analysis of ticket sales data, enabling targeted outreach and tailored marketing efforts based on constituent type.

Column 11: order_id

Field	Value
ID	`21ff34c28eb1109996c478258e5f9937`
Backend Name	`order_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`

Field	Value
Description	Identifier for the order associated with the ticket.
Embedding Input	The order_id column is an integer field that serves as a unique identifier for the order linked to the ticket. This nullable column is critical for tracking and managing ticket sales transactions, allowing for efficient order processing and customer service. It facilitates the relationship between ticket records and order details, enabling comprehensive reporting on sales performance and customer purchasing behavior.

Column 12: season

Field	Value
ID	`d89e51c5b5fe4874b1be4670bb602ac2`
Backend Name	`season`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Season during which the ticket is valid.
Embedding Input	The season column is a string field that indicates the specific season associated with the ticket, providing temporal context for the ticket's validity. This nullable field is important for managing seasonal events and promotions, allowing the organization to analyze ticket sales trends across different seasons and optimize marketing strategies accordingly.

Column 13: production_season

Field	Value
ID	`d29665641a80d5465eddbf782019c766`
Backend Name	`production_season`
Data Type	`string`

Field	Value
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Production season for the event related to the ticket.
Embedding Input	The production_season column is a string field that specifies the production season relevant to the event for which the ticket is issued. This nullable field aids in categorizing events based on their production timelines, supporting planning and promotional activities. It is useful for analyzing ticket sales in relation to specific production cycles and enhancing audience engagement strategies.

Column 14: campaign_id

Field	Value
ID	`dd4cd9630635b915cec8f522f6d018bb`
Backend Name	`campaign_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Identifier for the campaign associated with the ticket sale.
Embedding Input	The campaign_id column is an integer field that serves as a unique identifier for the campaign linked to the ticket sale. This nullable column is crucial for establishing relationships between ticket records and campaign details, facilitating analysis of marketing effectiveness and customer engagement strategies. It supports data integrity and relational queries within the marketing domain.

Column 15: source_id

Field	Value
ID	`831c8f0bd1b8856d12e1e5689e8982f8`
Backend Name	`source_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Identifier for the source associated with the ticket sale.
Embedding Input	The source_id column is an integer field that serves as a unique identifier for the source linked to the ticket sale. This nullable column is crucial for establishing relationships between ticket records and source details, facilitating analysis of sales performance and customer acquisition strategies. It supports data integrity and relational queries within the sales domain.

Column 16: mode_of_sale

Field	Value
ID	`c6463ed34eebc7756c06efe13ac284d2`
Backend Name	`mode_of_sale`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Mode of sale for the ticket.
Embedding Input	The mode_of_sale column is a string field that indicates the method through which the ticket was sold, such as online, in-person, or via phone. This nullable field is important for analyzing sales performance across different modes and optimizing customer engagement strategies. It enables the

Field	Value
	organization to evaluate ticket sales based on the mode of sale, enhancing marketing efforts and operational efficiency.

Column 17: package_code

Field	Value
ID	`52c2e579ddea8e67fc8a6a6fcd08e83c`
Backend Name	`package_code`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Code representing the ticket package.
Embedding Input	The package_code column is a string field that specifies the code associated with the ticket package, providing context for bundled ticket offerings. This nullable field is important for managing ticket sales related to specific packages and promotions. It enables the organization to analyze sales performance based on package offerings, enhancing marketing strategies and customer engagement efforts.

Column 18: constituent_id

Field	Value
ID	`c17d08778e3b0fe1479366bd95cde7bf`
Backend Name	`constituent_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Identifier for the constituent associated with the ticket.

Field	Value
Embedding Input	The constituent_id column is an integer field that represents the unique identifier for the constituent linked to the ticket. This column is nullable, indicating that there may be instances where a ticket is not directly associated with a specific constituent. It plays a crucial role in establishing relationships between ticket records and constituent profiles, facilitating targeted marketing and customer engagement strategies. The data in this column is expected to align with the identifiers used in the constituents table, supporting data integrity and relational queries.

Column 19: campaign

Field	Value
ID	`01489e902c1065584d6d87c9c4077040`
Backend Name	`campaign`
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Campaign associated with the ticket sale.
Embedding Input	The campaign column is a string field that identifies the marketing campaign linked to the ticket sale. This nullable field is essential for tracking the effectiveness of various marketing initiatives and understanding customer acquisition channels. It enables the organization to evaluate campaign performance and optimize future marketing efforts based on ticket sales data.

Column 20: source

Field	Value
ID	`aaa0434360405a34131b6084bc9e2102`
Backend Name	`source`

Field	Value
Data Type	`string`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Source from which the ticket sale originated.
Embedding Input	The source column is a string field that indicates the origin of the ticket sale, providing context for understanding customer acquisition channels. This nullable field is important for analyzing the effectiveness of different sales channels and optimizing marketing strategies. It enables the organization to evaluate sales performance based on source data, enhancing customer engagement efforts.

Column 21: ticket_paid_amount

Field	Value
ID	`5bf3ea29b816e6216c58f7ac5028932b`
Backend Name	`ticket_paid_amount`
Data Type	`double`
Nullable	Yes
Parent Table ID	`f1c790944ccb6fb41f71489900ec4f6d`
Description	Amount paid for the ticket.
Embedding Input	The ticket_paid_amount column is a double field that captures the total amount paid for the ticket. This nullable field is essential for financial reporting and analysis of revenue generated from ticket sales. It supports the organization's ability to evaluate sales performance and make informed decisions regarding pricing strategies and promotional offers.

Columns for Table: Deceased Cont W Last Activity

Column Name	Data Type	Nullable	Description	Tags
customer_last_gift_dt (`customer_last_gift_dt`)	`string`	✅	Date of the last gift made by the customer.	`last gift date` , `customer engagement` , `donation history`
customer_no (`customer_no`)	`integer`	✅	Unique identifier for each customer.	`customer identifier` , `primary key` , `CRM`
customer_last_ticket_dt (`customer_last_ticket_dt`)	`string`	✅	Date of the last ticket purchased by the customer.	`last ticket date` , `customer activity` , `event participation`

Detailed Column Information for Deceased Cont W Last Activity

Column 1: customer_last_gift_dt

Field	Value
ID	`727da54f81c224508c5ed52b037d8e2b`
Backend Name	`customer_last_gift_dt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`4cb3544c21d1881216a12ebf8b4060ec`
Description	Date of the last gift made by the customer.
Embedding Input	The 'customer_last_gift_dt' column is a string field that captures the date of the last gift made by the customer, providing insights into their engagement and contribution history. This column is nullable, which means that there may be cases where this information is not available. It is crucial for analyzing customer behavior and trends in giving, allowing organizations to segment deceased customers based on their

Field	Value
	last contributions. The expected format for this date is a standard string representation, and it is used in reporting and analytical processes to assess the impact of customer contributions over time. This column supports compliance and legacy planning efforts by identifying key dates in customer interactions.

Column 2: customer_no

Field	Value
ID	`2ad46e69bcc50bdf5bbc90486b5ce001`
Backend Name	`customer_no`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`4cb3544c21d1881216a12ebf8b4060ec`
Description	Unique identifier for each customer.
Embedding Input	The 'customer_no' column is an integer field that serves as the primary key for the 'Deceased Cont W Last Activity' table, uniquely identifying each customer record. This column is nullable, indicating that there may be instances where a customer number is not available. As a critical component of the table, 'customer_no' facilitates the linking of customer data across various systems and reports, ensuring accurate tracking and analysis of deceased customers. It plays a vital role in joins and aggregations within analytical queries, supporting operational and compliance needs. The expected format is a non-negative integer, and it is essential for maintaining data integrity and relational structure within the CRM.

Column 3: customer_last_ticket_dt

Field	Value
ID	`69add9cbafd972dc32343bc0c6507f9f`

Field	Value
Backend Name	`customer_last_ticket_dt`
Data Type	`string`
Nullable	Yes
Parent Table ID	`4cb3544c21d1881216a12ebf8b4060ec`
Description	Date of the last ticket purchased by the customer.
Embedding Input	The 'customer_last_ticket_dt' column is a string field that records the date of the last ticket purchased by the customer, serving as an indicator of their engagement with events or services offered by the organization. This column is nullable, indicating that there may be instances where this information is not available. It plays a significant role in understanding customer activity patterns and can be utilized in segmentation analyses for targeted outreach or marketing efforts. The expected format for this date is a standard string representation, and it is essential for reporting and analytical purposes, particularly in evaluating customer loyalty and participation in organizational events. This column aids in compliance and strategic planning by providing insights into customer interactions.

Columns for Table: pseudonymous users

Column Name	Data Type	Nullable	Description	Tags
occurrence_date (`occurrence_date`)	`string`	✅	Indicates the occurrence date of the pseudonymous user's interaction.	`occurrence date` , `temporal analysis` , `user engagement`
audiences (`audiences`)	`string`	✅	Represents the audiences associated with the pseudonymous user.	`audience` , `segmentation` , `marketing`
user_ltv (`user_ltv`)	`string`	✅	Represents the lifetime value of the pseudonymous user.	`lifetime value` , `revenue forecasting` ,

Column Name	Data Type	Nullable	Description	Tags
				`customer relationship`
device (`device`)	`string`	✅	Indicates the device used by the pseudonymous user.	`device` , `user experience` , `analytics`
geo (`geo`)	`string`	✅	Stores geographical information related to the pseudonymous user.	`geography` , `location` , `analytics`
last_updated_date (`last_updated_date`)	`string`	✅	Records the last updated date for the pseudonymous user data.	`last updated` , `data integrity` , `audit`
user_properties (`user_properties`)	`string`	✅	Contains properties associated with the pseudonymous user.	`user properties` , `analytics` , `personalization`
privacy_info (`privacy_info`)	`string`	✅	Contains privacy-related information for the pseudonymous user.	`privacy` , `compliance` , `data protection`
pseudo_user_id (`pseudo_user_id`)	`string`	✅	Serves as the unique identifier for the pseudonymous user.	`identifier` , `primary key` , `user tracking`
stream_id (`stream_id`)	`string`	✅	Represents the stream ID associated with the pseudonymous user.	`stream ID` , `data lineage` , `source tracking`
user_info (`user_info`)	`string`	✅	Holds additional user information related to the pseudonymous user.	`user information` , `profiling` , `segmentation`

Detailed Column Information for pseudonymous users

Column 1: occurrence_date

Field	Value
ID	`09da78fb37db791fcc5e0cbfe22b3a85`
Backend Name	`occurrence_date`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Indicates the occurrence date of the pseudonymous user's interaction.
Embedding Input	The 'occurrence_date' column specifies the date when the pseudonymous user's interaction took place, providing a temporal context for user behavior analysis. This non-nullable string column is vital for time-based analytics, allowing businesses to understand trends and patterns in user engagement over specific periods.

Column 2: audiences

Field	Value
ID	`66e07b6a442e15fd63415a7f1b41df2f`
Backend Name	`audiences`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Represents the audiences associated with the pseudonymous user.
Embedding Input	The 'audiences' column captures the various audience segments that the pseudonymous user belongs to, enabling

Field	Value
	targeted analysis and marketing strategies. This column is of type string and is nullable, allowing for flexibility in data entry. It plays a significant role in understanding user demographics and behavior patterns, although it may not always contain data for every user.

Column 3: user_ltv

Field	Value
ID	`2c5be1c36a93d9b46d848e2a445455ff`
Backend Name	`user_ltv`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Represents the lifetime value of the pseudonymous user.
Embedding Input	The 'user_ltv' column captures the estimated lifetime value of the pseudonymous user, providing critical insights for revenue forecasting and customer relationship management. This nullable string column is important for understanding the financial impact of user interactions over time, although it may not always contain data for every user.

Column 4: device

Field	Value
ID	`fbf91d37096f0370a8e9eb49a194426a`
Backend Name	`device`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`

Field	Value
Description	Indicates the device used by the pseudonymous user.
Embedding Input	The 'device' column records the type of device utilized by the pseudonymous user during their interactions, which is crucial for analyzing user experience across different platforms. This column is a string type and nullable, reflecting the diversity of devices users may employ. Understanding device usage helps in optimizing digital content and improving user engagement.

Column 5: geo

Field	Value
ID	`23e207175314c40ec6a892d8a22c708d`
Backend Name	`geo`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Stores geographical information related to the pseudonymous user.
Embedding Input	The 'geo' column contains geographical data that indicates the location of the pseudonymous user, which is essential for regional analysis and targeted marketing efforts. This string-type column is nullable, allowing for cases where location data may not be available. Analyzing geographical trends can provide insights into user behavior and preferences across different regions.

Column 6: last_updated_date

Field	Value
ID	`38d7742448e703b4ef05733803dd9917`
Backend Name	`last_updated_date`

Field	Value
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Records the last updated date for the pseudonymous user data.
Embedding Input	The 'last_updated_date' column captures the timestamp of the most recent update to the pseudonymous user's data, ensuring data accuracy and relevance. This non-nullable string column is critical for maintaining data integrity and for auditing purposes, as it allows analysts to track changes over time and ensure that the data reflects the latest user interactions.

Column 7: user_properties

Field	Value
ID	`e4a8a72f3df1a0c90f2a3a26522bff33`
Backend Name	`user_properties`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Contains properties associated with the pseudonymous user.
Embedding Input	The 'user_properties' column holds various attributes and characteristics related to the pseudonymous user, which can be leveraged for advanced analytics and personalized marketing strategies. This nullable string column allows for a diverse range of data entries, although it may not always be populated. It is essential for enhancing user understanding and tailoring user experiences.

Column 8: privacy_info

Field	Value
ID	`7b9977945b760a65c046bbc8e6048475`
Backend Name	`privacy_info`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Contains privacy-related information for the pseudonymous user.
Embedding Input	The 'privacy_info' column holds data regarding the privacy measures and compliance status associated with the pseudonymous user, ensuring adherence to regulatory standards. This nullable string column is important for maintaining user trust and compliance with data protection regulations, although it may not always contain data for every user.

Column 9: pseudo_user_id

Field	Value
ID	`f98ffe01a16da6b0e57a362aae15a5cf`
Backend Name	`pseudo_user_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Serves as the unique identifier for the pseudonymous user.
Embedding Input	The 'pseudo_user_id' column is the primary key for the table, uniquely identifying each pseudonymous user within the dataset. This non-nullable string column is essential for establishing relationships with other data entities and for

Field	Value
	ensuring data integrity. It plays a critical role in user tracking and analysis, enabling businesses to derive insights from user behavior.

Column 10: stream_id

Field	Value
ID	`10f3fe7617ec717b01817c835bceb861`
Backend Name	`stream_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	Represents the stream ID associated with the pseudonymous user.
Embedding Input	The 'stream_id' column indicates the specific data stream from which the pseudonymous user's data was captured, providing context for data lineage and source tracking. This non-nullable string column is important for understanding the origin of the data and for ensuring accurate reporting and analysis.

Column 11: user_info

Field	Value
ID	`42987e7f34154d5abb82a8fb9c3cb51e`
Backend Name	`user_info`
Data Type	`string`
Nullable	Yes
Parent Table ID	`d56ce9c6b9bd0f5600449feaac6290b1`
Description	

Field	Value
	Holds additional user information related to the pseudonymous user.
Embedding Input	The 'user_info' column contains supplementary information about the pseudonymous user, which can enhance user profiling and segmentation efforts. This nullable string column allows for flexibility in data entry, although it may not always be populated. It is useful for enriching user data and providing deeper insights into user behavior.

Columns for Table: users

Column Name	Data Type	Nullable	Description	Tags
geo (`geo`)	`string`	✅	Contains geographical information related to the user.	`geography` , `demographics` , `analytics`
user_id (`user_id`)	`string`	✅	Uniquely identifies each user in the system.	`user_id` , `identifier` , `primary_key`
user_ltv (`user_ltv`)	`string`	✅	Represents the lifetime value of the user.	`lifetime_value` , `analytics` , `financial`
user_properties (`user_properties`)	`string`	✅	Contains various properties associated with the user.	`user_properties` , `attributes` , `analytics`
last_updated_date (`last_updated_date`)	`string`	✅	Records the last date the user data was updated.	`data_management` , `timestamp` , `analytics`
occurrence_date (`occurrence_date`)	`string`	✅	Represents the date of occurrence for user events.	`event_date` , `analytics` , `user_behavior`
privacy_info (`privacy_info`)	`string`	✅	Contains privacy-related information for the user.	`privacy` , `compliance` , `data_protection`

Column Name	Data Type	Nullable	Description	Tags
audiences (`audiences`)	`string`	✅	Represents the audiences associated with the user.	`audience` , `segmentation` , `marketing`
device (`device`)	`string`	✅	Indicates the device used by the user.	`device` , `user_experience` , `analytics`
user_info (`user_info`)	`string`	✅	Holds additional information about the user.	`user_info` , `attributes` , `personalization`

Detailed Column Information for users

Column 1: geo

Field	Value
ID	`21cfbc0a4f5a8c559b81d8cb2fdf37d9`
Backend Name	`geo`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Contains geographical information related to the user.
Embedding Input	The 'geo' column is a nullable string field that captures geographical data pertaining to the user's location. This information is essential for demographic analysis, allowing businesses to tailor their strategies based on regional user behavior and preferences. The column can be utilized in reporting to visualize user distribution across different geographical areas, enhancing market targeting and localization efforts.

Column 2: user_id

Field	Value
ID	`09a3e78d8e0d50d09e00486bc027f774`
Backend Name	`user_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Uniquely identifies each user in the system.
Embedding Input	The 'user_id' column is a non-nullable string field that serves as the primary key for the 'users' table, uniquely identifying each user within the dataset. This identifier is essential for establishing relationships with other tables and for ensuring data integrity across the database. It is used extensively in joins, filters, and aggregations, making it a cornerstone of user-centric analytics and reporting.

Column 3: user_ltv

Field	Value
ID	`324fcec971d8fba2165d3df40dc95534`
Backend Name	`user_ltv`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Represents the lifetime value of the user.
Embedding Input	The 'user_ltv' column is a nullable string field that captures the estimated lifetime value of the user, providing insights into the long-term revenue potential associated with each user. This metric is crucial for financial forecasting and strategic planning, enabling businesses to prioritize high-value users

Field	Value
	and optimize marketing investments. The column can be used in analytics to assess user profitability and inform retention strategies.

Column 4: user_properties

Field	Value
ID	`8ef447027e7c4410f0397584e3527f98`
Backend Name	`user_properties`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Contains various properties associated with the user.
Embedding Input	The 'user_properties' column is a nullable string field that holds diverse attributes related to the user, which may include demographic information, preferences, or behavioral traits. This column enriches the user profile and supports advanced analytics and segmentation strategies. It can be leveraged in reporting to gain deeper insights into user characteristics and enhance targeting efforts.

Column 5: last_updated_date

Field	Value
ID	`c12013bd838b8ae27b1a0563632a1671`
Backend Name	`last_updated_date`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`

Field	Value
Description	Records the last date the user data was updated.
Embedding Input	The 'last_updated_date' column is a non-nullable string field that indicates the most recent date on which the user's data was modified. This timestamp is critical for maintaining data integrity and ensuring that analytics reflect the latest user interactions. It supports data lifecycle management by providing insights into data freshness and relevance, which is vital for compliance and reporting purposes.

Column 6: occurrence_date

Field	Value
ID	`31840d0a2c31b6fde1116038c13274ac`
Backend Name	`occurrence_date`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Represents the date of occurrence for user events.
Embedding Input	The 'occurrence_date' column is a non-nullable string field that captures the date on which specific user events took place. This information is essential for chronological analysis of user behavior, enabling businesses to track engagement over time and identify trends. It plays a significant role in event-based analytics and reporting, allowing for the assessment of user activity patterns and the effectiveness of marketing campaigns.

Column 7: privacy_info

Field	Value
ID	`c8b3524fd1f94c9a5823a34f0e6f8c19`
Backend Name	`privacy_info`

Field	Value
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Contains privacy-related information for the user.
Embedding Input	The 'privacy_info' column is a nullable string field that holds data regarding the user's privacy preferences and settings. This column is crucial for compliance with data protection regulations and for ensuring that user data is handled in accordance with their consent. It supports privacy management practices and can be used to filter user data based on privacy considerations, enhancing trust and transparency in data usage.

Column 8: audiences

Field	Value
ID	`8a3318b9010b680eba8895ef7feb3ece`
Backend Name	`audiences`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Represents the audiences associated with the user.
Embedding Input	The 'audiences' column is a string type field that captures the various audience segments to which a user belongs. This column is nullable, indicating that not all users may be associated with specific audiences. It plays a vital role in targeted marketing and user segmentation strategies, allowing analysts to understand user distribution across different audience categories. The data in this column can be used for filtering and aggregating user insights based on audience characteristics.

Column 9: device

Field	Value
ID	`08739afe0924ae43182af33a8cbccfca`
Backend Name	`device`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Indicates the device used by the user.
Embedding Input	The 'device' column is a nullable string field that records the type of device utilized by the user during their interactions. This information is crucial for understanding user behavior across different platforms, such as mobile, desktop, or tablet. It aids in optimizing user experience and tailoring content delivery based on device preferences. The column can be leveraged in analytics to assess device-specific engagement metrics and trends.

Column 10: user_info

Field	Value
ID	`d3148a61739cf92b3b0f73614f567337`
Backend Name	`user_info`
Data Type	`string`
Nullable	Yes
Parent Table ID	`9bc65c2abec141778ffaa729489f3e87`
Description	Holds additional information about the user.
Embedding Input	The 'user_info' column is a nullable string field that contains supplementary details about the user, which may include preferences, interests, or other relevant attributes. This column enhances the richness of user profiles and supports

Field	Value
	personalized marketing efforts. It can be utilized in analytics to segment users based on their characteristics and improve engagement strategies.

Columns for Table: events

Column Name	Data Type	Nullable	Description	Tags
batch_event_index (`batch_event_index`)	`string`	✅	Index for batch events.	`batch processing` , `event index`
batch_page_id (`batch_page_id`)	`string`	✅	Identifier for the batch page.	`page identifier` , `event tracking`
event_bundle_sequence_id (`event_bundle_sequence_id`)	`string`	✅	Unique identifier for the event bundle.	`event bundle` , `identifier`
event_date (`event_date`)	`string`	✅	Date when the event occurred.	`event date` , `time series`
event_value_in_usd (`event_value_in_usd`)	`string`	✅	Value of the event in USD.	`event value` , `financial analysis`
is_active_user (`is_active_user`)	`string`	✅	Indicates if the user is active.	`user engagement` , `activity status`
session_traffic_source_last_click (`session_traffic_source_last_click`)	`string`	✅	Traffic source from the last click.	`last click` , `traffic source`
batch_ordering_id (`batch_ordering_id`)	`string`	✅	Unique identifier for batch ordering.	`batch ordering` , `event sequence`
device (`device`)	`string`	✅	Device used for the event.	`device type` , `user segmentation`
event_name (`event_name`)	`string`	✅	Name of the event.	`event name` , `user interaction`

Column Name	Data Type	Nullable	Description	Tags
event_timestamp (`event_timestamp`)	`string`	✅	Timestamp of when the event was recorded.	`event timestamp` , `chronological data`
traffic_source (`traffic_source`)	`string`	✅	Source of traffic for the event.	`traffic source` , `marketing analysis`
user_first_touch_timestamp (`user_first_touch_timestamp`)	`string`	✅	Timestamp of the user's first touch.	`first touch` , `user journey`
collected_traffic_source (`collected_traffic_source`)	`string`	✅	Source of collected traffic.	`traffic source` , `marketing analytics`
event_params (`event_params`)	`string`	✅	Parameters associated with the event.	`event parameters` , `data context`
stream_id (`stream_id`)	`string`	✅	Unique identifier for the stream.	`stream identifier` , `data integrity`
user_pseudo_id (`user_pseudo_id`)	`string`	✅	Pseudo identifier for the user.	`pseudo identifier` , `anonymous tracking`
ecommerce (`ecommerce`)	`string`	✅	Ecommerce-related event data.	`ecommerce` , `transaction data`
geo (`geo`)	`string`	✅	Geographical information related to the event.	`geolocation` , `user demographics`
items (`items`)	`string`	✅	Items associated with the event.	`items` , `product analysis`
platform (`platform`)	`string`	✅	Platform used for the event.	`platform` , `user experience`

Column Name	Data Type	Nullable	Description	Tags
privacy_info (`privacy_info`)	`string`	✅	Privacy information related to the event.	`privacy` , `compliance`
user_ltv (`user_ltv`)	`string`	✅	Lifetime value of the user.	`user lifetime value` , `financial metrics`
user_properties (`user_properties`)	`string`	✅	Properties associated with the user.	`user properties` , `segmentation`
user_id (`user_id`)	`string`	✅	Unique identifier for the user.	`user identifier` , `user analysis`

Detailed Column Information for events

Column 1: batch_event_index

Field	Value
ID	`efda010a80eeb2daf817be632e4207f9`
Backend Name	`batch_event_index`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Index for batch events.
Embedding Input	The 'batch_event_index' column is a string type that serves as an index for grouping events processed in batches. It is nullable, allowing for flexibility in data entry. This column is essential for identifying and managing batches of events, particularly in scenarios where events are processed in bulk. It may be used in analytical queries to filter or aggregate data based on batch processing.

Column 2: batch_page_id

Field	Value
ID	`c5514b5cdb90ef2add4b2c014e0ef71e`
Backend Name	`batch_page_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Identifier for the batch page.
Embedding Input	The 'batch_page_id' column is a nullable string that represents the identifier for the page associated with a batch of events. This column is useful for linking events to specific pages, enabling detailed analysis of user interactions on a per-page basis. It supports use cases in web analytics where understanding page-level engagement is critical.

Column 3: event_bundle_sequence_id

Field	Value
ID	`4b9ce4276918aa94fb04780f34e66e35`
Backend Name	`event_bundle_sequence_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Unique identifier for the event bundle.
Embedding Input	The 'event_bundle_sequence_id' column is a nullable string that uniquely identifies each event bundle. This primary key is crucial for ensuring data integrity and facilitating efficient data retrieval. It plays a significant role in linking related events and maintaining the context of user interactions.

Column 4: event_date

Field	Value
ID	`58fb2f5733a2e9a2a4fef01abb78a136`
Backend Name	`event_date`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Date when the event occurred.
Embedding Input	The 'event_date' column is a non-nullable string that records the date of the event. This column is essential for time-based analysis, allowing users to filter and aggregate events by date for reporting and trend analysis. It supports various analytical use cases, including cohort analysis and seasonal trends.

Column 5: event_value_in_usd

Field	Value
ID	`cebea7f0def365d9e8359885665486f0`
Backend Name	`event_value_in_usd`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Value of the event in USD.
Embedding Input	The 'event_value_in_usd' column is a nullable string that represents the monetary value associated with the event, expressed in USD. This column is crucial for financial analysis, enabling businesses to assess the economic impact of user interactions and optimize revenue strategies.

Column 6: is_active_user

Field	Value
ID	`5fe98316d534fc0d76e2b1d6c4ba48c3`
Backend Name	`is_active_user`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Indicates if the user is active.
Embedding Input	The 'is_active_user' column is a nullable string that indicates whether the user associated with the event is considered active. This column is important for user engagement analysis, helping businesses identify and target active users for retention strategies.

Column 7: session_traffic_source_last_click

Field	Value
ID	`0280b78a39905d5a9b481e00da0ec193`
Backend Name	`session_traffic_source_last_click`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Traffic source from the last click.
Embedding Input	The 'session_traffic_source_last_click' column is a nullable string that captures the traffic source from the last click before the event occurred. This information is vital for understanding the effectiveness of marketing channels and optimizing user acquisition strategies.

Column 8: batch_ordering_id

Field	Value
ID	`6441e33dcdac29eccb6277989c23b011`
Backend Name	`batch_ordering_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Unique identifier for batch ordering.
Embedding Input	The 'batch_ordering_id' column is a nullable string that uniquely identifies the order of events within a batch. This identifier is crucial for maintaining the sequence of events, especially when analyzing user interactions that occur in a specific order. It supports operational use cases where the order of events impacts analysis and reporting.

Column 9: device

Field	Value
ID	`031f069ec59226f67b4c51c7fb37013e`
Backend Name	`device`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Device used for the event.
Embedding Input	The 'device' column is a nullable string that captures the type of device used by the user when the event occurred. This information is essential for segmenting data based on device type, allowing for tailored analysis of user behavior across different platforms, such as mobile, desktop, or tablet.

Column 10: event_name

Field	Value
ID	`bcb029465481c581134396546638c2a7`
Backend Name	`event_name`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Name of the event.
Embedding Input	The 'event_name' column is a non-nullable string that specifies the name of the event being tracked. This column is critical for categorizing events and understanding user interactions. It supports operational and analytical use cases, enabling users to filter and analyze data based on specific event types.

Column 11: event_timestamp

Field	Value
ID	`cca5ba835e8687f86da311dce688bd33`
Backend Name	`event_timestamp`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Timestamp of when the event was recorded.
Embedding Input	The 'event_timestamp' column is a nullable string that records the exact timestamp when the event was captured. This information is vital for chronological analysis and understanding the sequence of user interactions. It supports various analytical scenarios, including real-time analytics and historical trend analysis.

Column 12: traffic_source

Field	Value
ID	`797b2625f9dda7db4a8857b7917eaeab`
Backend Name	`traffic_source`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Source of traffic for the event.
Embedding Input	The 'traffic_source' column is a nullable string that indicates the source of traffic for the event. This information is essential for analyzing user acquisition and understanding the effectiveness of different marketing channels.

Column 13: user_first_touch_timestamp

Field	Value
ID	`8ee3d0c3c28229fd40f6f75a0ce7c1c6`
Backend Name	`user_first_touch_timestamp`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Timestamp of the user's first touch.
Embedding Input	The 'user_first_touch_timestamp' column is a nullable string that records the timestamp of the user's first interaction with the platform. This information is vital for understanding user journeys and analyzing the effectiveness of marketing efforts over time.

Column 14: collected_traffic_source

Field	Value
ID	`4ff7f1f9c3c170cd475244f462f487e5`
Backend Name	`collected_traffic_source`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Source of collected traffic.
Embedding Input	The 'collected_traffic_source' column is a nullable string that indicates the source from which the traffic was collected. This information is vital for understanding the effectiveness of marketing channels and campaigns. It supports analytical efforts to optimize traffic acquisition strategies and improve ROI.

Column 15: event_params

Field	Value
ID	`339e5116028140779b2364d25e226310`
Backend Name	`event_params`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Parameters associated with the event.
Embedding Input	The 'event_params' column is a nullable string that contains additional parameters related to the event. This column allows for the capture of detailed context about each event, supporting complex analysis and reporting. It is essential for understanding the nuances of user interactions and enhancing data richness.

Column 16: stream_id

Field	Value
ID	`6a62d574a738d0dfd2d52f12b5fef434`
Backend Name	`stream_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Unique identifier for the stream.
Embedding Input	The 'stream_id' column is a non-nullable string that uniquely identifies the stream associated with the event. This identifier is crucial for linking events to specific data streams, supporting data integrity and analysis across different streams.

Column 17: user_pseudo_id

Field	Value
ID	`76e84a2fff1b8d9c7941fcecfd12afe5`
Backend Name	`user_pseudo_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Pseudo identifier for the user.
Embedding Input	The 'user_pseudo_id' column is a nullable string that serves as a pseudo identifier for the user, allowing for anonymous tracking of user interactions. This column is important for privacy compliance while still enabling user behavior analysis.

Column 18: ecommerce

Field	Value
ID	`52afc51c6a90655458eb7537eae2c522`
Backend Name	`ecommerce`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Ecommerce-related event data.
Embedding Input	The 'ecommerce' column is a nullable string that contains information related to ecommerce transactions associated with the event. This column is critical for analyzing sales performance, conversion rates, and user purchasing behavior, supporting business intelligence efforts in ecommerce optimization.

Column 19: geo

Field	Value
ID	`602f665a7dc146881fcfd118e5b9aadd`
Backend Name	`geo`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Geographical information related to the event.
Embedding Input	The 'geo' column is a nullable string that captures geographical data related to the event, such as location or region. This information is essential for geographic analysis, allowing businesses to understand user distribution and tailor marketing efforts based on location.

Column 20: items

Field	Value
ID	`8a72c392f958a292533a31b363d645e9`
Backend Name	`items`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Items associated with the event.
Embedding Input	The 'items' column is a nullable string that lists items related to the event, such as products purchased or interacted with. This information is critical for ecommerce analysis, enabling businesses to understand product performance and user preferences.

Column 21: platform

Field	Value
ID	`592251f0e3d2020c072a343a2bcb1088`
Backend Name	`platform`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Platform used for the event.
Embedding Input	The 'platform' column is a nullable string that indicates the platform on which the event occurred, such as web or mobile. This information is essential for understanding user behavior across different platforms and optimizing user experiences accordingly.

Column 22: privacy_info

Field	Value
ID	`0fe5ac9c9420ab57df5de81bceb4bed9`
Backend Name	`privacy_info`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Privacy information related to the event.
Embedding Input	The 'privacy_info' column is a nullable string that contains privacy-related information associated with the event. This column is important for compliance and regulatory considerations, ensuring that user data is handled according to privacy standards.

Column 23: user_ltv

Field	Value
ID	`b70001fc548fae2d25b83e02f2b77e31`
Backend Name	`user_ltv`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Lifetime value of the user.
Embedding Input	The 'user_ltv' column is a nullable string that represents the lifetime value of the user associated with the event. This information is essential for understanding user profitability and guiding marketing investment decisions.

Column 24: user_properties

Field	Value
ID	`08513a0a129b010dc9e68a774691025f`
Backend Name	`user_properties`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Properties associated with the user.
Embedding Input	The 'user_properties' column is a nullable string that contains various properties related to the user, such as demographics or preferences. This information is vital for user segmentation and targeted marketing efforts.

Column 25: user_id

Field	Value
ID	`83af0b4c7890b2f113234a187eaab13f`
Backend Name	`user_id`
Data Type	`string`
Nullable	Yes
Parent Table ID	`16908b0605f2645dfcb4c3a8d248cef3`
Description	Unique identifier for the user.
Embedding Input	The 'user_id' column is a nullable string that uniquely identifies the user associated with the event. This identifier is crucial for user-level analysis, enabling businesses to track user behavior and engagement over time.

Columns for Table: batch summary

Column Name	Data Type	Nullable	Description	Tags
batch_id (`batch_id`)	`integer`	✅	Unique identifier for each batch.	`identifier` , `primary key` , `batch`
post_date (`post_date`)	`date`	✅	Date when the batch was posted.	`post date` , `timestamp` , `tracking`
fiscal_year (`fiscal_year`)	`integer`	✅	Fiscal year associated with the batch.	`fiscal year` , `financial reporting` , `analysis`
contribution_id (`contribution_id`)	`integer`	✅	Identifier for contributions associated with the batch.	`contribution` , `identifier` , `foreign key`
batch_status (`batch_status`)	`string`	✅	Current status of the batch.	`batch status` , `workflow` , `monitoring`
batch_type (`batch_type`)	`string`	✅	Type of the batch.	`batch type` , `categorization` , `operational insight`
batch_type_group (`batch_type_group`)	`string`	✅	Group classification for the batch type.	`batch group` , `classification` , `analysis`

Detailed Column Information for batch summary

Column 1: batch_id

Field	Value
ID	`c1ebfa61dc39580aa7f08efe3649618b`
Backend Name	`batch_id`
Data Type	`integer`

Field	Value
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Unique identifier for each batch.
Embedding Input	The batch_id column is an integer type that serves as the primary key for the batch summary table, uniquely identifying each batch entry. It is nullable, allowing for flexibility in data management during batch creation. This identifier is critical for linking batch records to other related entities within the CRM system, facilitating joins and aggregations in reporting and analysis. The batch_id is expected to follow a sequential pattern, ensuring consistency and traceability across batch operations. It plays a vital role in maintaining data integrity and is often used in filters and joins for analytical queries.

Column 2: post_date

Field	Value
ID	`62fc4d72cfe3742b725d463ef71c69b9`
Backend Name	`post_date`
Data Type	`date`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Date when the batch was posted.
Embedding Input	The post_date column is a date type that records the date on which the batch was posted into the system. This nullable field is essential for tracking the timing of batch processing activities, enabling users to analyze batch performance over time. The post_date is critical for reporting purposes, allowing stakeholders to filter and aggregate data based on specific timeframes, such as fiscal periods or operational cycles. It supports compliance and auditing processes by providing a clear timeline of batch activities.

Column 3: fiscal_year

Field	Value
ID	`1ed920fb1794ba0ecfa0c8c1e6d2d416`
Backend Name	`fiscal_year`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Fiscal year associated with the batch.
Embedding Input	The fiscal_year column is an integer type that indicates the fiscal year during which the batch was processed. This nullable field is crucial for financial reporting and analysis, allowing users to align batch data with fiscal periods for budgetary and performance evaluations. The fiscal_year is often used in conjunction with other date-related fields to provide a comprehensive view of batch activities over time. It supports strategic planning and decision-making by enabling stakeholders to assess batch performance in the context of fiscal objectives.

Column 4: contribution_id

Field	Value
ID	`a437a95630e3c4528ac572dd99f9caf1`
Backend Name	`contribution_id`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Identifier for contributions associated with the batch.
Embedding Input	The contribution_id column is an integer type that represents the unique identifier for contributions linked to a specific

Field	Value
	batch. This nullable field allows for the association of multiple contributions to a batch, enhancing the granularity of data analysis. It is essential for establishing relationships with other tables that track contributions, thereby enabling comprehensive reporting on batch performance and contribution metrics. The contribution_id is used in various analytical contexts, including filters and joins, to derive insights into the effectiveness of batch processing.

Column 5: batch_status

Field	Value
ID	`55de054346c7b6ecbcc1b0925e7315db`
Backend Name	`batch_status`
Data Type	`string`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Current status of the batch.
Embedding Input	The batch_status column is a string type that indicates the current processing status of the batch. This nullable field is vital for operational monitoring, allowing users to quickly assess whether a batch is 'pending', 'completed', 'failed', or 'in progress'. The batch_status is instrumental in workflow management and reporting, providing real-time insights into batch processing activities and facilitating timely interventions when issues arise. It supports decision-making processes by highlighting the operational state of each batch.

Column 6: batch_type

Field	Value
ID	`4e4f05f6868fd74caf188159478fed98`
Backend Name	`batch_type`

Field	Value
Data Type	`string`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Type of the batch.
Embedding Input	The batch_type column is a string type that categorizes the nature of the batch being processed. This nullable field allows for diverse batch classifications, which can be leveraged in reporting and analysis to understand batch performance across different types. The batch_type is crucial for operational insights, enabling stakeholders to filter and analyze batches based on their specific characteristics. It may include values such as 'standard', 'urgent', or 'special', providing context for the processing priorities and operational strategies employed.

Column 7: batch_type_group

Field	Value
ID	`a57a8954eaa0b0494081b6cf4dfc5194`
Backend Name	`batch_type_group`
Data Type	`string`
Nullable	Yes
Parent Table ID	`fbc6e5b24dd857869918a3ed39527d1f`
Description	Group classification for the batch type.
Embedding Input	The batch_type_group column is a string type that provides a higher-level categorization for the batch type. This nullable field allows for the grouping of similar batch types, enhancing the ability to analyze and report on batch performance across broader categories. It is particularly useful for stakeholders looking to understand trends and patterns in batch processing, as it aggregates data into meaningful segments. The batch_type_group may include classifications such as 'regular', 'high priority', or 'seasonal', aiding in strategic planning and resource allocation.

Columns for Table: Promo Quarterly

Column Name	Data Type	Nullable	Description	Tags
customer_no (`customer_no`)	`integer`	✅	Unique identifier for customers participating in promotions.	`customer ID`, `promotion participation`, `analytics`
promotion_source_number (`promotion_source_number`)	`integer`	✅	Identifier for the source of the promotion.	`source ID`, `promotion channel`, `marketing analysis`
promotion_appeal (`promotion_appeal`)	`integer`	✅	Identifier for the promotional appeal being analyzed.	`promotion ID`, `campaign identifier`, `primary key`
promotion_response (`promotion_response`)	`integer`	✅	Response metric indicating customer engagement with the promotion.	`response metric`, `customer engagement`, `promotion analysis`
promotion_response_date (`promotion_response_date`)	`timestamp`	✅	Timestamp indicating when the promotion response was recorded.	`response date`, `timestamp`, `promotional analysis`

Detailed Column Information for Promo Quarterly

Column 1: customer_no

Field	Value
ID	`a608941236b2b12164084a37ad6dfda4`
Backend Name	`customer_no`
Data Type	`integer`

Field	Value
Nullable	Yes
Parent Table ID	`880c94f9e41c72a127590d7fffdb370d`
Description	Unique identifier for customers participating in promotions.
Embedding Input	The customer_no column is an integer field that represents a unique identifier assigned to each customer involved in promotional activities. This column is nullable, allowing for cases where customer participation may not be recorded. It plays a vital role in linking promotional responses to specific customers, enabling detailed analysis of customer behavior and response patterns. The data type is integer, ensuring efficient storage and retrieval. This column is essential for filtering and joining with customer-related tables to derive insights into customer engagement and promotional effectiveness.

Column 2: promotion_source_number

Field	Value
ID	`50c781ff692402d856ba74ce8ae2ce28`
Backend Name	`promotion_source_number`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`880c94f9e41c72a127590d7fffdb370d`
Description	Identifier for the source of the promotion.
Embedding Input	The promotion_source_number column is an integer that identifies the source or channel through which the promotion was delivered. This nullable field allows for flexibility in capturing various promotional sources, which is vital for analyzing the effectiveness of different marketing channels. The integer data type supports efficient storage and retrieval, making it useful for reporting and performance analysis. This column is key for understanding the relationship between promotional sources and customer responses, aiding in strategic marketing decisions.

Column 3: promotion_appeal

Field	Value
ID	`ced78cfb335bce94d9d1c061653add41`
Backend Name	`promotion_appeal`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`880c94f9e41c72a127590d7fffdb370d`
Description	Identifier for the promotional appeal being analyzed.
Embedding Input	The promotion_appeal column is an integer that serves as the primary key for the table, uniquely identifying each promotional campaign. This nullable field allows for flexibility in data entry, accommodating various promotional scenarios. It is crucial for linking promotional responses to specific campaigns, facilitating analysis of campaign effectiveness and customer engagement. The integer data type ensures efficient indexing and retrieval, making it a key component in reporting and analytical processes within the CRM system.

Column 4: promotion_response

Field	Value
ID	`47e64822dbd4f169eaacdd6984089b2e`
Backend Name	`promotion_response`
Data Type	`integer`
Nullable	Yes
Parent Table ID	`880c94f9e41c72a127590d7fffdb370d`
Description	Response metric indicating customer engagement with the promotion.
Embedding Input	The promotion_response column is an integer that quantifies the level of customer engagement with a specific promotional

Field	Value
	appeal. This nullable field allows for flexibility in capturing varying response levels, which can be critical for analyzing the success of promotional strategies. The integer data type supports efficient calculations and aggregations, making it valuable for reporting and performance analysis. This column is instrumental in understanding customer behavior and the effectiveness of marketing efforts.

Column 5: promotion_response_date

Field	Value
ID	`d7b5fc5396218d659e31b7d6c39c8610`
Backend Name	`promotion_response_date`
Data Type	`timestamp`
Nullable	Yes
Parent Table ID	`880c94f9e41c72a127590d7fffdb370d`
Description	Timestamp indicating when the promotion response was recorded.
Embedding Input	The promotion_response_date column is a timestamp that records the exact date and time when a customer response to a promotion was captured. This nullable field is essential for tracking the temporal aspects of promotional effectiveness, allowing for time-based analysis of customer engagement trends. The timestamp data type ensures precise recording of response times, which is critical for evaluating the timing of promotional efforts and their impact on customer behavior. This column supports analytical queries related to response patterns over time.

Edge Metadata

Total Edges: 382

Edge Label	Source	Target	Description
HAS_TABLE	`CRM`	`Contribution Transaction Link`	Links contribution transactions to their respective details.
HAS_TABLE	`CRM`	`Promo Quarterly`	Stores quarterly promotional data related to customer engagement.
HAS_TABLE	`CRM`	`Packages`	Table containing information about packages associated with orders.
HAS_TABLE	`CRM`	`Appeal Source Structure`	Structure representing various sources of appeals.
HAS_TABLE	`CRM`	`dimconstituentsanon`	A dimension table containing anonymized constituent information.
HAS_TABLE	`CRM`	`production season types`	This table stores different types of production seasons.
HAS_TABLE	`CRM`	`batch summary`	Summary of batches processed within the CRM system.
HAS_TABLE	`CRM`	`Deferrals and Receiveables Not in Model Yet`	Table containing deferrals and receivables that are not yet included in the financial model.
HAS_TABLE	`CRM`	`Ticket`	Table containing ticket information for events.
HAS_TABLE	`CRM`	`Funds`	This table stores information about funds and their

Edge Label	Source	Target	Description
			associated transactions.
HAS_TABLE	`CRM`	`members`	Table containing membership details for constituents.
HAS_TABLE	`CRM`	`Ticket Seat ID`	Table containing details about ticket seats.
HAS_TABLE	`CRM`	`Deceased Cont W Last Activity`	Table containing information about deceased customers along with their last activity dates.
HAS_TABLE	`CRM`	`Contact Types Relationships`	This table defines the relationships between different customer types.
HAS_TABLE	`CRM`	`Contribution Output`	Stores information about contributions made by constituents.
HAS_TABLE	`GA4`	`events`	Stores event data collected from GA4.
HAS_TABLE	`GA4`	`users`	Stores user-related data for analytics and reporting.
HAS_TABLE	`GA4`	`pseudonymous users`	Stores information about pseudonymous users captured from GA4.
HAS_COLUMN	`Packages`	`constituent_id`	Identifier for the constituent associated with the package.
HAS_COLUMN	`Packages`	`const_type`	

Edge Label	Source	Target	Description
			Type of the constituent related to the package.
HAS_COLUMN	`Packages`	`order_id`	Unique identifier for the order associated with the package.
HAS_COLUMN	`Packages`	`package_season`	Season during which the package is offered.
HAS_COLUMN	`Packages`	`package_code`	Code representing the package.
HAS_COLUMN	`Packages`	`campaign`	Campaign associated with the package.
HAS_COLUMN	`Packages`	`campaign_id`	Unique identifier for the campaign associated with the package.
HAS_COLUMN	`Packages`	`appeal`	Appeal associated with the package.
HAS_COLUMN	`Packages`	`appeal_id`	Unique identifier for the appeal associated with the package.
HAS_COLUMN	`Packages`	`source`	Source of the package information.
HAS_COLUMN	`Packages`	`source_id`	Unique identifier for the source of the package information.
HAS_COLUMN	`Packages`	`section`	Section of the package information.
HAS_COLUMN	`Packages`	`channel`	Channel through which the package is marketed.
HAS_COLUMN	`Packages`	`package_order_date`	

Edge Label	Source	Target	Description
			Date when the package order was placed.
HAS_COLUMN	`Packages`	`mode_of_sale`	Mode of sale for the package.
HAS_COLUMN	`Packages`	`package_size`	Size of the package.
HAS_COLUMN	`Packages`	`price_type_category`	Category of the price type for the package.
HAS_COLUMN	`Packages`	`price_type`	Specific price type for the package.
HAS_COLUMN	`Funds`	`trn_count`	Count of transactions associated with the fund.
HAS_COLUMN	`Funds`	`pledge`	Total amount pledged to the fund.
HAS_COLUMN	`Funds`	`pledge_payment`	Total amount of pledge payments received.
HAS_COLUMN	`Funds`	`gift`	Total amount of gifts received for the fund.
HAS_COLUMN	`Funds`	`restricted`	Total amount of restricted funds.
HAS_COLUMN	`Funds`	`write_off`	Total amount of funds written off.
HAS_COLUMN	`Funds`	`total_received`	Total amount received for the fund.
HAS_COLUMN	`Funds`	`batch_no`	Batch number associated with the fund transactions.
HAS_COLUMN	`Funds`	`ref_no`	Reference number for the fund transaction.

Edge Label	Source	Target	Description
HAS_COLUMN	`Funds`	`cont_dt`	Date of the contribution.
HAS_COLUMN	`Funds`	`trn_dt`	Date of the transaction.
HAS_COLUMN	`Funds`	`fund_no`	Fund number associated with the fund.
HAS_COLUMN	`Funds`	`fund_desc`	Description of the fund.
HAS_COLUMN	`Funds`	`fyear`	Fiscal year associated with the fund.
HAS_COLUMN	`Funds`	`campaign_no`	Campaign number associated with the fund.
HAS_COLUMN	`Funds`	`campaign`	Name of the campaign associated with the fund.
HAS_COLUMN	`Funds`	`cont_designation_id`	Contribution designation ID for the fund.
HAS_COLUMN	`Funds`	`cont_designation`	Contribution designation for the fund.
HAS_COLUMN	`Funds`	`channel_id`	Channel ID for the fund transactions.
HAS_COLUMN	`Funds`	`channel_desc`	Description of the channel for fund transactions.
HAS_COLUMN	`Funds`	`pmt_method_id`	Payment method ID for the fund transactions.
HAS_COLUMN	`Funds`	`pmt_method`	

Edge Label	Source	Target	Description
			Description of the payment method for fund transactions.
HAS_COLUMN	`Funds`	`pledge_pmt_amt`	Amount of pledge payment made.
HAS_COLUMN	`Funds`	`gift_pmt_amt`	Amount of gift payment made.
HAS_COLUMN	`Funds`	`pmt_count`	Count of payments made for the fund.
HAS_COLUMN	`Funds`	`customer_no`	Customer number associated with the fund.
HAS_COLUMN	`Funds`	`lname`	Last name of the customer associated with the fund.
HAS_COLUMN	`Funds`	`fname`	First name of the customer associated with the fund.
HAS_COLUMN	`Funds`	`creditee_type`	Type of the creditee associated with the fund.
HAS_COLUMN	`Funds`	`creditee_type_desc`	Description of the creditee associated with the fund.
HAS_COLUMN	`Funds`	`creditee_no`	Creditee number associated with the fund.
HAS_COLUMN	`Funds`	`creditee_name`	Name of the creditee associated with the fund.
HAS_COLUMN	`Funds`	`display_name`	Display name for the fund record.
HAS_COLUMN	`Funds`	`sort_name`	Sort name for the fund record.

Edge Label	Source	Target	Description
HAS_COLUMN	`members`	`membership_id`	Unique identifier for each membership record.
HAS_COLUMN	`members`	`constituent_id`	Identifier for the constituent associated with the membership.
HAS_COLUMN	`members`	`membership_category`	Category of the membership.
HAS_COLUMN	`members`	`amount`	Financial amount associated with the membership.
HAS_COLUMN	`members`	`initdate`	Date when the membership was initiated.
HAS_COLUMN	`members`	`expdate`	Date when the membership expires.
HAS_COLUMN	`members`	`source`	Source of the membership information.
HAS_COLUMN	`members`	`appeal`	Appeal associated with the membership.
HAS_COLUMN	`members`	`campaign`	Campaign associated with the membership.
HAS_COLUMN	`members`	`sales_channel`	Sales channel through which the membership was acquired.
HAS_COLUMN	`members`	`new_renew_reinstate_status`	Status of the membership regarding new, renewal, or reinstatement.

Edge Label	Source	Target	Description
HAS_COLUMN	`members`	`macro_level_trend`	Macro-level trend associated with the membership.
HAS_COLUMN	`members`	`micro_category_trend`	Micro-category trend associated with the membership.
HAS_COLUMN	`members`	`avc_amount`	Average contribution amount for the membership.
HAS_COLUMN	`members`	`membership_level`	Level of the membership.
HAS_COLUMN	`members`	`membership_level_code`	Code representing the membership level.
HAS_COLUMN	`members`	`membership_level_id`	Identifier for the membership level.
HAS_COLUMN	`members`	`membership_level_rank`	Rank of the membership level.
HAS_COLUMN	`members`	`membership_organization`	Organization associated with the membership.
HAS_COLUMN	`members`	`appeal_id`	Identifier for the appeal associated with the membership.
HAS_COLUMN	`members`	`campaign_id`	Identifier for the campaign associated with the membership.
HAS_COLUMN	`members`	`source_id`	Identifier for the source associated with the membership.
HAS_COLUMN	`Appeal Source Structure`	`campaign_no`	Unique identifier for the campaign

Edge Label	Source	Target	Description
			associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`campaign_desc`	Description of the campaign associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`campaign_category`	Category of the campaign associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`fyear`	Fiscal year in which the appeal campaign is active.
HAS_COLUMN	`Appeal Source Structure`	`appeal_no`	Unique identifier for the appeal.
HAS_COLUMN	`Appeal Source Structure`	`appeal_desc`	Description of the appeal.
HAS_COLUMN	`Appeal Source Structure`	`appeal_category`	Category of the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_no`	Unique identifier for the source of the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_name`	Name of the source associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_type`	Type of the source associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_group`	Group classification of the source associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_provider`	Provider of the source associated with the appeal.
HAS_COLUMN		`source_keycode`	

Edge Label	Source	Target	Description
	`Appeal Source Structure`		Keycode associated with the source of the appeal.
HAS_COLUMN	`Appeal Source Structure`	`source_inactive`	Indicates if the source is inactive.
HAS_COLUMN	`Appeal Source Structure`	`source_hotlist_status`	Status of the source in the hotlist.
HAS_COLUMN	`Appeal Source Structure`	`media_type`	Type of media associated with the appeal.
HAS_COLUMN	`Appeal Source Structure`	`acq_dt`	Acquisition date of the appeal.
HAS_COLUMN	`Appeal Source Structure`	`num_contacts`	Number of contacts made regarding the appeal.
HAS_COLUMN	`batch summary`	`batch_id`	Unique identifier for each batch.
HAS_COLUMN	`batch summary`	`contribution_id`	Identifier for contributions associated with the batch.
HAS_COLUMN	`batch summary`	`batch_type`	Type of the batch.
HAS_COLUMN	`batch summary`	`batch_status`	Current status of the batch.
HAS_COLUMN	`batch summary`	`batch_type_group`	Group classification for the batch type.
HAS_COLUMN	`batch summary`	`post_date`	Date when the batch was posted.
HAS_COLUMN	`batch summary`	`fiscal_year`	Fiscal year associated with the batch.
HAS_COLUMN	`Contact Types Relationships`	`customer_no`	Unique identifier for each customer.

Edge Label	Source	Target	Description
HAS_COLUMN	`Contact Types Relationships`	`customer_type_desc`	Description of the customer type.
HAS_COLUMN	`Contact Types Relationships`	`relationship_customer__`	Identifier for the related customer in the relationship.
HAS_COLUMN	`Contact Types Relationships`	`relationship_type`	Type of relationship between customers.
HAS_COLUMN	`Contact Types Relationships`	`relationship_a1_a2_indicator`	Indicator for the relationship status between customers.
HAS_COLUMN	`Contribution Transaction Link`	`contribution_id`	Identifier for the contribution associated with the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`transaction_id`	Unique identifier for the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`batch_id`	Identifier for the batch associated with the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`gl_entry_type`	Type of general ledger entry for the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`transaction_amount`	Amount of money involved in the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`transaction_type`	Type of transaction being recorded.
HAS_COLUMN	`Contribution Transaction Link`	`campaign_id`	Identifier for the campaign associated with the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`fund_id`	Identifier for the fund associated with the transaction.

Edge Label	Source	Target	Description
HAS_COLUMN	`Contribution Transaction Link`	`transaction_category`	Category of the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`credit_amount`	Amount of money credited in the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`debit_amount`	Amount of money debited in the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`sales_channel`	Channel through which the transaction was made.
HAS_COLUMN	`Contribution Transaction Link`	`mode_of_sale`	Mode of sale for the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`mode_of_sale_category`	Category of the mode of sale.
HAS_COLUMN	`Contribution Transaction Link`	`gl_account`	General ledger account associated with the transaction.
HAS_COLUMN	`Contribution Transaction Link`	`days_in_date`	Date associated with the transaction.
HAS_COLUMN	`Deferrals and Receiveables Not in Model Yet`	`batch_id`	Identifier for the batch of transactions.
HAS_COLUMN	`Deferrals and Receiveables Not in Model Yet`	`post_id`	Identifier for the post associated with the transaction.
HAS_COLUMN	`Deferrals and Receiveables Not in Model Yet`	`batch_type`	Type of the batch for categorization purposes.
HAS_COLUMN	`Deferrals and Receiveables Not in Model Yet`	`transaction_id`	Unique identifier for each transaction.
HAS_COLUMN			

Edge Label	Source	Target	Description
	`Deferrals and Receiveables Not in Model Yet`	`contribution_id`	Identifier for the contribution associated with the transaction.
HAS_COLUMN	`Deferrals and Receiveables Not in Model Yet`	`days_in_date`	Date associated with the transaction for tracking purposes.
HAS_COLUMN	`production season types`	`production_season`	The name of the production season.
HAS_COLUMN	`production season types`	`production_season_id`	Unique identifier for each production season.
HAS_COLUMN	`production season types`	`type`	Type of the production season.
HAS_COLUMN	`production season types`	`production_id`	Identifier for the associated production.
HAS_COLUMN	`production season types`	`performance_id`	Identifier for the performance metrics associated with the production season.
HAS_COLUMN	`production season types`	`season_id`	Identifier for the season.
HAS_COLUMN	`production season types`	`season`	The season classification.
HAS_COLUMN	`Ticket Seat ID`	`ticket_id`	Identifier for the ticket associated with the seat.
HAS_COLUMN	`Ticket Seat ID`	`seat_id`	Unique identifier for the seat.
HAS_COLUMN	`Ticket Seat ID`	`seat_num`	The number designation of the seat.
HAS_COLUMN			

Edge Label	Source	Target	Description
	`Ticket Seat ID`	`seat_row`	The row designation of the seat.
HAS_COLUMN	`Ticket Seat ID`	`section`	The section designation of the seat.
HAS_COLUMN	`Ticket Seat ID`	`screen`	The screen designation for the performance.
HAS_COLUMN	`Ticket Seat ID`	`performance_id`	Identifier for the performance associated with the seat.
HAS_COLUMN	`Ticket Seat ID`	`order_id`	Identifier for the order associated with the ticket sale.
HAS_COLUMN	`Ticket Seat ID`	`mode_of_sale`	The mode through which the ticket was sold.
HAS_COLUMN	`Contribution Output`	`constituent_id`	Unique identifier for each constituent.
HAS_COLUMN	`Contribution Output`	`appeal_id`	Identifier for the appeal associated with the contribution.
HAS_COLUMN	`Contribution Output`	`sales_channel`	Channel through which the contribution was made.
HAS_COLUMN	`Contribution Output`	`designation`	Designation of the contribution, if applicable.
HAS_COLUMN	`Contribution Output`	`contribution_id`	Unique identifier for each contribution.
HAS_COLUMN	`Contribution Output`	`days_in_date`	Date associated with the contribution.

Edge Label	Source	Target	Description
HAS_COLUMN	`Contribution Output`	`fund_id`	Identifier for the fund associated with the contribution.
HAS_COLUMN	`Contribution Output`	`amount`	Monetary amount of the contribution.
HAS_COLUMN	`Contribution Output`	`type`	Type of contribution (e.g., one-time, recurring).
HAS_COLUMN	`Contribution Output`	`worker_constituent_id`	Identifier for the worker associated with the contribution.
HAS_COLUMN	`Contribution Output`	`source_id`	Identifier for the source of the contribution.
HAS_COLUMN	`Contribution Output`	`billing_type`	Type of billing associated with the contribution.
HAS_COLUMN	`Contribution Output`	`campaign_id`	Identifier for the campaign associated with the contribution.
HAS_COLUMN	`Contribution Output`	`balance_amount`	Balance amount remaining for the contribution.
HAS_COLUMN	`dimconstituentsanon`	`constituent_id`	Unique identifier for each constituent.
HAS_COLUMN	`dimconstituentsanon`	`primary_address_postcode`	Postcode of the primary address associated with the constituent.
HAS_COLUMN	`dimconstituentsanon`	`type`	Type of constituent, indicating their classification.
HAS_COLUMN	`dimconstituentsanon`	`constituencies`	List of constituencies associated with the constituent.

Edge Label	Source	Target	Description
HAS_COLUMN	`Promo Quarterly`	`customer_no`	Unique identifier for customers participating in promotions.
HAS_COLUMN	`Promo Quarterly`	`promotion_appeal`	Identifier for the promotional appeal being analyzed.
HAS_COLUMN	`Promo Quarterly`	`promotion_response`	Response metric indicating customer engagement with the promotion.
HAS_COLUMN	`Promo Quarterly`	`promotion_response_date`	Timestamp indicating when the promotion response was recorded.
HAS_COLUMN	`Promo Quarterly`	`promotion_source_number`	Identifier for the source of the promotion.
HAS_COLUMN	`Ticket`	`constituent_id`	Identifier for the constituent associated with the ticket.
HAS_COLUMN	`Ticket`	`const_type`	Type of the constituent associated with the ticket.
HAS_COLUMN	`Ticket`	`order_id`	Identifier for the order associated with the ticket.
HAS_COLUMN	`Ticket`	`season`	Season during which the ticket is valid.
HAS_COLUMN	`Ticket`	`production_season`	Production season for the event related to the ticket.
HAS_COLUMN	`Ticket`	`campaign`	Campaign associated with the ticket sale.

Edge Label	Source	Target	Description
HAS_COLUMN	`Ticket`	`campaign_id`	Identifier for the campaign associated with the ticket sale.
HAS_COLUMN	`Ticket`	`appeal`	Appeal associated with the ticket sale.
HAS_COLUMN	`Ticket`	`appeal_id`	Identifier for the appeal associated with the ticket sale.
HAS_COLUMN	`Ticket`	`source`	Source from which the ticket sale originated.
HAS_COLUMN	`Ticket`	`source_id`	Identifier for the source associated with the ticket sale.
HAS_COLUMN	`Ticket`	`channel`	Channel through which the ticket was sold.
HAS_COLUMN	`Ticket`	`order_date`	Date when the ticket was ordered.
HAS_COLUMN	`Ticket`	`mode_of_sale`	Mode of sale for the ticket.
HAS_COLUMN	`Ticket`	`package_code`	Code representing the ticket package.
HAS_COLUMN	`Ticket`	`ticket_paid_amount`	Amount paid for the ticket.
HAS_COLUMN	`Ticket`	`price_type`	Type of price for the ticket.
HAS_COLUMN	`Ticket`	`section`	Section associated with the ticket.
HAS_COLUMN	`Ticket`	`price_type_category`	Category of the price type for the ticket.
HAS_COLUMN	`Ticket`	`ticket_id`	

Edge Label	Source	Target	Description
			Unique identifier for the ticket.
HAS_COLUMN	`Ticket`	`seat_id`	Identifier for the seat associated with the ticket.
HAS_COLUMN	`Deceased Cont W Last Activity`	`customer_no`	Unique identifier for each customer.
HAS_COLUMN	`Deceased Cont W Last Activity`	`customer_last_gift_dt`	Date of the last gift made by the customer.
HAS_COLUMN	`Deceased Cont W Last Activity`	`customer_last_ticket_dt`	Date of the last ticket purchased by the customer.
HAS_COLUMN	`pseudonymous users`	`audiences`	Represents the audiences associated with the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`device`	Indicates the device used by the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`geo`	Stores geographical information related to the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`last_updated_date`	Records the last updated date for the pseudonymous user data.
HAS_COLUMN	`pseudonymous users`	`occurrence_date`	Indicates the occurrence date of the pseudonymous user's interaction.
HAS_COLUMN	`pseudonymous users`	`privacy_info`	Contains privacy-related information for the pseudonymous user.

Edge Label	Source	Target	Description
HAS_COLUMN	`pseudonymous users`	`pseudo_user_id`	Serves as the unique identifier for the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`stream_id`	Represents the stream ID associated with the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`user_info`	Holds additional user information related to the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`user_ltv`	Represents the lifetime value of the pseudonymous user.
HAS_COLUMN	`pseudonymous users`	`user_properties`	Contains properties associated with the pseudonymous user.
HAS_COLUMN	`users`	`audiences`	Represents the audiences associated with the user.
HAS_COLUMN	`users`	`device`	Indicates the device used by the user.
HAS_COLUMN	`users`	`geo`	Contains geographical information related to the user.
HAS_COLUMN	`users`	`last_updated_date`	Records the last date the user data was updated.
HAS_COLUMN	`users`	`occurrence_date`	Represents the date of occurrence for user events.
HAS_COLUMN	`users`	`privacy_info`	Contains privacy-related information for the user.

Edge Label	Source	Target	Description
HAS_COLUMN	`users`	`user_id`	Uniquely identifies each user in the system.
HAS_COLUMN	`users`	`user_info`	Holds additional information about the user.
HAS_COLUMN	`users`	`user_ltv`	Represents the lifetime value of the user.
HAS_COLUMN	`users`	`user_properties`	Contains various properties associated with the user.
HAS_COLUMN	`events`	`batch_event_index`	Index for batch events.
HAS_COLUMN	`events`	`batch_ordering_id`	Unique identifier for batch ordering.
HAS_COLUMN	`events`	`batch_page_id`	Identifier for the batch page.
HAS_COLUMN	`events`	`collected_traffic_source`	Source of collected traffic.
HAS_COLUMN	`events`	`device`	Device used for the event.
HAS_COLUMN	`events`	`ecommerce`	Ecommerce-related event data.
HAS_COLUMN	`events`	`event_bundle_sequence_id`	Unique identifier for the event bundle.
HAS_COLUMN	`events`	`event_date`	Date when the event occurred.
HAS_COLUMN	`events`	`event_name`	Name of the event.
HAS_COLUMN	`events`	`event_params`	Parameters associated with the event.

Edge Label	Source	Target	Description
HAS_COLUMN	`events`	`event_timestamp`	Timestamp of when the event was recorded.
HAS_COLUMN	`events`	`event_value_in_usd`	Value of the event in USD.
HAS_COLUMN	`events`	`geo`	Geographical information related to the event.
HAS_COLUMN	`events`	`is_active_user`	Indicates if the user is active.
HAS_COLUMN	`events`	`items`	Items associated with the event.
HAS_COLUMN	`events`	`platform`	Platform used for the event.
HAS_COLUMN	`events`	`privacy_info`	Privacy information related to the event.
HAS_COLUMN	`events`	`session_traffic_source_last_click`	Traffic source from the last click.
HAS_COLUMN	`events`	`stream_id`	Unique identifier for the stream.
HAS_COLUMN	`events`	`traffic_source`	Source of traffic for the event.
HAS_COLUMN	`events`	`user_first_touch_timestamp`	Timestamp of the user's first touch.
HAS_COLUMN	`events`	`user_id`	Unique identifier for the user.
HAS_COLUMN	`events`	`user_ltv`	Lifetime value of the user.
HAS_COLUMN	`events`	`user_properties`	Properties associated with the user.
HAS_COLUMN	`events`	`user_pseudo_id`	

Edge Label	Source	Target	Description
			Pseudo identifier for the user.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`Deferrals and Receiveables Not in Model Yet`	References contribution transactions for tracking pending financial transactions.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`Ticket`	References contribution transactions for ticket sales and event management.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`production season types`	Referenced by production season types: This table links contribution transactions to details, which may relate to production seasons for fundraising analysis.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`batch summary`	Referenced by batch summary: Connects contribution transactions to batch summaries for detailed financial reporting.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`Funds`	Referenced by Funds: Links contributions to their respective funds for tracking financial contributions.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`members`	Referenced by members: Transactions related to contributions are linked to memberships,

Edge Label	Source	Target	Description
			providing a comprehensive view of financial support.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be linked to contribution transactions.
HAS_FOREIGN_KEY	`Contribution Transaction Link`	`Contribution Output`	Referenced by Contribution Output: Links contribution transactions to their respective details for financial reporting.
HAS_CROSS_REFERENCE	`Contribution Transaction Link`	`pseudonymous users`	Referenced by pseudonymous users: This table links contribution transactions to their details, potentially connecting to pseudonymous users through transaction identifiers.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Packages`	Links package information to specific promotional appeals for sales analysis.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Appeal Source Structure`	Connects appeal sources to promotional campaigns for effectiveness tracking.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Ticket`	Associates ticket sales with promotional appeals for event performance analysis.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Promo Quarterly`	`Contribution Output`	Links contributions to promotional appeals for fundraising effectiveness evaluation.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Contribution Transaction Link`	Referenced by Contribution Transaction Link: Associates contribution transactions with promotional campaigns for performance evaluation.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Packages`	Referenced by Packages: The Packages table references promotional campaigns to evaluate the effectiveness of package-related marketing strategies.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Appeal Source Structure`	Referenced by Appeal Source Structure: Links promotional campaigns to appeal sources for analyzing customer engagement.
HAS_FOREIGN_KEY	`Promo Quarterly`	`production season types`	Referenced by production season types: This table stores promotional data, which may relate to production seasons for analyzing customer engagement.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Promo Quarterly`	`batch summary`	Referenced by batch summary: Links promotional campaigns to batch summaries for customer engagement analysis.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include transactions related to promotional campaigns, linking to promotional data.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Ticket`	Referenced by Ticket: Links ticket sales to promotional campaigns for analyzing customer engagement.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Funds`	Referenced by Funds: Associates promotional campaigns with specific funds for marketing analysis.
HAS_FOREIGN_KEY	`Promo Quarterly`	`members`	Referenced by members: Promotional campaigns are linked to memberships, enabling analysis of member responses to marketing efforts.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be associated with promotional

Edge Label	Source	Target	Description
			campaigns for ticket sales.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Contact Types Relationships`	Referenced by Contact Types Relationships: This table stores promotional data related to customer engagement, which may be influenced by the relationships defined in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`Promo Quarterly`	`Contribution Output`	Referenced by Contribution Output: Associates contributions with quarterly promotional campaigns for marketing analysis.
HAS_FOREIGN_KEY	`Packages`	`Ticket`	The Ticket table references the Packages table to associate ticket sales with specific package orders.
HAS_FOREIGN_KEY	`Packages`	`Ticket Seat ID`	The Ticket Seat ID table references the Packages table to link seat allocations to specific package orders.
HAS_FOREIGN_KEY	`Packages`	`Contribution Transaction Link`	Referenced by Contribution Transaction Link: Links contribution transactions to package details associated with customer orders.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Packages`	`dimconstituentsanon`	Referenced by dimconstituentsanon: The Packages table includes information about packages associated with orders, linking each package to the corresponding constituent's anonymized profile.
HAS_FOREIGN_KEY	`Packages`	`production season types`	Referenced by production season types: This table contains information about packages associated with orders, which may relate to production seasons for sales analysis.
HAS_FOREIGN_KEY	`Packages`	`batch summary`	Referenced by batch summary: Associates packages with batch summaries for order processing insights.
HAS_FOREIGN_KEY	`Packages`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions associated with specific packages, linking to order details.
HAS_FOREIGN_KEY	`Packages`	`Funds`	Referenced by Funds: Links package details to funds for tracking sales and contributions.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Packages`	`members`	Referenced by members: Packages purchased by members are linked to their membership records, facilitating sales analysis.
HAS_FOREIGN_KEY	`Packages`	`Deceased Cont W Last Activity`	Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references package information associated with deceased customers' orders.
HAS_FOREIGN_KEY	`Packages`	`Contribution Output`	Referenced by Contribution Output: Associates contributions with packages linked to customer orders.
HAS_CROSS_REFERENCE	`Packages`	`events`	Referenced by events: Events may be linked to specific packages associated with orders, connecting event data to sales and marketing strategies.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Packages`	References appeal sources to analyze package offerings linked to specific appeals.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Ticket`	Links ticket sales to appeal sources for understanding sales performance related

Edge Label	Source	Target	Description
			to fundraising campaigns.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`members`	Associates membership records with appeal sources for analyzing membership growth driven by appeals.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Contribution Transaction Link`	Referenced by Contribution Transaction Link: Links contributions to their respective appeal sources for campaign effectiveness tracking.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`production season types`	Referenced by production season types: This table captures sources of appeals, which may be linked to production seasons for campaign effectiveness analysis.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`batch summary`	Referenced by batch summary: Associates batch summaries with appeal sources for campaign effectiveness tracking.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions related to specific appeals,

Edge Label	Source	Target	Description
			linking to appeal sources.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Ticket`	Referenced by Ticket: Associates ticket sales with specific appeal campaigns for performance tracking.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Funds`	Referenced by Funds: Links appeal sources to funds for tracking fundraising effectiveness.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`members`	Referenced by members: Memberships are linked to specific appeals, allowing for targeted fundraising efforts based on member data.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be linked to specific appeals made to customers.
HAS_FOREIGN_KEY	`Appeal Source Structure`	`Contribution Output`	Referenced by Contribution Output: Links contributions to specific appeal sources for campaign effectiveness analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Contribution Transaction Link`	Referenced by Contribution Transaction Link: Links contributions to anonymized constituent information for

Edge Label	Source	Target	Description
			demographic analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Appeal Source Structure`	Referenced by Appeal Source Structure: Anonymized constituent information linked to appeal sources for demographic analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`production season types`	Referenced by production season types: This table contains anonymized constituent information, which may relate to production season types for demographic analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`batch summary`	Referenced by batch summary: Links batch summary to anonymized constituent information for demographic analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table captures transactions related to constituents, linking to anonymized constituent information.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Ticket`	

Edge Label	Source	Target	Description
			Referenced by Ticket: Links ticket information to anonymized constituent data for demographic analysis and engagement tracking.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Funds`	Referenced by Funds: Links anonymized constituent data to funds for demographic analysis.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`members`	Referenced by members: Anonymized constituent data is linked to membership records, allowing for demographic analysis without revealing identities.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be linked to a constituent who purchased the ticket.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Deceased Cont W Last Activity`	Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references anonymized constituent information for deceased customers.
HAS_FOREIGN_KEY	`dimconstituentsanon`	`Contribution Output`	Referenced by Contribution Output:

Edge Label	Source	Target	Description
			Links contributions to anonymized constituent information for demographic analysis.
HAS_CROSS_REFERENCE	`dimconstituentsanon`	`events`	Referenced by events: Events may involve interactions with constituents, linking event data to anonymized constituent information for analysis.
HAS_CROSS_REFERENCE	`dimconstituentsanon`	`pseudonymous users`	Referenced by pseudonymous users: The dimconstituentsanon table contains anonymized constituent information linked to pseudonymous users.
HAS_FOREIGN_KEY	`production season types`	`Ticket`	This table contains ticket information that may reference production season types for event categorization.
HAS_FOREIGN_KEY	`production season types`	`Ticket Seat ID`	This table contains details about ticket seats that may reference production season types for performance context.
HAS_FOREIGN_KEY	`production season types`	`batch summary`	Referenced by batch summary: Connects batch summaries to specific production

Edge Label	Source	Target	Description
			seasons for operational tracking.
HAS_FOREIGN_KEY	`production season types`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include transactions related to specific production seasons, linking to season types.
HAS_FOREIGN_KEY	`production season types`	`Ticket`	Referenced by Ticket: Connects ticket data to specific production seasons, aiding in performance and event management.
HAS_FOREIGN_KEY	`production season types`	`Funds`	Referenced by Funds: Links production season data to funds for financial planning.
HAS_FOREIGN_KEY	`production season types`	`members`	Referenced by members: Memberships may be associated with specific production seasons, linking member engagement to seasonal activities.
HAS_FOREIGN_KEY	`production season types`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be associated with a specific production season for events.
HAS_FOREIGN_KEY	`production season types`	`Contribution Output`	Referenced by Contribution Output: Associates contributions with

Edge Label	Source	Target	Description
			specific production seasons for event planning.
HAS_CROSS_REFERENCE	`production season types`	`events`	Referenced by events: Events may be categorized by production seasons, linking event data to seasonal classifications for operational insights.
HAS_CROSS_REFERENCE	`batch summary`	`events`	Associates events with batch summaries for user interaction analysis.
HAS_FOREIGN_KEY	`batch summary`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table records transactions that are processed in batches, linking to batch summaries.
HAS_FOREIGN_KEY	`batch summary`	`Ticket`	Referenced by Ticket: Links ticket transactions to batch processing for operational oversight.
HAS_FOREIGN_KEY	`batch summary`	`Funds`	Referenced by Funds: Associates batch processing activities with specific funds for operational tracking.
HAS_FOREIGN_KEY	`batch summary`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may be associated with a

Edge Label	Source	Target	Description
			batch of ticket sales processed together.
HAS_CROSS_REFERENCE	`batch summary`	`events`	Referenced by events: The events table captures event data that is processed in batches, linking each event to its corresponding batch for operational oversight.
HAS_CROSS_REFERENCE	`batch summary`	`pseudonymous users`	Referenced by pseudonymous users: The batch summary table tracks batches processed and is linked to pseudonymous users through batch identifiers.
HAS_FOREIGN_KEY	`Deferrals and Receivables Not in Model Yet`	`Funds`	Referenced by Funds: Associates pending financial transactions with specific funds for financial tracking.
HAS_FOREIGN_KEY	`Deferrals and Receivables Not in Model Yet`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may relate to financial transactions pending in the system.
HAS_CROSS_REFERENCE	`Deferrals and Receivables Not in Model Yet`	`events`	Referenced by events: Events may be associated with financial transactions that are pending integration into the financial model, linking event data to transaction records.

Edge Label	Source	Target	Description
HAS_CROSS_REFERENCE	`Deferrals and Receiveables Not in Model Yet`	`pseudonymous users`	Referenced by pseudonymous users: This table tracks financial transactions that may be linked to pseudonymous users through transaction identifiers.
HAS_FOREIGN_KEY	`Ticket`	`Ticket Seat ID`	Referenced by ticket data to identify specific seats associated with ticket purchases.
HAS_FOREIGN_KEY	`Ticket`	`Deferrals and Receiveables Not in Model Yet`	References ticket transactions for tracking financial operations related to ticket sales.
HAS_FOREIGN_KEY	`Ticket`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table tracks transactions that may include ticket purchases, linking to ticket details.
HAS_FOREIGN_KEY	`Ticket`	`Funds`	Referenced by Funds: Links ticket sales to specific funds for event-related contributions.
HAS_FOREIGN_KEY	`Ticket`	`members`	Referenced by members: Each ticket is associated with a member's purchase or attendance, linking ticket sales to membership details.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Ticket`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat is associated with a specific ticket for an event.
HAS_FOREIGN_KEY	`Ticket`	`Deceased Cont W Last Activity`	Referenced by Deceased Cont W Last Activity: The Deceased Cont W Last Activity table references ticket information related to deceased customers' event participation.
HAS_FOREIGN_KEY	`Ticket`	`Contact Types Relationships`	Referenced by Contact Types Relationships: This table captures ticket information for events, which may involve customer types defined in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`Ticket`	`Contribution Output`	Referenced by Contribution Output: Associates contributions with ticket purchases made by constituents.
HAS_CROSS_REFERENCE	`Ticket`	`events`	Referenced by events: Each event may correspond to a specific ticket issued, linking event data to ticket information for event management.
HAS_FOREIGN_KEY	`Funds`	`Deceased Cont W Last Activity`	Referenced by Deceased Cont W Last Activity: The

Edge Label	Source	Target	Description
			Deceased Cont W Last Activity table references fund designations related to deceased customers.
HAS_FOREIGN_KEY	`Funds`	`Contribution Output`	Referenced by Contribution Output: Links contributions to specific funds for financial tracking.
HAS_FOREIGN_KEY	`members`	`Funds`	Referenced by Funds: Links membership details to specific funds for tracking member contributions.
HAS_FOREIGN_KEY	`members`	`Contact Types Relationships`	Referenced by Contact Types Relationships: This table contains membership details for constituents, which may relate to customer types in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`members`	`Contribution Output`	Referenced by Contribution Output: Connects contributions to membership details of constituents.
HAS_CROSS_REFERENCE	`members`	`events`	Referenced by events: Events may be associated with specific memberships, linking event data to membership details for engagement tracking.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Ticket Seat ID`	`Contribution Output`	Referenced by Contribution Output: Associates contributions with specific ticket seats for event management.
HAS_CROSS_REFERENCE	`Ticket Seat ID`	`pseudonymous users`	Referenced by pseudonymous users: The Ticket Seat ID table contains details about ticket seats that may be linked to pseudonymous users through seat identifiers.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`Promo Quarterly`	The Promo Quarterly table references deceased customers to analyze promotional engagement.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`Contribution Transaction Link`	Referenced by Contribution Transaction Link: Connects contribution transactions to deceased customer records for historical engagement analysis.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`production season types`	Referenced by production season types: This table tracks deceased customers, which may relate to production seasons for historical

Edge Label	Source	Target	Description
			engagement analysis.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`batch summary`	Referenced by batch summary: Links batch summaries to deceased customer records for historical engagement analysis.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may track transactions related to deceased customers, linking to their last activity.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`members`	Referenced by members: Deceased members are tracked alongside their last activities, providing insights into member engagement history.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may relate to customers who have passed away, impacting ticket sales.
HAS_FOREIGN_KEY	`Deceased Cont W Last Activity`	`Contribution Output`	Referenced by Contribution Output: Links contributions to deceased customers for historical analysis.
HAS_CROSS_REFERENCE	`Deceased Cont W Last Activity`	`events`	Referenced by events: Events may involve interactions

Edge Label	Source	Target	Description
			with deceased customers, linking event data to historical customer engagement records.
HAS_CROSS_REFERENCE	`Deceased Cont W Last Activity`	`users`	Referenced by users: The users table references deceased customers to manage user data related to customer interactions.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Deceased Cont W Last Activity`	This table tracks deceased customers, utilizing the customer_no to reference customer types defined in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Funds`	This table stores information about funds and their associated transactions, which may relate to customer types in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Contribution Transaction Link`	This table links contribution transactions to their respective details, potentially referencing customer types in the Contact Types Relationships table.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Appeal Source Structure`	Referenced by Appeal Source Structure: Defines relationships

Edge Label	Source	Target	Description
			between customer types and appeal sources for targeted marketing.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`production season types`	Referenced by production season types: This table defines relationships between customer types, which may relate to production seasons for targeted marketing.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include transactions related to different customer types, linking to customer relationships.
HAS_FOREIGN_KEY	`Contact Types Relationships`	`Ticket Seat ID`	Referenced by Ticket Seat ID: Each ticket seat may relate to different types of customer interactions.
HAS_CROSS_REFERENCE	`Contact Types Relationships`	`users`	Referenced by users: The users table references customer types to understand the relationships between different user profiles.
HAS_FOREIGN_KEY	`Contribution Output`	`batch summary`	Referenced by batch summary: Associates contributions made by constituents with batch summaries for fundraising insights.

Edge Label	Source	Target	Description
HAS_FOREIGN_KEY	`Contribution Output`	`Deferrals and Receiveables Not in Model Yet`	Referenced by Deferrals and Receiveables Not in Model Yet: The target table may include contributions linked to constituents, referencing contribution records.
HAS_FOREIGN_KEY	`Contribution Output`	`Contact Types Relationships`	Referenced by Contact Types Relationships: This table records contributions made by constituents, which are likely categorized by customer types in the Contact Types Relationships table.
HAS_CROSS_REFERENCE	`Contribution Output`	`events`	Referenced by events: Events may be related to contributions made by constituents, linking event data to contribution records for fundraising analysis.
HAS_CROSS_REFERENCE	`Contribution Output`	`pseudonymous users`	Referenced by pseudonymous users: The Contribution Output table tracks contributions made by constituents linked to pseudonymous users.
HAS_FOREIGN_KEY	`events`	`users`	Referenced by users: The users table references events to track user

Edge Label	Source	Target	Description
			interactions and behaviors associated with specific events.
HAS_FOREIGN_KEY	`events`	`pseudonymous users`	Referenced by pseudonymous users: The events table captures user interactions and is linked to pseudonymous users through event identifiers.
HAS_FOREIGN_KEY	`users`	`pseudonymous users`	The pseudonymous users table references users to maintain a link between pseudonymous identifiers and user profiles.
HAS_FOREIGN_KEY	`users`	`pseudonymous users`	Referenced by pseudonymous users: The users table contains user-related data that is linked to pseudonymous users through user identifiers.
HAS_CROSS_REFERENCE	`pseudonymous users`	`members`	The members table tracks membership details that may reference pseudonymous users through membership identifiers.

Summary

Metadata Type	Count
Sources	2
Tables	18
Columns	235
Edges	382

Report generated by MongoDB Metadata Extractor on 2025-08-21 at 12:04:28