



Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

# Processamento e Recuperação de Informação

## Learning to Rank

Departamento de Engenharia Informática  
Instituto Superior Técnico

1º Semestre  
2018/2019



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# Bibliography

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Ricardo Baeza-Yates, Berthier Ribeiro-Neto, Modern Information Retrieval, 2nd edition. Chapter 11.
- T.-Y. Liu, "Learning to rank for information retrieval," Foundations and Trends in Databases, vol. 3, no. 3, pp. 225-331, 2009.



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# Search Engine Ranking

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

**Ranking** is the hardest and most important function of a search engine

## Main challenges:

- Evaluation
- Managing Web spam
- Identification of relevant content
- Defining the ranking function



# Evaluating the Ranking

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Devise an adequate process of **evaluating the ranking**, in terms of **relevance** of results to the user
- Without such evaluation, it is close to impossible to fine tune the ranking function
- Without fine tuning the ranking, there is no state-of-the-art engine—this is an empirical field of science



# Dealing with Web Spam

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Avoiding, preventing, managing Web spam
- Spammers are malicious users who try to trick search engines by artificially inflating signals used for ranking
- A consequence of the economic incentives of the current advertising model adopted by search engines



# Defining Relevant Content

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Evidence of quality can be indicated by several signals such as:

- Domain names
- Text content
- Links (e.g. PageRank)
- Web page access patterns

Additional useful signals are provided by the layout of the Web page, its title, metadata, font sizes, etc.





# The Ranking Function

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Following: from simple ranking functions to complex combinations of signals



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# Evidences for Relevance

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Three main types of signals:

- 1 Content
- 2 Structure
- 3 Usage

In total we can have hundreds of distinct signals

- Bing claims to use  $> 1000$  (see [here](#))
- Google claims to use  $> 200$  many with  $> 50$  variations



# Content Signals

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Related to the **text** itself
- Can vary from **simple word counts** to a **full IR score**, such as TF-IDF or BM25
- Can be provided by the layout, that is, the HTML source
  - Simple **format** indicators (more weight given to titles/headings)
  - Sophisticated indicators as the **proximity** of certain tags in the page



# Structure Signals

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Intrinsic to the **linked structure** of the Web
- Some of them are textual in nature, such as **anchor text**
- Others pertain to the links themselves, such as **in-links** and **out-links** from a page
- Link-based signals find broad usage beyond classic search engine ranking



# Web Usage Signals

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Main one is the implicit feedback provided by the user clicks (**click-through**)
- Other usage signals include:
  - information on the user's **geographical context** (IP address, language)
  - **technological context** (operating system, browser)
  - **temporal context** (query history by the use of cookies)
  - even **site speed**



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function**
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# Simple Ranking Scheme

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Use only **text-based ranking**
  - E.g. BM25 or cosine similarity
- Applied in early search engines

Or...

- Use a global ranking function such as **PageRank**
- Quality of a Web page in the result set is independent of the query
- The query only selects pages to be ranked





# Simple Combination of Signals

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Use a linear combination of different ranking signals

## Example

- Consider the pages  $p$  that satisfy query  $Q$
- Rank score  $R(p, Q)$  of page  $p$  with regard to query  $Q$  can be computed as

$$R(p, Q) = \alpha BM25(p, Q) + (1 - \alpha) PR(p)$$

- $\alpha = 1$ : text-based ranking
- $\alpha = 0$ : link-based ranking, independent of the query



# A More Complex Combination

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Current engines combine a text-based ranking with a link-based ranking, most of them a lot more complex than BM25 and PageRank
- Value of  $\alpha$  is tuned experimentally using
  - Labeled data as ground truth, or
  - Clickthrough data
- $\alpha$  might even be query dependent
  - for *navigational* queries  $\alpha$  could be made smaller than for *informational* queries



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion**
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# Principle

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals


The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)





# Combining Similarity Scores

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- ① eliminate **duplicates**
- ② apply a fusion algorithm
  - using similarity scores provided by underlying SE

these techniques can be used also to combine ranking functions within a search engine



# Combination Using Similarities

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- $CombMIN(d_j) = \min(s_{1j}, s_{2j}, \dots, s_{kj})$   
(use the minimum ranking)
- $CombMAX(d_j) = \max(s_{1j}, s_{2j}, \dots, s_{kj})$
- $CombSUM(d_j) = \sum s_{ij}$   
(add the similarity scores)
- $CombMNZ(d_j) = CombSUM(d_j) \times r_j$ , where  $r_j$  is the number of systems that retrieved  $d_j$

*CombSUM* and *CombMNZ* perform better. *CombMNZ* slightly outperforms *CombSUM* in most cases.



# Combination using ranking positions

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

**Borda(1770) Ranking:** each voter assigns a linear preference order of candidates,  $n$  to the first,  $n - 1$  to the second, etc. Unranked candidates divide the votes. Winner gets the most points.

**Condorcet (1787) Ranking:** do pairwise comparisons to count how many times a doc “wins”, “loses” or “ties” against other documents (as in a soccer tournament). Doc with most wins gets highest score. Ties broken on number of losses.

**Reciprocal ranking:** assign a score  $1/pos$  to each doc. Rank based on sum of scores.



# Borda Ranking

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

5 underlying search engines,  
which have ranked four candidate pages  $a, b, c, d$ .

System 1:  $a, b, c, d$

System 2:  $b, a, d, c$

System 3:  $c, b, a, d$

System 4:  $c, b, d$

System 5:  $c, b$

Scores:

$$\text{Score}(a) = 4 + 3 + 2 + 1 + 1.5 = 11.5$$

$$\text{Score}(b) = 3 + 4 + 3 + 3 + 3 = 16$$

$$\text{Score}(c) = 2 + 1 + 4 + 4 + 4 = 15$$

$$\text{Score}(d) = 1 + 2 + 1 + 2 + 1.5 = 7.5$$

The final ranking is:  $b, c, a, d$





# Condorcet Ranking

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

System 1: a,b,c,d

System 2: b,a,d,c

System 3: c,b,a,d

System 4: c,b,d

System 5: c,b

comparisons (win:lose:tie):

pair	a	b	c	d
a	-	1:4:0	2:3:0	3:1:1
b	4:1:0	-	2:3:0	5:0:0
c	3:2:0	3:2:0	-	4:1:0
d	1:3:1	0:5:0	1:4:0	-

The final ranking is: *b, c, a, d*



# Reciprocal Ranking

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

5 underlying search engines,  
which have ranked four candidate pages  $a, b, c, d$ .

System 1:  $a, b, c, d$

System 2:  $b, a, d, c$

System 3:  $c, b, a, d$

System 4:  $c, b, d$

System 5:  $c, b$

Scores:


$$\text{Score}(a) = 1 + 1/2 + 1/3 + 0 + 0 = 1.83$$

$$\text{Score}(b) = 1/2 + 1 + 1/2 + 1/2 + 1/2 = 3$$

$$\text{Score}(c) = 1/3 + 1/4 + 1 + 1 + 1 = 3.55$$

$$\text{Score}(d) = 1/4 + 1/3 + 1/4 + 1/3 + 0 = 1.17$$

The final ranking is:  $c, b, a, d$



# Outline

## 1 Search Engine Ranking

## 2 Ranking Signals

### 3 The Ranking Function

#### 4 Unsupervised Rank Fusion

## 5 Learning to Rank

## 6 Some Context

## 7 Learning to Rank (cont.)

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ▶ ↺ 🔍 ↻



# Why Learning to Rank?

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Manual parameter tuning is usually difficult
  - Especially when there are many parameters and the evaluation measures are non-smooth
- Manual parameter tuning sometimes leads to **overfitting**
- It is non-trivial to combine the large number of models proposed in the literature (e.g. BM25, etc.) to obtain an even more effective model



# What is Learning to Rank?

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

**L2R:** apply machine learning techniques to learn the ranking of the results

- Use a **learning algorithm** fed with **training data** that contains ranking information
- **loss function to minimize:** number of mistakes done by the learned model



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context**
- 7 Learning to Rank (cont.)



# Supervised Learning

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Input:  $\{(x_i, y_i)\}_{i=1}^N, x_i \in \mathcal{R}^M, y_i \in \mathcal{R}$

Hypothesis space:  $h^* \in H$

Loss function:  $L(h(x), y)$

Learning Algorithm:  $\hat{h} = A(\{(x_i, y_i)\}_{i=1}^N)$ , such that  
$$\hat{h} = \operatorname{argmin}_h \sum_{i=1}^N L(h(x_i), y_i)$$

I.e. given a set of **training data** as input, use **learning algorithm**  $A$  to discover the function  $\hat{h}$  that minimizes the **loss** (e.g. the error)



# An Example: Linear Regression

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals


The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)



(source: [wikipedia](#))





# Linear Regression (cont.)

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- The hypothesis space:

$$h_{\vec{w}}(x) = w_0 + w_1 x$$

where  $\vec{w} = [w_0, w_1]$

- The loss function:

$$L(h_{\vec{w}}, y) = \sum_{i=1}^N (y_i - h_{\vec{w}}(x_i))^2$$

i.e. the sum of the squared error

- We want to find

$$w^* = \underset{w}{\operatorname{argmin}} L(h_{\vec{w}}, y)$$



# Minimizing the Loss

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- In the most simple case, we can easily find one (or more) solution(s)
  - Just take the derivatives and equal to 0
- In many cases this is not possible (or we may want to enforce some constraints on the parameters)
- In practice, there are many ways to estimate  $w^*$



# An Example: Gradient Descent

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion


Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

$w \leftarrow$  any point in the  
parameter space  
**loop** until convergence **do**  
  **for each**  $w_i$  **in**  $\vec{w}$  **do**  
     $w_i \leftarrow w_i - \alpha \frac{\partial}{\partial w_i} L(h_{\vec{w}}, y)$

$\alpha =$  learning rate



(source: [wikipedia](#))



# Other Types of Supervised Learning

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

(besides regression and ranking)

- Classification
  - Classify email as spam vs. ham
  - Loss: accuracy
- Structured prediction
  - Find faces in an image
  - Loss: Precision/Recall of faces



# Outline

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- 1 Search Engine Ranking
- 2 Ranking Signals
- 3 The Ranking Function
- 4 Unsupervised Rank Fusion
- 5 Learning to Rank
- 6 Some Context
- 7 Learning to Rank (cont.)



# The L2R Framework

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals


The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)





# L2R Techniques

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Three main approaches:

**Pointwise:** focuses on individual pages

**Pairwise:** focuses on comparing pairs of pages

**Listwise:** focuses on the ranked list of pages



# The Pointwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

	The Pointwise Approach		
	Regression	Classification	Ordinal Regression
Input Space	Single documents $y_j$		
Output Space	Real values	Non-ordered Categories	Ordinal categories
Hypothesis Space	Scoring function $f(x)$		
Loss Function	Regression loss	Classification loss	Ordinal regression loss
	$L(f; x_j, y_j)$		





# An Example: Ranking Perceptron

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Koby Crammer and Yoram Singer, "Pranking with ranking," In Proceedings of the 14th International Conference on Neural Information Processing Systems (NIPS'01), 2001.


Adaptation of the *Perceptron algorithm*:

Input space:  $\mathbf{x} = \{x_j\}_{j=1}^m$

Output space:  $y_j \in \{1, 2, 3, \dots\}$

Hypothesis Space:  $f(\mathbf{x}) = \mathbf{w} \cdot \mathbf{x}$

Loss function:  $L(f, x_j, y_j) = \sum_{j=1}^T |y_j - f(x_j)|$





# Problem with the Pointwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- The position of documents in the ranked list is invisible to the loss functions
- The overall loss function will be dominated by queries with a large number of documents



# The Pairwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

	The Pairwise Approach
Input Space	Document pairs $(x_u, x_v)$
Output Space	Preference $y_{u,v} \in \{+1, -1\}$
Hypothesis Space	Preference function $h(x_u, x_v) = 2 \cdot I_{\{f(x_u) > f(x_v)\}} - 1$
Loss Function	Pairwise classification loss $L(h; x_u, x_v, y_{u,v})$



# An Example: RankBoost

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

Y. Freund, R. Iyer, R. E. Schapire, and Y. Singer, "An efficient boosting algorithm for combining preferences," Journal of Machine Learning Research, vol. 4, pp. 933–969, 2003.

**Input space:** Document pairs  $(x_u, x_v)$

**Output space:** Relative order  $y_{u,v} \in \{-1, +1\}$

**Hypothesis Space:**  $f(x) = \sum_t \alpha_t f_t(x)$

**Loss function:**  $L(f; x_u; x_v; y_{u,v}) = e^{-y_{u,v}(f(x_u) - f(x_v))}$

---

## Algorithm 1 Learning Algorithm for RankBoost

---

**Input:** document pairs

**Given:** initial distribution  $\mathcal{D}_1$  on input document pairs.

**For**  $t = 1, \dots, T$

    Train weak ranker  $f_t$  based on distribution  $\mathcal{D}_t$ .

    Choose  $\alpha_t$

    Update  $\mathcal{D}_{t+1}(x_u^{(i)}, x_v^{(i)}) = \frac{1}{Z_t} \mathcal{D}_t(x_u^{(i)}, x_v^{(i)}) \exp(\alpha_t(f_t(x_u^{(i)}) - f_t(x_v^{(i)})))$

    where  $Z_t = \sum_{i=1}^n \sum_{u,v: y_{u,v}=1} \mathcal{D}_t(x_u^{(i)}, x_v^{(i)}) \exp(\alpha_t(f_t(x_u^{(i)}) - f_t(x_v^{(i)})))$ .

**Output:**  $f(x) = \sum_t \alpha_t f_t(x)$ .

---



# Improvement of Pairwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

## Advantage

Predicting relative order is closer to the nature of ranking than predicting class label or relevance score

## Problems

- Relative order of two documents still does not predict their final position
- The distribution of document pair number is more skewed than the distribution of document rank, with respect to different queries



# Document Pair Distribution

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals


The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)





# The Listwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

	The Listwise Approach	
	Listwise Loss Minimization	Direct Optimization of IR Measure
Input Space	Document set $\mathbf{x} = \{x_j\}_{j=1}^m$	
Output Space	Permutation $\pi_y$	Ordered categories $\mathbf{y} = \{y_j\}_{j=1}^m$
Hypothesis Space	$h(\mathbf{x}) = \text{sort}_\circ f(\mathbf{x})$	$h(\mathbf{x}) = f(\mathbf{x})$
Loss Function	Listwise loss $L(h; \mathbf{x}, \pi_y)$	1-surrogate measure $L(h; \mathbf{x}, \mathbf{y})$



# Direct Optimization of IR Measures

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- It is natural to directly optimize what is used to evaluate the ranking results
- However, it is non-trivial
- Evaluation measures such as NDCG are **non-continuous** and **non-differentiable** since they depend on the rank positions
- It is challenging to optimize such objective functions, since most optimization techniques in the literature were developed to handle continuous and differentiable cases





# Solutions

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)

- Approximate the objective
  - Soften (approximate) the evaluation measure so as to make it smooth and differentiable
- Bound the objective
  - Optimize a smooth and differentiable upper bound of the evaluation measure
- Optimize the non-smooth objective directly
  - Use IR measure to update the distribution in Boosting
  - Use genetic programming



# An Example: RankGP

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context

Learning to  
Rank (cont.)


J.-Y. Yeh et al, "Learning to rank for information retrieval using genetic programming," in SIGIR 2007 Workshop in Learning to Rank for Information Retrieval, 2007.

Input space:  $\mathbf{x} = \{x_j\}_{j=1}^m$

Output space: Relative order  $\mathbf{y} = \{y_j\}_{j=1}^m$

Hypothesis Space:  $f(x)$

Loss function: IR evaluation measure





# Improvement of Listwise Approach

Processamento  
e Recuperação  
de Informação

Search Engine  
Ranking

Ranking  
Signals

The Ranking  
Function

Unsupervised  
Rank Fusion

Learning to  
Rank

Some Context


Learning to  
Rank (cont.)

## Advantages

- Take all the documents associated with the same query as the learning instance
- Rank position is visible to the loss function

## Problems

- Complexity



## Ranking Signals

## The Ranking Function

## Unsupervised Rank Fusion

## Learning to Rank

## Some Context

## Learning to Rank (cont.)

# Questions?