

SOURCE CODE:

```
#include <stdio.h>
#include <stdlib.h>

int sort_asc(const void* a, const void* b) {
    return (*(const int*)a - *(const int*)b);
}

int sort_desc(const void* a, const void* b) {
    return (*(const int*)b - *(const int*)a);
}

int main() {
    int test_count;
    if (scanf("%d", &test_count) != 1) return 0;

    while (test_count--) {
        int pair_num;
        scanf("%d", &pair_num);

        int girls[pair_num], boys[pair_num];
        for (int i = 0; i < pair_num; i++) scanf("%d", &girls[i]);
        for (int i = 0; i < pair_num; i++) scanf("%d", &boys[i]);

        qsort(girls, pair_num, sizeof(int), sort_asc);
        qsort(boys, pair_num, sizeof(int), sort_desc);

        int compatible = 0;
        for (int i = 0; i < pair_num; i++) {
            if ((girls[i] % boys[i] == 0) || (boys[i] % girls[i] == 0)) {
                compatible++;
            }
        }
        printf("%d\n", compatible);
    }
    return 0;
}
```

OUTPUT:

```
1
4
3 6 9 12
4 12 3 9
2
```

```
2
4
3 6 9 12
4 12 16 9
4
1 1 1 1
2 2 2 2
3
4
```