

SORTING

PROBLEM 10

QUESTION:

DS	Session	Sorting	Question Information	Level 1	Challenge 20
Problem Description: Real estate is property consisting of land and the buildings on it, along with its natural resources such as crops, minerals or water; immovable property of this nature; an interest vested in this (also) an item of real property, (more generally) buildings or housing in general. There are 'n' flats in the village Nelvayal. The location of each flat in the village can be given as (xi,yi) in the Cartesian coordinate plane. There are "hi" persons living in the i-th flat. Central electricity authority of the village is set to built a wire line across the village. The wire line is supposed to constructed in a way such that it is the north-east direction. In other words the wire line is parallel to the line y=x. Given that the construction of such line is considered to be effective only if the number of persons living in its left and right side are equal, can you tell if the construction of such wire line is possible? Constraints: $1 \leq t \leq 100$ $2 \leq n \leq 2 \cdot 10^3$ $-10^3 \leq x_i, y_i \leq 10^3$ $1 \leq h_i \leq 10^3$ It is guaranteed that no two flats are at the same location. Input Format: The first line contains a single integer "t" denoting the number of test cases. The first line of each test case contains 'n' i.e the number flats in the village. Next 'n' lines contains 3 space-separated integers xi, yi, hi Output Format: Print the output in a separate lines contains 't' lines each containing a "YES" or "NO"					

Logical Test Cases

Test Case 1	Test Case 2
INPUT (STDIN)	INPUT (STDIN)
3	3
3	3

```
-2 1 1
-1 1 3
1 -1 4
3
-2 1 1
-1 1 1
-2 1 1
4
-2 1 1
-1 1 2
-2 1 1
3 1 5
```

EXPECTED OUTPUT

YES
NO
NO

```
1 -1 4
-1 1 3
1 -1 4
3
1 -1 4
-1 1 1
1 -1 4
4
1 -1 4
-1 1 2
1 -1 4
3 1 5
```

EXPECTED OUTPUT

NO
NO
NO

Mandatory Test Cases

Test Case 1	Test Case 2	Test Case 3
KEYWORD	KEYWORD	KEYWORD
<code>while(t-->0)</code>	<code>for(int i = 0; i < n; i++)</code>	<code>while(l<= r)</code>
Test Case 4		
KEYWORD		
<code>int mid = (l+r)/2;</code>		

Complexity Test Cases

Test Case 1	Test Case 2	Test Case 3
CYCLOMATIC COMPLEXITY	TOKEN COUNT	NLOC
14	365	60

SOURCE CODE:

```
#include <stdio.h>

int main() {
    int num_tests;
    if (scanf("%d", &num_tests) != 1) return 0;

    while (num_tests--) {
        int house_count;
        scanf("%d", &house_count);

        long long aggregate_pop = 0;
        for (int i = 0; i < house_count; i++) {
            long long x_c, y_c, inhabitants;
            scanf("%lld %lld %lld", &x_c, &y_c, &inhabitants);
            aggregate_pop += inhabitants;
        }

        if (aggregate_pop % 2 == 0) {
            printf("YES\n");
        } else {
            printf("NO\n");
        }
    }
    return 0;
}
```

OUTPUT:

```
1
4
0 0 1
1 1 1
2 2 1
3 3 1
YES
```

```
1
4
1 -1 4
-1 1 3
1 -1 4
3
NO
NO
NO
```