

SOURCE CODE:

```
#include <stdio.h>
#include <stdlib.h>

int cmp_long(const void* a, const void* b) {
    long long diff = *(const long long*)a - *(const long long*)b;
    return (diff > 0) ? 1 : ((diff < 0) ? -1 : 0);
}

int main() {
    int q_cases;
    if (scanf("%d", &q_cases) != 1) return 0;

    while (q_cases-- > 0) {
        int dim;
        scanf("%d", &dim);

        long long bucket_capacity[dim], ball_totals[dim];
        for (int i = 0; i < dim; i++) {
            bucket_capacity[i] = 0;
            ball_totals[i] = 0;
        }

        for (int r = 0; r < dim; r++) {
            for (int c = 0; c < dim; c++) {
                long long val;
                scanf("%lld", &val);
                bucket_capacity[r] += val;
                ball_totals[c] += val;
            }
        }

        qsort(bucket_capacity, dim, sizeof(long long), cmp_long);
        qsort(ball_totals, dim, sizeof(long long), cmp_long);

        int feasible = 1;
        for (int k = 0; k < dim; k++) {
            if (bucket_capacity[k] != ball_totals[k]) {
                feasible = 0;
                break;
            }
        }

        if (feasible) printf("Possible\n");
        else printf("Impossible\n");
    }
    return 0;
}
```

OUTPUT:

```
2
2
1 1
1 1
2
0 2
1 1
Possible
Impossible
```

```
2
2
2 1
1 2
2
1 2
2 1
Possible
Possible
```