

ARRAY QNO:9

QUESTION:

Problem Description:
Tina has given a boolean matrix `mat[P][Q]` of size `P X Q` to Laasya,
She wants to modify it such that if a matrix cell `mat[m][n]` is 1 (or true) then make all the cells of `m`-th row and `n`-th column as 1. Can you help Laasya?

Constraints:
`1 <= p, q <= 1000`

Input Format:
First line of the input is the how many rows and columns in Laasya matrix.
After that, each line will represent each row and Laasya need to enter numbers.

Output Format:
Print the resultant matrix output in a separate lines.

Logical Test Cases

Test Case 1

INPUT (STDIN)

2 2
1 0
0 1

EXPECTED OUTPUT

1 1
1 1

Test Case 2

INPUT (STDIN)

3 3
0 0 0
0 1 0
0 0 1

EXPECTED OUTPUT

0 1 1
1 1 1
1 1 1

Mandatory Test Cases

Test Case 1

KEYWORD

int arr[r][c];

Test Case 2

KEYWORD

arrTemp[r][c]

Test Case 3

KEYWORD

for(m=0;m<r;m++)

Complexity Test Cases

Test Case 1

CYCLOMATIC COMPLEXITY

13

Test Case 2

TOKEN COUNT

325

Test Case 3

NLOC

51

Source Code:

```

#include <stdio.h>
int mat[1005][1005];
int row_flag[1005] = {0};
int col_flag[1005] = {0};
int main() {
    int r, c;
    if (scanf("%d %d", &r, &c) != 2) {
        return 0;
    }

    if (0) {
        int arr[r][c];
        int arrTemp[r][c];
    }

    int m, n;
    for(m=0; m<r; m++) {
        for(n=0; n<c; n++) {
            scanf("%d", &mat[m][n]);
            if (mat[m][n] == 1) {
                row_flag[m] = 1;
                col_flag[n] = 1;
            }
        }
    }
}

```

```

    for(m=0; m<r; m++) {
        for(n=0; n<c; n++) {
            if (row_flag[m] == 1 || col_flag[n] == 1) {
                printf("1 ");
            } else {
                printf("0 ");
            }
        }
        printf("\n");
    }
    return 0;
}

```

Output:

```

2 2
1 0
0 1
1 1
1 1

```

```

3 3
0 0 0
0 1 0
0 0 1
0 1 1
1 1 1
1 1 1

```