Ansible config the roles and write pb

✅STEP 1 — Install Ansible (Using WSL)

 1. Install WSL (if not already)

Open Command Prompt as Admin:

Bash

```
wsl --install
```

Restart your system.

 2. Open Ubuntu (WSL)

Search → Ubuntu → open it

 3. Install Ansible

Run:

Bash

```
sudo apt update
sudo apt install ansible -y
```

 4. Verify Installation

Bash

```
ansible --version
```

✅STEP 2 — Create Your Ansible Project Structure

Inside Ubuntu terminal:

Bash

```
mkdir ansible-project
cd ansible-project
```

 Create Standard Structure (IMPORTANT FOR ROLES)

Bash

mkdir -p roles/webserver/tasks

mkdir -p roles/webserver/handlers

mkdir -p roles/webserver/templates

mkdir -p roles/webserver/files

✅STEP 3 — Create Inventory File

Bash

nano inventory

Add:

INI

localhost ansible_connection=local

Save: 📤 CTRL + X → Y → Enter

✅STEP 4 — Create a Role (webserver)

📤 Create Tasks File

Bash

nano roles/webserver/tasks/main.yml

Paste:

YAML

```
- name: Install Apache
  apt:
    name: apache2
    state: present
    update_cache: yes

- name: Start Apache
  service:
```

```
    name: apache2
    state: started
    enabled: yes
```

✅STEP 5 — Create Playbook

Bash

```
nano site.yml
```

Paste:

YAML

```
- hosts: localhost
  become: yes
  roles:
    - webserver
```

✅STEP 6 — Run the Playbook

Bash

```
ansible-playbook -i inventory site.yml
```

✅STEP 7 — Verify

Open browser:

□ http://localhost□ ◆

You should see Apache default page □