

API Documentation

Overview

Base URL: `http://localhost:5000` (development) | `https://api.example.com` (production)

Response Format: JSON

Authentication: Bearer token (JWT)

Rate Limits: 100 requests per minute

Authentication

Bearer Token

1. Obtain a token by logging in via the `/api/auth/login` endpoint.
2. Include the token in request headers: `Authorization: Bearer <token>`.
3. Token expires in 1 hour; refresh using the `/api/auth/refresh` endpoint.

Example Request with Auth

```
curl -X GET http://localhost:5000/api/expenses \
  -H "Authorization: Bearer your_token_here" \
  -H "Content-Type: application/json"
```

Endpoints

POST /api/expenses

Submit an expense for reimbursement.

Request:

- **Method:** POST
- **Path:** `/api/expenses`
- **Headers:** `Authorization: Bearer <token>`, `Content-Type: application/json`
- **Request Body:**

```
{
  "employeeId": "UUID",
  "amount": "Decimal",
  "description": "String",
  "receiptUrl": "String"
}
```

Response:

- **Status 201 (Created):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "status": "SUBMITTED"
  },
  "message": "Expense submitted successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X POST http://localhost:5000/api/expenses \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json" \
-d '{"employeeId":"123e4567-e89b-12d3-a456-426614174000","amount":100,"description":"Lun
```

POST /api/travel-requests

Submit a travel request for approval.

Request:

- **Method:** POST
- **Path:** /api/travel-requests
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json
- **Request Body:**

```
{
  "employeeId": "UUID",
  "destination": "String",
  "startDate": "YYYY-MM-DD",
  "endDate": "YYYY-MM-DD",
  "purpose": "String"
}
```

Response:

- **Status 201 (Created):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "status": "SUBMITTED"
  },
  "message": "Travel request submitted successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X POST http://localhost:5000/api/travel-requests \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json" \
-d '{"employeeId":"123e4567-e89b-12d3-a456-426614174000","destination":"Paris","startDate":'}
```

POST /api/expenses/<id>/approve

Approve an expense submission.

Request:

- **Method:** POST
- **Path:** /api/expenses/<id>/approve
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json
- **Request Body:**

```
{
  "managerId": "UUID",
  "approvalComment": "String"
}
```

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "status": "APPROVED"
  },
  "message": "Expense approved successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Expense not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X POST http://localhost:5000/api/expenses/123e4567-e89b-12d3-a456-426614174000/approvalComment
-H "Authorization: Bearer token" \
-H "Content-Type: application/json" \
-d '{"managerId":"123e4567-e89b-12d3-a456-426614174001","approvalComment":"Approved"}'
```

POST /api/expenses/<id>/reject

Reject an expense submission.

Request:

- **Method:** POST
- **Path:** /api/expenses/<id>/reject
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json
- **Request Body:**

```
{
  "managerId": "UUID",
  "rejectionComment": "String"
}
```

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "status": "REJECTED"
  },
  "message": "Expense rejected successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Expense not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X POST http://localhost:5000/api/expenses/123e4567-e89b-12d3-a456-426614174000/rejectionComment "Not eligible" \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json" \
-d '{"managerId": "123e4567-e89b-12d3-a456-426614174001", "rejectionComment": "Not eligible"}'
```

GET /api/expenses

Get all expenses submitted by employees.

Request:

- **Method:** GET
- **Path:** /api/expenses
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": [
    {
      "id": "UUID",
      "employeeId": "UUID",
      "amount": "Decimal",
      "description": "String",
      "status": "SUBMITTED"
    }
  ],
  "message": "Expenses retrieved successfully"
}
```

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/expenses \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

GET /api/expenses/<id>

Get an expense by its ID.

Request:

- **Method:** GET
- **Path:** /api/expenses/<id>
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "employeeId": "UUID",
    "amount": "Decimal",
    "description": "String",
    "status": "SUBMITTED"
  },
  "message": "Expense retrieved successfully"
}
```

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Expense not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/expenses/123e4567-e89b-12d3-a456-426614174000 \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

GET /api/travel-requests

Get all travel requests submitted by employees.

Request:

- **Method:** GET
- **Path:** /api/travel-requests
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": [
    {
      "id": "UUID",
      "employeeId": "UUID",
      "destination": "String",
      "startDate": "YYYY-MM-DD",
      "endDate": "YYYY-MM-DD",
      "status": "SUBMITTED"
    }
  ],
  "message": "Travel requests retrieved successfully"
}
```

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/travel-requests \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

GET /api/travel-requests/<id>

Get a travel request by its ID.

Request:

- **Method:** GET
- **Path:** /api/travel-requests/<id>
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "UUID",
    "employeeId": "UUID",
    "destination": "String",
    "startDate": "YYYY-MM-DD",
    "endDate": "YYYY-MM-DD",
    "status": "SUBMITTED"
  },
  "message": "Travel request retrieved successfully"
}
```

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Travel request not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/travel-requests/123e4567-e89b-12d3-a456-426614174000 \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

GET /api/reports/expenses

Get department-wise spend report.

Request:

- **Method:** GET
- **Path:** /api/reports/expenses
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "department": "String",
    "totalSpend": "Decimal",
    "policyViolations": "Integer",
    "outstandingReimbursements": "Decimal"
  },
  "message": "Department-wise spend report retrieved successfully"
}
```

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://
```