

API Documentation

Overview

Base URL: `http://localhost:5000` (development) | `https://api.example.com` (production)

Response Format: JSON

Authentication: Bearer token using JWT with Spring Security

Rate Limits: 100 requests per minute

Authentication

Bearer Token

1. Obtain a token by logging in via the `/api/auth/login` endpoint with username and password.
2. Include in request headers: `Authorization: Bearer <token>`
3. Token expires in 1 hour; refresh using the `/api/auth/refresh` endpoint.

Example Request with Auth

```
curl -X GET http://localhost:5000/api/leave-requests \
  -H "Authorization: Bearer your_token_here" \
  -H "Content-Type: application/json"
```

Endpoints

POST /api/leave-requests

Submit a new leave request.

Request:

- **Method:** POST
- **Path:** `/api/leave-requests`
- **Headers:** `Authorization: Bearer <token>`, `Content-Type: application/json`
- **Request Body:**

```
{
  "employeeId": "1",
  "leaveType": "SICK",
  "startDate": "2023-10-01",
  "endDate": "2023-10-05"
}
```

Response:

- **Status 201 (Created):**

```
{
  "success": true,
  "data": {
    "id": "1",
    "status": "PENDING"
  },
  "message": "Leave request submitted successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X POST http://localhost:5000/api/leave-requests \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json" \
-d '{"employeeId":"1", "leaveType":"SICK", "startDate":"2023-10-01", "endDate":"2023-10-05"}
```

GET /api/leave-requests/{id}

Retrieve a leave request by ID.

Request:

- **Method:** GET
- **Path:** /api/leave-requests/{id}
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "1",
    "employeeId": "1",
    "leaveType": "SICK",
    "startDate": "2023-10-01",
    "endDate": "2023-10-05",
    "status": "PENDING"
  },
  "message": "Leave request retrieved successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Leave request not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/leave-requests/1 \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

PATCH /api/leave-requests/{id}/approve

Approve a leave request.

Request:

- **Method:** PATCH
- **Path:** /api/leave-requests/{id}/approve
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "1",
    "status": "APPROVED"
  },
  "message": "Leave request approved successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field

- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Leave request not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X PATCH http://localhost:5000/api/leave-requests/1/approve \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

PATCH /api/leave-requests/{id}/reject

Reject a leave request.

Request:

- **Method:** PATCH
- **Path:** /api/leave-requests/{id}/reject
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "id": "1",
    "status": "REJECTED"
  },
  "message": "Leave request rejected successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Leave request not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X PATCH http://localhost:5000/api/leave-requests/1/reject \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

GET /api/leave-balance/{employeeId}

Get leave balance for an employee.

Request:

- **Method:** GET
- **Path:** /api/leave-balance/{employeeId}
- **Headers:** Authorization: Bearer <token>, Content-Type: application/json

Response:

- **Status 200 (OK):**

```
{
  "success": true,
  "data": {
    "employeeId": "1",
    "leaveType": "SICK",
    "balance": 10
  },
  "message": "Leave balance retrieved successfully"
}
```

- **Status 400 (Bad Request):** Missing or invalid required field
- **Status 401 (Unauthorized):** Invalid or expired token
- **Status 403 (Forbidden):** Insufficient permissions
- **Status 404 (Not Found):** Employee not found
- **Status 500 (Server Error):** Unexpected error

Example:

```
curl -X GET http://localhost:5000/api/leave-balance/1 \
-H "Authorization: Bearer token" \
-H "Content-Type: application/json"
```

Error Codes and Meanings

Status	Code	Meaning	When It Occurs
400	BAD_REQUEST	Invalid input	Missing or invalid required field
401	UNAUTHORIZED	Invalid credentials	Token missing or expired
403	FORBIDDEN	Access denied	User lacks required role

Status	Code	Meaning	When It Occurs
404	NOT_FOUND	Resource not found	Leave request or employee not found
500	INTERNAL_ERROR	Server error	Unexpected error, check logs

Rate Limits and Quotas

- **100 requests per minute:** Exceeding this limit will result in a 429 RATE_LIMIT response.

Data Types and Formats

- **Timestamps:** ISO 8601 format (e.g., 2023-10-01T10:30:00Z)
- **Booleans:** true or false
- **IDs:** UUID v4 or numeric, as documented per entity
- **Enums:** Specific values listed in request/response examples

Pagination (if applicable)

This API does not support pagination.

SDK Examples

No SDKs are provided for this API.