

Brand	SVBONY	
Model	SV241 Pro	
Power Input	12V 10A Max DC5.5*2.5	
PC Input	USB3 Type B Connector	
DC Output:	Always on	12V 6A MaxDC5.5*2.1
		Cannot be switched on/off
	Switch1-5	12V 6A Max DC5.5*2.1
		Can be switched on/Off
	Regulated	0-15V adjustable Regulated Output
		Can be switched on/off 3A Max
	PWM1-2	12V 6A Max Black Colored RCA Connector
		Can be switched on/off
		PWM Control possible
USB HUB	2xUSB3.0 4xUSB2.0	USB type-c & USB2.0-1&USB2.0-2 Can be switched on/off together
		USB3.0-3&USB3.0-4&USB2.0-5 Can be switched on/off together
USB Power Supply	4xUSB2.0	5V 2.5A
	2xUSB3.0	5V 2.5A
Voltage/Current Monitor	Input current/ Voltage monitor	
Environment Sensor	2.5mm TRRS Jack(4-Pole)	SHT40 Temperature & humidity sensor
	2.5mm TRRS Jack(4-Pole)	DS08B20 Temperature probe
Temperature Range	Operating Temperature: -10°C to 50°C (Celsius)	
Humidity Range	Operating Humidity: 5% to 85% RH (non-condensing)	
Dew Heater Control	2 independent dewheaters	
	Dewpoint temperature difference control	
	Constant temperature control	
	Manual control	
ASCOM Compatibility	YES	
Screw Holes	M4 and UNC1/4-20 Holes	
Net Weight/g	approx.210g	
Product Size/mm	100.5x87.5x24.5	
Circuit Protection	Electrostatic Discharge (ESD) Protection	
	Reverse Polarity Protection	
	Backflow Prevention	
	Filtering Protection [Adapted for USB 3.0 Interface & DC Interface]	
	Fusible Link	
	Under-voltage Protection	
	Over-voltage Protection	
	Over-current Protection	
	Short-circuit Protection	
	Power Detection	
	Smart Restart Function	