# Collusion, Espionage, or Look-alikes? Auditing Information Flow between LLM Agents

Pairwise net influence with and without private inputs in a procurement auction

Marvin Kemper, Independent; with Apart Research

**Abstract**

Can a behaviour-based audit distinguish an instructed cartel from honest language-model bidders? We test pairwise net influence in a repeated procurement auction, comparing public-bid access with access to private costs. The sole confirmatory test distinguished strong-pair cartel markets from matched honest controls: AUROC 0.865, descriptive interval $[0.734, 0.968]$, and $p = 0.00002$ across 20 blocks. Same-access residual correlation achieved 0.9975. Net influence therefore shows no general advantage over correlation. In descriptive secondary comparisons, espionage was the only condition whose paired net-minus-correlation interval excluded zero in favour of net influence. Market-level flow labels remained largely weak or unclear. The Qwen judge returned invalid JSON for $322/600$ judgements; its matched comparisons cover only 1–8 blocks. Exploratory probes did not resolve an average linear bid response to partner cost. Their leak test has an anti-conservative bid-level permutation null because bids share regenerated messages. These results support screening for an assigned treatment in this game, not reliable identification of agreement, intent, or economic harm.

## 1 Introduction

When language-model agents bid on behalf of competing firms, oversight must address coordination that is invisible in the public record. Reading messages may be impossible, and similar bids need not imply an agreement: agents can respond to the same history or implement similar policies. Conversely, a firm that learns a rival's private cost can produce suspicious dependence without the rival's cooperation. A useful audit therefore asks both which pair is dependent and what information could account for that dependence.

Pairwise net influence (Bonjour et al., 2022) compares a pair's statistical influence with the strongest influence from a third agent. We test this screen in a procurement game with a designated pair of LLM bidders. Private costs provide an additional diagnostic: the partially observable statistic separates action dependence from dependence of a bid on another firm's private input. The distinction matters because the symmetric influence score can combine either unilateral or reciprocal information flow. Our auditors read no messages; this avoids reliance on message content, but does not constitute a test of steganographic channels.

The contributions are:

1. A pre-registered test of net influence on LLM auctions, with matched honest controls, correlation and judge baselines, and separate measures of discrimination, localisation, and abstention.
2. An audit comparison with and without private inputs, using an exact decomposition into action dependence and directional leaks, plus a partner-cost intervention on frozen contexts.
3. Targeted tests of honest look-alikes, unilateral leakage, cartel placement, and model breadth, with explicit limits on what detection implies.

The intended contribution is an assessment of the information an audit adds; superiority to a simpler screen is an empirical question.

## 2 Related Work

Bonjour et al. (2022) introduce information-theoretic collusion detection in multi-agent games, including a partially observable formulation. We implement their statistic and fixed-threshold rule, then examine private-input access and

permutation correction in LLM auctions. Work on algorithmic collusion by LLMs (Fish et al., 2024), double auctions (Agrawal et al., 2025), and market division (Lin et al., 2024) supplies the market context; our question concerns the audit of an assigned pair rather than whether collusion emerges spontaneously.

Steganographic collusion (Motwani et al., 2024) motivates audits that do not depend on readable messages. *Audit the Whisper* (Tailor, 2025) uses cross-run mutual information, permutation invariance, and interventions, including auctions. Its run-level focus differs from pair localisation and private-state directional decomposition here. Chain-of-thought monitoring (Lee and Park, 2026) and multi-agent interpretability/NARCBench (Rose et al., 2026) address complementary observation channels; we evaluate behaviour and private inputs, without access to model internals.

Statistical procurement screens provide a related application tradition (Huber and Imhof, 2019; Imhof and Wallimann, 2021; Wallimann et al., 2023). We treat a screen as a reason for further investigation. Concurrent sprint repositories also investigate net influence (Raj-Taware, 2026; soumya-nayak-commits, 2026); we make no claim to the first LLM application. The distinctive focus is the joint evaluation of pair detection, private-cost flow, and honest look-alikes under matched controls.

# 3 Methods

## 3.1 Game, conditions, and models

Each market has four firms and 200 rounds. Two strong firms draw independent costs uniformly from $\{1,2,3\}$; two fringe firms draw from $\{3,4,5\}$. Bids range from 2 to 7; the lowest wins, with random ties. The winner earns bid minus cost, others zero. Bids and winners become public. Bidders see their own cost, the last ten rounds, and their cumulative profit. Costs, tie-breaks, and assignments are seeded and matched by market index. Strong seats cycle through all six label pairs, hidden from auditors.

C1 assigns a cartel with a private channel (SS: strong–strong; SF: strong–fringe; FF: fringe–fringe). C2 removes the channel; E1 gives a firm unilateral access to its rival's cost. N0 is honest, and P0 is a scripted cartel positive control. Appendix Table 4 lists all conditions. C1 members exchange simultaneous private messages before bidding. The treatment bundles a joint-profit goal, partner naming, secrecy, a surveillance warning, and channel access. Assigned cartel markets remain included regardless of compliance or profit.

The core uses Qwen3.5-9B: 40 N0 markets and 20 per other core cell. Breadth covers Gemma-4-12B and Ministral-3-8B, their smaller counterparts Gemma-4-E4B and Ministral-3-3B, and Qwen3.5-4B. The amendment specifies 20 markets per breadth and A2 cell. Revisions and sampling are pinned; seeded re-collection is not bitwise reproducible (Appendix B).

## 3.2 Auditor access and influence

L1 receives bids $B_i$ and winners; L2 additionally receives costs $C_i$. Neither sees messages, role texts, condition labels, or model identities. The public state $H_t$ is the previous winning bid, with a start code and carry-forward after an all-invalid round; masking preserves this chronology. At L1, $\gamma_{ij} = I(B_i; B_j \mid H)$. At L2, set $S_i = (C_i, H)$. Equation 3 of Bonjour et al. (2022) becomes

$$\gamma_{ij} = \sum_{s_{ij}} p(s_{ij}) \sum_{b_i, b_j} p(b_i, b_j \mid s_{ij}) \log_2 \frac{p(b_i, b_j \mid s_{ij})}{p(b_i \mid s_i) p(b_j \mid s_j)}. \tag{1}$$

The chain rule gives the exact decomposition

$$\gamma_{ij} = \underbrace{I(B_i; B_j \mid C_i, C_j, H)}_{\text{action dependence}} + \underbrace{I(B_i; C_j \mid C_i, H)}_{L_{j\to i}} + \underbrace{I(B_j; C_i \mid C_j, H)}_{L_{i\to j}}. \tag{2}$$

Under independent costs and no other access to a rival's current cost, leaks probe private-information flow; omitted history can induce action dependence. Arrows indicate cost source and bid receiver, not intent. Estimates use plug-in counts in bits, our replication convention inferred from the paper's results; the paper does not specify the log base.

For any influence matrix $x$, define the paper's net transformation and mutual rule (its Equations 4–5) as

$$\Gamma_{ij}[x] = x_{ij} - \max_{k \neq i,j} x_{kj}, \qquad \Gamma_{ij}[\hat{\gamma}] \geq \alpha \text{ and } \Gamma_{ji}[\hat{\gamma}] \geq \alpha, \quad \alpha = 0.05. \tag{3}$$

Only a unique passing pair is reported. Symmetric $\gamma$ need not imply symmetric $\Gamma$: the rival comparisons differ. Net direction is not leak direction.

## 3.3 Permutation correction and flow labels

Within each market, 999 symmetric permutations shuffle each firm's bids independently within its own strata: $H$ at L1 and $(C_i, H)$ at L2. Define

$$g_{ij} = \hat{\gamma}_{ij} - \frac{1}{999}\sum_{r=1}^{999} \hat{\gamma}_{ij}^{(r)}, \qquad s_{ij} = \min\{\Gamma_{ij}[g], \Gamma_{ji}[g]\}. \tag{4}$$

Corrections remain signed. A candidate requires a permutation $p$-value for raw influence at most $0.05/6$ and both corrected net directions positive; only a unique candidate is reported. The test concerns influence, not net influence. The raw fixed-threshold rule is reported separately. The secondary leak score sums the two corrected leaks; a leak candidate requires either direction to pass $0.05/12$, again with unique-pair reporting.

Flow labels are both directions detected; one detected, reverse weak; neither detected, both weak; or unclear. "Weak" requires $p \geq 0.20$ and a corrected leak at most 0.05 bits. Labels cover designated pairs and the full detection pipeline. Weak evidence does not establish absence; one-way flow can arise in a cartel with unilateral sharing. Permutation validity requires within-stratum exchangeability, which adaptive policies can violate. Per-market alarm rates are descriptive, without a general calibration guarantee or error control across all analyses.

## 3.4 Baselines and evaluation

The L1 correlation baseline is uncorrected Cramér's V. L2 uses absolute Pearson correlation after subtracting each firm's mean bid at its own cost within the market; constant residuals score zero and signed correlations are also retained. These baselines do not adjust for history. A strength-only benchmark ranks the strong pair first, exposing a localisation shortcut.

The frozen Qwen3.5-9B judge uses thinking and returns raw pair probabilities from rules and masked round records, with costs only at L2 and no treatment information. There is no recalibration or answer selection; content failures remain failures. Comparisons use common judged markets and report coverage; descriptive Brier scores state the artificial prevalence. A Gemma-4-12B counter-judge was attempted on core N0/C1-SS indices 0–9 at both levels. Qwen judging Qwen remains a family-overlap limitation.

The market is the analysis unit. AUROC (area under the receiver operating characteristic curve) is the probability that a randomly chosen treatment market scores above a control market, with half credit for ties. All methods use rounds with four valid bids; more than 20 incomplete rounds makes a market ineligible and removes the matched block. A no-bid-category sensitivity retains missing bids. The sole confirmatory test compares designated-pair L2 net scores in Qwen C1-SS and N0 indices 0–19 over 200 rounds. With 99,999 within-block label swaps (seed 20261027),

$$p = \frac{1 + \#\{\mathrm{AUC}^* \geq \mathrm{AUC}_{\mathrm{obs}}\}}{100000}; \qquad \text{reject if } \mathrm{AUC}_{\mathrm{obs}} > 0.5 \text{ and } p \leq 0.05. \tag{5}$$

This tests paired label exchangeability, not the composite null AUROC $\leq 0.5$. Secondary estimates use 10,000 whole matched-block bootstraps and pointwise 95% percentile intervals. Top-1 is the fraction of credit for ranking the assigned pair first, shared equally across ties. Localisation also reports reciprocal rank, correct/wrong unique reports, and abstention; $1/6$ is a guessing benchmark, not a null. Honest-market alarms include counts and Clopper–Pearson intervals. E1 flow detection is not a collusion positive.

A2 tests paired fringe-placement swaps with Holm correction across seven endpoints, not a pure model-sameness mechanism. Pooled fingerprints align roles, bootstrap markets, and permute within markets. The exploratory probe regenerates a partner's message under counterfactual cost, then samples bids with the recipient's cost and history fixed; draws remain nested in markets (Appendix E).

## 3.5 Pre-registration and deviations

Design and executable analysis were frozen before collection; A1–A3 preceded LLM outcome analysis. Six deviations cover warm-up transport; fenced-JSON parsing and labelled Gemma/Ministral recollection; caching, streaming and checkpoints; disk exhaustion and relocation; and later recovery, call ceilings, loader paths, and an exceeded budget cap; and judge transport recovery plus budget cancellation of breadth judging. Core Qwen prompts and sampling were retained. Appendix E records the freezes, amendment, and deviations separately.

# 4 Results

All LLM results below use the frozen final analysis, the complete-round mask, and the full market horizon. Intervals are descriptive and pointwise unless stated otherwise. The required scripted rock–paper–scissors replication recovered the rising detection pattern with coordination probability and sample size, but not every published percentage. Its state convention and full comparison are in Appendix A; it is separate from the LLM evidence.

## 4.1 Discrimination: a positive primary test, a strong baseline

The preregistered L2 net-influence score discriminated C1-SS from matched N0 markets: AUROC 0.865 with interval $[0.734, 0.968]$, $p = 0.00002$, and 20 matched blocks. This rejects within-block condition-label exchangeability, the sole confirmatory null. Correlation scored 0.9875 at L1 and 0.9975 at L2. The paired L2 net-minus-correlation difference was $-0.1325$ $[-0.2647, -0.0309]$. Figure 1 compares treatments with their own controls. There is no general discrimination advantage for net influence. The small L1 advantages in C1-FF and Qwen-4B have difference intervals including zero; absence of an advantage is not evidence of equivalence.

In C2, net/correlation AUROCs were $0.6100/0.4625$ at L1 and $0.6550/0.4950$ at L2. The respective differences were $+0.1475$ $[-0.1818, 0.4422]$ and $+0.1600$ $[-0.1250, 0.4531]$. E1 is unilateral information access, not a collusion positive. Here net/correlation AUROCs were $0.6750/0.4825$ at L1 and $0.7000/0.4150$ at L2; differences were $+0.1925$ $[0.0222, 0.3599]$ and $+0.2850$ $[0.0620, 0.5150]$. L2 leak AUROC was 0.7025 $[0.5737, 0.8360]$. Each comparison uses 20 blocks. Only E1's paired difference intervals exclude zero in favour of net influence. These secondary comparisons do not establish a general benefit or incremental predictive value after accounting for correlation.

## 4.2 Localisation, unique reports, and honest-market alarms

Net influence localised assigned SF/FF pairs despite the strength baseline failing, although correlation performed similarly. Net top-1 for SF was $1.00/0.80$ at L1/L2, compared with correlation's $1.00/0.90$; FF was $1.00/1.00$ for both. Strength top-1 was zero for both placements. Ranking does not guarantee an operational report: in C1-SS at L2, net top-1 was 0.70, but correct unique reports occurred in 0.25 of markets, with 0.75 abstention and no wrong-pair reports.

In honest N0 markets, net had no designated-reference-pair alarms ($0/40$ at each access level; upper interval limit 0.0881). Any-pair alarms were nevertheless $1/40$ at L1 and $3/40$ at L2; L2 leak alarmed in $4/40$. Any-candidate and exactly-one-report counts coincided here (Figure 2). The paper's fixed-threshold rule alarmed in $40/40$ honest L2 markets. Its C2 continuous raw-net score had AUROC 0.8875, yet its threshold rule correctly reported the assigned pair in $0/20$ markets and a wrong pair in $20/20$. A useful score ranking and a useful reporting rule are different outcomes.

## 4.3 Behaviour and information-flow labels

Table 1 separates economic outcomes from flow classification. C1-SS increased joint profit and winning price relative to N0. C2 showed larger increases despite weaker discrimination. Removing the warning (A1) raised the L2 net AUROC point estimate by 0.0975 $[-0.0051, 0.2300]$ relative to C1-SS, while joint profit fell by 0.3478 $[0.2921, 0.4015]$ and winning price fell by 0.3335 $[0.2753, 0.3925]$. This divergence does not establish deliberate detector evasion.

C1-SS had no designated pairs with both leak directions detected or with one detected and the reverse weak; 8 were neither detected/both weak and 12 unclear. E1 had 0, 4, 8, and 8 in those categories. Thus, market-level flow labels did not reliably separate cartel and spy. Pooled fingerprints remain descriptive and are reported with numerical cautions in Appendix E.

## 4.4 Judges, breadth, and exploratory probes

The Qwen judge returned invalid JSON in $322/600$ judgements (53.67%) under the registered 12,000-token per-attempt limit. Most failed calls ended with `finish_reason=length` in the raw logs; the JSON failure code alone does not establish token exhaustion for every failure. Matched AUROC comparisons cover only 1–8 blocks. Successful outputs show a localisation pattern consistent with a preference for the strong pair: C1-SS and the N0 reference pair rank highly, whereas SF/FF are near zero. This is a behavioural pattern, not evidence of internal reasoning. Gemma returned only $5/40$ valid judgements and no evaluable matched C1-SS/N0 AUROC. All judge comparisons are descriptive and conditioned on successful output; breadth judges were cancelled for budget.





**Figure 1:** Detector discrimination and paired net-minus-correlation differences. Points and bars are AUROC estimates and pointwise 95% block-bootstrap intervals. Parentheses give matched blocks. E1 is visually separated because it tests espionage. Breadth labels denote channel-cartel treatments; each uses its registered control. Missing small-model comparisons are omitted from this plot and retained in the all-cells appendix.

Gemma-E4B had no eligible N0 or C1 markets. Ministral-3B had no eligible N0 markets and only 2 eligible C1 markets. Their matched discrimination results are unavailable, not negative findings. Available breadth results are in Figure 1; all amended markets, prefix checks and missing-bid sensitivity are retained in Appendix D. None of the seven preregistered A2 placement-swap endpoints rejected after Holm adjustment. The leak endpoint's raw $p = 0.03771$ became 0.26397. This does not establish no placement effect.

Exploratory frozen-context probes yielded a slope of 0.01347 $[-0.00353, 0.03195]$ across 199 complete contexts. The corrected leak was 0.08879 bits, with implemented permutation $p = 0.001$ across 2,997 observed bids. Five bids share each regenerated message, but the null permutes individual bids. This makes the leak null anti-conservative with respect to shared message variation. The slope is unresolved; the leak result is not validated causal evidence of partner-cost transmission.

## 5 Discussion and Limitations

The primary result supports net influence as a screen for an instructed cartel treatment in this game. It does not show a general advantage over same-access correlation. Correlation already captures much of the signal in open-channel

**Table 1:** Behaviour and designated-pair flow labels. Differences are treatment minus matched N0, in game units per round, with pointwise 95% intervals. Flow counts are both / one (reverse weak) / neither (both weak) / unclear / unavailable. E1 is unilateral access.

| Cell | Joint profit difference | Winning price difference | Flow counts |
|---|---|---|---|
| C1-SS | 0.144 [0.094, 0.192] | 0.295 [0.233, 0.358] | 0 / 0 / 8 / 12 / 0 |
| C2 | 0.399 [0.364, 0.434] | 0.798 [0.768, 0.826] | 0 / 0 / 11 / 9 / 0 |
| E1 | -0.116 [-0.137, -0.095] | -0.048 [-0.062, -0.034] | 0 / 4 / 8 / 8 / 0 |
| C1-NW | -0.204 [-0.229, -0.179] | -0.039 [-0.059, -0.017] | 0 / 1 / 8 / 11 / 0 |

treatments. E1 motivates further study of influence-based screens for unilateral information access, but its secondary intervals are pointwise and its economic setting differs from a cooperative cartel. Neither separate-score AUROCs nor their difference measure incremental predictive value in a combined detector.

Private costs make directional questions possible, but the observed labels rarely resolve the mechanism at the market level. Weak or unclear evidence must remain visible. Dependence on another firm's cost can reflect espionage, authorised disclosure, or cooperation. Net direction compares rival influences and does not identify a sender. A one-way leak is not a unique signature of espionage, and no detected leak does not establish independence. The unresolved probe slope and the shared-message flaw in its leak null reinforce this limit.

Reporting rules deserve separate evaluation. The fixed-threshold paper rule illustrates how high score discrimination can coexist with wrong-pair reports and pervasive honest-market alarms. Likewise, good top-1 ranking need not yield a unique report. No honest reference pair is a true colluding pair, so its ranking must not be called localisation accuracy. Observed alarm rates do not guarantee calibration when adaptive bidders use history omitted by the auditor.

The judge results are constrained by content failures and selection into successful-output subsets. Tiny matched samples cannot support a general claim that LLM judges are inferior. A strong-pair preference is consistent with the successful-output pattern but does not reveal the model's internal reasoning. Missing small-model cells also preclude conclusions about model size or inability to collude.

The auction is synthetic, the cartel is instructed, and the treatment bundles objectives, partner information and communication. A1 varies a warning sentence; its economic and detector outcomes do not identify an evasion mechanism. A2 varies the specified model placement, including effects on other firms, rather than an isolated model-sameness property. L2 also assumes authorised access to private costs. These limits, privacy considerations, and dual-use risks are detailed in Appendix F.

Next tests should add independent markets and richer public-state controls, measure the value of combining scores, and evaluate honest private-information pathways. Probe inference needs independent regenerated messages within each cost/context and a null that respects that hierarchy. Simply relabelling whole message bundles does not repair conditional mutual information: within-context category relabelling leaves that statistic unchanged.

# 6 Conclusion

Net influence detects the instructed strong-pair cartel treatment in the registered experiment. Correlation is a demanding same-access baseline, and the results show no general advantage over it. Espionage provides a specific descriptive lead for further work. Reliable flow classification, judge comparisons under broad coverage, and causal probe inference remain unresolved. These methods can support investigation; they do not establish agreement, intent, or harm.

# Code and Data

The final analysis is `results/analysis/final_v1/results.json`; `experiments/report_figures.py` regenerates the report figures and numerical tables without model calls. Appendix E gives the analysis command, execution provenance and checksums. **[TODO: Insert public repository and release archive URLs after release.]**





**Figure 2:** Localisation and false alarms. Top panels: assigned-pair top-1 on all eligible markets. Middle: all methods on the identical successful judge-matched blocks, with sample sizes shown. Bottom: honest-market alarm rates with exact binomial intervals; these are descriptive, not calibration guarantees. Bootstrap intervals accompany top-1. A degenerate interval in a tiny judge subset does not imply certainty.

# References


Kushal Agrawal, Verona Teo, Juan J. Vazquez, Sudarsh Kunnavakkam, Vishak Srikanth, and Andy Liu. Evaluating LLM agent collusion in double auctions. arXiv:2507.01413, 2025. URL https://arxiv.org/abs/2507.01413.

Trevor Bonjour, Vaneet Aggarwal, and Bharat Bhargava. Information theoretic approach to detect collusion in multi-agent games. In *Proceedings of the Thirty-Eighth Conference on Uncertainty in Artificial Intelligence*, volume 180 of *Proceedings of Machine Learning Research*, pages 223–232, 2022. URL https://proceedings.mlr.press/v180/bonjour22a.html.

Sara Fish, Yannai A. Gonczarowski, and Ran I. Shorrer. Algorithmic collusion by large language models. arXiv:2404.00806, 2024. URL https://arxiv.org/abs/2404.00806.

Martin Huber and David Imhof. Machine learning with screens for detecting bid-rigging cartels. *International Journal of Industrial Organization*, 65:277–301, 2019. doi: 10.1016/j.ijindorg.2019.04.002.

David Imhof and Hannes Wallimann. Detecting bid-rigging coalitions in different countries and auction formats. *International Review of Law and Economics*, 68:106016, 2021. doi: 10.1016/j.irle.2021.106016.

Dohun Lee and Hyunwoo Park. Faithful yet collusive: Why chain-of-thought monitoring cannot detect collusion in LLM pricing agents under oligopolistic competition. arXiv:2609.18346, 2026. URL https://arxiv.org/abs/2609.18346.

Ryan Y. Lin, Siddhartha Ojha, Kevin Cai, and Maxwell F. Chen. Strategic collusion of LLM agents: Market division in multi-commodity competitions. arXiv:2410.00031, 2024. URL https://arxiv.org/abs/2410.00031.

Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among AI agents: Multi-agent deception via steganography. In *Advances in Neural Information Processing Systems*, volume 37, 2024. doi: 10.52202/079017-2336.

Raj-Taware. collusion-net-influence. GitHub repository, https://github.com/Raj-Taware/collusion-net-influence, 2026. Commit 0e2aa44 (22 Oct 2026), accessed 24 Oct 2026.

Aaron Rose, Carissa Cullen, Sahar Abdelnabi, Philip Torr, Brandon Gary Kaplowitz, and Christian Schroeder de Witt. Detecting multi-agent collusion through multi-agent interpretability. arXiv:2604.01151, 2026. URL https://arxiv.org/abs/2604.01151.

soumya-nayak-commits. collusion-detetction. GitHub repository, https://github.com/soumya-nayak-commits/collusion-detetction, 2026. Commit ee0c111 (23 Oct 2026), accessed 24 Oct 2026.

Om Tailor. Audit the Whisper: Detecting steganographic collusion in multi-agent LLMs. arXiv:2510.04303, 2025. URL https://arxiv.org/abs/2510.04303.

Hannes Wallimann, David Imhof, and Martin Huber. A machine learning approach for flagging incomplete bid-rigging cartels. *Computational Economics*, 62(4):1669–1720, 2023. doi: 10.1007/s10614-022-10315-w.

# A Replication details

The scripted rock–paper–scissors replication implements the influence and mutual net-threshold rule of Bonjour et al. (2022). The comparison uses bits and the previous round's joint action as state, conventions inferred from the published results. The no-state variant is retained to show that conditioning choices matter. Detection rises with coordination and sample size, but the replication does not exactly reproduce all table entries. The values below distinguish the paper's published percentages from our simulation. These are development checks, not LLM results.

**Table 2:** Scripted RPS detection percentages: published values versus our previous-state and no-state replications.

| Coordination probability | Games | Paper | Previous state | No state |
|---|---|---|---|---|
| 0.3 | 100 | 37.1 | 36.3 | 84.4 |
| 0.3 | 200 | 48.3 | 60.1 | 94.4 |
| 0.3 | 300 | 71.0 | 77.0 | 98.1 |
| 0.3 | 400 | 82.8 | 87.1 | 99.5 |
| 0.3 | 500 | 89.6 | 92.2 | 99.9 |
| 0.3 | 1000 | 100.0 | 99.7 | 100.0 |
| 0.4 | 100 | 58.4 | 61.9 | 97.3 |
| 0.4 | 200 | 79.2 | 90.7 | 100.0 |
| 0.4 | 300 | 96.2 | 99.0 | 100.0 |
| 0.4 | 400 | 99.3 | 99.8 | 100.0 |
| 0.4 | 500 | 99.7 | 99.9 | 100.0 |
| 0.4 | 1000 | 100.0 | 100.0 | 100.0 |
| 1.0 | 60 | 100.0 | 100.0 | 100.0 |
| 0.2 | 1000 | 24.3 | 50.0 | 58.0 |
| 0.2 | 10000 | 82.3 | 83.7 | 88.5 |
| 0.1 | 1000 | 8.0 | 0.4 | 0.0 |

**Table 3:** Scripted RPS honest-market any-pair alarm rates (coordination probability zero). This is a separate simulation, not LLM calibration.

| State | Games | Fixed threshold | Permutation rule |
|---|---|---|---|
| none | 50 | 0.296 | 0.038 |
| none | 100 | 0.088 | 0.062 |
| none | 200 | 0.006 | 0.048 |
| none | 500 | 0.0 | 0.042 |
| none | 1000 | 0.0 | 0.038 |
| prev | 50 | 0.588 | 0.02 |
| prev | 100 | 0.484 | 0.036 |
| prev | 200 | 0.252 | 0.036 |
| prev | 500 | 0.046 | 0.026 |
| prev | 1000 | 0.0 | 0.038 |

The deterministic seed is 20261023; the full run uses 1000 trials per detection cell. Its calibration experiment uses 500 trials and 199 permutations. These settings differ from the registered LLM analysis. The complete calibration data, including positive conditions, are in `results/rps/calibration.csv`. Reproduction from the repository root:

```
.venv/Scripts/python experiments/rps_replication.py
```

# B Conditions, prompts and model configuration

The frozen manifest is `experiments/manifests/collection_v2.json`. It maps model identities to roles and hidden seat assignments. Exact prompt templates are in `src/collusion/llm/prompts.py`; model revisions and sampling settings are in the per-run configuration and reproducibility records named by `results/analysis_runs.json`. Request hashes, prompts, responses and parsing metadata remain associated with each raw run. `results/analysis_meta/pilot_qwen9b_v5_N0.json` records the pilot-derived N0 configuration explicitly. The manifest and source checksums accompanying this report allow these inputs to be checked without re-collecting outputs.

**Table 4:** Conditions and matched controls. SS, SF, and FF denote strong–strong, strong–fringe, and fringe–fringe designated pairs. X, Y, Z denote Qwen3.5-9B, Gemma-4-12B, and Ministral-3-8B. All A2 bidders are honest.

| Cell | Intervention or control |
|---|---|
| N0 / P0 | Honest market / live scripted strong cartel with honest LLM fringe. |
| C1-SS/SF/FF | LLM cartel with private channel; matched to N0. |
| C2 / E1 | SS cartel without channel / one strong firm sees the other's cost. |
| C1-NW (A1) | C1-SS without surveillance warning; matched N0/C1-SS triplets. |
| D / C1-XX | Honest / cartel strong pair (X,X), fringe (Y,Z). |
| H-XYZZ / C1-XY | Honest / cartel strong pair (X,Y), fringe (Z,Z). |
| LX, LY, LZ (A2) | Strong/fringe models (X,Y;X,Z), (Y,Z;Y,X), (Z,X;Z,Y), each with a twin swapping the fringe models. |

The A1 prompt removes only: "The competition authority monitors all bids, so behave inconspicuously." The joint-profit objective and private channel remain. This is a warning-removal treatment, not a direct test of an internal evasion strategy. Core Qwen and A1 retain the strict parser; the documented fenced-JSON parser cohort covers Gemma/Ministral, A2 and breadth collection. Bidders run without thinking, whereas the primary judge uses thinking. No treatment labels, messages or model identities are given to the judges.

# C Scripted validation

Scripted auctions test known cartels, spies and honest policies under the same observation constraints. Shared-history stress tests show why a coarse or incomplete public state can invalidate a permutation null. Power planning and conditional-table occupancy checks motivated the market horizon and weak-evidence category. These simulations inform the design; they do not establish calibration for arbitrary adaptive LLM bidders. The existing artefacts are in `results/auction_scripted/`, `results/auction_power/`, and `results/null_validity/`. Reproduction commands (each also accepts `-quick`):

```
.venv/Scripts/python experiments/auction_scripted.py
.venv/Scripts/python experiments/auction_checks.py
.venv/Scripts/python experiments/auction_power.py
.venv/Scripts/python experiments/null_validity.py
```

These commands regenerate development outputs. They were not rerun for this report update, which reads existing frozen analysis files only.

# D All registered cells and per-model results

The following single comprehensive table includes every registered cell, including unavailable detector results and cancelled breadth judges, at prefix 200 with the complete-round mask. It contains 312 detector/access rows spanning 28 cells. The full machine-readable table with every prefix and mask is `results/analysis/final_v1/all_cells.md`; no sensitivity rows are silently discarded from that file.

Cov. is successful detector coverage; *n* is the matched AUROC block count. A dash means unavailable or not applicable, never a score of zero. Unique/wrong/abstain are rates under the operational reporting rule; AUROC uses the continuous score, including for the paper detector. For honest cells, top-1 and mean reciprocal rank (MRR) describe the *designated reference pair*, not localisation accuracy. Similarly, "unique" is a report of that reference pair, and "wrong" is a report of another pair; neither is a correct collusion finding in an honest market. Alarm columns give any candidate, exactly one report, and designated reference-pair alarms, with exact binomial intervals.

Flow counts are ordered both detected / one detected, reverse weak / neither detected, both weak / unclear / unavailable. Pipeline counts use the same first categories, ending in no pair instead of unavailable. All-zero pipeline counts for score-only baselines mean no reporting rule, not evidence that no information flowed. Judge rows' label counts describe their available subset. Excluded markets fail the registered bid-validity rule. Superseded operational attempts are retained in the raw record, but are not extra independent markets in this registered cohort.

**Table 5:** All registered cells at the full prefix and complete mask. See the surrounding text for column definitions.

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| **core.N0**; declared 40, collected 40, missing 0, ineligible 0, eligible 40 | | | | |
| L1 corr. | 40/– | – | 0.050 [0.000, 0.125] | – / – / – |
| MRR 0.242 [0.192, 0.307]; flow 0/0/32/8/0; pipeline 0/0/0/0/0. | | | | |
| L1 G judge | 1/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/1/0/39; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 21/– | – | 0.952 [0.840, 1.000] | – / – / – |
| MRR 0.964 [0.880, 1.000]; flow 0/0/19/2/19; pipeline 0/0/0/0/0. | | | | |
| L1 net | 40/– | – | 0.100 [0.025, 0.200] | 0.000 / 0.025 / 0.975 |
| MRR 0.385 [0.321, 0.462]; flow 0/0/32/8/0; pipeline 0/0/0/1/39. Alarms: any 1/40 [0.001, 0.132]; one 1/40 [0.001, 0.132]; ref. 0/40 [0.000, 0.088] | | | | |
| L1 paper | 40/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.600 / 0.400 |
| MRR 0.418 [0.378, 0.454]; flow 0/0/32/8/0; pipeline 0/0/16/8/16. Alarms: any 24/40 [0.433, 0.751]; one 24/40 [0.433, 0.751]; ref. 0/40 [0.000, 0.088] | | | | |
| L1 strength | 40/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/32/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 40/– | – | 0.175 [0.075, 0.300] | – / – / – |
| MRR 0.415 [0.330, 0.508]; flow 0/0/32/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 G judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/40; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 15/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/13/2/25; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 40/– | – | 0.050 [0.000, 0.125] | 0.000 / 0.100 / 0.900 |
| MRR 0.333 [0.283, 0.394]; flow 0/0/32/8/0; pipeline 0/3/0/1/36. Alarms: any 4/40 [0.028, 0.237]; one 4/40 [0.028, 0.237]; ref. 0/40 [0.000, 0.088] | | | | |
| L2 net | 40/– | – | 0.075 [0.000, 0.151] | 0.000 / 0.075 / 0.925 |
| MRR 0.369 [0.307, 0.439]; flow 0/0/32/8/0; pipeline 0/0/0/3/37. Alarms: any 3/40 [0.016, 0.204]; one 3/40 [0.016, 0.204]; ref. 0/40 [0.000, 0.088] | | | | |
| L2 paper | 40/– | – | 0.000 [0.000, 0.000] | 0.000 / 1.000 / 0.000 |
| MRR 0.408 [0.369, 0.444]; flow 0/0/32/8/0; pipeline 0/0/25/15/0. Alarms: any 40/40 [0.912, 1.000]; one 40/40 [0.912, 1.000]; ref. 0/40 [0.000, 0.088] | | | | |
| L2 strength | 40/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/32/8/0; pipeline 0/0/0/0/0. | | | | |
| **core.P0**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 5/4 | 0.000 [0.000, 0.000] | 0.033 [0.000, 0.111] | – / – / – |
| MRR 0.304 [0.250, 0.367]; flow 5/0/0/0/15; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 20/0/0/0/0. | | | | |
| L1 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 20/0/0/0/0. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 4/3 | 0.000 [0.000, 0.000] | 0.083 [0.000, 0.167] | – / – / – |
| MRR 0.330 [0.250, 0.500]; flow 4/0/0/0/16; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 0.950 / 0.000 / 0.050 |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 19/0/0/0/1. | | | | |
| L2 net | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 20/0/0/0/0. | | | | |
| L2 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 20/0/0/0/0. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 20/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| **core.C1-SS**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.988 [0.959, 1.000] | 0.750 [0.550, 0.933] | – / – / – |
| MRR 0.863 [0.750, 0.963]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| L1 G judge | 3/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/1/2/17; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 13/8 | 0.320 [0.069, 0.617] | 0.808 [0.583, 1.000] | – / – / – |
| MRR 0.835 [0.643, 1.000]; flow 0/0/6/7/7; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L1 net | 20/20 | 0.912 [0.796, 1.000] | 0.850 [0.680, 1.000] | 0.800 / 0.000 / 0.200 |
| MRR 0.908 [0.800, 1.000]; flow 0/0/8/12/0; pipeline 0/0/6/10/4. | | | | |
| L1 paper | 20/20 | 0.885 [0.765, 0.991] | 0.150 [0.000, 0.318] | 0.100 / 0.300 / 0.600 |
| MRR 0.527 [0.433, 0.627]; flow 0/0/8/12/0; pipeline 0/0/4/4/12. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.998 [0.986, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| L2 G judge | 1/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/0/1/19; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 7/1 | 0.000 [0.000, 0.000] | 0.881 [0.583, 1.000] | – / – / – |
| MRR 0.898 [0.643, 1.000]; flow 0/0/3/4/13; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.640 [0.428, 0.836] | 0.300 [0.105, 0.519] | 0.000 / 0.050 / 0.950 |
| MRR 0.530 [0.387, 0.678]; flow 0/0/8/12/0; pipeline 0/0/0/1/19. | | | | |
| L2 net | 20/20 | 0.865 [0.734, 0.968] | 0.700 [0.500, 0.889] | 0.250 / 0.000 / 0.750 |
| MRR 0.823 [0.693, 0.938]; flow 0/0/8/12/0; pipeline 0/0/0/5/15. | | | | |
| L2 paper | 20/20 | 0.882 [0.776, 0.970] | 0.000 [0.000, 0.000] | 0.000 / 0.950 / 0.050 |
| MRR 0.443 [0.395, 0.485]; flow 0/0/8/12/0; pipeline 0/0/11/8/1. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| **core.C2**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.463 [0.242, 0.694] | 0.300 [0.111, 0.522] | – / – / – |
| MRR 0.453 [0.300, 0.624]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 10/4 | 0.344 [0.000, 1.000] | 0.833 [0.583, 1.000] | – / – / – |
| MRR 0.857 [0.643, 1.000]; flow 0/0/4/6/10; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.610 [0.413, 0.785] | 0.067 [0.000, 0.188] | 0.000 / 0.150 / 0.850 |
| MRR 0.393 [0.317, 0.485]; flow 0/0/11/9/0; pipeline 0/0/0/3/17. | | | | |
| L1 paper | 20/20 | 0.710 [0.550, 0.854] | 0.000 [0.000, 0.000] | 0.000 / 0.800 / 0.200 |
| MRR 0.467 [0.426, 0.500]; flow 0/0/11/9/0; pipeline 0/0/4/12/4. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.495 [0.271, 0.713] | 0.400 [0.190, 0.619] | – / – / – |
| MRR 0.541 [0.378, 0.712]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 9/3 | 0.333 [0.000, 1.000] | 0.907 [0.688, 1.000] | – / – / – |
| MRR 0.921 [0.732, 1.000]; flow 0/0/8/1/11; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.562 [0.366, 0.760] | 0.050 [0.000, 0.167] | 0.000 / 0.000 / 1.000 |
| MRR 0.357 [0.284, 0.448]; flow 0/0/11/9/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/20 | 0.655 [0.467, 0.833] | 0.050 [0.000, 0.167] | 0.050 / 0.000 / 0.950 |
| MRR 0.391 [0.315, 0.483]; flow 0/0/11/9/0; pipeline 0/0/0/1/19. | | | | |
| L2 paper | 20/20 | 0.887 [0.764, 0.979] | 0.000 [0.000, 0.000] | 0.000 / 1.000 / 0.000 |
| MRR 0.487 [0.458, 0.500]; flow 0/0/11/9/0; pipeline 0/0/7/13/0. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| **core.E1**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.482 [0.337, 0.628] | 0.100 [0.000, 0.250] | – / – / – |
| MRR 0.276 [0.179, 0.401]; flow 0/4/8/8/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 12/5 | 0.600 [0.167, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/6/4/8; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.675 [0.493, 0.845] | 0.300 [0.105, 0.500] | 0.050 / 0.000 / 0.950 |
| MRR 0.570 [0.440, 0.708]; flow 0/4/8/8/0; pipeline 0/0/1/0/19. | | | | |
| L1 paper | 20/20 | 0.620 [0.453, 0.785] | 0.000 [0.000, 0.000] | 0.000 / 0.900 / 0.100 |
| MRR 0.463 [0.425, 0.492]; flow 0/4/8/8/0; pipeline 0/0/11/7/2. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/4/8/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.415 [0.233, 0.615] | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.378 [0.263, 0.515]; flow 0/4/8/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 7/1 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/1/4/13; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.703 [0.574, 0.836] | 0.300 [0.105, 0.520] | 0.200 / 0.000 / 0.800 |
| MRR 0.568 [0.440, 0.704]; flow 0/4/8/8/0; pipeline 0/4/0/0/16. | | | | |
| L2 net | 20/20 | 0.700 [0.529, 0.877] | 0.400 [0.188, 0.625] | 0.000 / 0.050 / 0.950 |
| MRR 0.607 [0.460, 0.759]; flow 0/4/8/8/0; pipeline 0/0/0/1/19. | | | | |
| L2 paper | 20/20 | 0.652 [0.485, 0.821] | 0.000 [0.000, 0.000] | 0.000 / 1.000 / 0.000 |
| MRR 0.464 [0.422, 0.500]; flow 0/4/8/8/0; pipeline 0/0/13/7/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/4/8/8/0; pipeline 0/0/0/0/0. | | | | |
| **core.C1-SF**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/10/9/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 14/7 | 0.602 [0.250, 0.880] | 0.048 [0.011, 0.091] | – / – / – |
| MRR 0.273 [0.251, 0.295]; flow 0/1/5/8/6; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.993 [0.969, 1.000] | 1.000 [1.000, 1.000] | 0.650 / 0.000 / 0.350 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/10/9/0; pipeline 0/1/4/8/7. | | | | |
| L1 paper | 20/20 | 0.998 [0.986, 1.000] | 0.950 [0.833, 1.000] | 0.550 / 0.000 / 0.450 |
| MRR 0.975 [0.917, 1.000]; flow 0/1/10/9/0; pipeline 0/1/3/7/9. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.250 [0.250, 0.250]; flow 0/1/10/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.980 [0.927, 1.000] | 0.900 [0.750, 1.000] | – / – / – |
| MRR 0.950 [0.875, 1.000]; flow 0/1/10/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 11/3 | 0.667 [0.000, 1.000] | 0.030 [0.000, 0.074] | – / – / – |
| MRR 0.260 [0.233, 0.288]; flow 0/1/6/4/9; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.645 [0.479, 0.801] | 0.350 [0.143, 0.565] | 0.050 / 0.000 / 0.950 |
| MRR 0.534 [0.376, 0.695]; flow 0/1/10/9/0; pipeline 0/1/0/0/19. | | | | |
| L2 net | 20/20 | 0.850 [0.723, 0.958] | 0.800 [0.609, 0.952] | 0.400 / 0.050 / 0.550 |
| MRR 0.872 [0.743, 0.974]; flow 0/1/10/9/0; pipeline 0/0/2/7/11. | | | | |
| L2 paper | 20/20 | 0.995 [0.978, 1.000] | 0.600 [0.381, 0.812] | 0.450 / 0.200 / 0.350 |
| MRR 0.800 [0.690, 0.906]; flow 0/1/10/9/0; pipeline 0/1/5/7/7. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.250 [0.250, 0.250]; flow 0/1/10/9/0; pipeline 0/0/0/0/0. | | | | |
| **core.C1-FF**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.993 [0.972, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 10/4 | 0.438 [0.000, 1.000] | 0.100 [0.000, 0.333] | – / – / – |
| MRR 0.383 [0.250, 0.561]; flow 0/1/2/7/10; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/1/4/15/0. | | | | |
| L1 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/1/4/15/0. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.250 [0.250, 0.250]; flow 0/1/4/15/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 14/7 | 0.551 [0.344, 0.812] | 0.012 [0.000, 0.039] | – / – / – |
| MRR 0.383 [0.308, 0.455]; flow 0/1/3/10/6; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.868 [0.727, 0.964] | 0.600 [0.375, 0.812] | 0.150 / 0.000 / 0.850 |
| MRR 0.724 [0.565, 0.871]; flow 0/1/4/15/0; pipeline 0/1/0/2/17. | | | | |
| L2 net | 20/20 | 0.998 [0.986, 1.000] | 1.000 [1.000, 1.000] | 0.950 / 0.000 / 0.050 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/1/3/15/1. | | | | |
| L2 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/4/15/0; pipeline 0/1/4/15/0. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.250 [0.250, 0.250]; flow 0/1/4/15/0; pipeline 0/0/0/0/0. | | | | |
| **labs.gemma-12b.N0**; declared 20, collected 20, missing 0, ineligible 6, eligible 14 | | | | |
| L1 corr. | 14/– | – | 0.071 [0.000, 0.231] | – / – / – |
| MRR 0.288 [0.192, 0.426]; flow 0/0/8/6/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/14; pipeline 0/0/0/0/0. | | | | |
| L1 net | 14/– | – | 0.143 [0.000, 0.357] | 0.000 / 0.071 / 0.929 |
| MRR 0.430 [0.300, 0.581]; flow 0/0/8/6/0; pipeline 0/0/1/0/13. Alarms: any 1/14 [0.002, 0.339]; one 1/14 [0.002, 0.339]; ref. 0/14 [0.000, 0.232] | | | | |
| L1 paper | 14/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.357 / 0.643 |
| MRR 0.401 [0.332, 0.464]; flow 0/0/8/6/0; pipeline 0/0/3/2/9. Alarms: any 5/14 [0.128, 0.649]; one 5/14 [0.128, 0.649]; ref. 0/14 [0.000, 0.232] | | | | |
| L1 strength | 14/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/6/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 14/– | – | 0.286 [0.067, 0.545] | – / – / – |
| MRR 0.483 [0.310, 0.674]; flow 0/0/8/6/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/14; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 leak | 14/– | – | 0.071 [0.000, 0.231] | 0.000 / 0.071 / 0.929 |
| MRR 0.374 [0.270, 0.500]; flow 0/0/8/6/0; pipeline 0/1/0/0/13. Alarms: any 1/14 [0.002, 0.339]; one 1/14 [0.002, 0.339]; ref. 0/14 [0.000, 0.232] | | | | |
| L2 net | 14/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.214 / 0.786 |
| MRR 0.363 [0.292, 0.431]; flow 0/0/8/6/0; pipeline 0/0/1/2/11. Alarms: any 3/14 [0.047, 0.508]; one 3/14 [0.047, 0.508]; ref. 0/14 [0.000, 0.232] | | | | |
| L2 paper | 14/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.857 / 0.143 |
| MRR 0.457 [0.393, 0.500]; flow 0/0/8/6/0; pipeline 0/0/8/4/2. Alarms: any 12/14 [0.572, 0.982]; one 12/14 [0.572, 0.982]; ref. 0/14 [0.000, 0.232] | | | | |
| L2 strength | 14/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/6/0; pipeline 0/0/0/0/0. | | | | |
| **labs.gemma-12b.C1**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/14 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/14 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 0.900 / 0.000 / 0.100 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/1/5/12/2. | | | | |
| L1 paper | 20/14 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 0.950 / 0.000 / 0.050 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/1/5/13/1. | | | | |
| L1 strength | 20/14 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/14 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/14 | 0.969 [0.876, 1.000] | 0.600 [0.375, 0.812] | 0.050 / 0.000 / 0.950 |
| MRR 0.758 [0.613, 0.890]; flow 0/1/5/14/0; pipeline 0/1/0/0/19. | | | | |
| L2 net | 20/14 | 0.995 [0.973, 1.000] | 1.000 [1.000, 1.000] | 0.550 / 0.000 / 0.450 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/1/3/7/9. | | | | |
| L2 paper | 20/14 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/1/5/14/0. | | | | |
| L2 strength | 20/14 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/5/14/0; pipeline 0/0/0/0/0. | | | | |
| **labs.ministral-8b.N0**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.100 [0.000, 0.250] | – / – / – |
| MRR 0.378 [0.275, 0.496]; flow 0/1/12/7/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.100 [0.000, 0.250] | 0.050 / 0.250 / 0.700 |
| MRR 0.419 [0.322, 0.530]; flow 0/1/12/7/0; pipeline 0/0/2/4/14. Alarms: any 6/20 [0.119, 0.543]; one 6/20 [0.119, 0.543]; ref. 1/20 [0.001, 0.249] | | | | |
| L1 paper | 20/– | – | 0.050 [0.000, 0.167] | 0.000 / 0.000 / 1.000 |
| MRR 0.384 [0.302, 0.474]; flow 0/1/12/7/0; pipeline 0/0/0/0/20. Alarms: any 0/20 [0.000, 0.168]; one 0/20 [0.000, 0.168]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/12/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.200 [0.045, 0.389] | – / – / – |
| MRR 0.445 [0.322, 0.579]; flow 0/1/12/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.150 [0.000, 0.320] | 0.050 / 0.050 / 0.900 |
| MRR 0.392 [0.280, 0.522]; flow 0/1/12/7/0; pipeline 0/2/0/0/18. Alarms: any 2/20 [0.012, 0.317]; one 2/20 [0.012, 0.317]; ref. 1/20 [0.001, 0.249] | | | | |
| L2 net | 20/– | – | 0.050 [0.000, 0.167] | 0.000 / 0.150 / 0.850 |
| MRR 0.359 [0.290, 0.447]; flow 0/1/12/7/0; pipeline 0/0/0/3/17. Alarms: any 3/20 [0.032, 0.379]; one 3/20 [0.032, 0.379]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.300 / 0.700 |
| MRR 0.303 [0.252, 0.356]; flow 0/1/12/7/0; pipeline 0/0/1/5/14. Alarms: any 6/20 [0.119, 0.543]; one 6/20 [0.119, 0.543]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/12/7/0; pipeline 0/0/0/0/0. | | | | |
| **labs.ministral-8b.C1**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.897 [0.785, 0.975] | 0.650 [0.435, 0.857] | – / – / – |
| MRR 0.808 [0.687, 0.922]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.860 [0.712, 0.975] | 0.800 [0.611, 0.955] | 0.550 / 0.000 / 0.450 |
| MRR 0.877 [0.756, 0.975]; flow 0/0/8/12/0; pipeline 0/0/5/6/9. | | | | |
| L1 paper | 20/20 | 0.922 [0.803, 1.000] | 0.750 [0.550, 0.938] | 0.450 / 0.000 / 0.550 |
| MRR 0.854 [0.734, 0.963]; flow 0/0/8/12/0; pipeline 0/0/5/4/11. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.828 [0.707, 0.935] | 0.600 [0.375, 0.812] | – / – / – |
| MRR 0.771 [0.639, 0.896]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.675 [0.469, 0.859] | 0.250 [0.062, 0.455] | 0.000 / 0.000 / 1.000 |
| MRR 0.512 [0.387, 0.650]; flow 0/0/8/12/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/20 | 0.745 [0.567, 0.908] | 0.600 [0.375, 0.815] | 0.200 / 0.150 / 0.650 |
| MRR 0.756 [0.615, 0.891]; flow 0/0/8/12/0; pipeline 0/0/3/4/13. | | | | |
| L2 paper | 20/20 | 0.935 [0.838, 0.992] | 0.650 [0.429, 0.857] | 0.450 / 0.050 / 0.500 |
| MRR 0.770 [0.621, 0.910]; flow 0/0/8/12/0; pipeline 0/0/3/7/10. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/8/12/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.qwen-4b.N0**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.314 [0.193, 0.463]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.050 [0.000, 0.167] | 0.050 / 0.100 / 0.850 |
| MRR 0.361 [0.282, 0.455]; flow 0/0/13/7/0; pipeline 0/0/2/1/17. Alarms: any 3/20 [0.032, 0.379]; one 3/20 [0.032, 0.379]; ref. 1/20 [0.001, 0.249] | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.650 / 0.350 |
| MRR 0.429 [0.369, 0.482]; flow 0/0/13/7/0; pipeline 0/0/4/9/7. Alarms: any 13/20 [0.408, 0.846]; one 13/20 [0.408, 0.846]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.200 [0.045, 0.392] | – / – / – |
| MRR 0.452 [0.324, 0.594]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.050 [0.000, 0.167] | 0.000 / 0.150 / 0.850 |
| MRR 0.352 [0.277, 0.447]; flow 0/0/13/7/0; pipeline 0/3/0/0/17. Alarms: any 3/20 [0.032, 0.379]; one 3/20 [0.032, 0.379]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 net | 20/– | – | 0.150 [0.000, 0.333] | 0.000 / 0.000 / 1.000 |
| MRR 0.384 [0.272, 0.518]; flow 0/0/13/7/0; pipeline 0/0/0/0/20. Alarms: any 0/20 [0.000, 0.168]; one 0/20 [0.000, 0.168]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 1.000 / 0.000 |
| MRR 0.437 [0.383, 0.483]; flow 0/0/13/7/0; pipeline 0/0/10/10/0. Alarms: any 20/20 [0.832, 1.000]; one 20/20 [0.832, 1.000]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.qwen-4b.C1**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.978 [0.926, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/12/8/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.993 [0.972, 1.000] | 1.000 [1.000, 1.000] | 0.900 / 0.000 / 0.100 |
| MRR 1.000 [1.000, 1.000]; flow 0/0/12/8/0; pipeline 0/0/11/7/2. | | | | |
| L1 paper | 20/20 | 1.000 [1.000, 1.000] | 0.400 [0.190, 0.619] | 0.100 / 0.450 / 0.450 |
| MRR 0.700 [0.595, 0.810]; flow 0/0/12/8/0; pipeline 0/0/6/5/9. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/12/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.955 [0.843, 1.000] | 0.950 [0.833, 1.000] | – / – / – |
| MRR 0.975 [0.917, 1.000]; flow 0/0/12/8/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.463 [0.279, 0.652] | 0.200 [0.048, 0.389] | 0.000 / 0.000 / 1.000 |
| MRR 0.452 [0.326, 0.589]; flow 0/0/12/8/0; pipeline 0/0/0/0/20. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 net | 20/20 | 0.943 [0.866, 0.992] | 0.700 [0.500, 0.895] | 0.750 / 0.050 / 0.200 |
| MRR 0.833 [0.714, 0.941]; flow 0/0/12/8/0; pipeline 0/0/8/8/4. | | | | |
| L2 paper | 20/20 | 0.960 [0.903, 1.000] | 0.000 [0.000, 0.000] | 0.000 / 0.950 / 0.050 |
| MRR 0.483 [0.444, 0.500]; flow 0/0/12/8/0; pipeline 0/0/13/6/1. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/12/8/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.gemma-e4b.N0**; declared 20, collected 20, missing 0, ineligible 20, eligible 0 | | | | |
| L1 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.gemma-e4b.C1**; declared 20, collected 20, missing 0, ineligible 20, eligible 0 | | | | |
| L1 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.ministral-3b.N0**; declared 20, collected 20, missing 0, ineligible 20, eligible 0 | | | | |
| L1 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 net | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 paper | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 strength | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/0; pipeline 0/0/0/0/0. | | | | |
| **sizes.ministral-3b.C1**; declared 20, collected 20, missing 0, ineligible 18, eligible 2 | | | | |
| L1 corr. | 2/– | – | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.292 [0.250, 0.333]; flow 0/0/2/0/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/2; pipeline 0/0/0/0/0. | | | | |
| L1 net | 2/– | – | 0.000 [0.000, 0.000] | 0.000 / 1.000 / 0.000 |
| MRR 0.500 [0.500, 0.500]; flow 0/0/2/0/0; pipeline 0/0/2/0/0. | | | | |
| L1 paper | 2/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.500 / 0.500 |
| MRR 0.417 [0.333, 0.500]; flow 0/0/2/0/0; pipeline 0/0/1/0/1. | | | | |
| L1 strength | 2/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/2/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 2/– | – | 0.500 [0.000, 1.000] | – / – / – |
| MRR 0.750 [0.500, 1.000]; flow 0/0/2/0/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/2; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 2/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.267 [0.200, 0.333]; flow 0/0/2/0/0; pipeline 0/0/0/0/2. | | | | |
| L2 net | 2/– | – | 0.500 [0.000, 1.000] | 0.500 / 0.000 / 0.500 |
| MRR 0.600 [0.200, 1.000]; flow 0/0/2/0/0; pipeline 0/0/1/0/1. | | | | |
| L2 paper | 2/– | – | 0.500 [0.000, 1.000] | 0.000 / 0.500 / 0.500 |
| MRR 0.625 [0.250, 1.000]; flow 0/0/2/0/0; pipeline 0/0/1/0/1. | | | | |
| L2 strength | 2/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/2/0/0; pipeline 0/0/0/0/0. | | | | |
| **mixed.D**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.226 [0.199, 0.254]; flow 0/2/13/5/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.200 [0.048, 0.389] | 0.000 / 0.000 / 1.000 |
| MRR 0.491 [0.374, 0.621]; flow 0/2/13/5/0; pipeline 0/0/0/0/20. Alarms: any 0/20 [0.000, 0.168]; one 0/20 [0.000, 0.168]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.327 [0.268, 0.388]; flow 0/2/13/5/0; pipeline 0/0/0/0/20. Alarms: any 0/20 [0.000, 0.168]; one 0/20 [0.000, 0.168]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/13/5/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.366 [0.251, 0.501]; flow 0/2/13/5/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.150 [0.000, 0.333] | 0.100 / 0.050 / 0.850 |
| MRR 0.432 [0.324, 0.558]; flow 0/2/13/5/0; pipeline 0/3/0/0/17. Alarms: any 3/20 [0.032, 0.379]; one 3/20 [0.032, 0.379]; ref. 2/20 [0.012, 0.317] | | | | |
| L2 net | 20/– | – | 0.250 [0.062, 0.455] | 0.000 / 0.050 / 0.950 |
| MRR 0.431 [0.289, 0.591]; flow 0/2/13/5/0; pipeline 0/1/0/0/19. Alarms: any 1/20 [0.001, 0.249]; one 1/20 [0.001, 0.249]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.100 / 0.900 |
| MRR 0.254 [0.209, 0.308]; flow 0/2/13/5/0; pipeline 0/0/1/1/18. Alarms: any 2/20 [0.012, 0.317]; one 2/20 [0.012, 0.317]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/13/5/0; pipeline 0/0/0/0/0. | | | | |
| **mixed.C1-XX**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.990 [0.963, 1.000] | 0.850 [0.667, 1.000] | – / – / – |
| MRR 0.925 [0.833, 1.000]; flow 0/2/8/10/0; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.965 [0.898, 1.000] | 0.950 [0.833, 1.000] | 0.800 / 0.000 / 0.200 |
| MRR 0.975 [0.917, 1.000]; flow 0/2/8/10/0; pipeline 0/2/6/8/4. | | | | |
| L1 paper | 20/20 | 0.955 [0.848, 1.000] | 0.900 [0.750, 1.000] | 0.450 / 0.000 / 0.550 |
| MRR 0.950 [0.875, 1.000]; flow 0/2/8/10/0; pipeline 0/1/2/6/11. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/8/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.998 [0.986, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/8/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.695 [0.505, 0.858] | 0.350 [0.143, 0.571] | 0.100 / 0.000 / 0.900 |
| MRR 0.545 [0.396, 0.706]; flow 0/2/8/10/0; pipeline 0/2/0/0/18. | | | | |
| L2 net | 20/20 | 0.885 [0.779, 0.965] | 0.700 [0.500, 0.889] | 0.500 / 0.100 / 0.400 |
| MRR 0.833 [0.714, 0.939]; flow 0/2/8/10/0; pipeline 0/2/3/7/8. | | | | |
| L2 paper | 20/20 | 0.993 [0.969, 1.000] | 0.950 [0.833, 1.000] | 0.600 / 0.000 / 0.400 |
| MRR 0.975 [0.917, 1.000]; flow 0/2/8/10/0; pipeline 0/1/5/6/8. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/2/8/10/0; pipeline 0/0/0/0/0. | | | | |
| **mixed.H-XYZZ**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.333 [0.250, 0.432]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.050 / 0.950 |
| MRR 0.391 [0.331, 0.446]; flow 0/0/17/3/0; pipeline 0/0/1/0/19. Alarms: any 1/20 [0.001, 0.249]; one 1/20 [0.001, 0.249]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.050 / 0.950 |
| MRR 0.368 [0.305, 0.428]; flow 0/0/17/3/0; pipeline 0/0/1/0/19. Alarms: any 1/20 [0.001, 0.249]; one 1/20 [0.001, 0.249]; ref. 0/20 [0.000, 0.168] | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.369 [0.292, 0.462]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.050 / 0.950 |
| MRR 0.342 [0.251, 0.457]; flow 0/0/17/3/0; pipeline 0/1/0/0/19. Alarms: any 1/20 [0.001, 0.249]; one 1/20 [0.001, 0.249]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 net | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.100 / 0.900 |
| MRR 0.430 [0.334, 0.541]; flow 0/0/17/3/0; pipeline 0/1/1/0/18. Alarms: any 2/20 [0.012, 0.317]; one 2/20 [0.012, 0.317]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.350 / 0.650 |
| MRR 0.269 [0.217, 0.327]; flow 0/0/17/3/0; pipeline 0/1/2/4/13. Alarms: any 7/20 [0.154, 0.592]; one 7/20 [0.154, 0.592]; ref. 0/20 [0.000, 0.168] | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| **mixed.C1-XY**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 0.950 / 0.000 / 0.050 |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/5/7/7/1. | | | | |
| L1 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/6/7/7/0. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 0/– | – | – | – / – / – |
| MRR –; flow 0/0/0/0/20; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.860 [0.701, 0.989] | 0.750 [0.550, 0.933] | 0.350 / 0.000 / 0.650 |
| MRR 0.838 [0.702, 0.956]; flow 0/6/7/7/0; pipeline 0/6/0/1/13. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 net | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/6/7/7/0. | | | | |
| L2 paper | 20/20 | 1.000 [1.000, 1.000] | 1.000 [1.000, 1.000] | 1.000 / 0.000 / 0.000 |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/6/7/7/0. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/6/7/7/0; pipeline 0/0/0/0/0. | | | | |
| **core.C1-NW**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/20 | 0.993 [0.960, 1.000] | 0.900 [0.750, 1.000] | – / – / – |
| MRR 0.933 [0.833, 1.000]; flow 0/1/8/11/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 12/5 | 0.480 [0.000, 1.000] | 0.931 [0.762, 1.000] | – / – / – |
| MRR 0.940 [0.796, 1.000]; flow 0/0/4/8/8; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/20 | 0.968 [0.903, 1.000] | 0.800 [0.609, 0.955] | 0.600 / 0.000 / 0.400 |
| MRR 0.892 [0.786, 0.976]; flow 0/1/8/11/0; pipeline 0/0/4/8/8. | | | | |
| L1 paper | 20/20 | 0.932 [0.847, 0.994] | 0.350 [0.150, 0.565] | 0.100 / 0.400 / 0.500 |
| MRR 0.667 [0.562, 0.778]; flow 0/1/8/11/0; pipeline 0/0/5/5/10. | | | | |
| L1 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/8/11/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/20 | 0.985 [0.932, 1.000] | 0.950 [0.833, 1.000] | – / – / – |
| MRR 0.975 [0.917, 1.000]; flow 0/1/8/11/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 10/5 | 0.800 [0.500, 1.000] | 0.900 [0.667, 1.000] | – / – / – |
| MRR 0.950 [0.833, 1.000]; flow 0/0/4/6/10; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/20 | 0.682 [0.505, 0.844] | 0.200 [0.048, 0.389] | 0.100 / 0.050 / 0.850 |
| MRR 0.464 [0.340, 0.598]; flow 0/1/8/11/0; pipeline 0/2/0/1/17. | | | | |
| L2 net | 20/20 | 0.963 [0.910, 1.000] | 0.650 [0.438, 0.857] | 0.650 / 0.050 / 0.300 |
| MRR 0.817 [0.704, 0.923]; flow 0/1/8/11/0; pipeline 0/1/5/8/6. | | | | |
| L2 paper | 20/20 | 0.975 [0.901, 1.000] | 0.000 [0.000, 0.000] | 0.000 / 0.950 / 0.050 |
| MRR 0.492 [0.472, 0.500]; flow 0/1/8/11/0; pipeline 0/0/12/7/1. | | | | |
| L2 strength | 20/20 | 0.500 [0.500, 0.500] | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/1/8/11/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LX**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.214 [0.188, 0.251]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 14/– | – | 0.881 [0.702, 1.000] | – / – / – |
| MRR 0.898 [0.745, 1.000]; flow 0/0/8/6/6; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.050 [0.000, 0.167] | 0.000 / 0.050 / 0.950 |
| MRR 0.368 [0.289, 0.461]; flow 0/0/10/10/0; pipeline 0/0/0/1/19. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.100 / 0.900 |
| MRR 0.283 [0.231, 0.339]; flow 0/0/10/10/0; pipeline 0/0/1/1/18. | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.316 [0.240, 0.411]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 9/– | – | 0.907 [0.688, 1.000] | – / – / – |
| MRR 0.921 [0.732, 1.000]; flow 0/0/5/4/11; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.150 [0.000, 0.318] | 0.000 / 0.000 / 1.000 |
| MRR 0.420 [0.306, 0.548]; flow 0/0/10/10/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/– | – | 0.150 [0.000, 0.318] | 0.000 / 0.000 / 1.000 |
| MRR 0.398 [0.292, 0.524]; flow 0/0/10/10/0; pipeline 0/0/0/0/20. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.600 / 0.400 |
| MRR 0.237 [0.203, 0.279]; flow 0/0/10/10/0; pipeline 0/0/8/4/8. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LX-swap**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.231 [0.194, 0.280]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 7/– | – | 0.881 [0.583, 1.000] | – / – / – |
| MRR 0.898 [0.643, 1.000]; flow 0/0/4/3/13; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.000 / 1.000 |
| MRR 0.399 [0.307, 0.509]; flow 0/0/13/7/0; pipeline 0/0/0/0/20. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.277 [0.228, 0.336]; flow 0/0/13/7/0; pipeline 0/0/0/0/20. | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.100 [0.000, 0.250] | – / – / – |
| MRR 0.393 [0.296, 0.506]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L2 Q judge | 8/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/6/2/12; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.000 / 1.000 |
| MRR 0.403 [0.316, 0.513]; flow 0/0/13/7/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/– | – | 0.200 [0.048, 0.391] | 0.000 / 0.050 / 0.950 |
| MRR 0.438 [0.315, 0.582]; flow 0/0/13/7/0; pipeline 0/0/1/0/19. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.650 / 0.350 |
| MRR 0.237 [0.204, 0.276]; flow 0/0/13/7/0; pipeline 0/0/9/4/7. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/13/7/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LY**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.000 [0.000, 0.000] | – / – / – |
| MRR 0.188 [0.172, 0.210]; flow 0/0/15/5/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 10/– | – | 0.783 [0.528, 1.000] | – / – / – |
| MRR 0.867 [0.717, 1.000]; flow 0/0/8/2/10; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.150 / 0.850 |
| MRR 0.340 [0.241, 0.461]; flow 0/0/15/5/0; pipeline 0/0/2/1/17. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.350 / 0.650 |
| MRR 0.382 [0.326, 0.438]; flow 0/0/15/5/0; pipeline 0/0/3/4/13. | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/15/5/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.250 [0.059, 0.450] | – / – / – |
| MRR 0.520 [0.391, 0.655]; flow 0/0/15/5/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 6/– | – | 0.611 [0.233, 1.000] | – / – / – |
| MRR 0.742 [0.481, 1.000]; flow 0/0/3/3/14; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.301 [0.254, 0.353]; flow 0/0/15/5/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.100 / 0.900 |
| MRR 0.334 [0.280, 0.390]; flow 0/0/15/5/0; pipeline 0/0/1/1/18. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.950 / 0.050 |
| MRR 0.299 [0.251, 0.352]; flow 0/0/15/5/0; pipeline 0/0/8/11/1. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/15/5/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LY-swap**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.276 [0.209, 0.371]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 12/– | – | 0.778 [0.533, 1.000] | – / – / – |
| MRR 0.814 [0.613, 1.000]; flow 0/0/11/1/8; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.050 [0.000, 0.167] | 0.050 / 0.000 / 0.950 |
| MRR 0.386 [0.312, 0.473]; flow 0/0/17/3/0; pipeline 0/0/1/0/19. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.400 / 0.600 |
| MRR 0.387 [0.330, 0.440]; flow 0/0/17/3/0; pipeline 0/0/5/3/12. | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.420 [0.310, 0.548]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 7/– | – | 0.762 [0.444, 1.000] | – / – / – |
| MRR 0.796 [0.524, 1.000]; flow 0/0/6/1/13; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.050 / 0.950 |
| MRR 0.367 [0.277, 0.478]; flow 0/0/17/3/0; pipeline 0/1/0/0/19. | | | | |
| L2 net | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.150 / 0.850 |
| MRR 0.313 [0.274, 0.356]; flow 0/0/17/3/0; pipeline 0/0/0/3/17. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.900 / 0.100 |
| MRR 0.355 [0.296, 0.412]; flow 0/0/17/3/0; pipeline 0/0/10/8/2. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/17/3/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LZ**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.317 [0.235, 0.418]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 12/– | – | 0.944 [0.810, 1.000] | – / – / – |
| MRR 0.958 [0.857, 1.000]; flow 0/0/6/6/8; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.150 [0.000, 0.333] | 0.000 / 0.050 / 0.950 |
| MRR 0.386 [0.275, 0.517]; flow 0/0/11/9/0; pipeline 0/0/0/1/19. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.249 [0.198, 0.308]; flow 0/0/11/9/0; pipeline 0/0/0/0/20. | | | | |

| Level / detector | Cov./n | AUROC [interval] | Top-1 [interval] | Unique / wrong / abstain |
|---|---|---|---|---|
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.376 [0.265, 0.511]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 6/– | – | 0.667 [0.250, 1.000] | – / – / – |
| MRR 0.806 [0.542, 1.000]; flow 0/0/2/4/14; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.200 [0.048, 0.389] | 0.000 / 0.000 / 1.000 |
| MRR 0.429 [0.305, 0.572]; flow 0/0/11/9/0; pipeline 0/0/0/0/20. | | | | |
| L2 net | 20/– | – | 0.100 [0.000, 0.250] | 0.050 / 0.150 / 0.800 |
| MRR 0.362 [0.268, 0.478]; flow 0/0/11/9/0; pipeline 0/0/0/4/16. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.250 / 0.750 |
| MRR 0.258 [0.212, 0.312]; flow 0/0/11/9/0; pipeline 0/0/1/4/15. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/11/9/0; pipeline 0/0/0/0/0. | | | | |
| **lookalike.LZ-swap**; declared 20, collected 20, missing 0, ineligible 0, eligible 20 | | | | |
| L1 corr. | 20/– | – | 0.050 [0.000, 0.167] | – / – / – |
| MRR 0.246 [0.189, 0.342]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L1 Q judge | 8/– | – | 0.583 [0.259, 0.889] | – / – / – |
| MRR 0.696 [0.455, 0.917]; flow 0/0/4/4/12; pipeline 0/0/0/0/0. | | | | |
| L1 net | 20/– | – | 0.100 [0.000, 0.250] | 0.000 / 0.000 / 1.000 |
| MRR 0.353 [0.257, 0.473]; flow 0/0/10/10/0; pipeline 0/0/0/0/20. | | | | |
| L1 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.000 / 1.000 |
| MRR 0.211 [0.181, 0.251]; flow 0/0/10/10/0; pipeline 0/0/0/0/20. | | | | |
| L1 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 corr. | 20/– | – | 0.150 [0.000, 0.333] | – / – / – |
| MRR 0.354 [0.243, 0.494]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |
| L2 Q judge | 5/– | – | 0.800 [0.333, 1.000] | – / – / – |
| MRR 0.880 [0.600, 1.000]; flow 0/0/4/1/15; pipeline 0/0/0/0/0. | | | | |
| L2 leak | 20/– | – | 0.250 [0.062, 0.450] | 0.000 / 0.050 / 0.950 |
| MRR 0.506 [0.381, 0.646]; flow 0/0/10/10/0; pipeline 0/1/0/0/19. | | | | |
| L2 net | 20/– | – | 0.300 [0.111, 0.520] | 0.050 / 0.050 / 0.900 |
| MRR 0.512 [0.372, 0.666]; flow 0/0/10/10/0; pipeline 0/0/0/2/18. | | | | |
| L2 paper | 20/– | – | 0.000 [0.000, 0.000] | 0.000 / 0.150 / 0.850 |
| MRR 0.254 [0.208, 0.309]; flow 0/0/10/10/0; pipeline 0/1/0/2/17. | | | | |
| L2 strength | 20/– | – | 1.000 [1.000, 1.000] | – / – / – |
| MRR 1.000 [1.000, 1.000]; flow 0/0/10/10/0; pipeline 0/0/0/0/0. | | | | |

## D.1 Prefix, missing-bid and breadth sensitivity

The following compact table provides the score trajectories. Full intervals, coverage, flow labels and reporting outcomes for every prefix/mask remain in `results/analysis/final_v1/all_cells.md`. A3 merges all registered breadth indices; it does not select the first subset after observing scores. The unavailable Gemma-E4B and Ministral-3B cells remain in the comprehensive table above. Mixed XX and XY treatments each use their own composition-matched honest control; their contrast does not isolate model identity.

**Table 6:** Prefix and missing-bid sensitivity for every available treatment comparison. Each entry is AUROC; exact intervals, exclusions and other metrics for every prefix/mask are in all_cells.md.

| Cell / level / detector | Mask | n (full) | Prefix 50 | 100 | 200 |
|---|---|---|---|---|---|
| core.P0/L1/net | complete | 20 | 1.000 | 1.000 | 1.000 |
| core.P0/L1/net | no_bid | 20 | 1.000 | 1.000 | 1.000 |
| core.P0/L1/correlation | complete | 20 | 1.000 | 1.000 | 1.000 |
| core.P0/L1/correlation | no_bid | 20 | 1.000 | 1.000 | 1.000 |
| core.P0/L2/net | complete | 20 | 0.897 | 1.000 | 1.000 |
| core.P0/L2/net | no_bid | 20 | 0.890 | 1.000 | 1.000 |
| core.P0/L2/correlation | complete | 20 | 0.978 | 1.000 | 1.000 |
| core.P0/L2/correlation | no_bid | 20 | 0.978 | 1.000 | 1.000 |
| core.P0/L2/leak | complete | 20 | 0.953 | 1.000 | 1.000 |
| core.P0/L2/leak | no_bid | 20 | 0.953 | 1.000 | 1.000 |
| core.C1-SS/L1/net | complete | 20 | 0.882 | 0.915 | 0.912 |
| core.C1-SS/L1/net | no_bid | 20 | 0.882 | 0.915 | 0.917 |
| core.C1-SS/L1/correlation | complete | 20 | 0.968 | 0.978 | 0.988 |

| Cell / level / detector | Mask | n (full) | Prefix 50 | 100 | 200 |
|---|---|---|---|---|---|
| core.C1-SS/L1/correlation | no_bid | 20 | 0.968 | 0.975 | 0.988 |
| core.C1-SS/L2/net | complete | 20 | 0.650 | 0.795 | 0.865 |
| core.C1-SS/L2/net | no_bid | 20 | 0.660 | 0.785 | 0.858 |
| core.C1-SS/L2/correlation | complete | 20 | 0.975 | 0.998 | 0.998 |
| core.C1-SS/L2/correlation | no_bid | 20 | 0.915 | 0.990 | 1.000 |
| core.C1-SS/L2/leak | complete | 20 | 0.522 | 0.562 | 0.640 |
| core.C1-SS/L2/leak | no_bid | 20 | 0.520 | 0.560 | 0.627 |
| core.C1-SF/L1/net | complete | 20 | 0.762 | 0.840 | 0.993 |
| core.C1-SF/L1/net | no_bid | 20 | 0.760 | 0.870 | 0.970 |
| core.C1-SF/L1/correlation | complete | 20 | 0.902 | 0.990 | 1.000 |
| core.C1-SF/L1/correlation | no_bid | 20 | 0.902 | 0.993 | 1.000 |
| core.C1-SF/L2/net | complete | 20 | 0.700 | 0.720 | 0.850 |
| core.C1-SF/L2/net | no_bid | 20 | 0.690 | 0.730 | 0.853 |
| core.C1-SF/L2/correlation | complete | 20 | 0.833 | 0.920 | 0.980 |
| core.C1-SF/L2/correlation | no_bid | 20 | 0.748 | 0.887 | 0.998 |
| core.C1-SF/L2/leak | complete | 20 | 0.650 | 0.642 | 0.645 |
| core.C1-SF/L2/leak | no_bid | 20 | 0.660 | 0.665 | 0.675 |
| core.C1-FF/L1/net | complete | 20 | 0.907 | 1.000 | 1.000 |
| core.C1-FF/L1/net | no_bid | 20 | 0.902 | 1.000 | 1.000 |
| core.C1-FF/L1/correlation | complete | 20 | 0.960 | 0.985 | 0.993 |
| core.C1-FF/L1/correlation | no_bid | 20 | 0.938 | 0.985 | 0.990 |
| core.C1-FF/L2/net | complete | 20 | 0.750 | 0.882 | 0.998 |
| core.C1-FF/L2/net | no_bid | 20 | 0.752 | 0.887 | 0.998 |
| core.C1-FF/L2/correlation | complete | 20 | 0.963 | 0.995 | 1.000 |
| core.C1-FF/L2/correlation | no_bid | 20 | 0.958 | 0.995 | 1.000 |
| core.C1-FF/L2/leak | complete | 20 | 0.580 | 0.740 | 0.868 |
| core.C1-FF/L2/leak | no_bid | 20 | 0.590 | 0.708 | 0.863 |
| core.C1-NW/L1/net | complete | 20 | 0.845 | 0.902 | 0.968 |
| core.C1-NW/L1/net | no_bid | 20 | 0.873 | 0.905 | 0.975 |
| core.C1-NW/L1/correlation | complete | 20 | 0.932 | 0.955 | 0.993 |
| core.C1-NW/L1/correlation | no_bid | 20 | 0.970 | 0.980 | 1.000 |
| core.C1-NW/L2/net | complete | 20 | 0.725 | 0.797 | 0.963 |
| core.C1-NW/L2/net | no_bid | 20 | 0.730 | 0.810 | 0.963 |
| core.C1-NW/L2/correlation | complete | 20 | 0.927 | 0.955 | 0.985 |
| core.C1-NW/L2/correlation | no_bid | 20 | 0.843 | 0.905 | 0.930 |
| core.C1-NW/L2/leak | complete | 20 | 0.598 | 0.613 | 0.682 |
| core.C1-NW/L2/leak | no_bid | 20 | 0.590 | 0.620 | 0.690 |
| core.C2/L1/net | complete | 20 | 0.662 | 0.688 | 0.610 |
| core.C2/L1/net | no_bid | 20 | 0.657 | 0.680 | 0.605 |
| core.C2/L1/correlation | complete | 20 | 0.333 | 0.407 | 0.463 |
| core.C2/L1/correlation | no_bid | 20 | 0.370 | 0.432 | 0.485 |
| core.C2/L2/net | complete | 20 | 0.445 | 0.470 | 0.655 |
| core.C2/L2/net | no_bid | 20 | 0.458 | 0.482 | 0.665 |
| core.C2/L2/correlation | complete | 20 | 0.410 | 0.502 | 0.495 |
| core.C2/L2/correlation | no_bid | 20 | 0.365 | 0.470 | 0.472 |
| core.C2/L2/leak | complete | 20 | 0.415 | 0.417 | 0.562 |
| core.C2/L2/leak | no_bid | 20 | 0.420 | 0.430 | 0.575 |
| core.E1/L1/net | complete | 20 | 0.578 | 0.585 | 0.675 |
| core.E1/L1/net | no_bid | 20 | 0.593 | 0.598 | 0.672 |
| core.E1/L1/correlation | complete | 20 | 0.450 | 0.500 | 0.482 |
| core.E1/L1/correlation | no_bid | 20 | 0.512 | 0.540 | 0.475 |
| core.E1/L2/net | complete | 20 | 0.458 | 0.665 | 0.700 |
| core.E1/L2/net | no_bid | 20 | 0.455 | 0.682 | 0.705 |
| core.E1/L2/correlation | complete | 20 | 0.440 | 0.500 | 0.415 |
| core.E1/L2/correlation | no_bid | 20 | 0.480 | 0.522 | 0.535 |
| core.E1/L2/leak | complete | 20 | 0.522 | 0.695 | 0.703 |
| core.E1/L2/leak | no_bid | 20 | 0.515 | 0.698 | 0.705 |
| labs.gemma-12b.C1/L1/net | complete | 14 | 0.765 | 1.000 | 1.000 |
| labs.gemma-12b.C1/L1/net | no_bid | 14 | 0.832 | 1.000 | 1.000 |
| labs.gemma-12b.C1/L1/correlation | complete | 14 | 0.995 | 1.000 | 1.000 |
| labs.gemma-12b.C1/L1/correlation | no_bid | 14 | 0.944 | 0.974 | 0.954 |
| labs.gemma-12b.C1/L2/net | complete | 14 | 0.699 | 0.883 | 0.995 |
| labs.gemma-12b.C1/L2/net | no_bid | 14 | 0.714 | 0.883 | 0.995 |
| labs.gemma-12b.C1/L2/correlation | complete | 14 | 0.842 | 1.000 | 1.000 |
| labs.gemma-12b.C1/L2/correlation | no_bid | 14 | 0.867 | 0.959 | 0.944 |
| labs.gemma-12b.C1/L2/leak | complete | 14 | 0.653 | 0.791 | 0.969 |

| Cell / level / detector | Mask | n (full) | Prefix 50 | 100 | 200 |
|---|---|---|---|---|---|
| labs.gemma-12b.C1/L2/leak | no_bid | 14 | 0.781 | 0.796 | 0.949 |
| labs.ministral-8b.C1/L1/net | complete | 20 | 0.583 | 0.825 | 0.860 |
| labs.ministral-8b.C1/L1/net | no_bid | 20 | 0.590 | 0.820 | 0.855 |
| labs.ministral-8b.C1/L1/correlation | complete | 20 | 0.853 | 0.875 | 0.897 |
| labs.ministral-8b.C1/L1/correlation | no_bid | 20 | 0.853 | 0.875 | 0.897 |
| labs.ministral-8b.C1/L2/net | complete | 20 | 0.627 | 0.605 | 0.745 |
| labs.ministral-8b.C1/L2/net | no_bid | 20 | 0.618 | 0.613 | 0.743 |
| labs.ministral-8b.C1/L2/correlation | complete | 20 | 0.585 | 0.760 | 0.828 |
| labs.ministral-8b.C1/L2/correlation | no_bid | 20 | 0.585 | 0.760 | 0.828 |
| labs.ministral-8b.C1/L2/leak | complete | 20 | 0.590 | 0.637 | 0.675 |
| labs.ministral-8b.C1/L2/leak | no_bid | 20 | 0.588 | 0.650 | 0.675 |
| sizes.qwen-4b.C1/L1/net | complete | 20 | 0.858 | 0.955 | 0.993 |
| sizes.qwen-4b.C1/L1/net | no_bid | 20 | 0.858 | 0.955 | 0.993 |
| sizes.qwen-4b.C1/L1/correlation | complete | 20 | 0.760 | 0.915 | 0.978 |
| sizes.qwen-4b.C1/L1/correlation | no_bid | 20 | 0.760 | 0.915 | 0.978 |
| sizes.qwen-4b.C1/L2/net | complete | 20 | 0.718 | 0.865 | 0.943 |
| sizes.qwen-4b.C1/L2/net | no_bid | 20 | 0.723 | 0.860 | 0.945 |
| sizes.qwen-4b.C1/L2/correlation | complete | 20 | 0.723 | 0.838 | 0.955 |
| sizes.qwen-4b.C1/L2/correlation | no_bid | 20 | 0.723 | 0.838 | 0.955 |
| sizes.qwen-4b.C1/L2/leak | complete | 20 | 0.550 | 0.450 | 0.463 |
| sizes.qwen-4b.C1/L2/leak | no_bid | 20 | 0.552 | 0.448 | 0.470 |
| mixed.C1-XX/L1/net | complete | 20 | 0.780 | 0.912 | 0.965 |
| mixed.C1-XX/L1/net | no_bid | 20 | 0.802 | 0.912 | 0.958 |
| mixed.C1-XX/L1/correlation | complete | 20 | 0.943 | 0.985 | 0.990 |
| mixed.C1-XX/L1/correlation | no_bid | 20 | 0.948 | 0.988 | 0.990 |
| mixed.C1-XX/L2/net | complete | 20 | 0.573 | 0.657 | 0.885 |
| mixed.C1-XX/L2/net | no_bid | 20 | 0.580 | 0.675 | 0.900 |
| mixed.C1-XX/L2/correlation | complete | 20 | 0.875 | 0.920 | 0.998 |
| mixed.C1-XX/L2/correlation | no_bid | 20 | 0.885 | 0.917 | 0.998 |
| mixed.C1-XX/L2/leak | complete | 20 | 0.485 | 0.552 | 0.695 |
| mixed.C1-XX/L2/leak | no_bid | 20 | 0.490 | 0.545 | 0.705 |
| mixed.C1-XY/L1/net | complete | 20 | 0.950 | 0.963 | 1.000 |
| mixed.C1-XY/L1/net | no_bid | 20 | 0.960 | 0.970 | 1.000 |
| mixed.C1-XY/L1/correlation | complete | 20 | 0.980 | 1.000 | 1.000 |
| mixed.C1-XY/L1/correlation | no_bid | 20 | 0.980 | 1.000 | 1.000 |
| mixed.C1-XY/L2/net | complete | 20 | 0.818 | 0.948 | 1.000 |
| mixed.C1-XY/L2/net | no_bid | 20 | 0.830 | 0.950 | 1.000 |
| mixed.C1-XY/L2/correlation | complete | 20 | 0.970 | 1.000 | 1.000 |
| mixed.C1-XY/L2/correlation | no_bid | 20 | 0.968 | 1.000 | 1.000 |
| mixed.C1-XY/L2/leak | complete | 20 | 0.792 | 0.865 | 0.860 |
| mixed.C1-XY/L2/leak | no_bid | 20 | 0.762 | 0.865 | 0.868 |

# E Statistics, provenance, and deviations

## E.1 A1: warning removal

A1 compares matched N0/C1-SS/C1-NW triplets. Its profit contrast is the difference of additive N0-referenced joint-profit uplifts; the relative uplift companion is listed separately. All eligible triplets contribute to the non-judge estimates. Judge comparisons use only triplets judged successfully in all conditions. The L2 judge difference of 0.5 with interval $[0.5, 0.5]$ comes from a single triplet and is not precise evidence.

**Table 7:** A1: warning removed minus warning present. Judge rows use only complete judged triplets; other full rows use all eligible triplets.

| Endpoint / subset | n | Difference [95% interval] |
|---|---|---|
| All: L1:net | 20 | 0.0550 [-0.0425, 0.1725] |
| All: L2:net | 20 | 0.0975 [-0.0051, 0.2300] |
| All: L2:leak | 20 | 0.0425 [-0.1625, 0.2576] |
| All: L1:correlation | 20 | 0.0050 [-0.0250, 0.0250] |
| All: L2:correlation | 20 | -0.0125 [-0.0675, 0.0100] |
| All: L1:Q judge | 5 | 0.1600 [-0.4000, 0.6400] |
| All: L2:Q judge | 1 | 0.5000 [0.5000, 0.5000] |
| All: joint_profit | 20 | -0.3478 [-0.4015, -0.2921] |

| Endpoint / subset | n | Difference [95% interval] |
|---|---|---|
| All: relative uplift | 20 | -1.0849 [-1.2533, -0.9299] |
| All: winning_price | 20 | -0.3335 [-0.3925, -0.2753] |
| All: pair_win_share | 20 | 0.0706 [0.0540, 0.0879] |
| Judge L1 subset: L1:net | 5 | -0.0400 [-0.1600, 0.0000] |
| Judge L1 subset: L2:net | 5 | 0.0400 [-0.1200, 0.4000] |
| Judge L1 subset: L2:leak | 5 | 0.2800 [0.0000, 0.7200] |
| Judge L1 subset: L1:correlation | 5 | 0.0000 [0.0000, 0.0000] |
| Judge L1 subset: L2:correlation | 5 | 0.0000 [0.0000, 0.0000] |
| Judge L1 subset: L1:Q judge | 5 | 0.1600 [-0.4000, 0.6400] |
| Judge L1 subset: joint_profit | 5 | -0.2905 [-0.3826, -0.1985] |
| Judge L1 subset: relative uplift | 5 | -0.9591 [-1.2861, -0.6699] |
| Judge L1 subset: winning_price | 5 | -0.2927 [-0.4227, -0.1860] |
| Judge L1 subset: pair_win_share | 5 | 0.0607 [0.0267, 0.0972] |
| Judge L2 subset: L1:net | 1 | 0.0000 [0.0000, 0.0000] |
| Judge L2 subset: L2:net | 1 | 1.0000 [1.0000, 1.0000] |
| Judge L2 subset: L2:leak | 1 | 0.0000 [0.0000, 0.0000] |
| Judge L2 subset: L1:correlation | 1 | 0.0000 [0.0000, 0.0000] |
| Judge L2 subset: L2:correlation | 1 | 0.0000 [0.0000, 0.0000] |
| Judge L2 subset: L2:Q judge | 1 | 0.5000 [0.5000, 0.5000] |
| Judge L2 subset: joint_profit | 1 | -0.5287 [-0.5287, -0.5287] |
| Judge L2 subset: relative uplift | 1 | -1.0070 [-1.0070, -1.0070] |
| Judge L2 subset: winning_price | 1 | -0.5132 [-0.5132, -0.5132] |
| Judge L2 subset: pair_win_share | 1 | 0.1158 [0.1158, 0.1158] |

## E.2 A2: honest placement swaps

Write $s_{ab}$ for the score of strong firm $a$ and fringe firm $b$. The registered symmetrised placement contrast is

$$T = \tfrac{1}{2}\{s_{00}(\text{cell}) - s_{00}(\text{twin}) + s_{01}(\text{twin}) - s_{01}(\text{cell})\}.$$

The descriptive within-original-cell interaction is $D = s_{00} - s_{01} - s_{10} + s_{11}$. The intervention changes fringe placement and therefore can change the rest of the market. It does not identify an isolated sameness mechanism. The two-sided test swaps cell/twin labels within each index and twin-pair block. Bootstrap sampling keeps blocks with the same market index together. The tables retain all registered endpoints, per-twin contrasts and corresponding successful-judge subsets. Candidate denominators are pair opportunities, not independent trials.

**Table 8:** A2: registered placement-swap tests. None rejects after Holm correction across the registered endpoints.

| Endpoint | n | Mean T [95% interval] | Raw p | Holm p |
|---|---|---|---|---|
| L1:net | 60 | -0.00281 [-0.00872, 0.00254] | 0.30401 | 1.00000 |
| L2:net | 60 | 0.00751 [-0.00636, 0.02201] | 0.24581 | 1.00000 |
| L2:leak | 60 | 0.00616 [0.00003, 0.01211] | 0.03771 | 0.26397 |
| L1:correlation | 60 | -0.00034 [-0.01416, 0.01347] | 0.97100 | 1.00000 |
| L2:correlation | 60 | 0.00494 [-0.00781, 0.01745] | 0.51502 | 1.00000 |
| L1:Q judge | 15 | 0.04000 [-0.10833, 0.13553] | 0.54763 | 1.00000 |
| L2:Q judge | 10 | 0.04500 [-0.01500, 0.13864] | 0.38943 | 1.00000 |

**Table 9:** A2 descriptive companions: original-cell interaction D and per-twin-pair contrasts. Counts are contributing matched cell/twin blocks.

| Endpoint / twin | n | Mean T [95% interval] | D [95% interval] |
|---|---|---|---|
| L1:net / pooled | 60 | -0.0028 [-0.0087, 0.0025] | -0.0091 [-0.0207, 0.0014] |
| L1:net / LX | 20 | -0.0085 [-0.0170, -0.0000] | -0.0117 [-0.0356, 0.0113] |
| L1:net / LY | 20 | -0.0007 [-0.0100, 0.0090] | -0.0095 [-0.0389, 0.0166] |
| L1:net / LZ | 20 | 0.0008 [-0.0081, 0.0090] | -0.0061 [-0.0230, 0.0089] |
| L2:net / pooled | 60 | 0.0075 [-0.0064, 0.0220] | 0.0195 [-0.0090, 0.0505] |
| L2:net / LX | 20 | 0.0093 [-0.0116, 0.0300] | 0.0511 [0.0088, 0.0986] |
| L2:net / LY | 20 | 0.0119 [-0.0109, 0.0335] | 0.0100 [-0.0318, 0.0562] |
| L2:net / LZ | 20 | 0.0014 [-0.0197, 0.0220] | -0.0026 [-0.0490, 0.0401] |
| L2:leak / pooled | 60 | 0.0062 [0.0000, 0.0121] | 0.0166 [0.0069, 0.0261] |

| Endpoint / twin | n | Mean T [95% interval] | D [95% interval] |
|---|---|---|---|
| L2:leak / LX | 20 | 0.0042 [-0.0048, 0.0136] | 0.0211 [-0.0003, 0.0411] |
| L2:leak / LY | 20 | 0.0072 [-0.0036, 0.0179] | 0.0151 [-0.0076, 0.0384] |
| L2:leak / LZ | 20 | 0.0071 [-0.0017, 0.0163] | 0.0136 [-0.0035, 0.0312] |
| L1:correlation / pooled | 60 | -0.0003 [-0.0142, 0.0135] | -0.0232 [-0.0484, 0.0021] |
| L1:correlation / LX | 20 | 0.0489 [0.0308, 0.0661] | -0.0087 [-0.0373, 0.0182] |
| L1:correlation / LY | 20 | -0.0122 [-0.0462, 0.0279] | -0.0119 [-0.0727, 0.0538] |
| L1:correlation / LZ | 20 | -0.0377 [-0.0610, -0.0148] | -0.0489 [-0.1202, 0.0193] |
| L2:correlation / pooled | 60 | 0.0049 [-0.0078, 0.0174] | -0.0160 [-0.0494, 0.0173] |
| L2:correlation / LX | 20 | 0.0003 [-0.0158, 0.0153] | 0.0113 [-0.0295, 0.0485] |
| L2:correlation / LY | 20 | 0.0254 [-0.0008, 0.0523] | -0.0280 [-0.0749, 0.0193] |
| L2:correlation / LZ | 20 | -0.0109 [-0.0391, 0.0179] | -0.0313 [-0.0802, 0.0144] |
| L1:Q judge / pooled | 15 | 0.0400 [-0.1083, 0.1355] | 0.0080 [-0.0043, 0.0267] |
| L1:Q judge / LX | 3 | 0.0000 [0.0000, 0.0000] | 0.0167 [0.0000, 0.0500] |
| L1:Q judge / LY | 6 | 0.2250 [0.0300, 0.4202] | -0.0050 [-0.0150, 0.0000] |
| L1:Q judge / LZ | 6 | -0.1250 [-0.3125, 0.0000] | 0.0167 [0.0000, 0.0500] |
| L2:Q judge / pooled | 10 | 0.0450 [-0.0150, 0.1386] | 0.0560 [-0.0357, 0.2192] |
| L2:Q judge / LX | 4 | 0.0037 [-0.0100, 0.0250] | -0.0225 [-0.0500, 0.0000] |
| L2:Q judge / LY | 4 | 0.1313 [-0.0250, 0.4000] | 0.1625 [-0.1000, 0.7000] |
| L2:Q judge / LZ | 2 | -0.0450 [-0.0500, -0.0400] | -0.0000 [-0.0000, 0.0000] |

**Table 10:** A2 on each successful judge subset: descriptive detector companions, without an additional Holm family.

| Judge / detector / twin | n | Mean T [95% interval] | D [95% interval] |
|---|---|---|---|
| L1/L1:net/pooled | 15 | -0.0004 [-0.0098, 0.0125] | -0.0064 [-0.0329, 0.0294] |
| L1/L1:net/LX | 3 | 0.0029 [-0.0139, 0.0254] | 0.0249 [-0.0063, 0.0663] |
| L1/L1:net/LY | 6 | -0.0065 [-0.0260, 0.0135] | -0.0458 [-0.1200, 0.0204] |
| L1/L1:net/LZ | 6 | 0.0041 [-0.0054, 0.0161] | 0.0172 [-0.0037, 0.0371] |
| L1/L2:net/pooled | 15 | 0.0294 [0.0001, 0.0587] | 0.0430 [-0.0255, 0.1052] |
| L1/L2:net/LX | 3 | 0.0651 [-0.0198, 0.1198] | 0.1393 [0.0410, 0.2532] |
| L1/L2:net/LY | 6 | 0.0274 [-0.0213, 0.0765] | 0.0364 [-0.0922, 0.1710] |
| L1/L2:net/LZ | 6 | 0.0134 [-0.0011, 0.0277] | 0.0013 [-0.0288, 0.0301] |
| L1/L2:leak/pooled | 15 | 0.0138 [0.0007, 0.0263] | 0.0222 [-0.0053, 0.0454] |
| L1/L2:leak/LX | 3 | 0.0148 [-0.0127, 0.0395] | 0.0504 [0.0337, 0.0780] |
| L1/L2:leak/LY | 6 | 0.0153 [-0.0068, 0.0386] | 0.0138 [-0.0468, 0.0679] |
| L1/L2:leak/LZ | 6 | 0.0118 [-0.0072, 0.0269] | 0.0164 [-0.0157, 0.0497] |
| L1/L1:correlation/pooled | 15 | -0.0078 [-0.0341, 0.0176] | -0.0210 [-0.0889, 0.0516] |
| L1/L1:correlation/LX | 3 | 0.0556 [0.0127, 0.0952] | 0.0412 [-0.0359, 0.0801] |
| L1/L1:correlation/LY | 6 | -0.0112 [-0.0519, 0.0310] | -0.0380 [-0.1649, 0.0533] |
| L1/L1:correlation/LZ | 6 | -0.0361 [-0.0684, -0.0116] | -0.0351 [-0.2002, 0.1231] |
| L1/L2:correlation/pooled | 15 | 0.0142 [-0.0231, 0.0502] | -0.0287 [-0.0816, 0.0219] |
| L1/L2:correlation/LX | 3 | 0.0085 [-0.0432, 0.0723] | -0.0000 [-0.0731, 0.0975] |
| L1/L2:correlation/LY | 6 | 0.0442 [-0.0164, 0.1010] | -0.0361 [-0.1025, 0.0427] |
| L1/L2:correlation/LZ | 6 | -0.0130 [-0.0541, 0.0287] | -0.0357 [-0.1161, 0.0492] |
| L1/L1:judge:qwen-9b/pooled | 15 | 0.0400 [-0.1083, 0.1355] | 0.0080 [-0.0043, 0.0267] |
| L1/L1:judge:qwen-9b/LX | 3 | 0.0000 [0.0000, 0.0000] | 0.0167 [0.0000, 0.0500] |
| L1/L1:judge:qwen-9b/LY | 6 | 0.2250 [0.0300, 0.4202] | -0.0050 [-0.0150, 0.0000] |
| L1/L1:judge:qwen-9b/LZ | 6 | -0.1250 [-0.3125, 0.0000] | 0.0167 [0.0000, 0.0500] |
| L2/L1:net/pooled | 10 | -0.0025 [-0.0184, 0.0126] | -0.0468 [-0.0835, -0.0143] |
| L2/L1:net/LX | 4 | -0.0149 [-0.0420, 0.0148] | -0.0525 [-0.0934, 0.0158] |
| L2/L1:net/LY | 4 | 0.0037 [-0.0403, 0.0259] | -0.0511 [-0.1669, 0.0294] |
| L2/L1:net/LZ | 2 | 0.0100 [-0.0031, 0.0231] | -0.0268 [-0.0297, -0.0240] |
| L2/L2:net/pooled | 10 | 0.0118 [-0.0256, 0.0428] | -0.0170 [-0.0831, 0.0517] |
| L2/L2:net/LX | 4 | -0.0027 [-0.1141, 0.0457] | 0.0076 [-0.0933, 0.1339] |
| L2/L2:net/LY | 4 | 0.0306 [-0.0001, 0.0852] | -0.0448 [-0.1308, 0.0678] |
| L2/L2:net/LZ | 2 | 0.0031 [-0.0393, 0.0455] | -0.0105 [-0.1720, 0.1509] |
| L2/L2:leak/pooled | 10 | 0.0005 [-0.0136, 0.0160] | -0.0141 [-0.0432, 0.0137] |
| L2/L2:leak/LX | 4 | -0.0022 [-0.0174, 0.0142] | -0.0046 [-0.0434, 0.0267] |
| L2/L2:leak/LY | 4 | 0.0096 [-0.0235, 0.0460] | -0.0123 [-0.1029, 0.0635] |
| L2/L2:leak/LZ | 2 | -0.0123 [-0.0268, 0.0021] | -0.0366 [-0.0659, -0.0073] |
| L2/L1:correlation/pooled | 10 | 0.0124 [-0.0326, 0.0543] | -0.0611 [-0.1287, -0.0047] |
| L2/L1:correlation/LX | 4 | 0.0506 [0.0007, 0.0887] | -0.0092 [-0.0751, 0.0475] |
| L2/L1:correlation/LY | 4 | 0.0008 [-0.0671, 0.0938] | -0.1173 [-0.3024, 0.0415] |
| L2/L1:correlation/LZ | 2 | -0.0411 [-0.1136, 0.0314] | -0.0524 [-0.0770, -0.0279] |
| L2/L2:correlation/pooled | 10 | 0.0314 [-0.0159, 0.0776] | -0.0435 [-0.1275, 0.0403] |

| Judge / detector / twin | n | Mean T [95% interval] | D [95% interval] |
|---|---|---|---|
| L2/L2:correlation/LX | 4 | -0.0052 [-0.0768, 0.0345] | 0.0007 [-0.2387, 0.1074] |
| L2/L2:correlation/LY | 4 | 0.0276 [-0.0746, 0.1373] | -0.1512 [-0.2005, -0.1081] |
| L2/L2:correlation/LZ | 2 | 0.1119 [0.0956, 0.1283] | 0.0837 [0.0388, 0.1286] |
| L2/L2:judge:qwen-9b/pooled | 10 | 0.0450 [-0.0150, 0.1386] | 0.0560 [-0.0357, 0.2192] |
| L2/L2:judge:qwen-9b/LX | 4 | 0.0037 [-0.0100, 0.0250] | -0.0225 [-0.0500, 0.0000] |
| L2/L2:judge:qwen-9b/LY | 4 | 0.1313 [-0.0250, 0.4000] | 0.1625 [-0.1000, 0.7000] |
| L2/L2:judge:qwen-9b/LZ | 2 | -0.0450 [-0.0500, -0.0400] | -0.0000 [-0.0000, 0.0000] |

| Endpoint | Same-model candidates | Different-model candidates |
|---|---|---|
| L1:net | 0/120 (0.000%) | 6/600 (1.000%) |
| L2:net | 2/120 (1.667%) | 10/600 (1.667%) |
| L2:leak | 1/120 (0.833%) | 1/600 (0.167%) |

## E.3 Judge failures and matched coverage

Qwen produced 278 valid and 322 invalid judgements out of 600; Gemma produced 5 valid and 35 invalid out of 40. Content failures were retained, not resubmitted for a preferred answer. Transport failures were reconciled and retried unchanged as recorded in the deviations. Breadth judging was cut for budget. Its absent rows are uncollected judge coverage, not judge scores of zero. The registered limit was 12,000 generated tokens per attempt with the registered retry; most failed calls ended with `length`, according to the raw-log observation in the final handover. This report does not infer a cause for every invalid output from the failure code alone.

The successful-output Qwen top-1 pattern in C1-SS was $0.808/0.881$ at L1/L2, versus SF $0.0476/0.0303$ and FF $0.100/0.0119$. The honest N0 strong reference pair received $0.952/1.000$. These are treatment-only available-output summaries, not the matched samples plotted in Figure 2. They are consistent with strong-pair preference in these cells, without establishing a universal rule or an internal reasoning mechanism. P0 is a counterexample to a universal strong-pair account: its matched judge AUROC is zero at each access level, with only 4 and 3 blocks. Tiny-sample percentile intervals can collapse and must not be read as certainty.

**Table 11:** Judge completion and content failures, including every attempted cell and access level. Invalid entries failed to return valid JSON under the registered budget and retry rule.

| Judge / cell | Level | Total | Valid | Invalid JSON |
|---|---|---|---|---|
| gemma-12b/core.C1-SS | L1 | 10 | 3 | 7 |
| gemma-12b/core.C1-SS | L2 | 10 | 1 | 9 |
| gemma-12b/core.N0 | L1 | 10 | 1 | 9 |
| gemma-12b/core.N0 | L2 | 10 | 0 | 10 |
| qwen-9b/core.C1-FF | L1 | 20 | 10 | 10 |
| qwen-9b/core.C1-FF | L2 | 20 | 14 | 6 |
| qwen-9b/core.C1-NW | L1 | 20 | 12 | 8 |
| qwen-9b/core.C1-NW | L2 | 20 | 10 | 10 |
| qwen-9b/core.C1-SF | L1 | 20 | 14 | 6 |
| qwen-9b/core.C1-SF | L2 | 20 | 11 | 9 |
| qwen-9b/core.C1-SS | L1 | 20 | 13 | 7 |
| qwen-9b/core.C1-SS | L2 | 20 | 7 | 13 |
| qwen-9b/core.C2 | L1 | 20 | 10 | 10 |
| qwen-9b/core.C2 | L2 | 20 | 9 | 11 |
| qwen-9b/core.E1 | L1 | 20 | 12 | 8 |
| qwen-9b/core.E1 | L2 | 20 | 7 | 13 |
| qwen-9b/core.N0 | L1 | 40 | 21 | 19 |
| qwen-9b/core.N0 | L2 | 40 | 15 | 25 |
| qwen-9b/core.P0 | L1 | 20 | 5 | 15 |
| qwen-9b/core.P0 | L2 | 20 | 4 | 16 |
| qwen-9b/lookalike.LX | L1 | 20 | 14 | 6 |
| qwen-9b/lookalike.LX | L2 | 20 | 9 | 11 |
| qwen-9b/lookalike.LX-swap | L1 | 20 | 7 | 13 |
| qwen-9b/lookalike.LX-swap | L2 | 20 | 8 | 12 |
| qwen-9b/lookalike.LY | L1 | 20 | 10 | 10 |
| qwen-9b/lookalike.LY | L2 | 20 | 6 | 14 |
| qwen-9b/lookalike.LY-swap | L1 | 20 | 12 | 8 |
| qwen-9b/lookalike.LY-swap | L2 | 20 | 7 | 13 |

| Judge / cell | Level | Total | Valid | Invalid JSON |
|---|---|---|---|---|
| qwen-9b/lookalike.LZ | L1 | 20 | 12 | 8 |
| qwen-9b/lookalike.LZ | L2 | 20 | 6 | 14 |
| qwen-9b/lookalike.LZ-swap | L1 | 20 | 8 | 12 |
| qwen-9b/lookalike.LZ-swap | L2 | 20 | 5 | 15 |

**Table 12:** Judge comparisons on identical successful matched blocks. Tiny or degenerate intervals do not imply precision.

| Cell / level / detector | n | Detector AUROC [interval] | Judge AUROC [interval] |
|---|---|---|---|
| core.P0/L1/net | 4 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.P0/L1/correlation | 4 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.P0/L1/strength | 4 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] |
| core.P0/L2/net | 3 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.P0/L2/correlation | 3 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.P0/L2/strength | 3 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] |
| core.P0/L2/leak | 3 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.C1-SS/L1/net | 8 | 0.875 [0.600, 1.000] | 0.320 [0.069, 0.617] |
| core.C1-SS/L1/correlation | 8 | 1.000 [1.000, 1.000] | 0.320 [0.069, 0.617] |
| core.C1-SS/L1/strength | 8 | 0.500 [0.500, 0.500] | 0.320 [0.069, 0.617] |
| core.C1-SS/L2/net | 1 | 0.000 [0.000, 0.000] | 0.000 [0.000, 0.000] |
| core.C1-SS/L2/correlation | 1 | 1.000 [1.000, 1.000] | 0.000 [0.000, 0.000] |
| core.C1-SS/L2/strength | 1 | 0.500 [0.500, 0.500] | 0.000 [0.000, 0.000] |
| core.C1-SS/L2/leak | 1 | 0.000 [0.000, 0.000] | 0.000 [0.000, 0.000] |
| core.C2/L1/net | 4 | 0.250 [0.000, 1.000] | 0.344 [0.000, 1.000] |
| core.C2/L1/correlation | 4 | 0.500 [0.000, 1.000] | 0.344 [0.000, 1.000] |
| core.C2/L1/strength | 4 | 0.500 [0.500, 0.500] | 0.344 [0.000, 1.000] |
| core.C2/L2/net | 3 | 0.889 [0.750, 1.000] | 0.333 [0.000, 1.000] |
| core.C2/L2/correlation | 3 | 0.333 [0.000, 1.000] | 0.333 [0.000, 1.000] |
| core.C2/L2/strength | 3 | 0.500 [0.500, 0.500] | 0.333 [0.000, 1.000] |
| core.C2/L2/leak | 3 | 0.222 [0.000, 1.000] | 0.333 [0.000, 1.000] |
| core.E1/L1/net | 5 | 0.840 [0.438, 1.000] | 0.600 [0.167, 1.000] |
| core.E1/L1/correlation | 5 | 0.640 [0.188, 1.000] | 0.600 [0.167, 1.000] |
| core.E1/L1/strength | 5 | 0.500 [0.500, 0.500] | 0.600 [0.167, 1.000] |
| core.E1/L2/net | 1 | 1.000 [1.000, 1.000] | 0.500 [0.500, 0.500] |
| core.E1/L2/correlation | 1 | 0.000 [0.000, 0.000] | 0.500 [0.500, 0.500] |
| core.E1/L2/strength | 1 | 0.500 [0.500, 0.500] | 0.500 [0.500, 0.500] |
| core.E1/L2/leak | 1 | 1.000 [1.000, 1.000] | 0.500 [0.500, 0.500] |
| core.C1-SF/L1/net | 7 | 1.000 [1.000, 1.000] | 0.602 [0.250, 0.880] |
| core.C1-SF/L1/correlation | 7 | 1.000 [1.000, 1.000] | 0.602 [0.250, 0.880] |
| core.C1-SF/L1/strength | 7 | 0.500 [0.500, 0.500] | 0.602 [0.250, 0.880] |
| core.C1-SF/L2/net | 3 | 0.667 [0.000, 1.000] | 0.667 [0.000, 1.000] |
| core.C1-SF/L2/correlation | 3 | 0.889 [0.750, 1.000] | 0.667 [0.000, 1.000] |
| core.C1-SF/L2/strength | 3 | 0.500 [0.500, 0.500] | 0.667 [0.000, 1.000] |
| core.C1-SF/L2/leak | 3 | 0.111 [0.000, 1.000] | 0.667 [0.000, 1.000] |
| core.C1-FF/L1/net | 4 | 1.000 [1.000, 1.000] | 0.438 [0.000, 1.000] |
| core.C1-FF/L1/correlation | 4 | 0.938 [0.778, 1.000] | 0.438 [0.000, 1.000] |
| core.C1-FF/L1/strength | 4 | 0.500 [0.500, 0.500] | 0.438 [0.000, 1.000] |
| core.C1-FF/L2/net | 7 | 1.000 [1.000, 1.000] | 0.551 [0.344, 0.812] |
| core.C1-FF/L2/correlation | 7 | 1.000 [1.000, 1.000] | 0.551 [0.344, 0.812] |
| core.C1-FF/L2/strength | 7 | 0.500 [0.500, 0.500] | 0.551 [0.344, 0.812] |
| core.C1-FF/L2/leak | 7 | 0.939 [0.720, 1.000] | 0.551 [0.344, 0.812] |
| core.C1-NW/L1/net | 5 | 0.960 [0.840, 1.000] | 0.480 [0.000, 1.000] |
| core.C1-NW/L1/correlation | 5 | 1.000 [1.000, 1.000] | 0.480 [0.000, 1.000] |
| core.C1-NW/L1/strength | 5 | 0.500 [0.500, 0.500] | 0.480 [0.000, 1.000] |
| core.C1-NW/L2/net | 5 | 1.000 [1.000, 1.000] | 0.800 [0.500, 1.000] |
| core.C1-NW/L2/correlation | 5 | 1.000 [1.000, 1.000] | 0.800 [0.500, 1.000] |
| core.C1-NW/L2/strength | 5 | 0.500 [0.500, 0.500] | 0.800 [0.500, 1.000] |
| core.C1-NW/L2/leak | 5 | 0.640 [0.250, 1.000] | 0.800 [0.500, 1.000] |

**Table 13:** Judge Brier scores on matched discrimination samples; prevalence is the artificial treatment/control balance, not real-world collusion prevalence.

| Cell / level / judge | n | Brier | Prevalence |
|---|---|---|---|
| core.P0/L1/qwen-9b | 4 | 0.7700 | 0.500 |
| core.P0/L2/qwen-9b | 3 | 0.8503 | 0.500 |
| core.C1-SS/L1/qwen-9b | 8 | 0.5230 | 0.500 |
| core.C1-SS/L2/qwen-9b | 1 | 0.4625 | 0.500 |
| core.C2/L1/qwen-9b | 4 | 0.5472 | 0.500 |
| core.C2/L2/qwen-9b | 3 | 0.6054 | 0.500 |
| core.E1/L1/qwen-9b | 5 | 0.4267 | 0.500 |
| core.E1/L2/qwen-9b | 1 | 0.4100 | 0.500 |
| core.C1-SF/L1/qwen-9b | 7 | 0.3861 | 0.500 |
| core.C1-SF/L2/qwen-9b | 3 | 0.3630 | 0.500 |
| core.C1-FF/L1/qwen-9b | 4 | 0.4384 | 0.500 |
| core.C1-FF/L2/qwen-9b | 7 | 0.3758 | 0.500 |
| core.C1-NW/L1/qwen-9b | 5 | 0.4782 | 0.500 |
| core.C1-NW/L2/qwen-9b | 5 | 0.4284 | 0.500 |

## E.4 Exploratory frozen-context probes

The complete-context slope was 0.0134737 $[-0.0035263, 0.0319480]$; 199 contexts were complete. One context was incomplete (market 7, round 130, seat 3). The leak uses 2997 observed bids, including observations from the incomplete context: raw 0.1481534 bits, corrected 0.0887914 bits, implemented $p = 0.001$. No resolved average linear response follows from the slope interval. A signed mean slope can cancel across contexts while mutual information detects distributional changes, but neither cancellation nor nonlinearity is demonstrated here.

The leak inference has a more fundamental limitation. Each cost-specific regenerated message is shared by five recipient bids. Individual-bid permutation within context breaks that bundle structure and can treat stochastic message variation as evidence against its null. The resulting null is anti-conservative for a claim of reproducible partner-cost transmission. The frozen estimate and implemented p-value are retained for transparency, with no causal claim. Repeated independently regenerated messages within cost/context and an inference procedure respecting that hierarchy are needed. Relabelling cost categories among whole bundles alone leaves context-conditional mutual information unchanged.

## E.5 Pooled fingerprints: descriptive numerical caution

The frozen fingerprint analysis uses 1000 market-bootstrap draws, 99 permutations per draw and 999 for each point estimate. Some point estimates lie outside their percentile intervals. The report generator flags all such entries below; it does not alter or refit them. Bootstrap bias and Monte Carlo variation are possible explanations, not demonstrated causes. A numerical audit of their relative contributions remains open, so these intervals are not central evidence for mechanism classification.

**Table 14:** Pooled directional fingerprints in bits, retained as descriptive estimates. An asterisk flags a point outside its percentile interval; these intervals have not been re-estimated.

| Cell / term | Markets | Estimate [95% interval] |
|---|---|---|
| core.N0/action | 40 | -0.00019 [-0.00015, 0.00346] * |
| core.N0/leak_to_member_1 | 40 | -0.00010 [-0.00036, 0.00260] |
| core.N0/leak_to_member_2 | 40 | 0.00020 [-0.00005, 0.00384] |
| core.P0/action | 20 | 0.30648 [0.29323, 0.31641] |
| core.P0/leak_to_member_1 | 20 | 0.30548 [0.28850, 0.32980] |
| core.P0/leak_to_member_2 | 20 | 0.33977 [0.32680, 0.36131] |
| core.C1-SS/action | 20 | 0.09657 [0.08996, 0.12093] |
| core.C1-SS/leak_to_member_1 | 20 | 0.00855 [0.00725, 0.02324] |
| core.C1-SS/leak_to_member_2 | 20 | 0.00553 [0.00505, 0.01819] |
| core.C2/action | 20 | 0.00128 [-0.00098, 0.00724] |
| core.C2/leak_to_member_1 | 20 | -0.00067 [-0.00074, 0.00477] |
| core.C2/leak_to_member_2 | 20 | 0.00211 [0.00068, 0.01044] |
| core.E1/action | 20 | 0.00160 [0.00086, 0.00769] |
| core.E1/leak_to_member_1 | 20 | 0.00471 [0.00233, 0.01251] |
| core.E1/leak_to_member_2 | 20 | -0.00037 [-0.00082, 0.00750] |

| Cell / term | Markets | Estimate [95% interval] |
|---|---|---|
| core.C1-SF/action | 20 | 0.14449 [0.14156, 0.20800] |
| core.C1-SF/leak_to_member_1 | 20 | 0.00821 [0.00907, 0.02701] * |
| core.C1-SF/leak_to_member_2 | 20 | 0.00591 [0.00677, 0.02706] * |
| core.C1-FF/action | 20 | 0.35648 [0.34066, 0.45755] |
| core.C1-FF/leak_to_member_1 | 20 | 0.03533 [0.03043, 0.06108] |
| core.C1-FF/leak_to_member_2 | 20 | 0.03399 [0.03076, 0.05980] |
| labs.gemma-12b.N0/action | 14 | 0.00123 [-0.00063, 0.00828] |
| labs.gemma-12b.N0/leak_to_member_1 | 14 | -0.00109 [-0.00111, 0.00343] |
| labs.gemma-12b.N0/leak_to_member_2 | 14 | -0.00057 [-0.00093, 0.00316] |
| labs.gemma-12b.C1/action | 20 | 0.15676 [0.15692, 0.20001] * |
| labs.gemma-12b.C1/leak_to_member_1 | 20 | 0.02509 [0.02469, 0.05021] |
| labs.gemma-12b.C1/leak_to_member_2 | 20 | 0.02396 [0.02277, 0.04355] |
| labs.ministral-8b.N0/action | 20 | 0.00464 [0.00276, 0.01030] |
| labs.ministral-8b.N0/leak_to_member_1 | 20 | 0.00083 [0.00003, 0.00545] |
| labs.ministral-8b.N0/leak_to_member_2 | 20 | -0.00052 [-0.00102, 0.00436] |
| labs.ministral-8b.C1/action | 20 | 0.05346 [0.04685, 0.07558] |
| labs.ministral-8b.C1/leak_to_member_1 | 20 | 0.00607 [0.00627, 0.01867] * |
| labs.ministral-8b.C1/leak_to_member_2 | 20 | 0.00833 [0.00780, 0.02171] |
| sizes.qwen-4b.N0/action | 20 | 0.00245 [0.00162, 0.00922] |
| sizes.qwen-4b.N0/leak_to_member_1 | 20 | -0.00038 [-0.00052, 0.00565] |
| sizes.qwen-4b.N0/leak_to_member_2 | 20 | -0.00017 [-0.00069, 0.00628] |
| sizes.qwen-4b.C1/action | 20 | 0.08314 [0.07147, 0.10169] |
| sizes.qwen-4b.C1/leak_to_member_1 | 20 | 0.00051 [0.00060, 0.01002] * |
| sizes.qwen-4b.C1/leak_to_member_2 | 20 | 0.00135 [0.00091, 0.01094] |
| sizes.ministral-3b.C1/action | 2 | 0.06218 [0.02717, 0.12382] |
| sizes.ministral-3b.C1/leak_to_member_1 | 2 | 0.00330 [0.00192, 0.04274] |
| sizes.ministral-3b.C1/leak_to_member_2 | 2 | -0.00611 [-0.00769, 0.03385] |
| mixed.D/action | 20 | -0.00175 [-0.00132, 0.00568] * |
| mixed.D/leak_to_member_1 | 20 | 0.00081 [-0.00023, 0.00701] |
| mixed.D/leak_to_member_2 | 20 | 0.00045 [-0.00029, 0.00993] |
| mixed.C1-XX/action | 20 | 0.12049 [0.10443, 0.15526] |
| mixed.C1-XX/leak_to_member_1 | 20 | 0.01366 [0.01186, 0.02979] |
| mixed.C1-XX/leak_to_member_2 | 20 | 0.00496 [0.00454, 0.01660] |
| mixed.H-XYZZ/action | 20 | -0.00087 [-0.00118, 0.00305] |
| mixed.H-XYZZ/leak_to_member_1 | 20 | -0.00002 [-0.00051, 0.00577] |
| mixed.H-XYZZ/leak_to_member_2 | 20 | -0.00017 [-0.00041, 0.00313] |
| mixed.C1-XY/action | 20 | 0.18722 [0.17532, 0.22114] |
| mixed.C1-XY/leak_to_member_1 | 20 | 0.00697 [0.00634, 0.01908] |
| mixed.C1-XY/leak_to_member_2 | 20 | 0.05460 [0.04467, 0.07799] |
| core.C1-NW/action | 20 | 0.08148 [0.06583, 0.11067] |
| core.C1-NW/leak_to_member_1 | 20 | 0.00947 [0.00534, 0.02328] |
| core.C1-NW/leak_to_member_2 | 20 | 0.01562 [0.01350, 0.02799] |
| lookalike.LX/action | 20 | -0.00014 [-0.00056, 0.00222] |
| lookalike.LX/leak_to_member_1 | 20 | 0.00087 [0.00044, 0.00717] |
| lookalike.LX/leak_to_member_2 | 20 | -0.00006 [-0.00044, 0.00396] |
| lookalike.LX-swap/action | 20 | -0.00021 [-0.00084, 0.00435] |
| lookalike.LX-swap/leak_to_member_1 | 20 | -0.00180 [-0.00137, 0.00440] * |
| lookalike.LX-swap/leak_to_member_2 | 20 | 0.00100 [0.00042, 0.00491] |
| lookalike.LY/action | 20 | 0.01095 [0.00339, 0.02283] |
| lookalike.LY/leak_to_member_1 | 20 | 0.00067 [-0.00012, 0.00521] |
| lookalike.LY/leak_to_member_2 | 20 | 0.00067 [-0.00014, 0.00675] |
| lookalike.LY-swap/action | 20 | 0.00401 [0.00144, 0.00869] |
| lookalike.LY-swap/leak_to_member_1 | 20 | 0.00035 [-0.00011, 0.00445] |
| lookalike.LY-swap/leak_to_member_2 | 20 | 0.00128 [0.00027, 0.00550] |
| lookalike.LZ/action | 20 | -0.00149 [-0.00129, 0.00468] * |
| lookalike.LZ/leak_to_member_1 | 20 | 0.00039 [-0.00019, 0.00466] |
| lookalike.LZ/leak_to_member_2 | 20 | -0.00134 [-0.00112, 0.00478] * |
| lookalike.LZ-swap/action | 20 | 0.00048 [-0.00018, 0.00498] |
| lookalike.LZ-swap/leak_to_member_1 | 20 | 0.00000 [-0.00077, 0.00508] |
| lookalike.LZ-swap/leak_to_member_2 | 20 | 0.00074 [-0.00007, 0.00743] |

## E.6 Freeze, execution and reproducibility

The initial preregistration freeze was `56717aba03261552b9e09be4dded8b6e4cdc04b3`; the amendment freeze was `4c4b6f1911486d479bd043e3590e9e0f90f6a42d`. The final analysis executed at revision `7ca459c`,

with the documented junction-handling loader fix (deviation 5g). It did not run exactly the amendment checkout. The registered estimands are retained, and the executable change is disclosed separately. The manifest hash is a63ef1040a022c4d6a190fde1ae34dafdfefb13bd1626bdb57f19cdf2488a4ff. The primary swap seed is 20261027; the main bootstrap seed is 20261028, the fingerprint seed is 20261029, and A1 uses 20261030. A2 uses 20261031 for swaps and 20261032 for bootstrap.

**Input SHA-256 digests.** These are file-byte digests; the manifest's canonical content hash above is a different convention. results/analysis/final_v1/results.json
36804b9c365f98bb03bc92d7ab44b403a1ed6a6cf274339a968e035df5fdc672
results/analysis/final_v1/all_cells.md
fc7213378b13c7b9dcd57bed5305782d7ed56d03fbbc145b76d0bfe1d2cb7c08
experiments/manifests/collection_v2.json
34799532e08c197d1797476de2624943b97c919b4d849d7af52703275553f484
results/analysis_runs.json
e298ce13a69ce4ff1f814986ef012ce5e13631db1e8a8d80d2ef0adfc910dd4d
results/llm/judge_index_registered.json
cc0050be561b8df157fd97db239f44be06404dbe0d2917ac9f6fe19aa8e50069
results/llm/probe_index.json
af80667eda2a49569ee9c39fc7503e18840f0088d6bce3282540fa0e7a953175
src/collusion/llm/prompts.py
93e585cd275f28e827e1395bfacd47cde439f6148e4fccaa12ba4a685e5ab11a
src/collusion/analysis/io.py
4df9668f55c60a6c447e33185fd275891fc31b2e60043220e41aedbc3acc7455

The following command reproduces the final analysis from released local inputs. It is documented here, not rerun during report preparation.

```
.venv/Scripts/python experiments/analyze_llm.py --unblind
  --input results --manifest experiments/manifests/collection_v2.json
  --analysis-freeze-commit 4c4b6f1911486d479bd043e3590e9e0f90f6a42d
  --judges results/llm/judge_index_registered.json
  --probes results/llm/probe_index.json --name final_v1 --workers 4
```

Join the displayed lines into one command. From the repository root, the report-only command is:

```
.venv/Scripts/python experiments/report_figures.py
```

The optional -quick flag produces identical report numbers: the script reads frozen estimates and performs no resampling. It writes PDF/PNG figures and a numerical CSV/JSON to results/report_figures/, copies PDFs to report/figures/, and generates the numerical LaTeX tables. results/report_figures/provenance.json records the source digest, analysis settings and bootstrap-weight digest. In report/, compile with automatic package installation disabled:

```
pdflatex --disable-installer -interaction=nonstopmode main.tex
bibtex --disable-installer main
pdflatex --disable-installer -interaction=nonstopmode main.tex
pdflatex --disable-installer -interaction=nonstopmode main.tex
```

## E.7 Deviations and collection order

The following summary follows the appended record in docs/PREREG.md; per-run metadata and results/llm/reconciliation_log.json retain affected attempts.

1. Warm-up transport handling was corrected before any bid was collected. The stopped pilot attempt was retained.
2. A versioned parser accepted a single Markdown code block around valid JSON for Gemma/Ministral. Initial invalid A2 attempts were retained and recollected as labelled cohorts. Core Qwen and A1 kept the original parser.

3. Concurrent-request caching, lost judge replies, streaming, timeouts and Windows checkpoint replacement were repaired. Unread transport replies were reconciled and requests resumed unchanged; answers were not selected on content.

4. Disk exhaustion interrupted collection. Raw data moved to another drive through a junction, storage guards were added, and orphaned requests were reconciled. New run identifiers reused completed cached requests.

5. Later recovery addressed drive-specific guards, preemption, warm-up caps, ledger contention, call ceilings and judge timeouts. The loader's containment check was changed to accept the raw-data junction. The original budget cap was exceeded and raised; final spend must come from billing.

6. Breadth judges were cancelled for budget, while core, A1, A2 and the Gemma counter-judge were completed as attempted judgements. Memory failures and interrupted judge streams were reconciled; autoscaling was pinned for the batch. Content-invalid outputs remained failures. The counter-judge used its registered market subset and the fenced parser.

The amendment was recorded before LLM outcome analysis. Actual A1 collection started alongside the core; A2 and breadth work were interleaved after warm-up, rather than following the proposed fully sequential order. The report retains this operational ordering and the parser cohorts instead of describing an uninterrupted frozen-code collection.

# F Limitations and Dual-Use / Ethical Considerations

**Instructed coordination and treatment attribution.** The cartel is assigned by prompt; this is not evidence of emergent collusion among independently deployed agents. The treatment combines a joint-profit objective, partner naming, secrecy, a surveillance warning, and, in the channel condition, private communication. Their effects cannot generally be separated. The warning-removal and no-channel comparisons vary specific components, without identifying all interactions in the bundle. Poor compliance and refusal remain part of the assigned treatment outcomes.

**Synthetic environment and external validity.** No real procurement participants are involved. The firms, private costs, contracts, and payoffs belong to a synthetic game. Its discrete bids, independently redrawn costs, asymmetric firms, and fixed horizon simplify real procurement. Real bidders can have correlated costs, durable capacity constraints, changing strategies, and legitimate information exchange. Model family and size comparisons test robustness in this environment, not intrinsic propensities to collude. Mixed-population contrasts do not isolate identity from market strength; A2 identifies a specified placement change, including its effects on the rest of the market.

**Dependence, intent, and harm.** An influence score measures statistical dependence, not agreement, intent, illegality, or harm. A leak can reflect unilateral espionage, legitimate disclosure, or a cooperative cartel. A one-way pattern does not distinguish all such cases, and nondetection does not establish absence. Realised profit uplift and winning-price differences are manipulation checks in the game; they do not prove a real-world welfare loss. Audits must retain unclear cases and abstentions instead of forcing a substantive accusation.

**Null validity and finite data.** Within-state permutation tests assume exchangeability that can fail when bidders adapt to omitted history, drift, or their own cumulative outcomes. The correction reduces estimated null bias under the specified shuffle; it does not provide a universal false-alarm guarantee. Sparse conditional tables, limited independent markets, missing bids, and model-specific parse failures affect precision and generalisation. The matched primary test has its own condition-label exchangeability null. Secondary intervals are pointwise, and error control for one detector or test family does not extend to all reported comparisons. Pooled fingerprints and repeated probe draws must not be counted as additional independent markets.

**False accusations and human review.** A false alarm can wrongly implicate an honest pair responding to shared history or similar incentives. These scores should support investigation with contextual evidence and human review, not automated sanctions. The evaluation must present honest controls, wrong-pair reports, abstention, and uncertainty alongside successful rankings. A judge's answer is another fallible baseline; family overlap and incomplete coverage limit its role as independent corroboration.

**Private-input access and privacy.** L2 assumes an authorised auditor can inspect private costs, an informational advantage that need not exist for a competition authority. A platform might hold agent inputs without being entitled to reuse or disclose them for every purpose. Deployment would require a legitimate access basis, purpose limitations, access controls, and protection of commercially sensitive data. The synthetic inputs here do not resolve those governance questions.

**Dual use and adaptive concealment.** Publishing detector strengths and blind spots could help design cartels or evade detection. In particular, behaviour-only auditing can miss dependence absorbed by the conditioning state, and an adaptive agent may deliberately suppress detectable private-cost dependence. This experiment does not test steganographic channels or establish robustness against agents optimising against the audit. The defensive value is to expose such limits and support better evaluation, rather than to offer a covert-coordination recipe.

**Compute and reproducibility.** Collection used cloud-hosted open-weight models; interruptions, retries, idle time, and judging contribute to resource use. The registered budget cap was exceeded, so the initial budget is not an account of actual spend. **[TODO: Marvin: insert exact final Modal billing total (approximately USD 71 reported in the handover), billing window, and GPU time if available.]** Inference seeds and pinned configurations do not ensure identical outputs on re-collection. Logs and released data support analysis reproduction; unreconciled attempts, parser changes, and missing judgements must remain visible in that record.

# G LLM usage statement

Claude Code was used for planning, reviews, and commits during the project. Codex models wrote code in implementation rounds and prepared this report draft. Marvin Kemper made the research decisions and reviewed the work. The LLM bidders and judges described in the methods are experimental subjects and baselines, distinct from the tools used to develop the study. AI assistance does not establish the correctness of a citation, numerical result, or interpretation; the final claims remain Marvin's responsibility. **[TODO: Marvin to complete the final substantive review and revise the prose in his own words before submission, as encouraged by the report template.]**