```
STEP 1:
CREATE TABLE employee (
        varchar(15) not null,
  fname
          varchar(1),
  minit
        varchar(15) not null,
  lname
  ssn
          char(9),
  bdate
          date,
  address varchar(50),
  sex
           char,
  salary decimal(10,2),
  Super_ssn char(9),
  dno
          char(4),
  primary key (ssn));
CREATE TABLE department (
               varchar(25) not null,
  dname
  dnumber
               char(4),
  Mgr ssn
               char(9) not null,
  Mgr start date date,
  primary key (dnumber));
CREATE TABLE dept locations (
  dnumber char(4),
  dlocation varchar(15),
  primary key (dnumber,dlocation));
CREATE TABLE project (
            varchar(25) not null,
  pname
  pnumber
             char(4),
  plocation varchar(15),
             char(4) not null,
  dnum
  primary key (pnumber),
  unique (pname));
CREATE TABLE works on (
  essn char(9),
         char(4),
  pno
  hours decimal(4,1),
  primary key (essn,pno));
CREATE TABLE dependent (
  essn
                 char(9),
  dependent name varchar(15),
  sex
                 char,
  bdate
                 date,
  relationship varchar(8),
  primary key (essn,dependent name));
STEP #2:
INSERT INTO employee VALUES
  ('John','B','Smith','123456789',TO_DATE('09-JAN-1965','DD-MON-YYYY'),'731 Fondren, Houston,
TX','M',30000,333445555,5);
INSERT INTO employee VALUES
('Franklin','T','Wong','333445555',TO_DATE('08-DEC-1955','DD-MON-YYYY'),'638 Voss, Houston, TX','M',40000,'888665555',5);
INSERT INTO employee VALUES
  ('Alicia','J','Zelaya','999887777',TO DATE('19-JUL-1968','DD-MON-YYYY'),'3321 Castle, Spring,
TX', 'F', 25000, '987654321', 4);
INSERT INTO employee VALUES
  ('Jennifer','S','Wallace','987654321',TO_DATE('20-JUN-1941','DD-MON-YYYY'),'291 Berry, Bellaire,
TX', 'F', 43000, '888665555', 4);
INSERT INTO employee VALUES
  ('Ramesh','K','Narayan','666884444',TO DATE('15-SEP-1962','DD-MON-YYYY'),'975 Fire Oak, Humble,
```

```
TX', 'M', 38000, '333445555', 5);
INSERT INTO employee VALUES
  ('Joyce','A','English','453453453',TO_DATE('31-JUL-1972','DD-MON-YYYY'),'5631 Rice, Houston,
TX', 'F', 25000, '333445555', 5);
INSERT INTO employee VALUES
  ('Ahmad','V','Jabbar','987987987',TO_DATE('29-MAR-1969','DD-MON-YYYY'),'980 Dallas, Houston,
TX', 'M', 25000, '987654321', 4);
INSERT INTO employee VALUES
  ('James', 'E', 'Borg', '888665555', TO_DATE('10-NOV-1937', 'DD-MON-YYYY'), '450 Stone, Houston,
TX', 'M', 55000, null, 1);
INSERT INTO department VALUES ('Research', 5, '333445555', TO_DATE('22-MAY-1988','DD-MON-YYYY'));
INSERT INTO department VALUES ('Administration', 4, '987654321', TO_DATE('01-JAN-1995', 'DD-MON-YYYY'));
INSERT INTO department VALUES ('Headquarters', 1, '888665555', TO_DATE('19-JUN-1981','DD-MON-YYYY'));
INSERT INTO project VALUES ('ProductX',1,'Bellaire',5);
INSERT INTO project VALUES ('ProductY',2,'Sugarland',5);
INSERT INTO project VALUES ('ProductZ',3,'Houston',5);
INSERT INTO project VALUES ('Computerization', 10, 'Stafford', 4);
INSERT INTO project VALUES ('Reorganization', 20, 'Houston', 1);
INSERT INTO project VALUES ('Newbenefits',30,'Stafford',4);
INSERT INTO dept_locations VALUES (1, 'Houston');
INSERT INTO dept_locations VALUES (4,'Stafford');
INSERT INTO dept locations VALUES (5, 'Bellaire');
INSERT INTO dept_locations VALUES (5, 'Sugarland');
INSERT INTO dept locations VALUES (5, 'Houston');
INSERT INTO dependent VALUES ('333445555', 'Alice', 'F', TO_DATE('05-APR-86', 'DD-MON-YY'), 'Daughter');
INSERT INTO dependent VALUES ('333445555', 'Theodore', 'M', TO_DATE('25-OCT-83', 'DD-MON-YY'), 'Son');
INSERT INTO dependent VALUES ('333445555', 'Joy', 'F', TO_DATE('03-MAY-58', 'DD-MON-YY'), 'Spouse');
INSERT INTO dependent VALUES ('987654321', 'Abner', 'M', TO_DATE('28-FEB-42', 'DD-MON-YY'), 'Spouse');
INSERT INTO dependent VALUES ('123456789', 'Michael', 'M', TO_DATE('01-JAN-78', 'DD-MON-YY'), 'Son');
INSERT INTO dependent VALUES ('123456789', 'Alice', 'F', TO_DATE('31-DEC-88', 'DD-MON-YY'), 'Daughter');
INSERT INTO dependent VALUES ('123456789', 'Elizabeth', 'F', TO_DATE('05-MAY-67', 'DD-MON-YY'), 'Spouse');
INSERT INTO works_on VALUES ('123456789',1, 32.5);
INSERT INTO works_on VALUES ('123456789',2, 7.5);
INSERT INTO works on VALUES ('666884444',3, 40.0);
INSERT INTO works_on VALUES ('453453453',1, 20.0);
INSERT INTO works_on VALUES ('453453453',2, 20.0);
INSERT INTO works_on VALUES ('333445555',2, 10.0);
INSERT INTO works_on VALUES ('333445555',3, 10.0);
INSERT INTO works_on VALUES ('333445555',10,10.0);
INSERT INTO works_on VALUES ('333445555',20,10.0);
INSERT INTO works_on VALUES ('999887777',30,30.0);
INSERT INTO works on VALUES ('999887777',10,10.0);
INSERT INTO works_on VALUES ('987987987',10,35.0);
INSERT INTO works on VALUES ('987987987',30, 5.0);
INSERT INTO works on VALUES ('987654321',30,20.0);
INSERT INTO works on VALUES ('987654321',20,15.0);
INSERT INTO works on VALUES ('888665555',20,null);
STEP #3
ALTER TABLE EMPLOYEE
ADD CONSTRAINT employee superssn fk FOREIGN KEY (Super ssn)
         REFERENCES employee (ssn);
ALTER TABLE EMPLOYEE
ADD CONSTRAINT employee dno fk FOREIGN KEY (Dno)
         REFERENCES department (dnumber);
```

```
ALTER TABLE department
ADD CONSTRAINT department_mgrssn_fk FOREIGN KEY (Mgr_ssn)
       REFERENCES employee (ssn);
ALTER TABLE dept_locations
ADD CONSTRAINT deptlocations_dnumber_fk foreign key (dnumber)
references department(dnumber);
ALTER TABLE project
ADD CONSTRAINT project_dnum_fk foreign key (dnum)
references department(dnumber);
ALTER TABLE works on
ADD CONSTRAINT workson essn fk foreign key (essn)
references employee(ssn);
ALTER TABLE works on
ADD CONSTRAINT workson_pno_fk foreign key (pno)
references project(pnumber);
ALTER TABLE dependent
ADD CONSTRAINT dependent_essn_fk foreign key (essn)
references employee(ssn);
STEP #4
_____
SELECT *
FROM EMPLOYEE
```