EXPERIMENT – 16

CLONE A VIRTUAL MACHINE IN VMWARE WORKSTATION

Aim

To create a clone of an existing virtual machine using VMware Workstation.

Requirements

A computer with VMware Workstation and an existing virtual machine with a saved snapshot.

Procedure

1. Open VMware Workstation and select the virtual machine to be cloned.
2. Ensure the VM is powered off or in a supported snapshot state.
3. Open the VM menu or right-click the virtual machine and choose **Manage** → **Clone**.
4. Select the source snapshot or current state when prompted.
5. Choose **Create a full clone** or **Create a linked clone**, according to the lab requirement.
6. Enter a name and destination folder for the cloned VM.
7. Review the settings and click **Finish** to create the clone.
8. Wait for the clone process to complete, then verify the cloned VM appears in the library.
9. Select the cloned VM and check its name and hardware summary before powering it on.

Implementation Input

An existing Ubuntu 64-bit VM and a clone created from Snapshot 1.

OUTPUT

Actual VMware Workstation screenshot supplied for Experiment 16.



Figure 1: VMware Workstation displays “Clone of Ubuntu 64-bit (2)” as a separate virtual machine. The details identify the source VM configuration and show Snapshot 1.

Result

A cloned virtual machine is visible in VMware Workstation under the name “Clone of Ubuntu 64-bit (2)”. The screenshot documents the clone and its configuration summary. The VM is powered off, so it can be started after confirming the clone settings.