

Practical – Week6

Session 6:

1. Create a client-server application using Named Pipes (FIFOs). The client sends messages and the server processes and responds to them. Analyze FIFO behavior when multiple clients communicate simultaneously.

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/stat.h>
#define FIFO1 "client_to_server"
#define FIFO2 "server_to_client"
int main() {
    char message[100];
    int fd_read, fd_write;
    mkfifo(FIFO1, 0666);
    mkfifo(FIFO2, 0666);
    printf("Server started...\n");
    while (1) {
        fd_read = open(FIFO1, O_RDONLY);
        read(fd_read, message, sizeof(message));
        close(fd_read);
        printf("Client: %s\n", message);
        // Exit request
        if (strcmp(message, "exit") == 0) {
            break;
        }
        // Process message
        char response[150];
        snprintf(response, sizeof(response),
                 "Server processed: %s", message);
        // Open FIFO for writing
        fd_write = open(FIFO2, O_WRONLY);
        write(fd_write, response, strlen(response) + 1);
        close(fd_write);
    }
    unlink(FIFO1);
    unlink(FIFO2);
    printf("Server stopped.\n");
    return 0;
}
```

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#define FIFO1 "client_to_server"
#define FIFO2 "server_to_client"
int main() {
    char message[100];
    char response[150];
    int fd_write, fd_read;
    printf("Enter message: ");
    fgets(message, sizeof(message), stdin);
    message[strcspn(message, "\n")] = '\0';
    // Open FIFO for writing
    fd_write = open(FIFO1, O_WRONLY);
    write(fd_write, message, strlen(message) + 1);
    close(fd_write);
    // Exit request
    if (strcmp(message, "exit") == 0) {
        return 0;
    }
    // Open FIFO for reading
    fd_read = open(FIFO2, O_RDONLY);
    read(fd_read, response, sizeof(response));
    close(fd_read);
    printf("Server response: %s\n", response);
    return 0;
}

```

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#define FIF01 "client_to_server"
#define FIF02 "server_to_client"
int main(int argc, char *argv[]) {

    if (argc != 2) {
        printf("Usage: %s message\n", argv[0]);
        return 1;
    }

    char response[150];

    int fd_write, fd_read;

    // Send message to server
    fd_write = open(FIF01, O_WRONLY);

    write(fd_write, argv[1], strlen(argv[1]) + 1);

    close(fd_write);

    // Receive response
    fd_read = open(FIF02, O_RDONLY);

    read(fd_read, response, sizeof(response));

    close(fd_read);

    printf("Client received: %s\n", response);

    return 0;
}
```

```
ajithmutyala@Ajith: ~/OS_Lab x  ajithmutyala@Ajith: ~/OS_Lab x  +  v  -  □  X
ajithmutyala@Ajith:~$ cd ~/OS_Lab
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_client
Enter message: Hello server
Server response: Server processed: Hello server
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_client
Enter message: How are you?
Server response: Server processed: How are you?
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_client_auto "Client1 Hello"
Client received: Server processed: Client1 Hello
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_client_auto "Client2 Hello"
Client received: Server processed: Client2 Hello
ajithmutyala@Ajith:~/OS_Lab$ ls -l client_to_server server_to_client
prw-r--r-- 1 ajithmutyala ajithmutyala 0 Sep 16 06:44 client_to_server
prw-r--r-- 1 ajithmutyala ajithmutyala 0 Sep 16 06:44 server_to_client
ajithmutyala@Ajith:~/OS_Lab$ file client_to_server
client_to_server: fifo (named pipe)
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_client
Enter message: exit
ajithmutyala@Ajith:~/OS_Lab$ |

ajithmutyala@Ajith: ~/OS_Lab x  ajithmutyala@Ajith: ~/OS_Lab x  +  v  -  □  X
ajithmutyala@Ajith:~$ cd ~/OS_Lab
ajithmutyala@Ajith:~/OS_Lab$ nano fifo_server.c
ajithmutyala@Ajith:~/OS_Lab$ nano fifo_client.c
ajithmutyala@Ajith:~/OS_Lab$ nano fifo_client_auto.c
ajithmutyala@Ajith:~/OS_Lab$ gcc fifo_server.c -o fifo_server
ajithmutyala@Ajith:~/OS_Lab$ gcc fifo_client.c -o fifo_client
ajithmutyala@Ajith:~/OS_Lab$ gcc fifo_client_auto.c -o fifo_client_auto
ajithmutyala@Ajith:~/OS_Lab$ ls
builtin.c      fifo_client.c      fifo_server.c      shell_dispatch
export_env     fifo_client_auto   fork_example        shell_dispatch.c
export_env.c   fifo_client_auto.c fork_example.c      state_management
fifo_client    fifo_server        fork_example.c.save state_management.c
ajithmutyala@Ajith:~/OS_Lab$ ./fifo_server
Server started...
Client: Hello Server
Client:
Client: Hello server
Client: How are you?
Client: Client1 Hello
Client: Client2 Hello
Client: exit
Server stopped.
ajithmutyala@Ajith:~/OS_Lab$ |
```

Report: The program successfully implements client-server communication using named pipes (FIFOs). The client sends messages, and the server processes and responds to them. Multiple clients can communicate through the FIFO, demonstrating inter-process communication and FIFO behavior.

2. Create a POSIX signal handling program that captures SIGINT, SIGTERM, and SIGUSR1. Demonstrate asynchronous event handling and explain the role of signal handlers.

```
#include <stdio.h>
#include <stdlib.h>
#include <signal.h>
#include <unistd.h>
// Signal handler function
void handle_signal(int sig) {
    if (sig == SIGINT) {
        printf("\nSIGINT received: Ctrl+C pressed\n");
    }
    else if (sig == SIGTERM) {
        printf("\nSIGTERM received: Termination request\n");
    }
    else if (sig == SIGUSR1) {
        printf("\nSIGUSR1 received: User signal handled\n");
    }
    fflush(stdout);
}
int main() {
    // Register signal handlers
    signal(SIGINT, handle_signal);
    signal(SIGTERM, handle_signal);
    signal(SIGUSR1, handle_signal);
    printf("Signal handling program started\n");
    printf("Process ID: %d\n", getpid());
    printf("Press Ctrl+C or send signals from another terminal\n");

    while (1) {
        printf("Program running...\n");
        sleep(3);
    }

    return 0;
}
```

```
ajithmutyala@Ajith: ~/OS_Lab  X  ajithmutyala@Ajith: ~/OS_Lab  X  +  v
ajithmutyala@Ajith:~/OS_Lab$ kill -SIGUSR1 12345
-bash: kill: (12345) - No such process
ajithmutyala@Ajith:~/OS_Lab$ kill -SIGUSR1 990
ajithmutyala@Ajith:~/OS_Lab$ kill -SIGTERM 990
ajithmutyala@Ajith:~/OS_Lab$ kill 990
ajithmutyala@Ajith:~/OS_Lab$ ps -ef | grep signal_handler
ajithmutyala  990    320  0 06:51 pts/0    00:00:00 ./signal_handler
ajithmutyala 1054    758  0 06:54 pts/2    00:00:00 grep --color=auto signal_handler
ajithmutyala@Ajith:~/OS_Lab$ |
```

