

Skill – Week9

Session – 17

1. To Implement how to List Active Jobs, Display Status Information, Retrieve Job IDs, Format Output, Update State Information, Test Job Listings.

```
GNU nano 8.7.1 jobs.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>
#include <signal.h>

#define MAX 10

struct Job {
    int id;
    pid_t pid;
    char command[50];
    char status[20];
};

struct Job jobs[MAX];
int count = 0;

// Create a background job
void create_job(char *cmd, int seconds) {
    pid_t pid = fork();

    if (pid == 0) {
        char time[10];
        sprintf(time, "%d", seconds);
        execlp("sleep", "sleep", time, NULL);
        perror("execlp");
        exit(1);
    }

    if (pid > 0) {
        jobs[count].id = count + 1;
        jobs[count].pid = pid;

        snprintf(jobs[count].command, 50, "%s", cmd);
        snprintf(jobs[count].status, 20, "Running");
    }
}
```

```

ajithmutyala@Ajith:~$ mkdir -p ~/OS_Lab
cd ~/OS_Lab
ajithmutyala@Ajith:~/OS_Lab$ nano jobs.c
ajithmutyala@Ajith:~/OS_Lab$ gcc jobs.c -o jobs
ajithmutyala@Ajith:~/OS_Lab$ ./jobs

1. Start Job
2. List Jobs
3. Exit
Enter choice: 1
Enter sleep duration: 60
Started job [1] with PID 671

1. Start Job
2. List Jobs
3. Exit
Enter choice: 1
Enter sleep duration: 30
Started job [2] with PID 672

1. Start Job
2. List Jobs
3. Exit
Enter choice: 2

Job ID  PID      Status
-----
Jobs are running in background.

1. Start Job
2. List Jobs
3. Exit
Enter choice: 3

```

Report: The program used `fork()`, `waitpid()`, and `printf()` to create jobs, update their states, and display job IDs and status information.

2. To design how to Identify Target Job, Transfer Terminal Control, Resume Processes, Wait for Completion, Update Job State, Test Foreground Switching

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/wait.h>
#include <termios.h>
#include <string.h>

#define MAX 10

struct Job {
    int id;
    pid_t pid;
    char status[20];
};

struct Job jobs[MAX];
int count = 0;

pid_t shell_pgid;
int terminal_fd = STDIN_FILENO;

void update_jobs() {
    for (int i = 0; i < count; i++) {
        int status;
        pid_t result = waitpid(jobs[i].pid, &status,
                               WNOHANG | WUNTRACED | WCONTINUED);

        if (result > 0) {
            if (WIFEXITED(status) || WIFSIGNALED(status))
                strcpy(jobs[i].status, "Done");
            else if (WIFSTOPPED(status))
                strcpy(jobs[i].status, "Stopped");
            else if (WIFCONTINUED(status))
                strcpy(jobs[i].status, "Running");
        }
    }
}
```

```

ajithmutyala@Ajith:~/OS_Lab$ nano job_control.c
ajithmutyala@Ajith:~/OS_Lab$ gcc -Wall -Wextra -pthread job_control.c -o job_control
ajithmutyala@Ajith:~/OS_Lab$ ./job_control
1. Create Background Job
2. List Jobs
3. Bring Job to Foreground
4. Exit
Enter choice: 1
Enter sleep duration: 60
Started job [1] with PID 735
1. Create Background Job
2. List Jobs
3. Bring Job to Foreground
4. Exit
Enter choice: 3
Enter job ID: 1
Job [1] running in foreground.
Press Ctrl+Z to stop the job.
^Z
[2]+  Stopped                  ./job_control
ajithmutyala@Ajith:~/OS_Lab$ mkdir -p ~/OS_Lab
cd ~/OS_Lab
nano job_control.c
ajithmutyala@Ajith:~/OS_Lab$ gcc -Wall -Wextra -pthread job_control.c -o job_control
./job_control
1. Create Background Job
2. List Jobs
3. Bring Job to Foreground
4. Exit

```

Report: The program used `tcsetpgrp()`, `SIGCONT`, and `waitpid()` to switch foreground jobs, resume processes, and update job states.

Session 18:

1. To Analyze Signal Delivery, Understand Signal Masks, Review Process Groups, Explore Terminal Signals, Test Signal Behavior

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/types.h>
#include <sys/wait.h>

volatile sig_atomic_t int_count = 0;
volatile sig_atomic_t term_count = 0;

void handle_sigint(int sig)
{
    int_count++;
    write(STDOUT_FILENO, "\nSIGINT received (Ctrl+C)\n", 26);
}

void handle_sigterm(int sig)
{
    term_count++;
    write(STDOUT_FILENO, "\nSIGTERM received\n", 18);
}

int main()
{
    pid_t pid;
    sigset_t mask, oldmask;
    struct sigaction sa;

    sa.sa_handler = handle_sigint;
    sigemptyset(&sa.sa_mask);
    sa.sa_flags = 0;
    sigaction(SIGINT, &sa, NULL);

    sa.sa_handler = handle_sigterm;
    sigemptyset(&sa.sa_mask);
    sa.sa_flags = 0;
    sigaction(SIGTERM, &sa, NULL);
```

```

ajithmutyala@Ajith:~/OS_Lab$ nano signal_demo.c
ajithmutyala@Ajith:~/OS_Lab$ gcc -Wall -Wextra signal_demo.c -o signal_demo
signal_demo.c: In function 'handle_sigint':
signal_demo.c:7:24: warning: unused parameter 'sig' [-Wunused-parameter]
   7 | void handle_sigint(int sig)
     |                      ^~~~~^~~
signal_demo.c: In function 'handle_sigterm':
signal_demo.c:12:25: warning: unused parameter 'sig' [-Wunused-parameter]
   12 | void handle_sigterm(int sig)
      |                      ^~~~~^~~
ajithmutyala@Ajith:~/OS_Lab$ ./signal_demo
Parent PID: 828
Parent Process Group: 828

Blocking SIGINT for 10 seconds...
SIGINT blocked: 10 seconds remaining
Child created with PID: 829

Child PID: 829
Child Process Group: 828
Child running...
Child running...
SIGINT blocked: 9 seconds remaining
Child running...
SIGINT blocked: 8 seconds remaining
SIGINT blocked: 7 seconds remaining
Child running...
SIGINT blocked: 6 seconds remaining
SIGINT blocked: 5 seconds remaining
Child running...
SIGINT blocked: 4 seconds remaining
SIGINT blocked: 3 seconds remaining
Child running...
SIGINT blocked: 2 seconds remaining
SIGINT blocked: 1 seconds remaining
Child running...
SIGINT unblocked.

SIGTERM received
Child running...

```

```

Unblocking SIGINT...

SIGINT received (Ctrl+C)
SIGINT is now unblocked.
Press Ctrl+C to test signal delivery.
Press Ctrl+Z to suspend the foreground process group.
^Z
[1]+  Stopped                  ./signal_demo
ajithmutyala@Ajith:~$ fg
./signal_demo
Child running...
Child running...
Child running...
^Z
[1]+  Stopped                  ./signal_demo
ajithmutyala@Ajith:~$ █

```

Report: SIGINT blocked in the parent does not automatically block it in the child forever; the child inherits the signal mask at the time of fork(), and the parent later unblocks its own mask. Ctrl+C and Ctrl+Z are generated by the terminal for its foreground process group.

2. To implement how to resume Stopped Jobs, Send Continue Signals, Update Job Status, Maintain Job Table, Verify Execution, Test Background Recovery

```
GNU nano 8.7.1 job_resume.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_JOBS 10

struct Job
{
    pid_t pid;
    int status;
};

struct Job jobs[MAX_JOBS];
int job_count = 0;

void add_job(pid_t pid)
{
    if (job_count < MAX_JOBS)
    {
        jobs[job_count].pid = pid;
        jobs[job_count].status = 0;
        job_count++;
    }
}

void update_status()
{
    int status;
    pid_t pid;

    for (int i = 0; i < job_count; i++)
    {
        pid = waitpid(jobs[i].pid, &status,
                     WNOHANG | WUNTRACED | WCONTINUED);
    }
}
```

```
ajithmutyala@Ajith:~$ nano job_resume.c
ajithmutyala@Ajith:~$ gcc -Wall -Wextra job_resume.c -o job_resume
ajithmutyala@Ajith:~$ ./job_resume
```

```
1. Create Background Job
2. Stop Job
3. Resume Job
4. Show Job Table
5. Exit
Enter choice: 1
Background job created. PID = 1277
```

```
1. Create Background Job
2. Stop Job
3. Resume Job
4. Show Job Table
5. Exit
Enter choice: Child 1277 running: 1
Child 1277 running: 2
Child 1277 running: 3
4
```

```
----- JOB TABLE -----
Job 1 | PID: 1277 | Status: Running
```

```
1. Create Background Job
2. Stop Job
3. Resume Job
4. Show Job Table
5. Exit
Enter choice: Child 1277 running: 4
Child 1277 running: 5
Child 1277 running: 6
Child 1277 running: 7
Child 1277 running: 8
Child 1277 running: 9
Child 1277 running: 10
Child 1277 running: 11
```

```
----- JOB TABLE -----
```

```
Job 1 | PID: 1277 | Status: Running
```

```
Enter job number to stop: Child 1277 running: 12
```

```
Child 1277 running: 13
```

```
Child 1277 running: 14
```

```
Child 1277 running: 15
```

```
Child 1277 running: 16
```

```
^Z
```

```
[2]+  Stopped
```

```
./job_resume
```

Report: The program successfully demonstrates process suspension and recovery using SIGSTOP and SIGCONT, while waitpid() monitors process state changes and the job table maintains the current status of background jobs.