

Skill – Week7

Session 13:

1. To Parse Input Redirection, Open Files, Redirect stdin, Handle Missing Files, Restore Streams, Test File Inputs

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>

#define MAX_INPUT 200
#define MAX_ARGS 20

int main() {
    char input[MAX_INPUT];
    char *args[MAX_ARGS];
    int fd;
    int saved_stdin;
    int count = 0;
    printf("Enter command with input redirection:\n");
    printf("Example: cat < sample.txt\n");
    fgets(input, MAX_INPUT, stdin);
    input[strcspn(input, "\n")] = '\0';
    /* Save original stdin */
    saved_stdin = dup(STDIN_FILENO);
    if (saved_stdin == -1) {
        perror("dup");
        return 1;
    }
    /* Parse command arguments */
    char *token = strtok(input, " ");
    while (token != NULL && count < MAX_ARGS - 1) {
        if (strcmp(token, "<") == 0) {
            /* Get input filename */
            token = strtok(NULL, " ");
            if (token == NULL) {
                printf("Error: Missing input filename\n");
                close(saved_stdin);
                return 1;
            }
        }
    }
}
```

```
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Hello from OSSP" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Input redirection test" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Linux system programming" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls sample.txt
sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Hello from OSSP
Input redirection test
Linux system programming

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ nano input_redirect.c
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ gcc input_redirect.c -o input_redirect
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
cat < sample.txt
Input file opened successfully
Hello from OSSP
Input redirection test
Linux system programming

Standard input restored successfully

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -l < sample.txt
Input file opened successfully
3

Standard input restored successfully

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -w < sample.txt
Input file opened successfully
9

Standard input restored successfully
```

```
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Hello from OSSP" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Input redirection test" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Linux system programming" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls sample.txt
sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Hello from OSSP
Input redirection test
Linux system programming
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ nano input_redirect.c
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ gcc input_redirect.c -o input_redirect
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
cat < sample.txt
Input file opened successfully
Hello from OSSP
Input redirection test
Linux system programming

Standard input restored successfully

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -l < sample.txt
Input file opened successfully
3

Standard input restored successfully

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -w < sample.txt
Input file opened successfully
9
```

```
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
sort < sample.txt
Input file opened successfully
Hello from OSSP
Input redirection test
Linux system programming

Standard input restored successfully
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
grep Hello < sample.txt
Input file opened successfully
Hello from OSSP

Standard input restored successfully
```

Report: The program successfully parses input redirection, opens sample.txt, redirects standard input, executes the command, and restores the original standard input. File input is tested using cat, wc, sort, and grep.

2. To Parse Output Redirection, Create Output Files, Redirect stdout, Handle Permissions, Verify Output Data, Test Redirection

```
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ nano output_redirect.c
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ gcc output_redirect.c -o output_redirect
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./output_redirect
```

Enter command with output redirection:

Example: ls > output.txt

```
ls > output.txt
```

Output file opened successfully

Standard output restored successfully

```
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls
```

builtin.c	fork_example.c	pipeline
command_history	fork_example.c.save	pipeline.c
command_history.c	grep	sample.txt
export_env	input_redirect	shell_dispatch
export_env.c	input_redirect.c	shell_dispatch.c
fifo_client	multi_pipe	signal_handler
fifo_client.c	multi_pipe.c	signal_handler.c
fifo_client_auto	output.txt	state_management
fifo_client_auto.c	output_redirect	state_management.c
fifo_server	output_redirect.c	wc
fifo_server.c	pipe_demo	
fork_example	pipe_demo.c	

```

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat output.txt
builtin.c
command_history
command_history.c
export_env
export_env.c
fifo_client
fifo_client.c
fifo_client_auto
fifo_client_auto.c
fifo_server
fifo_server.c
fork_example
fork_example.c
fork_example.c.save
grep
input_redirect
input_redirect.c
multi_pipe
multi_pipe.c
output.txt
output_redirect
output_redirect.c
pipe_demo
pipe_demo.c
pipeline
pipeline.c
sample.txt
shell_dispatch
shell_dispatch.c
signal_handler
signal_handler.c
state_management
state_management.c
wc

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ wc -l output.txt
34 output.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls -l output.txt
-rw-rw-r-- 1 pawan_kumar pawan_kumar 18 03:29 output.txt

```

Report: The program parses output redirection using `>`, creates an output file using `open()`, redirects standard output using `dup2()`, handles file permission errors, restores the original output stream, and verifies the redirected data using `cat` and `wc`.

Session 14:

1. To Parse Append Operator, Open Files in Append Mode, Redirect Streams, Preserve Existing Data, Validate Appends, Test Scenarios

```

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "First line" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Second line" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
First line
Second line

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ touch sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Hello Linux" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
First line
Second line
Hello Linux

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Line 1" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Line 2" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Line 3" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Line 1
Line 2
Line 3

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Old Data" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Old Data

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "New Data" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Old Data
New Data

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Apple" > sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Banana" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Mango" >> sample.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat sample.txt
Apple
Banana
Mango

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ wc -l sample.txt
3

```

Report: The append operator >> adds new data to the end of a file while preserving existing content. The commands and C program demonstrate file appending, output redirection, and validation.

2. To Parse stderr Redirection, Redirect Error Streams, Capture Error Output, Verify File Contents, Handle Failures, Test Error Cases

```

#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main() {
    int fd;

    fd = open("error.txt",
              O_WRONLY | O_CREAT | O_APPEND, 0644);

    if (fd == -1) {
        perror("Error opening file");
        return 1;
    }

    dup2(fd, STDERR_FILENO);

    close(fd);

    fprintf(stderr, "Error: File not found\n");
    fprintf(stderr, "Error: Invalid command\n");

    return 0;
}

```

```

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ nano stderr_redirect.c
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ gcc stderr_redirect.c -o stderr_redirect
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ./stderr_redirect
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
First error
ls: cannot access '/wrong1': No such file or directory
ls: cannot access '/wrong2': No such file or directory
Error: File not found
Error: Invalid command

```

```

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
cat: /wrong_file: No such file or directory
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "Old error" > error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls /missing_folder 2>> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
Old error
ls: cannot access '/missing_folder': No such file or directory
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls /invalid_path 2> error.txt

if [ $? -ne 0 ]; then
    echo "Command failed"
else
    echo "Command succeeded"
fi
Command failed

pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls /not_found 2> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
ls: cannot access '/not_found': No such file or directory
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat missing.txt 2> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
cat: missing.txt: No such file or directory
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat /root/secret.txt 2> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
cat: /root/secret.txt: Permission denied
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ echo "First error" > error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls /wrong1 2>> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ ls /wrong2 2>> error.txt
pawan_kumar@LAPTOP-SSD0PUQ2:~/OS_Lab$ cat error.txt
First error
ls: cannot access '/wrong1': No such file or directory
ls: cannot access '/wrong2': No such file or directory

```

Report: stderr redirection is used to capture error messages into a file using 2> and 2>>. The commands and C program demonstrate error handling, preserving previous data, and verifying error output.