



Re: Updated

From RP DATASCIENCE

Date Sat 2/14/2026 11:59 AM

To Abhi Kamleshbhai Kanani <23130100608@reva.edu.in>

Here's a clear summary of the document you're viewing on **Principal Component Analysis (PCA) using Scikit**:

Main Points

- **Purpose of PCA**

- Reduces data dimensions to address the *curse of dimensionality*.
- Helps in detecting outliers, removing noise, and applications like speech recognition.
- Creates orthogonal (uncorrelated) components that retain most of the original data's information with fewer variables.

- **Underlying Technique**

- PCA relies on **Singular Value Decomposition (SVD)**, a linear algebra method.

- **Use in Modeling**

- Either the principal components or their loadings can be used in further modeling instead of raw data, reducing redundancy and noise.

- **Criteria for Choosing Number of Components**

1. Components should explain at least **80% of the variance** (preferred).
 2. Each component's **eigenvalue ≥ 1** (captures at least one variable's worth of information).
 3. **Elbow/Scree method**: select components at the "elbow" point in variance explained.
- Often, a combination of these methods is used.

- **Preprocessing Requirement**

- Data must be **standardized or normalized** before applying PCA.

- **Case Study Approach**

- The document demonstrates PCA using the first criterion (explaining $\geq 80\%$ variance).

Would you like me to also break this down into **practical steps for applying PCA in Scikit-learn** (like code workflow: scaling $\rightarrow$ fitting PCA $\rightarrow$ selecting components), so you can directly connect the theory to implementation?

explain other related points as well

Here are some **additional related points** from the document on PCA that complement the main ideas we discussed earlier:

Other Key Insights

- **Orthogonality of Components**

- Each principal component is orthogonal (uncorrelated) to the others, ensuring that they capture unique variance in the data without overlap.

- **Variance Explained**

- The first few components usually capture most of the variance. Later components often represent noise or minor variations.

- **Eigenvalues and Eigenvectors**

- Eigenvalues indicate the importance (variance explained) of each component.
- Eigenvectors define the direction of the new axes (principal components).

- **Dimensionality Reduction Benefits**

- Simplifies models, reduces computation time, and helps avoid overfitting.
- Makes visualization easier (e.g., reducing to 2D or 3D for plotting).

- **Limitations of PCA**

- PCA is a **linear method**; it may not capture complex nonlinear relationships.
- Sensitive to scaling — improper preprocessing can distort results.
- Interpretation of components can be challenging since they are combinations of original variables.

- **Applications Beyond Noise Reduction**

- Feature extraction for machine learning.
- Data compression.
- Visualization of high-dimensional datasets.
- Preprocessing step before clustering or classification.

- **Implementation Notes in Scikit-learn**

- `StandardScaler` is typically used before PCA.
- `PCA()` class allows specifying the number of components or variance threshold.
- Attributes like `.explained_variance_ratio_` help decide how many components to keep

Thanks, RP

Cell- +91 9620958943