A MATHEMATICAL FRAMEWORK FOR WAVELENGTH DENSITY AND FREQUENCY DENSITY: DIMENSIONAL ANALYSIS AND APPLICATIONS TO SOUND AND LIGHT WAVES

Author: Pawan Upadhyay

Affiliation: Independent Scientist and Independent Researcher

1st Email: pawanupadhyay28@hotmail.com


2nd Email: pawankanyakubj@gmail.com

ORCID iD: https://orcid.org/0009-0007-9077-5924

Field: Theoretical Physics – Gravitation

Year: 2025 - 2026

Research Area: Wave Physics, Mathematical Physics, Acoustics, and Optics



ABSTRACT

This research paper proposes two volume-normalized quantities: wavelength density and frequency density. Wavelength density is defined as wavelength divided by volume, while frequency density is defined as frequency divided by volume. The proposed equations are $\lambda_d = \lambda/V$ and $f_d = f/V$, respectively. This paper examines their dimensional consistency, mathematical relationships, and possible applications to sound waves and light waves. Both fixed-volume and variable-volume conditions are investigated. Using the conventional wave equation, $v = \lambda f$, the study derives the relationship $v = \lambda_d f_d V^2$. The analysis shows that the proposed definitions are dimensionally consistent. However, their independent physical significance and usefulness as new physical quantities require further theoretical investigation and experimental validation.

Keywords: Wavelength density, frequency density, wavelength, frequency, volume, dimensional analysis, sound waves, light waves, wave propagation.

1. INTRODUCTION

Waves are fundamental to numerous physical phenomena, including sound propagation and electromagnetic radiation. The conventional relationship between wave speed, wavelength, and frequency is:

$v = \lambda f$

Where:

- v = wave propagation speed
- λ = wavelength
- f = frequency

This paper proposes two additional mathematical quantities that incorporate the volume of a selected region containing a wave.

The proposed quantities are wavelength density and frequency density. The purpose of this investigation is to examine how wavelength and frequency can be normalized by volume and how these quantities behave when the selected volume remains constant or changes.

The proposed equations are mathematical definitions. Their usefulness as physical quantities must be established separately through theoretical or experimental research.

2. OBJECTIVES

The objectives of this research are:

1. To define wavelength density and frequency density mathematically.
2. To establish their SI units and dimensions.
3. To derive their relationship with the conventional wave-speed equation.
4. To investigate fixed-volume and variable-volume conditions.
5. To examine their potential applications to sound waves and light waves.
6. To identify limitations and directions for future research.

3. PROPOSED MATHEMATICAL DEFINITIONS

3.1 Wavelength Density

Wavelength density is defined as:

$\lambda_d = \lambda/V$

Where:

λ_d = wavelength density
λ = wavelength
V = volume of the selected region

3.2 Frequency Density

Frequency density is defined as:

$f_d = f/V$

Where:

f_d = frequency density
f = frequency
V = volume of the selected region

Both definitions require $V > 0$.

In this paper, the term “density” refers to the mathematical normalization of wavelength or frequency by volume. These proposed quantities are not assumed to be established standard physical densities.

4. DIMENSIONAL ANALYSIS

Dimensional analysis determines the units and dimensions of the proposed quantities.

4.1 Dimensions of Wavelength Density

The SI unit of wavelength λ is the metre (m).

The SI unit of volume V is the cubic metre (m^3).

According to the proposed equation:

$\lambda_d = \lambda/V$

Therefore:

Unit of $\lambda_d = m/m^3$

Simplifying:

Unit of $\lambda_d = m^{-2}$

The dimensional formula is:

$[\lambda_d] = L^{-2}$

Thus, wavelength density has the SI unit of inverse square metres.

4.2 Dimensions of Frequency Density

The SI unit of frequency f is the hertz (Hz), equivalent to s^{-1}.

According to the proposed equation:

$f_d = f/V$

Therefore:

Unit of $f_d = s^{-1}/m^3$

Simplifying:

Unit of $f_d = s^{-1}\ m^{-3}$

Equivalently:

Unit of $f_d = Hz/m^3$

The dimensional formula is:

$[f_d] = T^{-1}L^{-3}$

Thus, frequency density has the SI unit of hertz per cubic metre.

4.3 Summary of Dimensions

Wavelength, λ:

- SI unit: m
- Dimension: L

Frequency, f:

- SI unit: Hz
- Dimension: T^{-1}

Volume, V:

- SI unit: m^3
- Dimension: L^3

Wavelength density, λ_d:

- SI unit: m^{-2}
- Dimension: L^{-2}

Frequency density, f_d:

- SI unit: Hz/m^3
- Dimension: $T^{-1}L^{-3}$

Wave speed, v:

- SI unit: m/s
- Dimension: LT^{-1}

These units and dimensions follow directly from the proposed definitions.

5. DERIVATION OF THE WAVE-SPEED RELATIONSHIP

The conventional wave equation is:

$$v = \lambda f$$

The proposed wavelength-density equation is:

$$\lambda_d = \lambda/V$$

Rearranging:

$$\lambda = \lambda_d V$$

The proposed frequency-density equation is:

$$f_d = f/V$$

Rearranging:

$$f = f_d V$$

Substituting both expressions into the conventional wave equation gives:

$$v = (\lambda_d V)(f_d V)$$

Therefore:

$$\mathbf{v = \lambda_d f_d V^2}$$

This is the principal derived relationship in the proposed framework.

It can also be written as:

$\lambda_d f_d = v/V^2$

Or:

$\lambda_d f_d V^2 = v$

5.1 Dimensional Verification

The dimensions of the right-hand side of the equation $v = \lambda_d f_d V^2$ are:

$[\lambda_d f_d V^2] = L^{-2} \times T^{-1}L^{-3} \times L^6$

Combining the dimensions:

$[\lambda_d f_d V^2] = L^{-2}\, T^{-1}\, L^{-3}\, L^6$

Therefore:

$[\lambda_d f_d V^2] = LT^{-1}$

This is the dimension of wave speed.

Consequently, the derived equation is dimensionally consistent.

However, this equation is a mathematical consequence of the proposed definitions and the conventional wave equation. It is not an independent physical law.

6. CONDITION A: FIXED VOLUME

Consider a region whose volume remains constant.

$V = V_0$

Here, V_0 represents a fixed, nonzero volume.

The proposed definitions become:

$\lambda_d = \lambda/V_0$

$f_d = f/V_0$

The derived wave-speed equation becomes:

$v = \lambda_d f_d V_0^2$

If wave speed is also constant, then:

$\lambda_d f_d = v/V_0^2$

Since v and V_0 are constant:

$\lambda_d f_d$ = constant

Therefore:

$f_d = C/\lambda_d$

Where $C = v/V_0^2$.

Under these conditions, wavelength density and frequency density are inversely related.

For example, if λ_d doubles while volume and wave speed remain constant, f_d must halve.

This result follows from the conventional inverse relationship between wavelength and frequency at constant wave speed.

7. CONDITION B: VARIABLE VOLUME

Now consider a region whose volume changes.

$V = V(t)$

The proposed definitions become:

$\lambda_d(t) = \lambda(t)/V(t)$

$f_d(t) = f(t)/V(t)$

The derived relationship remains:

$v(t) = \lambda_d(t) f_d(t) V(t)^2$

If wave speed remains constant:

$\lambda_d(t) f_d(t) = v/V(t)^2$

For two states of the same wave speed:

$\lambda_{d1} f_{d1} V_1^2 = \lambda_{d2} f_{d2} V_2^2$

Therefore:

$(\lambda_{d_2} f_{d_2})/(\lambda_{d_1} f_{d_1}) = (V_1/V_2)^2$

If volume doubles, the product $\lambda_d f_d$ becomes one-quarter of its original value, provided wave speed remains constant.

This result determines the product of the two densities but does not determine their individual changes without additional information.

7.1 Case B1: Wavelength and Frequency Remain Constant

If λ and f remain constant while V changes:

λ_d is proportional to 1/V.

f_d is proportional to 1/V.

Both proposed densities decrease inversely with increasing volume.

For example, doubling the volume halves both λ_d and f_d.

7.2 Case B2: Wavelength and Frequency Also Change

If wavelength and frequency change with volume, their corresponding densities depend on both the original wave properties and the volume.

The rate of change of wavelength density is:

$d\lambda_d/dV = (1/V)(d\lambda/dV) - \lambda/V^2$

The rate of change of frequency density is:

$df_d/dV = (1/V)(df/dV) - f/V^2$

These equations show that a density can increase, decrease, or remain constant depending on how its original quantity changes relative to volume.

For example, suppose wavelength increases in direct proportion to volume:

$\lambda = kV$

Where k is constant.

Then:

$\lambda_d = \lambda/V$

Substituting $\lambda = kV$:

$\lambda_d = kV/V$

Therefore:

$\lambda_d = k$

The wavelength density remains constant even though the volume increases.

An analogous mathematical result applies to frequency density when f is proportional to V.

Whether these conditions occur in a particular physical system requires further investigation.

8. APPLICATION TO SOUND WAVES

Sound waves are mechanical waves that propagate through a material medium, such as air.

The conventional sound-wave equation is:

$v_s = \lambda f$

Where v_s is the sound-wave propagation speed.

Using the proposed definitions gives:

$v_s = \lambda_d f_d V^2$

This relationship can be used to calculate the proposed densities for sound waves studied in regions of different volumes.

8.1 Numerical Example

Consider a sound wave with:

$\lambda = 2$ m
$f = 170$ Hz
$V = 30$ m³

The sound speed under the assumed conditions is:

$v_s = \lambda f$

$v_s = 2 \times 170$

$v_s = 340$ m/s

Wavelength density is:

$\lambda_d = \lambda/V$

$\lambda_d = 2/30$

$\lambda_d \approx 0.0667\ m^{-2}$

Frequency density is:

$f_d = f/V$

$f_d = 170/30$

$f_d \approx 5.667\ Hz/m^3$

Now consider the same wavelength and frequency in a selected volume of 300 m^3.

Wavelength density:

$\lambda_d = 2/300$

$\lambda_d \approx 0.00667\ m^{-2}$

Frequency density:

$f_d = 170/300$

$f_d \approx 0.5667\ Hz/m^3$

The calculations show that the proposed densities change with the selected volume even when wavelength and frequency remain unchanged.

In actual rooms, sound fields are also affected by reflections, absorption, interference, room geometry, and resonant modes. The proposed definitions do not independently predict these effects.

9. APPLICATION TO LIGHT WAVES

Light is electromagnetic radiation that can propagate through a vacuum.

The speed of light in a vacuum is approximately:

$c = 2.998 \times 10^8\ m/s$

The conventional relationship is:

$c = \lambda f$

For light in a vacuum, the proposed definitions give:

$c = \lambda_d f_d V^2$

9.1 Numerical Example

Consider light with a wavelength of 500 nanometres.

$\lambda = 500 \text{ nm}$

$\lambda = 5.00 \times 10^{-7} \text{ m}$

Its frequency is calculated as:

$f = c/\lambda$

$f \approx 5.996 \times 10^{14} \text{ Hz}$

For a selected volume of 1 m^3:

$\lambda_d = 5.00 \times 10^{-7} \text{ m}^{-2}$

$f_d \approx 5.996 \times 10^{14} \text{ Hz/m}^3$

For a selected volume of 10 m^3, while wavelength and frequency remain unchanged:

$\lambda_d = 5.00 \times 10^{-8} \text{ m}^{-2}$

$f_d \approx 5.996 \times 10^{13} \text{ Hz/m}^3$

The proposed densities decrease as the selected volume increases.

This change results from dividing wavelength and frequency by volume. It does not mean that the physical wavelength or frequency of light changes merely because the selected region becomes larger.

For light propagating through a material medium, the relevant propagation speed and wavelength must be used. In dispersive media, phase velocity and group velocity are distinct quantities.

10. COMPARATIVE ANALYSIS OF SOUND AND LIGHT

The proposed definitions can be applied mathematically to both sound waves and light waves.

Sound waves are mechanical waves that require a material medium.

Light waves are electromagnetic waves that can propagate through a vacuum.

For sound waves:

$v_s = \lambda_d f_d V^2$

For light waves in a vacuum:

$c = \lambda_d f_d V^2$

In both cases, the proposed densities depend on the volume selected for analysis.

A small room, a large room, and an outdoor region can therefore produce different calculated density values when different volumes are used.

However, an open field does not have a unique natural volume. A specific region must be defined before the proposed densities can be calculated.

11. DISCUSSION AND LIMITATIONS

11.1 Mathematical Consistency

The proposed definitions are dimensionally consistent. The derived relationship:

$v = \lambda_d f_d V^2$

has the correct dimensions of wave speed.

11.2 Dependence on Selected Volume

The calculated values depend directly on the volume chosen for analysis.

Comparisons between rooms or outdoor regions require clearly defined measurement boundaries and consistent measurement methods.

11.3 Physical Interpretation

Wavelength density has units of inverse square metres, while frequency density has units of hertz per cubic metre.

These units follow from the proposed definitions and are not mathematical errors.

However, the physical meaning of these quantities must be established. Researchers must determine what measurable properties they describe and whether they offer useful information beyond the original wavelength, frequency, and volume.

11.4 Relationship to Established Physics

The derived equation is equivalent to the conventional wave equation after substituting the proposed definitions.

Consequently, it does not independently establish a new physical law or demonstrate a new physical effect.

To establish additional scientific value, the framework would need to generate useful predictions, explain observations, or support an experimentally testable hypothesis that provides insight beyond existing wave theory.

11.5 Experimental Requirements

Future experiments could measure wavelength, frequency, and the dimensions of a specified region, calculate the proposed densities, and compare their behavior as the selected volume changes.

For sound, room geometry, reflections, absorption, and boundary conditions should be considered.

For light, the propagation medium, optical geometry, and measurement region should be specified.

12. FUTURE RESEARCH DIRECTIONS

Future research should investigate the following questions:

1. Can λ_d and f_d be assigned operational physical meanings beyond volume-normalized quantities?

2. Can these definitions help compare sound fields or electromagnetic fields across different spatial regions?

3. Can they be related to established quantities such as acoustic energy density, electromagnetic energy density, or modal density?

4. Can experiments identify useful predictions that are not already explained by conventional wave theory?

5. How should the measurement region be defined for waves propagating through unbounded open space?

Answers to these questions would help establish whether the proposed framework is a useful mathematical representation or a basis for a broader physical model.

13. CONCLUSION

This paper has proposed two mathematical quantities:

Wavelength density:

$\lambda_d = \lambda/V$

Frequency density:

$f_d = f/V$

Dimensional analysis shows that wavelength density has SI units of m^{-2}, while frequency density has SI units of Hz/m^3.

Using the conventional wave equation, the proposed definitions produce the relationship:

$v = \lambda_d f_d V^2$

This relationship remains valid under fixed-volume and variable-volume conditions, provided the relevant wave equation applies and V is nonzero.

The framework can be applied mathematically to sound waves and light waves. It also demonstrates how the calculated densities change when the selected volume changes.

However, mathematical consistency does not establish a new physical law. The physical interpretation, predictive usefulness, and experimental significance of the proposed quantities remain open questions for future research.

REFERENCES

1. Halliday, D., Resnick, R., and Walker, J. Fundamentals of Physics. Wiley. General reference for waves, wavelength, frequency, and wave speed.

2. Kinsler, L. E., Frey, A. R., Coppens, A. B., and Sanders, J. V. Fundamentals of Acoustics. Wiley. Reference for sound propagation and room acoustics.

3. Hecht, E. Optics. Pearson. Reference for electromagnetic waves, wavelength, frequency, and propagation in different media.


4. International Bureau of Weights and Measures (BIPM). The International System of Units (SI Brochure). Reference for SI units and dimensional conventions.

RESEARCH STATUS

This paper presents a theoretical proposal based on the author's definitions. No new experimental results are claimed. The independent physical significance of wavelength density and frequency density remains to be investigated through further theoretical work and experimental validation.

NOTES 1: WAVELENGTH DENSITY AND FREQUENCY DENSITY OF SOUND WAVES IN SMALL AND LARGE ROOMS

Author: Pawan Upadhyay



1. Introduction

Sound is a mechanical wave that propagates through a material medium, such as air. When sound travels through a room, it may encounter walls, ceilings, floors, furniture, and other objects.

These surfaces can reflect, absorb, transmit, or scatter sound energy. Reflected sound waves can overlap with incoming waves, producing interference and, under suitable conditions, room resonances.

This note examines these phenomena in relation to the proposed wavelength-density and frequency-density equations.

2. Proposed Equations

Wavelength density:

$\lambda_d = \lambda/V$

Frequency density:

$f_d = f/V$

Where:

λ_d = wavelength density
λ = sound wavelength
f_d = frequency density
f = sound frequency
V = volume of the selected region

The SI units are:

Wavelength density: m^{-2}

Frequency density: Hz/m^3

3. Sound Waves Encountering Walls

In a small room, sound waves can reach walls over relatively short distances. When they encounter a surface:

1. Some sound energy may be reflected.
2. Some may be absorbed by the material.
3. Some may pass through the wall.

4. Some may be scattered in different directions.

The reflected waves can overlap with incoming waves. Depending on their phase and frequency, they can produce constructive or destructive interference.

Room resonances can occur when the room dimensions and boundary conditions support particular standing-wave patterns.

However, the wavelength itself does not collide with the wall. The sound wave interacts with the surface.

4. Does a Small Room Change the Wavelength?

Not necessarily.

The conventional relationship is:

$v = \lambda f$

Therefore:

$\lambda = v/f$

If the speed of sound and frequency remain constant, the wavelength remains constant even when the sound reflects from a wall.

For example:

Sound speed = 340 m/s
Frequency = 170 Hz

Wavelength:

$\lambda = 340/170$

$\lambda = 2$ m

The wavelength is 2 m under these conditions.

A room can alter the sound field through reflections and resonances without automatically changing the wavelength of the incident sound.

5. Application of the Proposed Density Equations

Suppose the same sound wave is studied in two regions with different volumes.

For Region 1:

$\lambda_d_1 = \lambda/V_1$

$f_d_1 = f/V_1$

For Region 2:

$\lambda_d_2 = \lambda/V_2$

$f_d_2 = f/V_2$

If wavelength and frequency remain unchanged, then:

$\lambda_d_1/\lambda_d_2 = V_2/V_1$

$f_d_1/f_d_2 = V_2/V_1$

Thus, both proposed densities are inversely proportional to the selected volume when wavelength and frequency are fixed.

6. Small Room Versus Large Room

For the same wavelength and frequency:

- A smaller selected volume produces larger calculated values of λ_d and f_d.
- A larger selected volume produces smaller calculated values of λ_d and f_d.

These results follow directly from the proposed definitions.

The difference in calculated density does not, by itself, demonstrate that wall reflections have increased or decreased either quantity.

7. Fixed-Volume and Variable-Volume Conditions

Fixed volume

If V is constant:

$\lambda_d = \lambda/V$

$f_d = f/V$

Changes in wavelength or frequency produce proportional changes in their respective densities.

Variable volume

If V changes:

$\lambda_d = \lambda(V)/V$

$f_d = f(V)/V$

The densities depend on both the changes in wavelength or frequency and the change in volume.

If wavelength and frequency remain constant, both densities decrease inversely with increasing volume.

8. Derived Wave-Speed Relationship

From the proposed definitions:

$\lambda = \lambda_d V$

$f = f_d V$

Substituting into $v = \lambda f$ gives:

$v = \lambda_d f_d V^2$

This equation is dimensionally consistent. It follows from the proposed definitions and the conventional wave equation.

9. Scientific Limitations

The proposed equations describe wavelength and frequency divided by a selected volume. They do not independently calculate:

- The amount of reflected sound.
- The sound-pressure distribution.
- The strength of room resonances.
- The amount of sound energy absorbed by the walls.
- The effects of room geometry on the acoustic field.

These properties require additional physical variables and appropriate acoustic models.

10. Conclusion


Sound waves can reflect, interfere, and resonate in enclosed spaces. A small room and a large room can therefore have different acoustic characteristics.

According to the proposed equations, wavelength density and frequency density also differ when different volumes are used, even if the original wavelength and frequency remain constant.

Further research should investigate whether these proposed quantities provide a useful way to characterize measurable acoustic properties beyond the effects already described by established acoustics.

NOTES 2: WAVELENGTH DENSITY AND FREQUENCY DENSITY OF LIGHT WAVES IN SMALL AND LARGE ENCLOSED SPACES

Author: Pawan Upadhyay



1. Introduction

Light is electromagnetic radiation that can propagate through a vacuum and through transparent materials.

When light enters an enclosed room, it can interact with walls, windows, mirrors, and other surfaces. Depending on the material, light may be reflected, absorbed, transmitted, or scattered.

This note examines these interactions in relation to the proposed wavelength-density and frequency-density equations.

2. Proposed Equations

Wavelength density:

$\lambda_d = \lambda/V$

Frequency density:

$f_d = f/V$

Where:

λ_d = wavelength density
λ = wavelength of light
f_d = frequency density
f = frequency of light
V = volume of the selected region

The SI units are:

Wavelength density: m^{-2}

Frequency density: Hz/m^3

These definitions can be applied mathematically to light waves.

3. Light Waves Encountering Walls

When light reaches a wall or another surface, several interactions may occur:

1. Reflection: light is redirected from the surface.
2. Absorption: light energy is absorbed by the material.
3. Transmission: some light passes through the material.
4. Scattering: light is redirected by surface irregularities or particles.
5. Interference: overlapping coherent light waves can produce variations in intensity.

A room with reflective surfaces can support multiple reflections of light. The resulting light distribution depends on the source, wavelength, surface properties, room geometry, and other optical conditions.

The wavelength itself does not collide with the wall. The electromagnetic wave interacts with the material.

4. Does a Small Room Change the Wavelength of Light?

Not necessarily.

For light in a vacuum:

$c = \lambda f$

Therefore:

$\lambda = c/f$

Where c is the speed of light in a vacuum.

If the frequency remains unchanged, the wavelength in a vacuum remains unchanged during ordinary reflection from a stationary surface.

When light enters a material, its propagation speed and wavelength can change. For a stationary boundary, the frequency ordinarily remains the same across that boundary.

Consequently, the effects of a room's walls on the light distribution should be distinguished from changes in wavelength or frequency.

5. Application of the Proposed Density Equations

Consider the same light wave studied in two selected regions with different volumes.

For Region 1:

$\lambda_d_1 = \lambda/V_1$

$f_d_1 = f/V_1$

For Region 2:

$\lambda_d_2 = \lambda/V_2$

$f_d_2 = f/V_2$

If wavelength and frequency remain unchanged:

$\lambda_d_1/\lambda_d_2 = V_2/V_1$

$f_d_1/f_d_2 = V_2/V_1$

Thus, both proposed densities are inversely proportional to the selected volume when wavelength and frequency are fixed.

A smaller selected volume produces larger calculated density values, while a larger selected volume produces smaller values.

6. Small Room Versus Large Room

For the same light wave, the proposed densities depend on the volume used in the calculations.

However, the change in calculated density results from the mathematical division by volume. It does not establish that light physically becomes more concentrated, gains energy, or changes wavelength merely because the selected region is smaller.

Actual optical intensity and energy distributions require separate measurements or calculations.

An open field also requires a defined measurement region because it does not have a unique natural volume.

7. Fixed-Volume and Variable-Volume Conditions

Fixed volume

If V is constant:

$\lambda_d = \lambda/V$

$f_d = f/V$

The densities change in proportion to their respective original quantities.

Variable volume

If V changes:

$\lambda_d = \lambda(V)/V$

$f_d = f(V)/V$

The resulting densities depend on changes in wavelength or frequency and on the change in volume.

If wavelength and frequency remain constant, both densities decrease inversely with increasing volume.

8. Derived Wave-Speed Relationship

The proposed definitions give:

$\lambda = \lambda_d V$

$f = f_d V$

For light in a vacuum, the conventional wave equation is:

$c = \lambda f$

Substitution gives:

$c = \lambda_d f_d V^2$

This equation is dimensionally consistent and follows from the proposed definitions and the conventional wave equation.

It does not independently establish a new law of electromagnetic propagation.

9. Scientific Limitations

The proposed equations do not independently determine:

- The intensity of light in a room.
- The number of reflections from the walls.
- The amount of light absorbed or transmitted.
- The electromagnetic energy density.
- The distribution of light intensity across the room.
- The behavior of a laser cavity or other resonant optical system.

These phenomena require additional optical or electromagnetic models.

10. Conclusion

Light can reflect, scatter, and be absorbed when it interacts with surfaces in an enclosed room. A small room and a large room may therefore have different light-distribution characteristics.

According to the proposed definitions, wavelength density and frequency density also differ when the selected volumes differ, even if wavelength and frequency remain unchanged.


Further research should investigate whether these volume-normalized quantities can provide a useful description of a measurable optical property beyond the standard relationships among wavelength, frequency, and propagation speed.

WAVELENGTH DENSITY AND FREQUENCY DENSITY: A COMPARATIVE MATHEMATICAL STUDY OF SOUND WAVES AND LIGHT WAVES

A Research Paper on Proposed Volume-Normalized Wave Quantities

Researcher: Pawan Upadhyay

Research Area: Wave Physics, Mathematical Physics, Acoustics, and Optics



ABSTRACT

This research paper presents a mathematical investigation of two proposed quantities: wavelength density and frequency density. The original definitions are preserved as follows:

- Wavelength density: $\lambda_d = \lambda / V$
- Frequency density: $f_d = f / V$

Here, λ represents wavelength, f represents frequency, and V represents the volume of the specified region under investigation.

The study examines the dimensional consistency of these definitions and their mathematical relationship with established wave physics. It considers applications to both sound waves and light waves and compares the proposed quantities with established physical quantities, including wavelength, frequency, wave speed, mass density, and energy density.

Using the established wave equation, $v = f\lambda$, the study derives the mathematical relationship $v = \lambda_d f_d V^2$. This relationship follows directly from the proposed definitions and does not, by itself, establish a new physical law.

The paper also proposes experimental approaches for investigating whether wavelength density and frequency density offer additional predictive value when studying acoustic and optical systems.

The principal conclusion is that wavelength density and frequency density are mathematically consistent, volume-normalized descriptors. Their independent physical significance, predictive usefulness, and possible applications remain questions for further theoretical and experimental investigation.

Keywords: Wavelength density, frequency density, sound waves, light waves, volume normalization, wave equation, dimensional analysis, acoustics, optics, mathematical physics.

---

1. INTRODUCTION

Waves are fundamental to many physical phenomena. Sound waves transmit mechanical disturbances through material media, while light waves are electromagnetic waves that can propagate through a vacuum and through material media.

Established wave physics describes wave propagation through measurable quantities such as:

- Wavelength
- Frequency
- Wave speed
- Amplitude
- Intensity
- Energy
- Medium properties
- Boundary conditions

The standard relationship between wave speed, wavelength, and frequency is:

$v = f\lambda$

This equation applies to a propagating wave when the quantities are defined consistently for the wave and medium under consideration. For light in a vacuum, the corresponding relationship is $c = f\lambda$.

The present research introduces two proposed mathematical quantities:

- Wavelength density, defined as wavelength divided by a specified volume.
- Frequency density, defined as frequency divided by the same specified volume.

The central objective is to examine what follows mathematically from these definitions and whether the resulting quantities could provide a useful framework for studying sound and light.

An essential scientific distinction must be maintained throughout this research: defining a new mathematical quantity does not automatically establish a new physical phenomenon. Its scientific value depends on whether it can be measured consistently, interpreted clearly, or used to make useful predictions.

2. RESEARCH OBJECTIVES

The objectives of this research are:

- To preserve and formally define wavelength density and frequency density.
- To determine their SI units and dimensions.
- To derive their relationship with the established wave equation.
- To examine their mathematical application to sound waves.
- To examine their mathematical application to light waves.
- To compare the proposed quantities with established physical quantities.
- To distinguish mathematical consequences from unverified physical hypotheses.
- To propose experiments that could test their potential scientific usefulness.

3. ORIGINAL DEFINITIONS

3.1. Wavelength Density

The proposed definition is:

$\lambda_d = \lambda / V$

Where:

- λ_d = Wavelength density
- λ = Wavelength
- V = Volume of the specified region

Wavelength density is defined in this research as the wavelength normalized by the selected volume.

Its SI unit is:

metre / cubic metre = m^{-2}

Therefore, the dimensional expression is:

$[\lambda_d] = L^{-2}$

3.2. Frequency Density

The proposed definition is:

$f_d = f / V$

Where:

- f_d = Frequency density
- f = Frequency
- V = Volume of the specified region

Frequency density is defined in this research as the frequency normalized by the selected volume.

Its SI unit is:

hertz / cubic metre = $s^{-1}\ m^{-3}$

Therefore, its dimensional expression is:

$[f_d] = T^{-1}L^{-3}$

3.3. Meaning of the Specified Volume

The volume V must be defined before either proposed quantity can be calculated.

Examples include:

- The volume of a room containing a sound field.
- The volume of an acoustic test chamber.
- The volume of a defined optical cavity.
- A specified region used to analyse an optical field.

The selected volume is part of the definition and must be reported in any calculation or experiment.

A different choice of reference volume produces different numerical values of wavelength density and frequency density, even when the wave itself remains unchanged.

This point is fundamental to the interpretation of the proposed quantities.

4. DIMENSIONAL ANALYSIS

Dimensional analysis determines whether mathematical relationships are consistent with the dimensions of the quantities involved.

For wavelength density:

$\lambda_d = \lambda / V$

Since wavelength has dimensions L and volume has dimensions L^3:

$[\lambda_d] = L / L^3$

Therefore:

$[\lambda_d] = L^{-2}$

For frequency density:

$f_d = f / V$

Since frequency has dimensions T^{-1} and volume has dimensions L^3:

$[f_d] = T^{-1} / L^3$

Therefore:

$[f_d] = T^{-1}L^{-3}$

The proposed definitions are dimensionally consistent.

However, dimensional consistency establishes only that the units follow logically from the definitions. It does not establish that these quantities correspond to independent physical mechanisms or previously unknown effects.

5. MATHEMATICAL DERIVATION FROM THE WAVE EQUATION

The established wave-speed equation is:

$v = f\lambda$

The proposed definitions are:

$\lambda_d = \lambda / V$

$f_d = f / V$

Rearranging the wavelength-density definition gives:

$\lambda = \lambda_d V$

Rearranging the frequency-density definition gives:

$f = f_d V$

Substituting both expressions into the standard wave equation:

$v = (f_d V)(\lambda_d V)$

Therefore:

$v = \lambda_d f_d V^2$

The derived equation is:

$v = \lambda_d f_d V^2$

Rearranging gives:

$\lambda_d f_d = v / V^2$

These relationships are mathematical consequences of the proposed definitions and the established wave equation.

Interpretation

When wave speed and reference volume are fixed:

- The product $\lambda_d f_d$ is constant for that wave speed and volume.
- The individual values of λ_d and f_d depend on the corresponding wavelength and frequency.
- The product is determined by v/V^2.

When the reference volume changes but the actual wave and its speed remain unchanged:

- Wavelength density changes inversely with volume.
- Frequency density changes inversely with volume.
- Their product changes inversely with the square of volume.

These results follow from the definitions. They do not independently demonstrate a new law of wave propagation.

6. COMPARISON WITH ESTABLISHED PHYSICAL QUANTITIES

6.1. Wavelength

Established quantity:

λ

- SI unit: metre.
- Represents the spatial period of a wave.
- Relates to frequency and wave speed through the wave equation.

Relationship to this research:

Wavelength is the numerator in the proposed wavelength-density definition.

6.2. Frequency

Established quantity:

f

- SI unit: hertz.
- Represents the number of cycles per second.
- Relates to wavelength and wave speed.

Relationship to this research:

Frequency is the numerator in the proposed frequency-density definition.

6.3. Volume

Established quantity:

V

- SI unit: cubic metre.
- Represents the three-dimensional volume of a specified region.

Relationship to this research:

Volume is the denominator in both proposed definitions.

6.4. Mass Density

Established quantity:

$\rho = m / V$

- SI unit: kg/m³.
- Represents mass per unit volume.

Comparison:

Mass density and the proposed wave quantities share the mathematical feature of division by volume. However, mass density has an established physical interpretation as mass per unit volume.

Wavelength density and frequency density use wavelength and frequency as their numerators. Their physical interpretations therefore cannot simply be assumed to match that of mass density.

6.5. Energy Density

A general definition of energy density is:

$u = E / V$

Where:

- u = Energy density
- E = Energy within the defined region
- V = Volume of that region

Its SI unit is J/m³.

Energy density is associated with a measurable physical quantity: energy contained within a specified volume.

The proposed quantities are different because wavelength and frequency are not amounts of energy.

Therefore, the mathematical similarity between these expressions does not establish an equivalent physical meaning.

7. APPLICATION TO SOUND WAVES

7.1. Established Physics of Sound

Sound is a mechanical wave that propagates through a material medium.

Its wave speed, frequency, and wavelength are related by:

$v_s = f_s \lambda_s$

Where:

- v_s = Sound speed in the medium
- f_s = Sound frequency
- λ_s = Sound wavelength

Established acoustic phenomena include:

- Sound-pressure variation.
- Reflection and absorption at boundaries.
- Transmission through materials.
- Interference between waves.
- Resonance in rooms and cavities.
- Reverberation.
- Acoustic energy transport.

The behaviour of sound depends on factors such as medium properties, frequency, boundary conditions, and the geometry of the environment.

7.2. Proposed Quantities for Sound

The proposed wavelength density for sound is:

$\lambda_{d,s} = \lambda_s / V$

The proposed frequency density for sound is:

$f_{d,s} = f_s / V$

Where V represents the specified volume associated with the analysis.

7.3. Hypothesis S1: Volume Normalization

If the wavelength and frequency of a sound wave remain unchanged while the reference volume increases:

- Wavelength density decreases in inverse proportion to volume.
- Frequency density decreases in inverse proportion to volume.

Mathematically:

$\lambda_{d,s} \propto 1/V$

$f_{d,s} \propto 1/V$

This prediction follows directly from the proposed definitions.

7.4. Hypothesis S2: Relationship with Acoustic Behaviour

A physical change in room geometry may alter:

- Resonance frequencies.
- Sound-pressure distribution.
- Interference patterns.
- Reverberation time.
- Acoustic energy distribution.

The proposed densities could be calculated alongside these established acoustic quantities.

However, an observed correlation would not establish that wavelength density or frequency density causes the acoustic change.

Further investigation would be needed to determine whether the proposed quantities offer any additional predictive value.

7.5. Important Distinction

Changing only the volume used in a calculation is different from changing the physical environment.

For example:

- If the same sound wave is measured while the selected reference volume changes, the proposed densities change by definition.
- If the room itself changes, the acoustic field may also change because of established wave interactions with the room boundaries.

A scientific experiment must distinguish these two effects.

8. APPLICATION TO LIGHT WAVES

8.1. Established Physics of Light

Light is an electromagnetic wave.

For light propagating in a vacuum:

$c = f\lambda$

Where:

- c = Speed of light in a vacuum.
- f = Frequency.
- λ = Wavelength.

The speed of light in a vacuum is exactly 299,792,458 metres per second.

In a material medium, the phase speed and wavelength depend on the optical properties of the medium.

Established optical phenomena include:

- Reflection.
- Refraction.
- Interference.
- Diffraction.
- Absorption.
- Transmission.
- Optical resonance.
- Electromagnetic energy transport.

The behaviour of light depends on its frequency, wavelength, medium, field distribution, and boundary conditions.

8.2. Proposed Quantities for Light

The proposed wavelength density for light is:

$\lambda_{d,L} = \lambda_L / V$

The proposed frequency density for light is:

$f_{d,L} = f_L / V$

Where V represents the specified optical region or cavity.

8.3. Hypothesis L1: Optical Volume Normalization

If the wavelength and frequency of light remain unchanged while only the reference volume changes:

- Wavelength density decreases inversely with volume.
- Frequency density decreases inversely with volume.

Mathematically:

$\lambda_{d,L} \propto 1/V$

$f_{d,L} \propto 1/V$

These relationships follow directly from the proposed definitions.

8.4. Hypothesis L2: Relationship with Optical Fields

A physical change in the geometry of an optical cavity may alter:

- Optical modes.
- Field distribution.
- Resonance frequencies.
- Intensity distribution.
- Electromagnetic energy distribution.

The proposed densities could be calculated alongside these established quantities.

The research question is whether the proposed quantities provide useful predictions beyond those already available from conventional optical theory.

This remains unverified.

8.5. Important Distinction

Changing the volume assigned to a light field does not necessarily change the light itself.

If the optical field remains unchanged, the proposed densities change only because their denominator changes.

If physical boundaries are altered, the optical field may change as well. Such changes must be analysed using established electromagnetic theory before attributing them to the proposed quantities.

9. COMPARISON BETWEEN SOUND AND LIGHT

The proposed definitions can be applied to both sound and light:

Wavelength density:

$\lambda_d = \lambda / V$

Frequency density:

$f_d = f / V$

The same mathematical framework applies, but the underlying wave mechanisms differ.

Sound waves:

- Require a material medium for ordinary acoustic propagation.
- Are mechanical disturbances.
- Interact with boundaries through reflection, absorption, transmission, and other acoustic processes.
- Can produce room resonances and reverberation.

Light waves:

- Can propagate through a vacuum.
- Are electromagnetic disturbances.
- Interact with materials through electromagnetic processes.
- Can form optical interference patterns and cavity resonances.

The proposed definitions do not erase these differences.

Their common feature is the mathematical normalization of wavelength and frequency by a specified volume.

Any further claim that they reveal a common physical mechanism must be supported by additional theoretical development and experimental evidence.

10. EXPERIMENTAL RESEARCH FRAMEWORK

10.1. Sound-Wave Experiment

The following procedure could be used to investigate the proposed quantities:

- Generate a stable sound wave in an acoustic test chamber.
- Measure its frequency.
- Determine its wavelength using appropriate acoustic measurements.
- Define the reference volume precisely.
- Calculate wavelength density and frequency density.
- Repeat the calculation for different reference volumes while keeping the wave conditions unchanged, where practical.
- In a separate experiment, alter the chamber geometry.
- Measure changes in sound pressure, resonance frequencies, and reverberation.
- Compare the results with established acoustic predictions.

The first experiment tests the mathematical normalization. The second investigates physical changes in the acoustic environment.

10.2. Light-Wave Experiment

A corresponding optical study could follow these steps:

- Use a stable monochromatic light source.
- Determine its wavelength and frequency.
- Define the optical region or cavity.
- Specify its volume and boundaries.
- Calculate wavelength density and frequency density.
- Change the reference volume mathematically without changing the optical field.
- Separately investigate changes in physical cavity geometry.
- Measure optical intensity, field distribution, or cavity resonance.
- Compare the measurements with established optical predictions.

10.3. Experimental Controls

For either experiment, the researcher should record:

- The measured wavelength.
- The measured frequency.
- The specified volume.
- The measurement uncertainty.
- The medium and environmental conditions.
- The geometry and boundary conditions.
- The calculated proposed densities.
- The relevant established physical measurements.

These controls help distinguish mathematical changes in the proposed quantities from changes in the actual wave field.

11. RESEARCH HYPOTHESES AND SCIENTIFIC STATUS

The following statements summarize the current status of the research.

- Hypothesis 1: Wavelength density is defined as $\lambda_d = \lambda/V$.

  Status: A proposed mathematical definition.

- Hypothesis 2: Frequency density is defined as $f_d = f/V$.

  Status: A proposed mathematical definition.

- Hypothesis 3: The proposed quantities have dimensionally consistent units.

Status: Established by dimensional analysis.

- Hypothesis 4: The relationship $v = \lambda_d f_d V^2$ follows from the definitions and the standard wave equation.

  Status: Mathematically derived.

- Hypothesis 5: The proposed quantities decrease inversely with volume when wavelength and frequency remain fixed.

  Status: A mathematical consequence of the definitions.

- Hypothesis 6: The proposed quantities can provide additional predictions for sound-wave behaviour.

  Status: An unverified research hypothesis.

- Hypothesis 7: The proposed quantities can provide additional predictions for light-wave behaviour.

  Status: An unverified research hypothesis.

- Hypothesis 8: The proposed quantities constitute a new physical law.

  Status: Not established by the current mathematical analysis.

To support the last three hypotheses, the research would need reproducible measurements and evidence that the proposed quantities provide useful predictive information beyond established physical variables.

12. LIMITATIONS OF THE PRESENT RESEARCH

Several limitations must be acknowledged.

12.1. Dependence on the Selected Volume

The value of each proposed density depends on the selected reference volume.

For an open wave field, there may be no unique natural volume. Researchers must specify the region being measured.

12.2. Mathematical Definition Versus Physical Interpretation

A mathematical quantity can be defined consistently without representing a new physical mechanism.

The proposed quantities are currently volume-normalized descriptors. Their broader physical meaning remains to be established.

12.3. Lack of Experimental Validation

No experimental results are presented in this paper.

The research therefore does not establish that the proposed quantities cause, govern, or independently predict any physical effect.

12.4. Need for Comparison with Existing Models

Any future experimental results should be compared with established theories of acoustics and electromagnetism.

The proposed quantities would provide stronger scientific value if they offered reproducible predictive advantages, improved modelling, or a useful interpretation that could not be obtained as effectively from the existing variables.

13. FUTURE RESEARCH DIRECTIONS

Future research could investigate the following questions:

- Can wavelength density and frequency density be measured consistently across different experimental arrangements?
- How sensitive are the calculated values to the choice of reference volume?
- Can the proposed quantities improve the description of acoustic or optical systems?
- Do they provide useful predictions when room or cavity geometry changes?
- Can they be connected to established observables such as sound pressure, acoustic energy density, optical intensity, or electromagnetic energy density?
- Do they offer a practical advantage over using wavelength, frequency, volume, and geometry separately?

These questions provide a route for evaluating the proposed quantities scientifically without assuming their physical significance in advance.

14. CONCLUSION

This research presents two proposed mathematical quantities:

Wavelength density:

$\lambda_d = \lambda / V$

Frequency density:

$f_d = f / V$

The definitions are dimensionally consistent and can be applied to both sound waves and light waves when the relevant wavelength, frequency, and reference volume are specified.

Using the established wave equation, the following relationship is derived:

$v = \lambda_d f_d V^2$

Equivalently:

$\lambda_d f_d = v / V^2$

These equations follow mathematically from the proposed definitions and the standard wave equation. They do not independently establish a new physical law.

The comparison with established physics shows that wavelength density and frequency density resemble volume-normalized quantities mathematically, but their physical interpretations differ from established mass density and energy density.

For sound, further investigation could compare the proposed quantities with acoustic pressure, resonance, and reverberation. For light, future experiments could compare them with optical modes, intensity distributions, and cavity resonance.

The present research therefore establishes a mathematical framework and identifies possible experimental directions. Whether wavelength density and frequency density offer independent scientific or practical value remains an open question that requires further theoretical analysis and reproducible experiments.

15. REFERENCES

- Bureau International des Poids et Mesures (BIPM). The International System of Units (SI), SI Brochure. Available at: https://www.bipm.org/en/publications/si-brochure

- OpenStax. Physics, Section 14.1, “Speed of Sound, Frequency, and Wavelength.” Available at: https://openstax.org/books/physics/pages/14-1-speed-of-sound-frequency-and-wavelength

- OpenStax. University Physics, Volume 1, Section 17.2, “Speed of Sound.” Available at: https://openstax.org/books/university-physics-volume-1/pages/17-2-speed-of-sound

- Bureau International des Poids et Mesures (BIPM). SI Base Units: Metre. Available at: https://www.bipm.org/en/si-base-units/metre

---

FINAL RESEARCH NOTE

This paper preserves the original definitions proposed by Pawan Upadhyay and examines their mathematical consequences for sound and light waves. It distinguishes established scientific principles from proposed hypotheses and does not claim experimental confirmation or discovery of a new physical law.

The next stage of research should focus on defining measurable experimental conditions and determining whether the proposed quantities provide predictive value beyond established wave physics.

2nd Research Paper

A MATHEMATICAL FRAMEWORK FOR WAVELENGTH DENSITY AND FREQUENCY DENSITY: DIMENSIONAL ANALYSIS AND APPLICATIONS TO ELECTROMAGNETIC WAVES, BULB LIGHT, SUNLIGHT, AND MATERIAL MEDIA

Author: Pawan Upadhyay
Affiliation: Independent Scientist and Independent Researcher

Research Field: Theoretical Physics — Gravitation
Research Areas: Mathematical Physics, Wave Physics, Electromagnetic Radiation, and Optics
Research Period: 2025–2026

ABSTRACT

This research paper presents a mathematical framework for two proposed volume-normalized quantities: wavelength density and frequency density. Wavelength density is defined as wavelength divided by a specified volume, while frequency density is defined as frequency divided by the same volume.

The proposed equations are:

Wavelength density = Wavelength / Volume

Frequency density = Frequency / Volume

The research examines the dimensional consistency of these definitions and derives their relationship with the conventional wave-velocity equation, velocity = wavelength × frequency. The resulting mathematical relationship is:

Velocity = Wavelength density × Frequency density × Volume²

The framework is applied to electromagnetic radiation emitted by an electric bulb and the Sun. Both sources emit electromagnetic radiation, although their spectral distributions and emission mechanisms differ. The study considers bulb light in a small room, a large room, and a defined reference region in an open field, as well as the propagation of light through material media.

The speed of light in a vacuum is exactly 299,792,458 metres per second. Light from a bulb and light from the Sun propagate at this same speed in a vacuum. In material media, the phase velocity of light can depend on the refractive index and, in dispersive materials, on wavelength.

Illustrative calculations demonstrate how the proposed wavelength density and frequency density change when the selected reference volume changes. The research distinguishes these mathematical changes from physical changes in wavelength, frequency, propagation velocity, and optical intensity.

The principal conclusion is that the proposed quantities are mathematically consistent with the conventional wave equation. Their independent physical significance, predictive usefulness, and potential applications require further theoretical investigation and experimental validation.

Keywords: Wavelength density, frequency density, electromagnetic waves, bulb light, sunlight, velocity of light, speed of light in vacuum, refractive index, dimensional analysis, optical dispersion, mathematical physics.

1. INTRODUCTION

Waves are fundamental to the description of physical phenomena. Sound waves propagate through material media, whereas electromagnetic waves can propagate through a vacuum as well as through suitable material media.

Visible light emitted by an electric bulb and visible light received from the Sun are both electromagnetic radiation. Their sources differ, and their spectral distributions can differ, but both are governed by the principles of electromagnetic wave propagation.

The conventional relationship between wave velocity, wavelength, and frequency is:

Velocity = Wavelength × Frequency

$v = \lambda \times f$

For electromagnetic radiation in a vacuum, this relationship becomes:

Speed of light in vacuum = Wavelength × Frequency

$c = \lambda \times f$

The exact value of the speed of light in a vacuum is:

$c = 299{,}792{,}458$ m/s

This paper proposes two additional mathematical quantities that normalize wavelength and frequency by the volume of a specified spatial region.

The proposed quantities are called wavelength density and frequency density.

The central research question is whether these volume-normalized quantities can provide a useful mathematical framework for comparing wave properties across different spatial regions.

The investigation applies the proposed definitions to electromagnetic radiation from an electric bulb and the Sun, while distinguishing mathematical normalization from the established physical behaviour of light.

2. RESEARCH OBJECTIVES

The objectives of this research are:

1. To define wavelength density and frequency density mathematically.
2. To establish the SI units and dimensions of the proposed quantities.
3. To derive their relationship with the conventional wave-velocity equation.
4. To investigate the effect of changing the selected reference volume.

5. To apply the framework to bulb light in small rooms, large rooms, and open-field regions.
6. To compare the electromagnetic nature and propagation of bulb light and sunlight.
7. To distinguish the speed of light in a vacuum from phase velocity in material media.
8. To investigate the potential usefulness of the proposed quantities in acoustics and optics.
9. To identify scientific limitations and propose directions for experimental research.

3. PROPOSED MATHEMATICAL DEFINITIONS

3.1. Wavelength Density

Wavelength density is defined in this research as the wavelength divided by the volume of a specified region.

Equation:

Wavelength density = Wavelength / Volume

Symbolically:

$\lambda_d = \lambda / V$

Where:

λ_d = Wavelength density

λ = Wavelength of the wave

V = Volume of the specified region

The SI unit of wavelength is the metre, and the SI unit of volume is the cubic metre.

Therefore:

Unit of wavelength density = m / m^3

Unit of wavelength density = m^{-2}

The dimensional formula is:

Dimension of wavelength density = L^{-2}

3.2. Frequency Density

Frequency density is defined as the frequency divided by the volume of the same specified region.

Equation:

Frequency density = Frequency / Volume

Symbolically:

$f_d = f / V$

Where:

f_d = Frequency density

f = Frequency of the wave

V = Volume of the specified region

The SI unit of frequency is hertz, equivalent to inverse seconds.

Therefore:

Unit of frequency density = Hz/m^3

Equivalent SI units = $s^{-1}\ m^{-3}$

The dimensional formula is:

Dimension of frequency density = $T^{-1}L^{-3}$

3.3. Meaning of the Selected Volume

The volume V must be specified before either proposed quantity can be calculated.

Examples include:

- The volume of a small room containing a bulb.
- The volume of a large room containing a light source.
- The volume of a defined optical chamber.
- A specified reference region in an open field.
- A defined region used to analyse a sound field.

The selected volume is part of the mathematical definition. Different reference volumes produce different numerical values even when the original wavelength and frequency remain unchanged.

In this paper, the term “density” describes volume normalization. It does not automatically establish the same physical interpretation as mass density or energy density.

4. DIMENSIONAL ANALYSIS

Dimensional analysis determines whether the proposed quantities and equations have consistent dimensions.

4.1. Wavelength Density

Wavelength has dimension L.

Volume has dimension L^3.

Therefore:

Dimension of wavelength density = L / L^3

Dimension of wavelength density = L^{-2}

The SI unit is m^{-2}.

4.2. Frequency Density

Frequency has dimension T^{-1}.

Volume has dimension L^3.

Therefore:

Dimension of frequency density = T^{-1} / L^3

Dimension of frequency density = $T^{-1}L^{-3}$

The SI unit is Hz/m^3.

4.3. Summary of Dimensions

Wavelength:

- SI unit: m
- Dimension: L

Frequency:

- SI unit: Hz
- Dimension: T^{-1}

Volume:

- SI unit: m^3
- Dimension: L^3

Wavelength density:

- SI unit: m^{-2}
- Dimension: L^{-2}

Frequency density:

- SI unit: Hz/m^3
- Dimension: $T^{-1}L^{-3}$

Velocity:

- SI unit: m/s
- Dimension: LT^{-1}

The proposed definitions are dimensionally consistent.

However, dimensional consistency alone does not establish that a mathematical quantity represents an independent physical mechanism or a previously unknown phenomenon.

5. DERIVATION OF THE PROPOSED VELOCITY EQUATION

The conventional wave-velocity equation is:

Velocity = Wavelength × Frequency

$v = \lambda \times f$

The proposed wavelength-density equation is:

$\lambda_d = \lambda / V$

Rearranging:

$\lambda = \lambda_d \times V$

The proposed frequency-density equation is:

$f_d = f / V$

Rearranging:

$f = f_d \times V$

Substituting both expressions into the conventional wave-velocity equation gives:

$v = (\lambda_d \times V) \times (f_d \times V)$

Therefore:

$v = \lambda_d \times f_d \times V^2$

This is the principal derived equation of the proposed framework.

It can also be expressed as:

Wavelength density × Frequency density = Velocity / Volume²

Symbolically:

$\lambda_d \times f_d = v / V^2$

5.1. Dimensional Verification

The dimensions on the right-hand side of the proposed velocity equation are:

Dimension of wavelength density × Dimension of frequency density × Dimension of volume squared

$= L^{-2} \times T^{-1}L^{-3} \times L^{6}$

Simplifying:

$= L^{-2} \times T^{-1} \times L^{-3} \times L^{6}$

$= LT^{-1}$

This is the dimension of velocity.

Therefore, the proposed velocity equation is dimensionally consistent.

5.2. Scientific Interpretation

The equation follows directly from the proposed definitions and the conventional wave equation.

It allows the original velocity to be expressed in terms of the two volume-normalized quantities and the selected volume.

It does not independently establish a new law of wave propagation.

To demonstrate additional scientific value, the framework would need to provide a useful physical interpretation or a testable prediction beyond what can already be obtained from wavelength, frequency, volume, and conventional wave theory.

6. ELECTROMAGNETIC NATURE OF BULB LIGHT AND SUNLIGHT

6.1. Common Physical Nature

Light emitted by an electric bulb and light emitted by the Sun are both electromagnetic radiation.

Electromagnetic waves consist of coupled electric and magnetic fields that propagate through space.

Both sources can emit visible light, and their radiation can contain overlapping wavelength ranges.

However, their emission mechanisms and spectral distributions differ.

An incandescent bulb produces light through thermal radiation from a heated filament. Other bulb technologies, including LEDs and fluorescent lamps, produce light through different physical processes.

The Sun emits radiation through thermal processes in its hot atmosphere, with its energy ultimately supplied by nuclear fusion in its interior.

These differences affect the emitted spectrum and intensity. They do not imply that bulb light and sunlight have different propagation speeds in a vacuum.

6.2. Speed of Bulb Light in a Vacuum

The speed of light in a vacuum is:

$c = 299{,}792{,}458$ m/s

For a particular bulb-light component:

Velocity = Wavelength × Frequency

$v = \lambda \times f$

For light in a vacuum:

$v = c$

Therefore:

$\lambda \times f = 299{,}792{,}458$ m/s

6.3. Speed of Sunlight in a Vacuum

For a particular sunlight component:

Velocity = Wavelength × Frequency

$v = \lambda \times f$

For light in a vacuum:

$v = c$

Therefore:

$\lambda \times f = 299{,}792{,}458$ m/s

6.4. Comparison

The vacuum propagation speed of bulb light and sunlight is the same.

Their wavelengths and frequencies can differ, but for each individual spectral component, wavelength multiplied by frequency equals the speed of light in a vacuum.

The source of the light does not independently determine its vacuum propagation speed.

7. WAVELENGTH DENSITY OF BULB LIGHT IN A SMALL ROOM

This section illustrates the proposed wavelength-density framework using a representative wavelength of visible light.

For the numerical example, the selected wavelength is 550 nanometres.

Conversion into metres:

Wavelength = 550 nm

Wavelength = 550×10^{-9} m

Wavelength = 5.50×10^{-7} m

The selected volume of the small room is assumed to be 30 m^3.

These values are illustrative assumptions rather than measurements from an actual bulb or room.

7.1. Calculation of Wavelength Density

Wavelength density = Wavelength / Volume

Wavelength density = $(5.50 \times 10^{-7}) / 30$

Therefore:

Wavelength density ≈ 1.833×10^{-8} m^{-2}

7.2. Calculation of Frequency

For light in a vacuum:

Frequency = Speed of light / Wavelength

Frequency = $299{,}792{,}458 / (5.50 \times 10^{-7})$

Therefore:

Frequency ≈ 5.451×10^{14} Hz

This is the vacuum frequency associated with the selected wavelength.

7.3. Calculation of Frequency Density

Frequency density = Frequency / Volume

Frequency density = $(5.451 \times 10^{14}) / 30$

Therefore:

Frequency density ≈ 1.817×10^{13} Hz/m^3

7.4. Velocity Calculation

Using the proposed equation:

Velocity = Wavelength density × Frequency density × $Volume^2$

Substituting the unrounded values gives approximately:

Velocity = 299,792,458 m/s

This is the result for the vacuum wavelength and frequency used in the example.

It is not a direct measurement of the phase velocity inside a room filled with air.

8. WAVELENGTH DENSITY OF BULB LIGHT IN A LARGE ROOM

Now consider the same wavelength component in a room with an assumed volume of 300 m^3.

Wavelength = 5.50×10^{-7} m

Volume = 300 m^3

8.1. Wavelength Density

Wavelength density = Wavelength / Volume

Wavelength density = $(5.50 \times 10^{-7}) / 300$

Therefore:

Wavelength density ≈ 1.833×10^{-9} m^{-2}

8.2. Frequency Density

Frequency ≈ 5.451×10^{14} Hz

Frequency density = Frequency / Volume

Frequency density = $(5.451 \times 10^{14}) / 300$

Therefore:

Frequency density ≈ 1.817×10^{12} Hz/m^3

8.3. Velocity Calculation

Using the proposed equation:

Velocity = Wavelength density × Frequency density × $Volume^2$

Using unrounded values:

Velocity = 299,792,458 m/s

The calculated wavelength density and frequency density are each one-tenth of their corresponding values for the small room.

The velocity remains unchanged because the same wavelength and frequency have been used.

9. WAVELENGTH DENSITY OF BULB LIGHT IN AN OPEN FIELD

An open field has no unique natural volume. A defined reference region must be selected for this calculation.

For illustration, the reference volume is assumed to be 3000 m^3.

Wavelength = 5.50×10^{-7} m

Volume = 3000 m^3

9.1. Wavelength Density

Wavelength density = Wavelength / Volume

Wavelength density = $(5.50 \times 10^{-7}) / 3000$

Therefore:

Wavelength density ≈ 1.833×10^{-10} m^{-2}

9.2. Frequency Density

Frequency density = Frequency / Volume

Frequency density = $(5.451 \times 10^{14}) / 3000$

Therefore:

Frequency density ≈ 1.817×10^{11} Hz/m^3

9.3. Velocity Calculation

Velocity = Wavelength density × Frequency density × Volume²

Using unrounded values:

Velocity = 299,792,458 m/s

The result demonstrates the mathematical consistency of the proposed equation when the original vacuum wavelength and frequency remain unchanged.

The smaller calculated wavelength density does not imply that light physically loses wavelength or speed because the selected reference region is larger.

10. COMPARATIVE ANALYSIS OF SMALL ROOM, LARGE ROOM, AND OPEN FIELD

The illustrative calculations are summarized below.

Small room

Selected volume: 30 m^3

Wavelength density: approximately $1.833 \times 10^{-8}\ m^{-2}$

Frequency density: approximately $1.817 \times 10^{13}\ Hz/m^3$

Calculated vacuum velocity: 299,792,458 m/s

Large room

Selected volume: 300 m^3

Wavelength density: approximately $1.833 \times 10^{-9}\ m^{-2}$

Frequency density: approximately $1.817 \times 10^{12}\ Hz/m^3$

Calculated vacuum velocity: 299,792,458 m/s

Open-field reference region

Selected volume: 3000 m^3

Wavelength density: approximately $1.833 \times 10^{-10}\ m^{-2}$

Frequency density: approximately $1.817 \times 10^{11}\ Hz/m^3$

Calculated vacuum velocity: 299,792,458 m/s

The results show that, when wavelength and frequency are held constant, the proposed wavelength density and frequency density decrease inversely with the selected volume.

When the volume increases tenfold, each proposed density decreases tenfold.

Their product decreases by a factor of one hundred, while the volume-squared term increases by a factor of one hundred.

Consequently, the derived equation reproduces the original velocity.

These results follow from the mathematical definitions. They do not demonstrate that the physical speed of light depends on the volume selected for analysis.

11. COMPARISON OF BULB LIGHT AND SUNLIGHT IN MATERIAL MEDIA

The speed of light in a material medium can differ from its speed in a vacuum.

For a transparent medium under appropriate conditions, the phase velocity can be expressed as:

Phase velocity = Speed of light in vacuum / Refractive index

$v = c / n$

Where:

v = Phase velocity in the material

c = Speed of light in a vacuum

n = Refractive index at the relevant wavelength

11.1. Role of the Refractive Index

The refractive index describes how the phase velocity in a material compares with the speed of light in a vacuum.

In a dispersive medium, the refractive index depends on wavelength.

Therefore, two electromagnetic waves with different wavelengths can have different phase velocities in the same material.

This is a property of the interaction between electromagnetic radiation and the material.

It is not caused merely by the light having originated from a bulb or from the Sun.

11.2. Illustrative Comparison in Water

Consider two representative wavelengths propagating through water under approximately the same conditions.

Example A: Green light

Wavelength: 550 nm

Approximate refractive index: 1.334

Phase velocity = 299,792,458 / 1.334

Phase velocity ≈ 224.7 million m/s

Example B: Red light

Wavelength: 650 nm

Approximate refractive index: 1.331

Phase velocity = 299,792,458 / 1.331

Phase velocity ≈ 225.3 million m/s

These approximate values illustrate wavelength-dependent phase velocity in water.

Green and red wavelength components can occur in sunlight and in light from suitable bulbs. The calculation compares wavelength components, not exclusive categories of light sources.

For an actual experiment, the refractive index should be obtained for the specific wavelength and material conditions.

11.3. Scientific Interpretation

If bulb light and sunlight contain components of the same wavelength and both components propagate through the same homogeneous material under the same conditions, their phase velocities are the same.

If their wavelengths differ and the material is dispersive, their phase velocities may differ.

Therefore, the scientifically relevant comparison is between the wavelengths, frequencies, refractive indices, and propagation conditions of the selected electromagnetic wave components.

12. APPLYING THE PROPOSED DENSITY EQUATIONS TO MATERIAL MEDIA

The proposed equations are:

Wavelength density = Wavelength / Volume

Frequency density = Frequency / Volume

Velocity = Wavelength density × Frequency density × Volume²

For light travelling through a material, the wavelength used must be the wavelength in that material.

The frequency of a light component ordinarily remains unchanged when it crosses a stationary boundary between transparent media, while its wavelength changes with the phase velocity.

The proposed velocity equation reproduces the conventional phase velocity when the wavelength and frequency refer consistently to the same wave component in the material.

However, the proposed density definitions do not independently determine the refractive index or explain why the phase velocity changes with wavelength.

Those effects require established electromagnetic theory and material-specific optical data.

13. DISTINGUISHING MATHEMATICAL NORMALIZATION FROM PHYSICAL CHANGE

This distinction is central to the interpretation of the research.

Changing only the reference volume in a calculation changes the proposed wavelength density and frequency density.

Physically changing the dimensions of a room or optical cavity can also change the electromagnetic field, depending on the boundary conditions and the properties of the surfaces.

These situations must not be confused.

A larger room does not automatically increase the wavelength of the light or decrease its propagation speed.

A smaller room does not automatically increase the physical concentration of electromagnetic energy merely because the calculated wavelength density is greater.

The proposed equations alone do not determine:

- Optical intensity.
- Illuminance.
- Luminous flux.

- Electromagnetic energy density.
- The spatial distribution of light.
- The refractive index of a material.
- The amount of light absorbed or reflected.

These properties require separate definitions, measurements, or established optical models.

14. POTENTIAL EXPERIMENTAL RESEARCH

Further research could investigate whether wavelength density and frequency density provide useful information beyond conventional wave physics.

A possible investigation would involve:

1. Selecting a bulb with a measured emission spectrum.
2. Identifying specific wavelength components in the bulb's emission.
3. Identifying corresponding wavelength components in sunlight.
4. Defining reference volumes for a small room, a large room, and an open-field region.
5. Calculating the proposed wavelength densities and frequency densities.
6. Determining the refractive index of the relevant material at each wavelength.
7. Calculating phase velocity using the conventional optical relationship.
8. Comparing theoretical results with independent optical measurements.
9. Repeating calculations using different reference volumes without changing the optical field.
10. Conducting separate tests in which the physical environment or material changes.
11. Investigating whether the proposed quantities provide additional predictive information.

The experimental design should distinguish mathematical changes caused by volume normalization from physical changes caused by material properties, optical boundaries, or the source spectrum.

No experimental result should be interpreted as evidence of a new physical law without appropriate controls, reproducibility, and comparison with established theory.

15. SCIENTIFIC LIMITATIONS

The present research has several limitations.

First, wavelength density and frequency density are proposed mathematical quantities defined by dividing wavelength and frequency by a specified volume.

Second, the room volumes and open-field reference volume used in the numerical examples are illustrative assumptions.

Third, a wavelength of 550 nm represents one component of visible light and does not represent the entire spectrum of an ordinary white bulb or sunlight.

Fourth, the numerical velocity calculations using 299,792,458 m/s apply to light in a vacuum. Light propagating through air, water, glass, or another material must be analysed using the relevant propagation velocity and wavelength.

Fifth, the material-medium example uses approximate refractive-index values for illustration. Accurate experimental work must specify the wavelength and material conditions.

Sixth, the proposed equations do not independently calculate optical intensity, electromagnetic energy density, or the spatial distribution of light.

Finally, the mathematical consistency of the equations does not establish that wavelength density and frequency density are independent physical quantities with predictive value beyond existing optical theory.

16. FUTURE RESEARCH DIRECTIONS

Future research should address the following questions:

1. Can wavelength density and frequency density be assigned operational physical meanings beyond volume normalization?
2. Can these quantities provide useful comparisons of optical fields across spatial regions?
3. Can they be related meaningfully to established quantities such as electromagnetic energy density or optical mode density?
4. Can experiments identify predictions that cannot already be obtained from conventional electromagnetic theory?
5. How should the reference volume be defined for electromagnetic radiation propagating through unbounded space?
6. Can the framework be extended to include wavelength-dependent refractive indices in material media?
7. Does the proposed framework provide any additional insight when comparing electromagnetic radiation from different sources?

Answering these questions would help determine whether the framework is a useful mathematical representation or a basis for a broader physical model.

17. CONCLUSION

This research proposes a mathematical framework for wavelength density and frequency density and applies it to electromagnetic radiation from an electric bulb and the Sun.

The proposed definitions are:

Wavelength density = Wavelength / Volume

Frequency density = Frequency / Volume

Combining these definitions with the conventional wave-velocity equation gives:

Velocity = Wavelength density × Frequency density × Volume²

Dimensional analysis confirms that the derived expression has the correct dimensions of velocity.

The research also establishes an important physical distinction: bulb light and sunlight are both electromagnetic radiation and propagate at the same speed in a vacuum, exactly 299,792,458 metres per second. Their wavelength distributions may differ, but their different sources do not independently produce different vacuum propagation speeds.

In material media, phase velocity can depend on wavelength through the refractive index. Thus, different wavelength components from bulb light and sunlight may have different phase velocities in a dispersive material.

The numerical comparisons involving a small room, a large room, and an open-field reference region demonstrate how the proposed wavelength density and frequency density change when the selected volume changes. They do not establish that the physical speed, wavelength, or intensity of light changes merely because the reference volume is different.

The proposed velocity equation remains a mathematical consequence of the definitions and the conventional wave equation. Its scientific significance depends on whether further theoretical or experimental research establishes an independent physical interpretation or useful predictive capability.

Research status: The framework is a mathematical proposal supported by dimensional analysis and illustrative calculations. Its independent physical significance and experimental validation remain open questions for future research.

REFERENCES

1. Halliday, D., Resnick, R., and Walker, J. *Fundamentals of Physics*. Wiley. General reference for wave motion, wavelength, frequency, and wave velocity.

2. Hecht, E. *Optics*. Pearson. Reference for electromagnetic radiation, refractive index, optical dispersion, and light propagation in materials.

3. Kinsler, L. E., Frey, A. R., Coppens, A. B., and Sanders, J. V. *Fundamentals of Acoustics*. Wiley. Reference for wave propagation and acoustic theory.

4. International Bureau of Weights and Measures (BIPM). *The International System of Units (SI Brochure)*. Reference for SI units and physical constants.

5. Standard optical reference data for the refractive index of water at specified wavelengths and material conditions.

RESEARCH STATUS STATEMENT

This paper presents a proposed mathematical framework based on the author's definitions of wavelength density and frequency density. The derivations and numerical examples illustrate the consequences of these definitions and their relationship to conventional wave physics.

No new experimental results are claimed. Further theoretical development and experimental validation are required to determine whether the proposed quantities provide independent physical significance or predictive value beyond established scientific models.

Separate Note: The Physical Properties and Physical Nature of Waves Remain Unchanged

The mathematical definitions of wavelength density ($\lambda_d = \lambda / V$) and frequency density ($f_d = f / V$) do not, by themselves, change the physical properties or physical nature of a wave. These quantities are mathematical descriptions obtained by relating wavelength and frequency to a defined reference volume.

Both bulb light and sunlight are electromagnetic waves. Changing the reference volume from a small room to a large room or an open-field region changes the calculated values of wavelength density and frequency density, provided the wavelength and frequency remain fixed. However, this mathematical change does not mean that the electromagnetic wave itself has acquired a different physical nature.

The fundamental characteristics of a wave—such as its electromagnetic nature, wavelength, frequency, polarization, and propagation behavior—must be distinguished from quantities defined through a reference volume. In a uniform medium, changing only the reference volume does not, by itself, change the wave's intrinsic properties.

A distinction is also necessary when a wave enters a material medium. Its propagation speed and wavelength may change according to the properties of the medium, while its frequency generally remains constant at a stationary boundary between media. In a dispersive medium, different wavelength components may propagate at different phase velocities. These changes

result from the interaction between the wave and the medium, not merely from calculating wavelength density or frequency density.

Therefore, wavelength density and frequency density should be understood as volume-normalized mathematical quantities. Their calculated values may change with the chosen reference volume, while the wave's underlying physical nature remains the same unless actual physical conditions or interactions alter its properties.

Wavelength Density of Bulb Light in a Small Room, a Large Room, and an Open Field

Author: Pawan Upadhyay

Research Area: Mathematical Physics, Wave Physics, and Optics

1. Introduction

An electric bulb emits light that propagates through the surrounding space. When a bulb is placed in a small room, a large room, or an open field, the volume selected for mathematical analysis can differ significantly.

This research section applies the proposed wavelength-density equation to bulb light in these three environments. The objective is to investigate how wavelength density changes when the selected volume increases, while the wavelength of the light remains constant.

The analysis follows the proposed mathematical framework for wavelength density developed in the research paper, "A Mathematical Framework for Wavelength Density and Frequency Density: Dimensional Analysis and Applications to Sound and Light Waves."

2. Proposed Mathematical Definition

Wavelength density is defined as:

Wavelength density = Wavelength / Volume

Symbolically:

$\lambda_d = \lambda / V$

Where:

λ_d = Wavelength density

λ = Wavelength of light

V = Volume of the selected region

The SI unit of wavelength is the metre (m), and the SI unit of volume is the cubic metre (m^3).

Therefore:

Unit of wavelength density = m / m^3

Unit of wavelength density = m^{-2}

The proposed wavelength density is a volume-normalized mathematical quantity. Its independent physical significance requires further investigation.

3. Assumptions for the Numerical Investigation

For this illustrative mathematical comparison, the following assumptions are used:

1. The same representative wavelength of light is considered in all three environments.
2. The wavelength remains constant during the calculations.
3. The selected volumes are 30 m^3, 300 m^3, and 3000 m^3.
4. The selected volumes represent a small room, a large room, and a defined reference region in an open field, respectively.
5. The calculations examine the effect of the selected volume on wavelength density, not the actual intensity or energy distribution of light.

For this example, the selected wavelength is 550 nanometres.

Conversion into metres:

Wavelength = 550 nm

Wavelength = 550×10^{-9} m

Wavelength = 0.00000055 m

This wavelength represents one component of visible light. An ordinary white bulb emits a range of wavelengths, so a complete investigation of its light would require consideration of its emission spectrum.

4. Case A: Wavelength Density of Bulb Light in a Small Room

Suppose an electric bulb is placed in a small room with a volume of 30 m^3.

Given:

Wavelength = 5.50×10^{-7} m

Volume = 30 m^3

According to the proposed equation:

Wavelength density = Wavelength / Volume

Substituting the values:

Wavelength density = $(5.50 \times 10^{-7}) / 30$

Therefore:

Wavelength density = 1.833×10^{-8} m^{-2}

Thus, the calculated wavelength density for the selected wavelength in the small room is approximately 0.00000001833 m^{-2}.

This result is obtained by dividing the selected wavelength by the volume of the small room.

5. Case B: Wavelength Density of Bulb Light in a Large Room

Now consider the same wavelength of light in a large room with a volume of 300 m^3.

Given:

Wavelength = 5.50×10^{-7} m

Volume = 300 m^3

Using the proposed equation:

Wavelength density = Wavelength / Volume

Substituting the values:

Wavelength density = $(5.50 \times 10^{-7}) / 300$

Therefore:

Wavelength density = $1.833 \times 10^{-9}\ m^{-2}$

Thus, the calculated wavelength density in the large room is approximately 0.000000001833 m^{-2}.

The selected volume of the large room is ten times the volume of the small room.

Because the wavelength remains constant, the calculated wavelength density in the large room is one-tenth of the value obtained for the small room.

This result follows directly from the proposed mathematical definition.

6. Case C: Wavelength Density of Bulb Light in an Open Field

An open field does not have a unique natural volume. Therefore, a specific reference region must be defined before wavelength density can be calculated.

For this illustrative example, suppose the selected reference region in the open field has a volume of 3000 m^3.

Given:

Wavelength = 5.50×10^{-7} m

Volume = 3000 m^3

Using the proposed equation:

Wavelength density = Wavelength / Volume

Substituting the values:

Wavelength density = $(5.50 \times 10^{-7}) / 3000$

Therefore:

Wavelength density = $1.833 \times 10^{-10}\ m^{-2}$

Thus, the calculated wavelength density in the selected open-field region is approximately 0.0000000001833 m^{-2}.

The reference volume is ten times the volume of the large room and one hundred times the volume of the small room.

Consequently, for the same wavelength, the calculated wavelength density in the open-field reference region is one-hundredth of the value obtained for the small room.

This mathematical result does not establish that the physical wavelength of light decreases in an open field.

7. Comparative Analysis of the Three Environments

The calculated results are summarized below.

Environment 1: Small room

Selected volume = 30 m^3

Wavelength = 550 nm

Wavelength density = 1.833×10^{-8} m^{-2}

Environment 2: Large room

Selected volume = 300 m^3

Wavelength = 550 nm

Wavelength density = 1.833×10^{-9} m^{-2}

Environment 3: Open-field reference region

Selected volume = 3000 m^3

Wavelength = 550 nm

Wavelength density = 1.833×10^{-10} m^{-2}

The comparison demonstrates that the calculated wavelength density decreases as the selected volume increases, provided the wavelength remains constant.

When the selected volume increases tenfold, wavelength density decreases tenfold.

When the selected volume increases one hundredfold, wavelength density decreases one hundredfold.

8. Mathematical Relationship Between Wavelength Density and Volume

The proposed equation is:

Wavelength density = Wavelength / Volume

If the wavelength remains constant, wavelength density is inversely proportional to the selected volume.

This relationship can be expressed as:

Wavelength density is proportional to 1 / Volume.

For two selected regions:

Wavelength density in Region 1 / Wavelength density in Region 2 = Volume of Region 2 / Volume of Region 1.

This equation provides a mathematical comparison between wavelength density values calculated for different reference volumes.

For example, if the second region has ten times the volume of the first region, its calculated wavelength density will be one-tenth of the first region's value, provided the wavelength is unchanged.

The relationship follows directly from the proposed definition and does not independently establish a new law of light propagation.

9. Distinction Between Calculated Wavelength Density and Physical Light Distribution

An important scientific distinction must be maintained between the proposed wavelength density and the actual physical behaviour of bulb light.

First, changing the selected reference volume in a calculation does not, by itself, change the physical wavelength of light.

Second, the physical distribution of light in a small room, a large room, and an open field can differ because of distance from the bulb, the bulb's emission pattern, surface reflection, absorption, obstructions, and other optical conditions.

Third, the proposed wavelength-density equation does not independently calculate light intensity, luminous flux, electromagnetic energy density, or the distribution of optical energy.

Fourth, an open field requires a defined reference region because it does not have a unique natural volume for this calculation.

Therefore, the numerical differences obtained in this section demonstrate volume normalization. They should not be interpreted as direct measurements of the physical concentration or intensity of light.

10. Potential Experimental Investigation

Further research could investigate whether the proposed wavelength density provides useful information when considered alongside established optical measurements.

A possible investigation could involve the following steps:

1. Select a bulb with a known or measured emission spectrum.
2. Determine the wavelength or wavelengths to be analysed.
3. Define the volume of a small room, a large room, and a specified open-field region.
4. Calculate wavelength density using the proposed equation.
5. Measure relevant optical properties, such as illuminance and the spatial distribution of light.
6. Record the distances, environmental conditions, and surface properties associated with each measurement.
7. Compare the calculated wavelength densities with the measured optical properties.
8. Investigate whether wavelength density provides any predictive information beyond established optical models.

The experiment should distinguish between changes caused by selecting a different reference volume and changes caused by physically altering the environment.

Any claim of additional physical significance would require reproducible evidence and a clear theoretical explanation.

11. Scientific Limitations

The present investigation has the following limitations:

1. The selected wavelength of 550 nm is illustrative and is not claimed to be the measured wavelength of a particular bulb.
2. The volumes used for the small room, large room, and open-field region are assumed values for mathematical comparison.
3. The calculations do not include measurements of bulb output, illuminance, optical intensity, or electromagnetic energy density.
4. The proposed wavelength density depends on the selected reference volume.

5. The calculations do not establish that wavelength density is an independently measurable physical density in the same sense as mass density or energy density.
6. No new experimental results are claimed.

Further theoretical and experimental research is required to establish whether the proposed quantity has independent scientific usefulness.

12. Conclusion

This section applies the proposed wavelength-density equation to bulb light in a small room, a large room, and a defined open-field reference region.

Using a representative wavelength of 550 nm, the calculated wavelength density is approximately 1.833×10^{-8} m^{-2} for a volume of 30 m^3, 1.833×10^{-9} m^{-2} for a volume of 300 m^3, and 1.833×10^{-10} m^{-2} for a volume of 3000 m^3.

The results demonstrate the inverse mathematical relationship between the proposed wavelength density and the selected volume when wavelength remains constant.

The calculations do not imply that light physically loses wavelength or intensity merely because the reference volume increases. Instead, they demonstrate how the proposed volume-normalized quantity changes with the chosen spatial region.

Future research should investigate whether wavelength density can be associated with an independently measurable optical property or provide useful predictive information beyond established optical theory.

Research status: Mathematical illustration based on the proposed definition. Experimental validation and independent physical significance remain to be established.

---

1 Comparison of Bulb Light and Sunlight

Property	**Bulb Light**	**Sunlight**
Source	Electric bulb	Sun

Speed in a vacuum	299,792,458 m/s	299,792,458 m/s
Wavelengths emitted	Depends on the bulb type	Broad spectrum of wavelengths
Speed in a material medium	Depends on the medium and wavelength	Depends on the medium and wavelength

In a vacuum, light from both sources travels at the same speed, regardless of its source or intensity.

However, in a material such as glass or another optical medium, the propagation speed can depend on the medium and, in dispersive materials, on the wavelength.

Applying velocity equation

My Research paper proposes:

* Wavelength density = Wavelength / Volume

* Frequency density = Frequency / Volume

* Velocity = Wavelength density × Frequency density × Volume²

In symbols written as plain-text equations:

$v = \lambda_d \times f_d \times V^2$

For bulb light and sunlight, the equation becomes:

- **Bulb light velocity** = Bulb wavelength density × Bulb frequency density × Volume²
- **Sunlight velocity** = Sunlight wavelength density × Sunlight frequency density × Volume²

If both waves propagate in a vacuum, both calculations must reproduce the same speed when the wavelength, frequency, and density values are defined consistently.

An important research distinction: The wavelengths and frequencies of bulb light and sunlight can differ, but their product remains equal to the speed of light in a vacuum for each individual spectral component.