

Matrices and Numerical Linear Algebra

Matrices – Dense and Sparse

- Dense: No zero elements (or almost none)

$$\begin{bmatrix} 3.24 & 5.76 & -12.3 & 6.11 \\ -7.55 & 4.32 & -5.02 & 4.48 \\ 3.20 & 7.19 & 12.12 & 0.24 \\ -3.14 & 8.27 & -9.81 & -2.11 \end{bmatrix}$$

- Sparse: Many zero elements

$$\begin{bmatrix} 3.24 & 0 & 0 & 6.11 \\ 0 & 0 & -5.02 & 0 \\ 3.20 & 0 & 12.12 & 0 \\ -3.14 & 0 & 0 & 0 \end{bmatrix}$$

Why is there a distinction?
Storage and performance!

Dense matrices: Image processing





Image is a matrix, every element corresponds to a pixel (black/white level).

Sparse: Structural Analysis



- For bridge in equilibrium (i.e. not collapsing):
 - Sum of forces at each joint = 0
 - Sum of moments at each joint = 0

Force balance equation is sparse

$$\begin{pmatrix}
 1 & 1/2 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sqrt{3}/2 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & 0 & -1 & 0 & -1/2 & 1/2 & 1 & 0 & 0 & 0 \\
 0 & 0 & 0 & 0 & \sqrt{3}/2 & \sqrt{3}/2 & 0 & 0 & 0 & 0 \\
 0 & 0 & 0 & 0 & 0 & 0 & -1 & -1/2 & 0 & 0 \\
 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sqrt{3}/2 & 1 & 0 \\
 0 & -1/2 & 0 & 0 & 1/2 & 0 & 0 & 0 & 0 & 1 \\
 0 & -\sqrt{3}/2 & 0 & 0 & -\sqrt{3}/20 & 0 & 0 & 0 & 0 & 0 \\
 0 & 0 & 0 & 0 & 0 & -1/2 & 0 & 1/2 & 0 & -1 \\
 0 & 0 & 0 & 0 & 0 & -\sqrt{3}/2 & 0 & -\sqrt{3}/2 & 0 & 0
 \end{pmatrix}
 \begin{pmatrix}
 R_1 \\
 T_1 \\
 T_2 \\
 R_2 \\
 T_3 \\
 T_4 \\
 T_5 \\
 T_6 \\
 R_3 \\
 T_7
 \end{pmatrix}
 =
 \begin{pmatrix}
 F_{1x} \\
 F_{1y} \\
 F_{2x} \\
 F_{2y} \\
 F_{3x} \\
 F_{3y} \\
 F_{4x} \\
 F_{4y} \\
 F_{5x} \\
 F_{5y}
 \end{pmatrix}$$

Matrix is sparse because each link pin interacts with its neighbors only.

What matrices are dense or sparse?

- Dense: Image processing, video.
- Sparse: Statics.
- Dense: Time series – audio processing, stock price analysis.
- Sparse: Electronic circuit analysis.
- Sparse: Solving PDEs.
- Sparse: Graph theory.


Example: population dynamics



- Consider the domestic house fly.
- Lifespan is around 15 – 30 days.
- Model of fly's life: Consider weekly probability of death.


This population model is a Markov process – a **graph** of transitions

- Transition matrix
 - Notes are states
 - Edges are probabilities to jump
- Markov process



Example: housefly
life expectancy

Markov Matrix



$$\begin{array}{c} \text{Next} \\ \text{state} \\ \text{(row)} \end{array} \begin{array}{c} \text{Current state (col)} \\ \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & .9 & 0 & 0 & 0 & 0 \\ 0 & 0 & .8 & 0 & 0 & 0 \\ 0 & 0 & 0 & .7 & 0 & 0 \\ 0 & .1 & .2 & .3 & 1 & 1 \end{bmatrix} \end{array} \begin{bmatrix} b \\ w_1 \\ w_2 \\ w_3 \\ w_4 \\ d \end{bmatrix}$$

This matrix is sparse!

Storage of matrices in memory

- Why do I care about sparse vs. dense?
 - Because they are stored in totally different ways in memory.
 - When you start to scale up to large problems (“big data”), thinking about dealing with your memory becomes important.
- We'll also find later that certain algorithms are more performant with sparse matrices.



Memory as linear address space

- Memory is 1D array of storage locations
- Locations are each 8 bytes wide
- Each byte has an address (32 or 64 bit)
- Longer words occupy successive bytes
 - Endianness

A = 'cat'

⋮	⋮
2430	45
2431	A
2432	f
2433	12
A → 2434	c
2435	a
2436	t
2437	00
⋮	⋮

Storage of floating point scalars


- Consider 32 bit float (single) representation
 $B = -5.625$
- Hex representation:
C0B40000
- Word starts at address 2432
- Intel is “little endian”.

$B = \text{float}(-5.625)$

⋮	⋮
2430	45
2431	A
2432 → B	00
2433	00
2434	B4
2435	C0
2436	t
2437	00
⋮	⋮


Storage of vectors

- Vector elements are stored sequentially as words in memory
- In this case, the words are 16 bits long
- Note storage is little endian



Locality of Reference

- Computations frequently use values in memory which lie close to each other.
- Smart compilers exploit this fact by loading memory blocks up to 1KB into cache for faster access.



Storage of Matrices?


- Row major order

$$\begin{bmatrix} 3.24 & 5.76 & -12.3 & 6.11 \\ -7.55 & 4.32 & -5.02 & 4.48 \\ 3.20 & 7.19 & 12.12 & 0.24 \\ -3.14 & 8.27 & -9.81 & -2.11 \end{bmatrix}$$

- Column major order

$$\begin{bmatrix} 3.24 & 5.76 & -12.3 & 6.11 \\ -7.55 & 4.32 & -5.02 & 4.48 \\ 3.20 & 7.19 & 12.12 & 0.24 \\ -3.14 & 8.27 & -9.81 & -2.11 \end{bmatrix}$$

Column major



A 4x4 matrix with the following values:

3.24	5.76	-12.3	6.11
-7.55	4.32	-5.02	4.48
3.20	7.19	12.12	0.24
-3.14	8.27	-9.81	-2.11

Four magenta arrows illustrate column-major traversal: one vertical arrow pointing down each column, and three diagonal arrows pointing from the bottom of each column to the top of the next column.


```
octave:37> A = [1 2 3; 4 5 6]  
A =
```

```
1  2  3  
4  5  6
```

- Fortran
- Matlab
 - Linear indexing

```
octave:38> A(1)  
ans = 1  
octave:39> A(2)  
ans = 4  
octave:40> A(3)  
ans = 2  
octave:41> A(4)  
ans = 5  
octave:42> A(5)  
ans = 3  
octave:43> A(6)  
ans = 6
```

Row major



3.24	5.76	-12.3	6.11
-7.55	4.32	-5.02	4.48
3.20	7.19	12.12	0.24
-3.14	8.27	-9.81	-2.11

- C, C++

- Must be mindful when passing pointers to arrays to subroutines
- Also important for “locality of reference” when iterating over large arrays.

```
In [26]: A
Out[26]:
array([[1, 2, 3],
       [4, 5, 6]])
```

```
In [27]: A[numpy.unravel_index(0, A.shape)]
Out[27]: 1
```

```
In [28]: A[numpy.unravel_index(1, A.shape)]
Out[28]: 2
```

```
In [29]: A[numpy.unravel_index(2, A.shape)]
Out[29]: 3
```

```
In [30]: A[numpy.unravel_index(3, A.shape)]
Out[30]: 4
```

```
In [31]: A[numpy.unravel_index(4, A.shape)]
Out[31]: 5
```

- Python/NumPy

Sparse storage – the naive way

- Matrix stored as list of (i, j, value) triplets

$$\begin{bmatrix} 3.24 & 0 & 0 & 6.11 \\ 0 & 0 & -5.02 & 0 \\ 3.20 & 0 & 12.12 & 0 \\ -3.14 & 0 & 0 & 0 \end{bmatrix}$$

i	1	1	2	3	3	4
j	1	4	3	1	3	1
x	3.24	6.11	-5.02	3.20	12.12	-3.14

- This representation grows as $O(\text{nnz})$
- Dense grows as $O(N^2)$

Also in Matlab/Octave....

```
octave:3> sprandn(3, 4, .3)
```

```
ans =
```

```
Compressed Column Sparse (rows = 3, cols = 4, nnz = 3 [25%])
```

```
(2, 1) -> 0.97173
```

```
(3, 1) -> 0.76803
```


```
(3, 3) -> -0.64265
```

- Draw this on blackboard.
- This is how it's displayed, not how it's actually stored...


The basic difference between sparse and dense

- Think of dense matrices stored as one big rectangle laid out in linear memory.
- Think of sparse matrices as a list of (i, j, value) 3-tuples (or as three separate lists).
- Algorithms processing them will be completely different, and will try to take advantage of the difference between the two storage formats.

A big sparse matrix

- Consider Facebook.  1.5 Billion users at end of 2015.
- The connections of “friends” can be represented as a big adjacency matrix.

	A	B	C	D	E	F
A	-	1	1	1	1	
B	1	-		1	1	
C	1		-			1
D	1	1		-		1
E	1	1			-	1
F			1	1	1	-



- What is size of adjacency matrix (dense)?
- What is size of adjacency matrix (sparse)?

New Topic: Numerical Linear Algebra

$$Ax=b$$

- The classic linear algebra problem
- First we talk about matrix multiplication (today).
- Then we talk about solvers and matrix decompositions (today and next several classes).

Matrix Multiplication

$$\begin{matrix} & A & & B \\ \left(\begin{array}{ccccc} -3 & -1 & -1 & -5 & 1 \\ -3 & -3 & -4 & -5 & 3 \\ -1 & -5 & 3 & -1 & -3 \\ 3 & 2 & -1 & -4 & -4 \\ -5 & 3 & -2 & -1 & -1 \end{array} \right) & \left(\begin{array}{ccccc} 0 & 5 & 3 & -3 & 0 \\ 5 & 5 & 2 & 0 & -1 \\ 3 & 0 & -4 & -1 & -4 \\ 4 & 0 & -3 & 2 & 4 \\ 4 & -2 & 0 & -1 & 3 \end{array} \right) \end{matrix}$$

$$AB = \left(\begin{array}{ccccc} -24 & -22 & 8 & -1 & -12 \\ -35 & -36 & 16 & 0 & 8 \\ -32 & -24 & -22 & 1 & -20 \\ -25 & 33 & 29 & -12 & -26 \\ 1 & -8 & 2 & 16 & -2 \end{array} \right)$$

Naive algorithm uses 3 nested loops:

1. Rows of A
2. Cols of B
3. Loop over elements doing multiplication and sum

Matrix Multiplication -- Naive

```
function z = matmul(x, y)
    % Matrix multiplication the naive way, using loops.
    % This algorithm is  $O(n^3)$ 
    %  $z = x*y$ 
    % size(x) = [n, m]
    % size(y) = [m, p]
    % size(z) = [n, p]

    [n, m] = size(x);
    [m, p] = size(y);

    z = zeros(n, p);    % Preallocate z for performance
    for row = 1:n
        for col = 1:p
            for idx = 1:m
                z(row, col) = z(row, col) + x(row, idx)*y(idx, col);
            end
        end
    end

    return
```

- Three nested loops.

An aside.....

$$\begin{array}{cc}
 A & B \\
 \left(\begin{array}{ccccc|ccccc}
 -3 & -1 & -1 & -5 & 1 & 0 & 5 & 3 & -3 & 0 \\
 -3 & -3 & -4 & -5 & 3 & 5 & 5 & 2 & 0 & -1 \\
 -1 & -5 & 3 & -1 & -3 & 3 & 0 & -4 & -1 & -4 \\
 3 & 2 & -1 & -4 & -4 & 4 & 0 & -3 & 2 & 4 \\
 -5 & 3 & -2 & -1 & -1 & 4 & -2 & 0 & -1 & 3
 \end{array} \right) & \\
 \\
 AB = \left(\begin{array}{cc|cc|cc}
 -24 & -22 & 8 & -1 & -12 \\
 -35 & -36 & 16 & 0 & 8 \\
 -32 & -24 & -22 & 1 & -20 \\
 -25 & 33 & 29 & -12 & -26 \\
 1 & -8 & 2 & 16 & -2
 \end{array} \right)
 \end{array}$$

- Think about how dense matrix multiplication must be different from sparse matrix multiplication.
 - If both matrices have lots of zeros, it's a waste to loop over each and every element.

How does run time scale with matrix size?

- Three nested loops suggests run time should grow as N^3 .
- We call this an $O(N^3)$ algorithm
- Timing using `time_matmul()`

```
>> [x, y] = time_matmul;
N =      10, avg multiplication time =      0.00010812 sec
N =      30, avg multiplication time =      0.00107062 sec
N =     100, avg multiplication time =      0.02607275 sec
N =     300, avg multiplication time =      0.63386387 sec
N =    1000, avg multiplication time =     32.70939337 sec
Scaled time vec (seconds per multiplication) =      1.0e-06 *

      0.1081      0.0397      0.0261      0.0235      0.0327
```


Timing matmul

- This uses my naive implementation

```
>> [x, y] = time_matmul;  
N =      10, avg multiplication time =      0.00010812 sec  
N =      30, avg multiplication time =      0.00107062 sec  
N =     100, avg multiplication time =      0.02607275 sec  
N =     300, avg multiplication time =      0.63386387 sec  
N =    1000, avg multiplication time =     32.70939337 sec  
Scaled time vec (seconds per multiplication) =      1.0e-06 *
```

```
      0.1081      0.0397      0.0261      0.0235      0.0327
```

```
Multiplication is O(2.941)
```

Improving matmul: Strassen's algorithm

- Consider the usual algorithm:

$$\begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \cdot \begin{pmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{pmatrix} = \begin{pmatrix} c_{11} & c_{12} \\ c_{21} & c_{22} \end{pmatrix}$$

$$c_{11} = a_{11}b_{11} + a_{12}b_{21}$$

$$c_{12} = a_{11}b_{12} + a_{12}b_{22}$$

$$c_{21} = a_{21}b_{11} + a_{22}b_{21}$$

$$c_{22} = a_{21}b_{12} + a_{22}b_{22}$$

- 8 multiplies, 4 additions.

Floating point multiplication
performed in hardware.
Takes more time than
addition.

- Note that the elements can themselves be matrices (recursive computation).

Strassen's algorithm

$$\begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \cdot \begin{pmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{pmatrix} = \begin{pmatrix} c_{11} & c_{12} \\ c_{21} & c_{22} \end{pmatrix}$$

Take

$$q_1 = (a_{11} + a_{22}) * (b_{11} + b_{22})$$

$$q_2 = (a_{21} + a_{22}) * b_{11}$$

$$q_3 = a_{11} * (b_{12} - b_{22})$$

$$q_4 = a_{22} * (b_{21} - b_{11})$$

$$q_5 = (a_{11} + a_{12}) * b_{22}$$

$$q_6 = (a_{21} - a_{11}) * (b_{11} + b_{12})$$

$$q_7 = (a_{12} - a_{22}) * (b_{21} + b_{22})$$

Then

$$c_{11} = q_1 + q_4 - q_5 + q_7$$

$$c_{12} = q_3 + q_5$$


$$c_{21} = q_2 + q_4$$

$$c_{22} = q_1 + q_3 - q_2 + q_6$$

Fewer multiplications but more additions.

- 7 multiplies, 13 additions.
- Elements can also be matrices – recursive algorithm.

Progress in matmul



Source: Wikipedia

Timing matmul

- This uses MATLAB built-in multiplication (BLAS)

```
>> [x, y] = time_matmul;  
N =      10, avg multiplication time =      0.00001400 sec  
N =      30, avg multiplication time =      0.00002912 sec  
N =     100, avg multiplication time =      0.00025200 sec  
N =     300, avg multiplication time =      0.00333462 sec  
N =    1000, avg multiplication time =      0.08979813 sec  
Scaled time vec (seconds per multiplication) =      1.0e-07 *
```

0.1400	0.0108	0.0025	0.0012	0.0009
--------	--------	--------	--------	--------

Multiplication is $O(2.296)$

Much better than $O(N^3)$

Comparison: mymatmul vs. Matlab

```
>> time_matmul
```


```
----- mymatmul -----  
N =      3, avg multiplication time =      0.00005175 sec  
N =      5, avg multiplication time =      0.00001300 sec  
N =     10, avg multiplication time =      0.00003575 sec  
N =     20, avg multiplication time =      0.00024750 sec  
N =     30, avg multiplication time =      0.00093600 sec  
N =     50, avg multiplication time =      0.00428825 sec  
N =    100, avg multiplication time =      0.03385675 sec  
N =    200, avg multiplication time =      0.20763750 sec  
N =    300, avg multiplication time =      0.62138575 sec  
N =    500, avg multiplication time =      3.58971225 sec  
N =   1000, avg multiplication time =     36.35315700 sec
```

```
----- BLAS -----  
N =      3, avg multiplication time =      0.00000800 sec  
N =      5, avg multiplication time =      0.00000525 sec  
N =     10, avg multiplication time =      0.00000850 sec  
N =     20, avg multiplication time =      0.00001350 sec  
N =     30, avg multiplication time =      0.00002050 sec  
N =     50, avg multiplication time =      0.00008450 sec  
N =    100, avg multiplication time =      0.00023975 sec  
N =    200, avg multiplication time =      0.00169225 sec  
N =    300, avg multiplication time =      0.00588450 sec  
N =    500, avg multiplication time =      0.02320725 sec  
N =   1000, avg multiplication time =      0.08831325 sec
```

My multiplication is $O(N^{2.962})$

Matlabs multiplication is $O(N^{2.428})$

Scaling of matmul



- $O(N^p)$ is asymptotic behavior.
 - Naive implementation: $O(N^3)$
 - Matlab/BLAS: $\approx O(N^{2.4})$

Detour: Libraries for Linear Algebra

- Accessible as function calls from C, Fortran, Java, etc.
- BLAS – Basic operations on vectors and matrices
 - Level 1: vector-vector operations.
 - Level 2: matrix-vector operations
 - Level 3: matrix-matrix operations
- LAPACK – higher-level algorithms
 - Linear solvers
 - Matrix decompositions

BLAS/LAPACK naming convention

X	Y	Y	Z	Z	Z
d	g	e	m	m	

- X = S, D, C, Z for single, double, single complex, double complex.
- YY = Code for matrix type
 - ge = general
 - dl = diagonal
 - he = Hermitian
- ZZZ = Name of algorithm

Examples:

- dgemm – general matrix-matrix multiply for double: $A * B + \beta C$
- daxpy – vector vector addition for double: $\alpha X + Y$

This naming convention has carried over to other math packages as well.

BLAS

- BLAS cheat sheet

<http://www.netlib.org/lapack/lug/node145.html>

- Exploits locality of reference

- Try to perform all operation on elements close to each other in memory before moving to next set of elements.
- Block strategies for matrix multiply.
- Rely on optimizing cache hits for best performance.

$$\begin{matrix} & A & & B \\ \left(\begin{array}{ccccc} -3 & -1 & -1 & -5 & 1 \\ -3 & -3 & -4 & -5 & 3 \\ -1 & -5 & 3 & -1 & -3 \\ 3 & 2 & -1 & -4 & -4 \\ -5 & 3 & -2 & -1 & -1 \end{array} \right) & \left(\begin{array}{cc|ccc} 0 & 5 & 3 & -3 & 0 \\ 5 & 5 & 2 & 0 & -1 \\ 3 & 0 & -4 & -1 & -4 \\ 4 & 0 & -3 & 2 & 4 \\ 4 & -2 & 0 & -1 & 3 \end{array} \right) \end{matrix}$$

$$AB = \left(\begin{array}{cc|cc} -24 & -22 & 8 & -1 & -12 \\ -35 & -36 & 16 & 0 & 8 \\ -32 & -24 & -22 & 1 & -20 \\ -25 & 33 & 29 & -12 & -26 \\ 1 & -8 & 2 & 16 & -2 \end{array} \right)$$

Dgemm example

- Demo under:
`/home/sbrorson/Northeastern1_Spring2016/Class3/dgemm`

LAPACK – Linear algebra

- Overview

<http://www.netlib.org/lapack/lug/node19.html>

- Naming scheme

<http://www.netlib.org/lapack/lug/node24.html>

- Available routines

<http://www.netlib.org/lapack/lug/node27.html>

Users of BLAS and LAPACK

- Matlab – built in
 - <http://www.mathworks.com/company/newsletters/articles/matlab-incorporates-lapack.html>
- Octave, SciLab, Julia.... -- built in.
- C++/Boost – must #include
- You should too. These programs have been optimized by scores of incredibly smart people for many years. Don't re-invent the wheel.

New topic: Linear Solvers

- Linear system written out:

$$a_{11}x_1 + a_{12}x_2 + \cdots + a_{1n}x_n = b_1$$

$$a_{21}x_1 + a_{22}x_2 + \cdots + a_{2n}x_n = b_2$$

$$\vdots \quad \quad \quad \vdots \quad \quad \quad \vdots \quad \quad \quad \vdots$$

$$a_{m1}x_1 + a_{m2}x_2 + \cdots + a_{mn}x_n = b_m.$$

- Matrix notation:

$$Ax = b$$

- In general, we know A and b, want to find x.
- Never do this: $x = A^{-1}b$!!!

<http://www.johndcook.com/blog/2010/01/19/dont-invert-that-matrix/>

Solving a linear system in Matlab

- Linear system written out:

$$a_{11}x_1 + a_{12}x_2 + \cdots + a_{1n}x_n = b_1$$

$$a_{21}x_1 + a_{22}x_2 + \cdots + a_{2n}x_n = b_2$$


$$\vdots \quad \quad \quad \vdots \quad \quad \quad \vdots \quad \quad \quad \vdots$$

$$a_{m1}x_1 + a_{m2}x_2 + \cdots + a_{mn}x_n = b_m.$$

- In matrix notation

$$Ax = b$$

A, b known, x is
vector of unknowns



- Matlab solution:

$$x = A \backslash b$$

Solve $Ax = b$ using \backslash operator

```
octave:55> A = eye(4) + 0.006*randn(4);  
octave:56> x = A\b;  
octave:57> r1 = b - A*x ← Residual: This should be zero  
r1 =  
  
-2.7756e-17  
-2.2204e-16  
0.0000e+00  
-2.2204e-16
```

- Residual is (related to) the error of your solution x .
- Residual is generally non-zero, but the goal is to minimize it.

Four different division operators in Matlab

Solve

- mldivide “\”: $Ax=b \rightarrow x=A^{-1}b \rightarrow x=b \backslash A$

- mrdivide “/”: $xA=b \rightarrow x=b A^{-1} \rightarrow x=b/A$

- ldivide “.\”:

$$\begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \end{pmatrix} \backslash \begin{pmatrix} b_{11} & b_{12} & b_{13} \\ b_{21} & b_{22} & b_{23} \end{pmatrix} = \begin{pmatrix} b_{11}/a_{11} & b_{12}/a_{12} & b_{13}/a_{13} \\ b_{21}/a_{21} & b_{22}/a_{22} & b_{23}/a_{23} \end{pmatrix}$$

- rdivide “./”:

Elementwise divide

$$\begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \end{pmatrix} ./ \begin{pmatrix} b_{11} & b_{12} & b_{13} \\ b_{21} & b_{22} & b_{23} \end{pmatrix} = \begin{pmatrix} a_{11}/b_{11} & a_{12}/b_{12} & a_{13}/b_{13} \\ a_{21}/b_{21} & a_{22}/b_{22} & a_{23}/b_{23} \end{pmatrix}$$

Difference between residual and error

- Consider: $x = A \setminus b$
- Error: $x_{true} = x_{comp} + e$
- Residual: $r = b - Ax_{comp}$
- By definition: $Ax_{true} = b$
- Therefore: $A(x_{comp} + e) = b$

A and b are both known exactly. The computed x will have some small error.

$$Ae = b - Ax_{comp}$$

$$Ae = r$$

- Note that we can know r and A , but the value of e is not directly observable.

Find residual of simple computation

```
b = randn(4, 1);  
A = eye(4) + 0.006*randn(4);  
x = A\b;  
r1 = b - A*x
```

```
r1 =
```

```
1.0e-15 *
```

```
-0.0555
```

```
0
```

```
0.4441
```

```
0.0069
```

Residual: This should be zero



- Residual is small, but not zero

Try a different matrix

```
A = ones(4) + 0.006*randn(4);
```

```
x = A\b;
```

```
r2 = b - A*x
```

ones(4) is singular

```
r2 =
```

```
1.0e-13 *
```

Residual: This should be zero

```
-0.0466
```

```
-0.2043
```

```
-0.1577
```

```
-0.1016
```

- Larger error!
- This A is closer to singular matrix.
- In general, the closer A is to singular, the larger the residual.

How to characterize this effect?

We want a measure of how singular a matrix is.....

- Matrix condition number

$$k = \|A\| \cdot \|A^{-1}\|$$

Matrix norm $\|A\|$

- Small condition number (near 1), solvers are stable -> low error.
- Large condition number, solvers are error-prone -> high error.
- Matlab: `cond(A)`

Condition number requires matrix norm

- Vector norms:

- 1 norm: $\|x\|_1 = \sum_i |x_i|$
- Infinity norm: $\|x\|_\infty = \max(|x_0|, |x_1|, \dots, |x_n|)$
- Euclidian norm: $\|x\| = \sqrt{\sum_i |x_i|^2}$


- General p-norm for vectors:

$$\|x\|_p = \left(\sum_i |x_i|^p \right)^{1/p}$$

Matrix norm is generalization of vector norms

- 1 norm:


$$\|A\|_1 = \max_j \left(\sum_i |A_{ij}| \right)$$



$$\begin{bmatrix} 3.24 & 5.76 & -12.3 & 6.11 \\ -7.55 & 4.32 & -5.02 & 4.48 \\ 3.20 & 7.19 & 12.12 & 0.24 \\ -3.14 & 8.27 & -9.81 & -2.11 \end{bmatrix}$$

- Infinity norm:

$$\|A\|_\infty = \max_i \left(\sum_j |A_{ij}| \right)$$



$$\begin{bmatrix} 3.24 & 5.76 & -12.3 & 6.11 \\ -7.55 & 4.32 & -5.02 & 4.48 \\ 3.20 & 7.19 & 12.12 & 0.24 \\ -3.14 & 8.27 & -9.81 & -2.11 \end{bmatrix}$$


- Induced norm:

$$\|A\| = \max_i \left(\sqrt{\lambda(A^T A)} \right)$$

Maximum singular value of A


Matrix as linear transformation

- Consider vector x



- Apply matrix A to vector x via multiplication.

- We get new vector $y = Ax$



Induced matrix norm

- Ax is a vector. A acts on x , stretching and rotating x .
- Therefore, we can extend the concept of vector norm by focusing on product Ax .
- Consider action of A on all vectors x satisfying $\|x\| = 1$.
- This gives the “Induced norm”:
$$\|A\| = \max(\|Ax\|) \text{ when } \|x\| = 1.$$
- Therefore, the induced norm is (related to) max eigenvalue (singular value) of A


Induced matrix norm

- Start with vector norm:

$$\|x\|$$

- Define matrix norm by considering action of matrix on all vectors:

$$\|A\| = \max \left(\frac{\|Ax\|}{\|x\|} : x \in K^n \right)$$



Find largest extension of unit circle induced by matrix.

Condition number

$$k = \|A\| \cdot \|A^{-1}\|$$

```
>> A = eye(4) + 0.006*randn(4);
```

```
>> cond(A)
```

```
ans =
```

```
1.0107
```

Matrix is far from
singular – condition
number close to 1.

```
>> A = ones(4) + 0.006*randn(4);
```

```
>> cond(A)
```


```
ans =
```

```
2.3771e+03
```

Matrix is close to
singular – high
condition number.

- Which matrix norm is used for k ? Doesn't matter....

Main ideas in lecture

- Types of matrix: dense and sparse.
 - Difference is in how they are stored in memory.
 - This also implies a difference in processing algorithms.
- Matrix multiplication (dense).
- Solving $Ax = b$, and errors (residual).
- Matrix condition number  Important!
 - Characterizes potential for error.