


Initialization

```
import numpy as np
import matplotlib.pyplot as plt
import sklearn
import sklearn.datasets
from init_utils import sigmoid, relu, compute_loss, forward_propagation, backward_propagation
from init_utils import update_parameters, predict, load_dataset, plot_decision_boundary, predict_dec

%matplotlib inline
plt.rcParams['figure.figsize'] = (7.0, 4.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# load image dataset: blue/red dots in circles
train_X, train_Y, test_X, test_Y = load_dataset()
```



1 - Neural Network model

```
def model(X, Y, learning_rate = 0.01, num_iterations = 15000, print_cost = True, initialization = "he"):
    """
    Implements a three-layer neural network: LINEAR->RELU->LINEAR->RELU->LINEAR->SIGMOID.

    Arguments:
    X -- input data, of shape (2, number of examples)
    Y -- true "label" vector (containing 0 for red dots; 1 for blue dots), of shape (1, number of examples)
    learning_rate -- learning rate for gradient descent
    num_iterations -- number of iterations to run gradient descent
    print_cost -- if True, print the cost every 1000 iterations
    initialization -- flag to choose which initialization to use ("zeros", "random" or "he")

    Returns:
    parameters -- parameters learnt by the model
    """

    grads = {}
    costs = [] # to keep track of the loss
    m = X.shape[1] # number of examples
    layers_dims = [X.shape[0], 10, 5, 1]

    # Initialize parameters dictionary.
    if initialization == "zeros":
        parameters = initialize_parameters_zeros(layers_dims)
    elif initialization == "random":
        parameters = initialize_parameters_random(layers_dims)
    elif initialization == "he":
        parameters = initialize_parameters_he(layers_dims)

    # Loop (gradient descent)

    for i in range(0, num_iterations):

        # Forward propagation: LINEAR -> RELU -> LINEAR -> RELU -> LINEAR -> SIGMOID.
        a3, cache = forward_propagation(X, parameters)

        # Loss
```

```

cost = compute_loss(a3, Y)

# Backward propagation.
grads = backward_propagation(X, Y, cache)

# Update parameters.
parameters = update_parameters(parameters, grads, learning_rate)

# Print the loss every 1000 iterations
if print_cost and i % 1000 == 0:
    print("Cost after iteration {}: {}".format(i, cost))
    costs.append(cost)

# plot the loss
plt.plot(costs)
plt.ylabel('cost')
plt.xlabel('iterations (per hundreds)')
plt.title("Learning rate =" + str(learning_rate))
plt.show()

return parameters

```

▼ 2 - Zero initialization

```

# GRADED FUNCTION: initialize_parameters_zeros

def initialize_parameters_zeros(layers_dims):
    """
    Arguments:
    layer_dims -- python array (list) containing the size of each layer.

    Returns:
    parameters -- python dictionary containing your parameters "W1", "b1", ..., "WL", "bL":
        W1 -- weight matrix of shape (layers_dims[1], layers_dims[0])
        b1 -- bias vector of shape (layers_dims[1], 1)
        ...
        WL -- weight matrix of shape (layers_dims[L], layers_dims[L-1])
        bL -- bias vector of shape (layers_dims[L], 1)
    """

    parameters = {}
    L = len(layers_dims)      # number of layers in the network

    for l in range(1, L):
        ### START CODE HERE ### (≈ 2 lines of code)
        parameters['W' + str(l)] = np.zeros((layers_dims[l], layers_dims[l-1]))
        parameters['b' + str(l)] = np.zeros((layers_dims[l], 1))
        ### END CODE HERE ###
    return parameters

```

```

parameters = initialize_parameters_zeros([3,2,1])
print("W1 = " + str(parameters["W1"]))
print("b1 = " + str(parameters["b1"]))
print("W2 = " + str(parameters["W2"]))
print("b2 = " + str(parameters["b2"]))

```

```

W1 = [[0. 0. 0.]
 [0. 0. 0.]]
b1 = [[0.]
 [0.]]
W2 = [[0. 0.]]
b2 = [[0.]]


```

```

parameters = model(train_X, train_Y, initialization = "zeros")
print ("On the train set:")
predictions_train = predict(train_X, train_Y, parameters)
print ("On the test set:")
predictions_test = predict(test_X, test_Y, parameters)

```

```
Cost after iteration 0: 0.6931471805599453
Cost after iteration 1000: 0.6931471805599453
Cost after iteration 2000: 0.6931471805599453
Cost after iteration 3000: 0.6931471805599453
Cost after iteration 4000: 0.6931471805599453
Cost after iteration 5000: 0.6931471805599453
Cost after iteration 6000: 0.6931471805599453
Cost after iteration 7000: 0.6931471805599453
Cost after iteration 8000: 0.6931471805599453
Cost after iteration 9000: 0.6931471805599453
Cost after iteration 10000: 0.6931471805599455
Cost after iteration 11000: 0.6931471805599453
Cost after iteration 12000: 0.6931471805599453
Cost after iteration 13000: 0.6931471805599453
Cost after iteration 14000: 0.6931471805599453
```




As the trees are cut,

```
print ("predictions_train = " + str(predictions_train))
print ("predictions_test = " + str(predictions_test))
```

[illegible]

```
plt.title("Model with Zeros initialization")
axes = plt.gca()
axes.set_xlim([-1.5,1.5])
axes.set_ylim([-1.5,1.5])
plot_decision_boundary(lambda x: predict_dec(parameters, x.T), train_X, train_Y)
```



- ▼ 3 - Random initialization

```
# GRADED FUNCTION: initialize_parameters_random

def initialize_parameters_random(layers_dims):
    """
    Arguments:
```

```

layer_dims -- python array (list) containing the size of each layer.

Returns:
parameters -- python dictionary containing your parameters "W1", "b1", ..., "WL", "bL":
    W1 -- weight matrix of shape (layers_dims[1], layers_dims[0])
    b1 -- bias vector of shape (layers_dims[1], 1)
    ...
    WL -- weight matrix of shape (layers_dims[L], layers_dims[L-1])
    bL -- bias vector of shape (layers_dims[L], 1)
"""

np.random.seed(3)          # This seed makes sure your "random" numbers will be the as ours
parameters = {}
L = len(layers_dims)       # integer representing the number of layers

for l in range(1, L):
    ### START CODE HERE ### (≈ 2 lines of code)
    parameters['W' + str(l)] = np.random.randn(layers_dims[l], layers_dims[l-1]), * 10
    parameters['b' + str(l)] = np.zeros((layers_dims[l], 1))
    ### END CODE HERE ###

return parameters

```

```

#parameters = initialize_parameters_random([3, 2, 1])
#print("W1 = " + str(parameters["W1"]))
#print("b1 = " + str(parameters["b1"]))
#print("W2 = " + str(parameters["W2"]))
#print("b2 = " + str(parameters["b2"]))

```

```

#parameters = model(train_X, train_Y, initialization = "random")
#print ("On the train set:")
#predictions_train = predict(train_X, train_Y, parameters)
#print ("On the test set:")
#predictions_test = predict(test_X, test_Y, parameters)

```

```

#print (predictions_train)
#print (predictions_test)

```

```

#plt.title("Model with large random initialization")
#axes = plt.gca()
#axes.set_xlim([-1.5,1.5])
#axes.set_ylim([-1.5,1.5])
#plot_decision_boundary(lambda x: predict_dec(parameters, x.T), train_X, train_Y)

```

4 - He initialization

```

# GRADED FUNCTION: initialize_parameters_he

def initialize_parameters_he(layers_dims):
    """
    Arguments:
    layer_dims -- python array (list) containing the size of each layer.

    Returns:
    parameters -- python dictionary containing your parameters "W1", "b1", ..., "WL", "bL":
        W1 -- weight matrix of shape (layers_dims[1], layers_dims[0])
        b1 -- bias vector of shape (layers_dims[1], 1)
        ...
        WL -- weight matrix of shape (layers_dims[L], layers_dims[L-1])
        bL -- bias vector of shape (layers_dims[L], 1)
    """

    np.random.seed(3)
    parameters = {}
    L = len(layers_dims) - 1 # integer representing the number of layers

    for l in range(1, L + 1):
        ### START CODE HERE ### (≈ 2 lines of code)
        parameters['W' + str(l)] = np.random.randn(layers_dims[l], layers_dims[l-1]) * np.sqrt(2./layers_dims[l-1])
        parameters['b' + str(l)] = np.zeros((layers_dims[l], 1))

    ### END CODE HERE ###

```


```
return parameters
```

```
parameters = initialize_parameters_he([2, 4, 1])
print("W1 = " + str(parameters["W1"]))
print("b1 = " + str(parameters["b1"]))
print("W2 = " + str(parameters["W2"]))
print("b2 = " + str(parameters["b2"]))
```

```
W1 = [[ 1.78862847  0.43650985]
 [ 0.09649747 -1.8634927 ]
 [-0.2773882  -0.35475898]
 [-0.08274148 -0.62700068]]
b1 = [[0.]
 [0.]
 [0.]
 [0.]]
W2 = [[-0.03098412 -0.33744411 -0.92904268  0.62552248]]
b2 = [[0.]]
```


```
parameters = model(train_X, train_Y, initialization = "he")
print ("On the train set:")
predictions_train = predict(train_X, train_Y, parameters)
print ("On the test set:")
predictions_test = predict(test_X, test_Y, parameters)
```

```
Cost after iteration 0: 0.8830537463419761
Cost after iteration 1000: 0.6879825919728063
Cost after iteration 2000: 0.6751286264523371
Cost after iteration 3000: 0.6526117768893807
Cost after iteration 4000: 0.6082958970572938
Cost after iteration 5000: 0.5304944491717495
Cost after iteration 6000: 0.4138645817071795
Cost after iteration 7000: 0.3117803464844414
Cost after iteration 8000: 0.23696215330322565
Cost after iteration 9000: 0.18597287209206836
Cost after iteration 10000: 0.15015556280371808
Cost after iteration 11000: 0.12325079292273551
Cost after iteration 12000: 0.09917746546525935
Cost after iteration 13000: 0.08457055954024276
Cost after iteration 14000: 0.07357895962677363
```



```
On the train set:
Accuracy: 0.9933333333333333
On the test set:
Accuracy: 0.96
```

```
plt.title("Model with He initialization")
axes = plt.gca()
axes.set_xlim([-1.5,1.5])
axes.set_ylim([-1.5,1.5])
plot_decision_boundary(lambda x: predict_dec(parameters, x.T), train_X, train_Y)
```



✓ 0s completed at 12:17 AM ● ✕