

Database Assignment –5

Relational and Logical Operators.

1) Write a query that will give you all orders for more than Rs. 1,000.

```
mysql> select * from Orders
-> where AMT > 1000;
```

Onum	Amt	Odate	Cnum	Snum
3002	1900.1	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3008	4723	1990-10-05	2006	1001
3009	1713.23	1990-10-04	2002	1003
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
7 rows in set (0.00 sec)
```

2) Write a query that will give you the names and cities of all salespeople in London with a commission above .10.

```
mysql> SELECT `Sname`, `City` FROM `SALESPEOPLE` WHERE `
CITY` = 'London' AND `Comm`>0.10;
```

Sname	City
Peel	London
Motika	London

```
2 rows in set (0.00 sec)
```

3) Write a query on the Customers table whose output will exclude all customers with a rating <= 100, unless they are located in Rome.

```
mysql> select * from Customers
-> where Rating <= 100;
```

Cnum	Cname	City	Rating	Snum
2001	Hoffman	London	100	1001
2006	Clemens	London	100	1001
2007	Pereira	Rome	100	1004

```
3 rows in set (0.01 sec)
```

4) What will be the output from the following query?

Select * from Orders

where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
mysql> Select * from Orders
-> where (amt < 1000 OR
-> NOT (odate = '1990-10-03'
-> AND Cnum > 2003));
ERROR 1064 (42000): You have an error in your SQL syntax
; check the manual that corresponds to your MySQL server
version for the right syntax to use near '?1990-10-03?'
```

```
mysql> SELECT * FROM Orders WHERE (amt<1000 OR NOT (Odate='1990-10-03' AND Cnum>2003));
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3005	5160.45	1990-10-03	2003	1002
3007	75.75	1990-10-04	2004	1002
3008	4723	1990-10-05	2006	1001
3009	1713.23	1990-10-04	2002	1003
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
8 rows in set (0.00 sec)
```

5) What will be the output of the following query?

Select * from Orders

where NOT ((odate = '1990-10-03' OR snum > 1006) AND amt >= 1500);

```
mysql> Select * from Orders
-> where NOT ((odate = '1990-10-03' OR snum
-> >1006) AND amt >= 1500);
ERROR 1064 (42000): You have an error in your SQL syntax
; check the manual that corresponds to your MySQL server
version for the right syntax to use near '?1990-10-03?
OR snum
>1006) AND amt >= 1500)' at line 2
```

```
mysql> SELECT * FROM Orders WHERE NOT((Odate='1990-10-03
' OR Snum>1006) AND amt>=1500);
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723 | 1990-10-05 | 2006 | 1001 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3010 | 1309.95 | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-06 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

6) What is a simpler way to write this query?

Select snum, sname, city, comm From Salespeople
where (comm > .12 OR comm <.14);

```
mysql> Select snum, sname, city, comm From Salespeople
-> where (comm > .12 OR comm <.14);
+-----+-----+-----+-----+
| snum | sname  | city    | comm |
+-----+-----+-----+-----+
| 1001 | Peel   | London  | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
| 1003 | Axelord | New York | 0.10 |
| 1004 | Motika | London  | 0.11 |
| 1007 | Rifkin | Barcelona | 0.15 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```