

Database Assignment –4

Retrieving Information from Tables.

1) Write a select command that produces the order number, amount, and date for all rows in the Orders table.

```
mysql> select ONUM, AMT, ODATE from ORDERS;
```

ONUM	AMT	ODATE
3001	18.69	1990-10-03
3002	1900.1	1990-10-03
3003	767.19	1990-10-03
3005	5160.45	1990-10-03
3006	1098.16	1990-10-03
3007	75.75	1990-10-04
3008	4723	1990-10-05
3009	1713.23	1990-10-04
3010	1309.95	1990-10-06
3011	9891.88	1990-10-06

```
10 rows in set (0.06 sec)
```

2) Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
mysql> SELECT * FROM `CUSTOMERS` WHERE Snum=1001;
```

Cnum	Cname	City	Rating	Snum
2001	Hoffman	London	100	1001
2006	Clemens	London	100	1001

```
2 rows in set (0.00 sec)
```

3) Write a query that displays the Salespeople table with the columns in the following order: city, sname, snum, comm.

```
mysql> select CITY, SNAME, SNUM, COMM from Salespeople;
```

CITY	SNAME	SNUM	COMM
London	Peel	1001	0.12
San Jose	Serres	1002	0.13
New York	Axelrod	1003	0.10
London	Motika	1004	0.11
Barcelona	Rifkin	1007	0.15

```
5 rows in set (0.01 sec)
```

4) Write a select command that produces the rating followed by the name of each customer in San Jose.

```
mysql> SELECT `Rating`,`Cname` FROM `CUSTOMERS` WHERE `City` = 'San Jose';
```

Rating	Cname
200	Liu
300	Cisneros

```
2 rows in set (0.00 sec)
```

5) Write a query that will produce the snum values of all salespeople (suppress the duplicates) with orders in the Orders table.

```
mysql> SELECT DISTINCT `Snum` FROM `ORDERS`;
```

```
+-----+  
| Snum |
```

```
+-----+  
| 1007 |  
| 1004 |  
| 1001 |  
| 1002 |  
| 1003 |
```

```
+-----+
```

```
5 rows in set (0.01 sec)
```