ASSIGNMENT 1

NAME : SAHIL SATISH PAWAR

SUBJECT : FSDL LAB

PRN : 123B1B228

BATCH : D-1

ASSIGNMNET TITLE : Create a static web page which defines all text formatting tags of html in tabular format.

CODE :

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Text Formatting Tags of HTML</title>
    <style>
      body {
        margin: 0;
        padding: 20px;
        font-family: 'Roboto', sans-serif;
        background: linear-gradient(to right, #ffffff, #f3e8ff);
      }

      h1 {
        text-align: center;
        color: #000;
        margin-bottom: 20px;
      }

      table {
```

```
  width: 90%;
  margin: auto;
  border-collapse: collapse;
  background-color: #c7ebf1;
  border-radius: 15px;
  overflow: hidden;
}

th {
  background-color: #f8b3b3;
  color: #000;
  padding: 12px;
}

td {
  border: 2px dotted rgb(114, 136, 165);
  padding: 10px;
  text-align: center;
}

tr:nth-child(even) {
  background-color: #e6f7fa;
}

code {
  background-color: #f3f4f6;
  padding: 2px 5px;
  border-radius: 4px;
}
```

```
    pre {
      background-color: #f3f4f6;
      padding: 5px;
      border-radius: 4px;
    }
  </style>
</head>
<body>
  <h1>Text Formatting Tags of HTML</h1>

  <table>
    <tr>
      <th>Tag</th>
      <th>Description</th>
      <th>Example Output</th>
    </tr>

    <tr>
      <td>&lt;b&gt;</td>
      <td>Bold text</td>
      <td><b>Bold Text</b></td>
    </tr>

    <tr>
      <td>&lt;strong&gt;</td>
      <td>Important text</td>
      <td><strong>Strong Text</strong></td>
    </tr>

    <tr>
```

```
  <td>&lt;i&gt;</td>
  <td>Italic text</td>
  <td><i>Italic Text</i></td>
</tr>

<tr>
  <td>&lt;em&gt;</td>
  <td>Emphasized text</td>
  <td><em>Emphasized Text</em></td>
</tr>

<tr>
  <td>&lt;u&gt;</td>
  <td>Underlined text</td>
  <td><u>Underlined Text</u></td>
</tr>

<tr>
  <td>&lt;mark&gt;</td>
  <td>Marked / Highlighted text</td>
  <td><mark>Marked Text</mark></td>
</tr>

<tr>
  <td>&lt;small&gt;</td>
  <td>Smaller text</td>
  <td><small>Small Text</small></td>
</tr>

<tr>
```

```
  <td>&lt;del&gt;</td>
  <td>Deleted text</td>
  <td><del>Deleted Text</del></td>
</tr>

<tr>
  <td>&lt;ins&gt;</td>
  <td>Inserted text</td>
  <td><ins>Inserted Text</ins></td>
</tr>

<tr>
  <td>&lt;sub&gt;</td>
  <td>Subscript text</td>
  <td>H<sub>2</sub>O</td>
</tr>

<tr>
  <td>&lt;sup&gt;</td>
  <td>Superscript text</td>
  <td>X<sup>2</sup></td>
</tr>

<tr>
  <td>&lt;code&gt;</td>
  <td>Computer code</td>
  <td><code>printf()</code></td>
</tr>

<tr>
```

```
        <td>&lt;pre&gt;</td>
        <td>Preformatted text</td>
        <td>
          <pre>Text stays
as it is</pre>
        </td>
      </tr>
    </table>
  </body>
</html>
```

OUTPUT :

Text Formatting Tags of HTML

Tag	Description	Example Output
<b>	Bold text	**Bold Text**
	Important text	**Strong Text**
<i>	Italic text	*Italic Text*
	Emphasized text	*Emphasized Text*
<u>	Underlined text	Underlined Text
<mark>	Marked / Highlighted text	Marked Text
<small>	Smaller text	Small Text
<del>	Deleted text	~~Deleted Text~~
<ins>	Inserted text	Inserted Text
<sub>	Subscript text	H_2O
<sup>	Superscript text	X^2
<code>	Computer code	`printf()`
<pre>	Preformatted text	`Text stays` `as it is`