Course
mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7
DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Calculate Momentum

02:24

e a program that accepts the mass of an object (in kilograms) and its velocity meters per second), then calculates and displays the momentum of the object. momentum p is calculated using the formula:

$$p = m \times v$$

re:
s the mass of the object (in kilograms).
the velocity of the object (in meters per second).

ut Format:

- A single floating-point number representing the mass of the object in kilograms.
- A single floating-point number representing the velocity of the object in meters per second.

put Format:

- The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Sample Test Cases +

Explorer

calculate...

Submi

```
#Type Content here...
mass=float(input())
velocity=float(input())
momentum=mass*velocity
print(f"{momentum:.2f}kgm/s")
```

Average time	Maximum time
0.023 s	0.026 s
23.00 ms	26.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 23 ms Debug

Expected output	Actual output
5.0	5.0
10.0	10.0
50.00kgm/s	50.00kgm/s

Test case 2 20 ms

Terminal Test cases

Prev Reset Submit

Type here to search
30°C Clear ENG 23:06 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Conditional Calculation Based on the Number of Digits 15:07

e a Python program that accepts an integer n as input. Depending on the ber of digits in n.

straints:

$n \leq 999$

ut Format:

- The input consists of a single integer n.

put Format:

- If n is a single-digit number, print its square.
- If n is a two-digit number, print its square root (rounded to two decimal places).
- If n is a three-digit number, print its cube root (rounded to two decimal places).
- Else print "Invalid".

Sample Test Cases +

Explorer

condition...

Submi

```
import math
number=int(input())
if 1<=number<=9:
    print(number**2)
elif 10<=number<=99:
```

Average time **0.014 s** 14.43 ms

Maximum time **0.015 s** 15.00 ms

4 out of 4 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 1 15 ms Debug

Expected output	Actual output
9	9
81	81

Test case 2 15 ms

Test case 3 15 ms

Terminal Test cases

Prev Reset Submit

Type here to search 30°C Clear ENG 23:06 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Days between Two Dates 39:42

e a Python program to calculate number of days between two dates.

ut Format:

- The first line contains the first date in the format $YYYY - MM - DD$.
- The second line contains the second date in the format $YYYY - MM - DD$.

put Format:

- An integer representing the number of days between the given dates.

e:

- The first date should always be considered earlier than the second date.

Sample Test Cases +

Explorer

noOfDay...

Submi

```
from datetime import date
date1_str = input()
date2_str = input()

year1, month1, day1, = map(int, date1_str.split('-'))
```

Average time **0.022 s** 22.00 ms

Maximum time **0.025 s** 25.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 20 ms Debug

Expected output	Actual output
2014-07-02	2014-07-02
2014-11-02	2014-11-02
123	123

Test case 2 20 ms

Terminal Test cases

Prev Reset Submit

Type here to search 30°C Clear ENG 23:06 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Reverse a Number 02:38

e a Python program to reverse the digits of the number and print the reversed
ber.

ut Format:

- The input is a single integer.

put Format:

- The output prints a single integer, which is the reversed number.

Sample Test Cases +

Explorer

reverseN...

Submi

```
#write your code here...
num=int(input())
reversed_num=int(str(num)[::-1])
print(reversed_num)
```

Average time	Maximum time
0.014 s	**0.015 s**
13.60 ms	15.00 ms

2 out of 2 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 1 14 ms Debug

Expected output	Actual output
5367	5367
7635	7635

Test case 2 13 ms

Terminal Test cases

Prev Reset Submit

Type here to search

30°C Clear ENG 23:06 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Multiplication Table 12:45

e a Python program that takes an integer as input and prints the multiplication e for that integer from 1 to 10.

ut Format:

- The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

put Format:

- Print the multiplication table for the given number in the format:

```
umber> x <multiplier> = <result>
```

e:

- The character "x" is used in the output to represent multiplication.
- Refer to the visible test-cases for more clarity.

Sample Test Cases +

Explorer

multiplica...

Submi

```
#write your code here...
num=int(input())
for i in range(1,11):
    print(f"{num} x {i} = {num*i}")
```

Average time	Maximum time
0.015 s	0.016 s
15.00 ms	16.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 15 ms Debug

Expected output	Actual output
8	8
8 x 1 = 8	8 x 1 = 8
8 x 2 = 16	8 x 2 = 16
8 x 3 = 24	8 x 3 = 24
8 x 4 = 32	8 x 4 = 32
8 x 5 = 40	8 x 5 = 40

Terminal Test cases

Prev Reset Submit N

Type here to search 30°C Clear ENG 23:07 05-05-2026

. Pass or Fail

17:19

e a Python program that accepts the number of courses and the marks of a ent in those courses.

grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

ut Format:

- The first input will be an integer n, the number of courses.
- The second input will be n integers representing the marks of the student in each of the n courses, separated by a space.

put Format:

e student passes all courses:

- Print the aggregate percentage (formatted to two decimal places).
- Print the grade based on the aggregate percentage

Explorer

passorFa...

Submi

```python
n=int(input())
marks = list(map(int, input().split()))
if len(marks) !=n:
    print("Invalid input")
else:
```

Average time	Maximum time
0.024 s	0.028 s
23.70 ms	28.00 ms

5 out of 5 shown test case(s) passed

5 out of 5 hidden test case(s) passed

Test case 1 25 ms Debug

Expected output	Actual output
4	4
55 65 78 89	55 65 78 89
Aggregate Percentage: 71.75	Aggregate Percentage: 71.75
Grade: First Division	Grade: First Division

Test case 2 22 ms

Terminal Test cases

Prev Reset Submit N

Type here to search 30°C Clear ENG 23:07 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Fibonacci Series 01:37

e a Python program that uses recursion to print the first n terms of the Fibonacci es.

ut Format:

- A single integer n representing the number of terms to generate.

put Format:

- A single line containing the first n terms of the Fibonacci sequence, separated by spaces.

Sample Test Cases +

Explorer

fibonacci.... Submi

```
def fibonacci(n):

    if n==1:
        return 0
    elif n==2:
```

Average time **0.034 s** 33.50 ms

Maximum time **0.085 s** 85.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 16 ms Debug

Expected output	Actual output
5	5
0 1 1 2 3	0 1 1 2 3

Test case 2 14 ms

Terminal Test cases

Prev Reset Submit N

Type here to search 30°C Clear ENG 23:07 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Pattern - 1 01:32

e a Python program to print a pattern of asterisks in the form of a right-angled gle.

ut Format:

- The input is an integer, representing the number of rows in the pattern.

put Format

- The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

e: Refer to the displayed test cases for the sample pattern.

Sample Test Cases +

Explorer

rightangl...

Submi

```
n = int(input())
for i in range(1,n+1):
    for j in range(i):
        print("*",end=" ")
    print()
```

Average time 0.009 s 8.67 ms

Maximum time 0.009 s 9.00 ms

2 out of 2 shown test case(s) passed

4 out of 4 hidden test case(s) passed

Test case 1 9 ms Debug

Expected output	Actual output
5	5
*	*
* *	* *
* * *	* * *
* * * *	* * * *
* * * * *	* * * * *

Terminal Test cases

Prev Reset Submit

Type here to search Result ENG 23:08 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Pattern - 2 01:34

e a Python program to print a right-angled triangle pattern of numbers.

ut Format:

- The input is an integer, representing the number of rows in the pattern.

put Format:

- The output should display the pattern of numbers separated by space, with each row containing increasing numbers starting from 1 up to the row number.

e:

- Refer to the displayed test cases for the sample pattern.

Sample Test Cases +

Explorer

numberP... Submi

```
n = int(input())
for i in range(1, n+1):
    for j in range(1, i+1):
        print(j, end=" ")
    print()
```

Average time	Maximum time
0.014 s	0.015 s
14.00 ms	15.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 13 ms Debug

Expected output	Actual output
5	5
1	1
1 2	1 2
1 2 3	1 2 3
1 2 3 4	1 2 3 4
1 2 3 4 5	1 2 3 4 5

Terminal Test cases

Prev Reset Submit N

Type here to search Result ENG 23:08 05-05-2026