Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Linear search Technique 11:47

e a program to check whether the given element is present or not in the array ements using linear search.

ut format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

put format:

- If the element is found, print the index. If the element found multiple times, print the starting index
- If the element is not found, print **Not found**.

nple Test Case:

ut:

3 4 3 5 6

put:

Explorer

CTP1709... Submi

```
arr = list(map(int, input().split()))

# Read key element
key = int(input())
```

Average time **0.024 s** 23.50 ms

Maximum time **0.027 s** 27.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 21 ms Debug

Expected output	Actual output
1 2 3 4 3 5 6	1 2 3 4 3 5 6
3	3
2	2

Test case 2 22 ms

Terminal Test cases

Prev Reset Submit N

Type here to search CBSE class 12 result 2... ENG 23:10 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

CODETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. Captain of the Team 02:25

are provided with the heights of 11 cricket players (in centimeters). Your task is entify the tallest player, who will be selected as the captain of the team.

ut Format:

first line of input will contain 11 integers, each representing the height of a player centimeters), each separated by a space.

put Format

output should be the height (in centimeters) of the tallest player.

Sample Test Cases +

Explorer

captainof...

Submi

```
heights = list(map(int, input().split()))

tallest = max(heights)

print(tallest)
```

Average time **0.014 s** 14.00 ms

Maximum time **0.015 s** 15.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 15 ms Debug

Expected output	Actual output
171 169 185 156 174 191 186 190 187 172 160	171 169 185 156 174 191 186 190 187 172 160
191	191

Terminal Test cases

Prev Reset Submit

Type here to search

CBSE class 12 result 2...

ENG 23:10 05-05-2026

Course
mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7
DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

Numpy Array Operations

10:18

e a Python program to create a NumPy array based on user input and display following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

ume all input elements are valid integers.

ut Format:

- The first line contains two space-separated integers, r and c, representing the number of rows and the number of columns.
- The next r lines contain c space-separated integers representing the elements of the array, entered row by row.

put Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

numpyarr...

```python
import numpy as np
r,c = map(int,input().split())

data=[]
if r==0 and c==0:
```

Average time **0.035 s** 34.75 ms

Maximum time **0.056 s** 56.00 ms

2 out of 2 shown test case(s) passed

10 out of 10 hidden test case(s) passed

Test case 1 48 ms Debug

Expected output	Actual output
3 4	3 4
1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
9 10 11 12	9 10 11 12
[[1 2 3 4]	[[1 2 3 4]
[5 6 7 8]	[5 6 7 8]

Terminal Test cases

Prev Reset Submit

Type here to search
CBSE class 12 result 2...
ENG 23:13 05-05-2026

Course

mitaoe.codetantra.com/secure/course.jsp?eucId=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7

DETANTRA Home Learn Anywhere 202501090006@mitaoe.ac.in Support Logo

. List operations 34:07

e a Python program that implements a menu-driven interface for managing a of integers. The program should have the following menu options:
dd
emove
isplay
uit

program should repeatedly prompt the user to enter a choice from the menu. ending on the choice selected, the program should perform the following ons:

- **Add**: Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- **Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- **Display**: Displays the current list of integers. If the list is empty, display "List is empty".
- **Quit**: Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice" Ensure that the program continues to prompt the user until they

Explorer

listOps.py

Submi

```
list=[]
while True:
    print("1. Add")
    print("2. Remove")
    print("3. Display")
```

Average time	Maximum time
0.228 s	0.349 s
228.00 ms	349.00 ms

2 out of 2 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Test case 1 169 ms Debug

Expected output	Actual output
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 1	Enter choice: 1
Integer: 11	Integer: 11

Terminal Test cases

Prev Reset Submit

Type here to search CBSE class 12 result 2... ENG 23:10 05-05-2026

. Dictionary Operations

31:25

e a Python program to perform insertion, update, deletion, and traversal rations on a dictionary. An initial dictionary containing 10 predefined records is ady given in the program.

erations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

ut and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after

Explorer

DictOper...

Submi

```
# Initial dictionary with 10 predefined records
student = {
    1: "Amit",
    2: "Riya",
    3: "Kiran",
```

Average time	Maximum time
0.082 s	0.084 s
82.00 ms	84.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 83 ms Debug

Expected output	Actual output
Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}	Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
11	11
Suresh	Suresh
After Insertion: {1: 'Amit', 2: 'Riy	After Insertion: {1: 'Amit', 2: 'Riy

Terminal Test cases

Prev Reset Submit

Type here to search

CBSE class 12 result 2...

ENG 23:10 05-05-2026