

Bootstrapping Estimates of the CER Model

Econ 424/Amath 540


Eric Zivot

Summer 2012

Updated: July 17, 2012

© Eric Zivot 2006

Monthly Returns on MSFT, SBUX and S&P 500



© Eric Zivot 2006

Estimated Standard Errors

```
> se.muhat = sigmahat.vals/sqrt(nobs)
> rbind(muhat.vals,se.muhat)
```

	sbux	msft	sp500
muhat.vals	0.0277	0.0275	0.01253
se.muhat	0.0135	0.0106	0.00378

```
> se.sigma2hat = sigma2hat.vals/sqrt(nobs/2)
> rbind(sigma2hat.vals,se.sigma2hat)
```

	sbux	msft	sp500
sigma2hat.vals	0.01845	0.01141	0.00143
se.sigma2hat	0.00261	0.00161	0.00020

```
> se.sigmahat = sigmahat.vals/sqrt(2*nobs)
> rbind(sigmahat.vals,se.sigmahat)
```

	sbux	msft	sp500
sigmahat.vals	0.1358	0.1068	0.0378
se.sigmahat	0.0096	0.0075	0.0026

© Eric Zivot 2006

R function `sample()`

```
# random permutations of the index vector 1:5
> sample(5)
[1] 1 3 2 5 4

> sample(5)
[1] 4 2 3 5 1

# random sample of size 5 from MSFT return with replacement
> sample(MSFT, 5, replace=TRUE)
[1] -0.02904 0.12130 -0.01890 -0.15332 -0.14627
```

© Eric Zivot 2006

Brute Force Bootstrap

Same idea as Monte Carlo Simulation but instead of generating random data from an assumed distribution, you generate random data by sampling with replacement from the observed data

```
> B = 999 # why use 999?
> muhat.boot = rep(0, B)
> nobs = length(MSFT)
> for (i in 1:B) {
+   boot.data = sample(MSFT, nobs, replace=TRUE)
+   muhat.boot[i] = mean(boot.data)
+ }
```

© Eric Zivot 2006

Brute Force Bootstrap

```
# bootstrap bias
> mean(muhat.boot) - muhat.MSFT
[1] -0.0005643


# bootstrap SE
> sd(muhat.boot)
[1] 0.01045

# analytic SE
> sigmahat.MSFT/sqrt(length(MSFT))
[1] 0.01068
```

Bootstrap SE is very close to analytic SE

© Eric Zivot 2006

Brute Force Bootstrap



```
par(mfrow=c(1,2))
hist(muhat.boot, col="slateblue1")
abline(v=muhat.MSFT, col="white", lwd=2)
qqnorm(muhat.boot)
qqline(muhat.boot)
par(mfrow=c(1,1))
```

© Eric Zivot 2006

R Package boot

- Implements a variety of bootstrapping functions
- Background material is book by Davidson and Hinkley, *Bootstrap Methods and Their Application*, Cambridge University Press, 1997.
- Main functions are:
 - `boot()` bootstrap user supplied function
 - `boot.ci()` compute bootstrap confidence interval

© Eric Zivot 2006

Example: Bootstrapping sample mean

```
# function for bootstrapping sample mean
mean.boot = function(x, idx) {
  # arguments:
  # x          data to be resampled
  # idx        vector of scrambled indices created
  #            by boot() function
  # value:
  # ans        mean value computed using resampled
  #            data
  ans = mean(x[idx])
  ans
}
```

© Eric Zivot 2006

Example: Bootstrapping sample mean

```
> MSFT.mean.boot = boot(MSFT, statistic = mean.boot, R=999)
> class(MSFT.mean.boot)
[1] "boot"
```

Number of bootstrap samples

```
> MSFT.mean.boot
```

ORDINARY NONPARAMETRIC BOOTSTRAP

Call:

```
boot(data = MSFT, statistic = mean.boot, R = 999)
```

Bootstrap Statistics :


	original	bias	std. error
t1*	0.02756	-0.00013	0.01052

Sample mean

Bootstrap estimate of
bias

Bootstrap estimate of SE

© Eric Zivot 2006



UW

Compare Bootstrap Statistics with Analytic Formulas

ORDINARY NONPARAMETRIC BOOTSTRAP

Call:
`boot(data = MSFT, statistic = mean.boot, R = 999)`

Bootstrap Statistics :

	original	bias	std. error
t1*	0.02756	-0.00013	0.01052

compare boot SE with analytic SE

```
> se.muhat.MSFT = sigmahat.MSFT/sqrt(length(MSFT))
> se.muhat.MSFT
```

[1] 0.01068

© Eric Zivot 2006

Bootstrap Confidence Intervals

```
> boot.ci(MSFT.mean.boot, conf = 0.95, type =
+         c("norm","perc"))
BOOTSTRAP CONFIDENCE INTERVAL CALCULATIONS
Based on 999 bootstrap replicates

CALL :
boot.ci(boot.out = MSFT.mean.boot, conf = 0.95, type =
        c("norm", "perc"))

Intervals :
Level      Normal              Percentile
95%  ( 0.0071, 0.0483 )  ( 0.0065, 0.0471 )
Calculations and Intervals on Original Scale
```

© Eric Zivot 2006

Example: Bootstrapping Sample SD

```
# function for bootstrapping sample standard deviation
sd.boot = function(x, idx) {
# arguments:
# x          data to be resampled
# idx        vector of scrambled indices created by
#            boot() function
# value:
# ans        sd value computed using resampled data
  ans = sd(x[idx])
  ans
}
```

© Eric Zivot 2006

Example: Bootstrapping Sample SD

```
> MSFT.sd.boot = boot(MSFT, statistic = sd.boot, R=999)
> MSFT.sd.boot
```

ORDINARY NONPARAMETRIC BOOTSTRAP

Call:
boot(data = MSFT, statistic = sd.boot, R = 999)

Bootstrap Statistics :



	original	bias	std. error
t1*	0.1068	-0.00145	0.01078

```
# compare boot SE with analytic SE based on CLT
> se.sigmahat.MSFT = sigmahat.MSFT/sqrt(2*length(MSFT))
> se.sigmahat.MSFT
```

```
[1] 0.00755
```

© Eric Zivot 2006

Histogram of t



```
> plot(MSFT.sd.boot)
```

© Eric Zivot 2006

Example: Bootstrapping Normal VaR

```
ValueAtRisk.boot = function(x, idx, p=0.05, w=100000) {
# x.mat      data to be resampled
# idx       vector of scrambled indices created by
#           boot() function
# p         probability value for VaR calculation
# w         value of initial investment
# value:
# ans       Value-at-Risk computed using resampled data

  q = mean(x[idx]) + sd(x[idx])*qnorm(p)
  VaR = (exp(q) - 1)*w
  VaR
}
```

© Eric Zivot 2006

Example: Bootstrapping Normal VaR

```
> MSFT.VaR.boot
```

ORDINARY NONPARAMETRIC BOOTSTRAP

Call:

```
boot(data = MSFT, statistic = ValueAtRisk.boot, R = 999)
```

Bootstrap Statistics :

	original	bias	std. error
t1*	-13769.40	210.2801	1886.953

© Eric Zivot 2006

