

NodeJS

środowisko i technologia ServerSide

PAWEŁ ŁUKASZUK



HEAT SET TO

63

71

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava

Kulturní výstava
Kulturní výstava



MongoDB

420 systems in ranking, May 2024

Rank			DBMS	Database Model	Score		
May 2024	Apr 2024	May 2023			May 2024	Apr 2024	May 2023
1.	1.	1.	Oracle +	Relational, Multi-model i	1236.29	+2.02	+3.66
2.	2.	2.	MySQL +	Relational, Multi-model i	1083.74	-3.99	-88.72
3.	3.	3.	Microsoft SQL Server +	Relational, Multi-model i	824.29	-5.50	-95.80
4.	4.	4.	PostgreSQL +	Relational, Multi-model i	645.54	+0.49	+27.64
5.	5.	5.	MongoDB +	Document, Multi-model i	421.65	-2.31	-14.96
6.	6.	6.	Redis +	Key-value, Multi-model i	157.80	+1.36	-10.33
7.	7.	↑ 8.	Elasticsearch	Search engine, Multi-model i	135.35	+0.57	-6.28
8.	8.	↓ 7.	IBM Db2	Relational, Multi-model i	128.46	+0.97	-14.56
9.	9.	↑ 11.	Snowflake +	Relational	121.33	-1.87	+9.61
10.	10.	↓ 9.	SQLite +	Relational	114.32	-1.69	-19.54

<https://db-engines.com/en/ranking>

Password encoding

Connection string used by MongoDB is ultimately just an example of URI

```
mongodb+srv://login:pass@cluster.mongodb.net/?retryWrites=true
```

This is why some special characters in login and password needs to be encoded – replaced by special sequence.

For instance:

- / → %2F
- : → %3A
- @ → %40

This can be done using any URL encoding tool

or with standard JavaScript function: `encodeURIComponent`



CRUD

- Create
- Read
- Update
- Delete



Create

- `db.collection.insertOne()`
- `db.collection.insertMany()`

All write operations in MongoDB are atomic on the level of a single document.

If collection does not exist, insert operations will create new collection.

If an inserted document omits the `_id` field the MongoDB driver automatically generates an `ObjectId` for the `_id` field



Create

```
db.collection.insertOne({  
  firstName: 'Jan',  
  lastName: 'Kowalski'  
});
```


```
db.collection.insertMany([  
  {  
    firstName: 'Jan1',  
    lastName: 'Kowalski1'  
  }, {  
    firstName: 'Jan2',  
    lastName: 'Kowalski2'  
  }  
]);
```



Read


- `db.collection.findOne()`
- `db.collection.find()`

If multiple documents match the criteria, `findOne` function returns the first document according to the order the documents are stored on disk.



Read

```
const user = await db.collection.findOne();  
console.table(user);  
  
const users = await db.collection.find()  
                                .toArray();  
console.table(users);
```



Read

Find functions can be extended with:

- complex search conditions: Query
- instruction to retrieve only part of documents: Projection
- cursor functions to get data about multiple results (sort, skip, limit)

```
db.collection.findOne({ query });
```

```
db.collection.find({ query })  
    .project({ projection })  
    .cursorFunction();
```



Read – query

Find method supports many different query operators to filter data

- comparison
- logical
- element
- evaluation
- geospatial
- array
- bitwise

```
{ field : { $operator : value } }
```



Read – query operators

Comparison query operators

- `$eq` `=` `// equal`
- `$ne` `!=` `// not equal`
- `$in` element in given array `// in`
- `$nin` element is not in given array `// not in`
- `$lt` `<` `// lesser than`
- `$lte` `<=` `// lesser than or equal`
- `$gt` `>` `// greater than`
- `$gte` `>=` `//greater than or equal`



Read – query operators

```
db.collection.findOne({ lastName : { $eq : "Kowalski" } });  
db.collection.find({ age : { $gt : 15 } });
```

Instead of equality operator \$eq we can use short syntax:

```
{ field : value } // is equal to { field : { $eq : value } }
```

```
db.collection.findOne({ lastName : "Kowalski" });  
  
// is equal to  
db.collection.findOne({ lastName : { $eq : "Kowalski" } });
```

Read – query operators

To check multiple conditions we can combine multiple checks with logical operators

- \$and
- \$or

```
{ logical_operator : [{firstCondition},{secondCondition}] }
```

```
{ $or : [{ firstName: "Adam" }, { lastName: "Kowalski" }] }
```

```
{ $and : [{ firstName: "Adam" }, { lastName: "Kowalski" }] }
```

Read – query operators simplifications

And operation can be simplified to syntax:

```
{ $and : [{ firstName: "Adam" }, { lastName: "Kowalski" }] }
```

// is equal to

```
{ firstName: "Adam", lastName: "Kowalski" }
```

Short syntax, only when using same field in all expressions

```
{ $and: [ { age: { $lt : 40 } } , { age: { $gt : 30 } } ] }
```

// is equal to

```
{ age : { $lt:40, $gt:30 } }
```


Read – query with a bit of complexity

Operators can be combined in more complex manner:

```
{ $and: [  
  { firstName: { $eq: "Adam" } },  
  { $or: [ { age: { $gt: 20 } },  
            { height: { $lt: 200 } } ] },  
]  
}
```

// could be explained as:

```
// ( firstName == "Adam" and (age > 20 or height < 200) )
```

Read – query and nested objects

To access nested objects is necessary to wrap field names with "" signs

// given document in database

```
{  
  "_id": { "$oid": "64287a5f57d7d23554a7f499" },  
  "firstName": "Jan2",  
  "lastName": "Kowalski2",  
  "isActive": true,  
  "address": { "postCode": "00-000" }  
}
```

// can be found using query

```
find({ "address.postCode" : "00-000"})
```

Read – query with null

```
find({ address : null})
```

This query will returns documents where address is null or address does not exists.

Operator \$exists can be used to query documents where a field exists or not, regardless of its value.

```
{ address : { $exists : false } } // address does not exists
```

```
{ address : { $exists : true } } // address exists (can be null or has value)
```


Read – query by type

Operator \$type can be used to query documents where the value of a field is of a specified BSON type.

There is also the “number” alias which can match against all numeric types (double, 32-bit integer, 64-bit integer, decimal).



Type	Number	Alias	Notes
Double	1	"double"	
String	2	"string"	
Object	3	"object"	
Array	4	"array"	
Binary data	5	"binData"	
Undefined	6	"undefined"	Deprecated.
ObjectId	7	"objectId"	
Boolean	8	"bool"	
Date	9	"date"	
Null	10	"null"	
Regular Expression	11	"regex"	
DBPointer	12	"dbPointer"	Deprecated.
JavaScript	13	"javascript"	
Symbol	14	"symbol"	Deprecated.
JavaScript code with scope	15	"javascriptWithScope"	Deprecated in MongoDB 4.4.
32-bit integer	16	"int"	
Timestamp	17	"timestamp"	
64-bit integer	18	"long"	
Decimal128	19	"decimal"	
Min key	-1	"minKey"	
Max key	127	"maxKey"	

Read – query by type

```
db.collection.find({ firstName : { $type: "string" }});
```

// is equal to

```
db.collection.find({ firstName : { $type: 2 }});
```



Read – projection

Projection controls which fields appear in the documents returned by read operations. Projections can help you limit unnecessary network bandwidth usage.

Projections work in two ways:

- include fields with a value of 1. This has the side-effect of implicitly excluding all unspecified fields.
- exclude fields with a value of 0. This has the side-effect of implicitly including all unspecified fields.

These two methods of projection are mutually exclusive:

if you explicitly include fields, you cannot explicitly exclude fields, and vice versa.



Read – projection

Projection specifies the fields to return in the documents that match the query filter

- 1 or true : include the field
- 0 or false : exclude the field

By default `_id` field is always returned

```
// return all fields except firstName
db.collection.find().project({ firstName : 0 });

// return firstName and _id
db.collection.find().project({ firstName : 1 });
```



Read – projection

```
// return only firstName
```

```
db.collection.find().project({ firstName : 1, _id : 0 });
```

```
// return only firstName, lastName, and _id
```

```
db.collection.find().project({ firstName : 1, lastName : 1 });
```

```
// return only firstName and lastName
```

```
db.collection.find()  
    .project({firstName : true, lastName : true, _id : false});
```

Read – sort

Sort changes order in which read operations return documents.

To sort returned documents by a field in ascending (lowest first) order, use a value of 1.

To sort in descending (greatest first) order instead, use -1.

If you do not specify a sort, MongoDB does not guarantee the order of query results.



Read – sort

```
// sort by firstName ascending
```

```
db.collection.find().sort({ firstName: 1 });
```

```
// sort by firstName descending
```

```
db.collection.find().sort({ firstName: -1 });
```

```
// sort by lastName ascending and then by firstName ascending
```

```
db.collection.find().sort({ lastName: 1, firstName: 1 });
```

```
// if two users have same lastName first one will be this one
```

```
// which firstName is first in alphabetic order
```


Read — skip

Skip omits documents from the beginning of the list of returned documents for a read operation.

You can combine skip with sort to omit the top (for descending order) or bottom (for ascending order) results for a given query.

```
db.collection.find().skip(1);
```



Read – limit

Cap the number of documents that can be returned from a read operation.

Limit functions as a cap on the maximum number of documents that the operation can return, but the operation can return a smaller number of documents if there are not enough documents present to reach the limit.


```
db.collection.find().limit(2);
```



Read – count

The Node.js driver provides two methods for counting documents in a collection:

- `countDocuments()` – returns accurate number of documents based on given query or number of all documents when query is empty
- `estimatedDocumentCount()` – returns estimated number of documents based on collection metadata, does not accept query



Read – count

```
// estimated number of documents in collection
```

```
db.collection.estimatedDocumentCount();
```

```
// number of documents in collection
```

```
db.collection.countDocuments();
```

```
// number of documents in collection that fulfills given condition
```

```
db.collection.countDocuments({ lastName : "Kowalski" });
```


Update

- `db.collection.updateOne()`
- `db.collection.updateMany()`

Update operation is atomic on the level of a single document

- `_id` field cannot be replaced with different value
- `$set` creates field if not already existing



Update

// set firstName as "Marek" in all documents

```
db.collection.updateMany({}, { $set: { firstName: 'Marek' } });
```

// set firstName as "Marek" in first document

```
db.collection.updateOne({}, { $set: { firstName: 'Marek' } });
```

// set firstName as "Marek" and isActive as true in first document where
lastName is Kowalski

```
db.collection.updateOne({ lastName: 'Kowalski' },  
                        { $set: { firstName: 'Marek', isActive: true } }  
);
```

Update – upsert

Upsert - update on match of filter or insert no match of filter. By default is set to false.


```
// if no document match query then those functions will create one document  
// { lastName: "Kowalski", firstName: "Marek", isActive: true }
```

```
db.collection.updateOne({ lastName: 'Kowalski' },  
                        { $set: { firstName: 'Marek', isActive: true } },  
                        { upsert : true });
```

```
db.collection.updateMany({ lastName: 'Kowalski' },  
                         { $set: { firstName: 'Marek', isActive: true } },  
                         { upsert : true });
```

Delete

- `db.collection.deleteOne()`
- `db.collection.deleteMany()`



Delete

```
// delete first document with firstName equal "Marek"
```

```
db.collection.deleteOne( { firstName: 'Marek' } );
```

```
// delete all documents
```

```
db.collection.deleteMany();
```

Collection operations

Create collection:

```
db.createCollection("Users");
```

Drop collection:

```
db.collection.drop();
```

Index support

Indexes are data structures that support the efficient execution of queries in MongoDB. They contain copies of parts of the data in documents to make queries more efficient.

```
db.collection.createIndex(  
    { firstName: 1, lastName: 1 }  
);
```

