

# Functional Programming (FPR)

Pawel Sawicz

25th March 2019

# Introduction

## Getting started

This document is an essay for Functional Programming course at Software Engineering Programme. I have been given two tasks, firstly to solve weighting puzzle in Haskell and explain my reasoning and decisions behind the code.

At the begining of this essay you might find a lot of explanation about fundamentals of functional programing (FP) theory and Haskell syntax.

As we move along you will find less text and more compacted descriptions of my approach, as there is not point to repeat myself.

I am aware of the `module` concept in Haskell, in the case of this submission I did not use it.

## Importing libraries

In Haskell by default you are given access to `Prelude` library, which contains core functions of the language. In order to use functions from other libraries, you need to use keyword `import`, which imports `module`.

```
import Data.List
import Data.Ord
import Data.Function
```

## State and Test Algebraic datatypes

What is Algebraic datatype ?

First we shall define two algebraic datatypes, `State` and `Test`.

### State

State datatype has two data constructors `Pair` and `Triple`. It should be noted here that everything in Haskell is a function therefore data constructor is also a function.

### Partial application

`Pair` constructor is a type of `Int -> Int -> State`. It means that we can looks at this in two ways. First, function takes two arguments and returns `State`, or it takes one argument and returns a function that takes one argument and returns `State`. In latter we say that function can be partially applied.

```
data State = Pair Int Int | Triple Int Int Int
  deriving (Eq, Show)
```

## Test

Test datatype has two data constructors, TPair and TTrip. TPair constructor takes two tuples. Tuple represents cartesian product of an arguments.

```
data Test = TPair (Int, Int) (Int, Int) | TTrip (Int,Int,Int) (Int,Int,Int)
  deriving (Eq, Show)
```

## Cartisian product vs series of functions

As you can see there are two different ways of representing an argument of a function. As a cartesian product or as a series of functions.

In Haskell we have ability to transpose cartesian product to series of functions by using currying, and vice versa.

## deriving keyword

Another piece that needs an explanation is keyword **deriving**. Keyword deriving allows us to make a datatype an instance of typeclass, in the instance of **State**, **Test** it derives (Eq and Show). Compiler automatically finds out default implementation for instance of typeclass.

Alternatively we can manually make an instance of desired typeclass by denoting

```
instance Eq Test where
```

We shall define valid function such that determine whether a given test is valid in a given state.

By using pattern matching this guards that TPair test will be only conducted in a Pair state, and a TTrip test in a Triple state.

In addition to that there are predicates that checks validity of test against state.

We denoted following predicates :

1. The number of coins is the same in each pan of the scale
2. There is sufficiently many coins in the various piles for the test

```
valid :: State -> Test -> Bool
valid (Pair u g) (TPair (a, b) (c ,d)) =
  (a+b) == (c+d) &&
  (a+c) <= u &&
  (a+b+c+d) <= (u+g)
valid (Triple l h g) (TTrip (a, b, c) (d, e, f)) =
  (a+b+c) == (d+e+f) &&
```

```
(a+d) <= l &&  
(b+e) <= h &&  
(c+f) <= g
```

# Choosing and conducting a test

## Outcome function

We define function outcomes such that for state `s` and test `t` that `valid s t = True`, works out the possible outcomes.

As this is a partial function, if `valid s t = False` then return an error otherwise proceed with generation of outcomes.

This function returns three

```
outcomes :: State -> Test -> [State]
outcomes (Pair u g) (TPair (a, b) (c, d))
  | valid (Pair u g) (TPair (a, b) (c, d)) == True =
    [Pair un gc] ++
    [Triple l h gcc] ++
    [Triple l h gcc]
  | otherwise = error ("Invalid state or test" ++ (show (Pair u g)))
  where
    un = (u - (a + c))
    gcc = (u - (a + c)) + g
    gc = g + a + c
    l = a
    h = c
outcomes (Triple l h g) (TTrip (a, b, c) (d, e, f))
  | valid (Triple l h g) (TTrip (a, b, c) (d, e, f)) == True =
    [Triple (a+d) (b+e) (g+(1-(a+d))+(h-(b+e)))] ++ -- 1 1 10
    [Triple (a+d) (b+e) (g+(1-(a+d))+(h-(b+e)))] ++ -- 1 1 10
    [Triple (1-(a+d)) (h-(b+e)) (g+a+b+d+e)] -- 2 2 8
  | otherwise = error ("Invalid state or test:" ++ " "
    ++ (show (Triple l h g)) ++ " "
    ++ (show (TTrip (a, b, c) (d, e, f))))
```

## Weighings

Weighings function has different implementation for each of the `State` constructor. We uses set comprehension in order to generate valid weighings. As you can notice there are few predicates to generate sensible tests.

such that :

- $a+b+c = d+e+f$  - same number of coins per pan
- $a+b+c > 0$
- $c \times f = 0$
- $a + b \leq 1$
- $b + e \leq h$
- $c + f \leq g$
- $(a,b,c) \leq (d,e,f)$

```

weighings :: State -> [Test]
weighings (Pair u g) = [TPair (a,b) (a+b, 0) | a<-[0..u], b<-[0..g],
    (a+b) > 0,
    ((2*a)+b) <= u,
    b <= g]
weighings (Triple l h g) = [TTrip (a, b, c) (d, e, f) | k1<-[1..k],
    (a, b, c) <- choices k1 (l, h, g),
    (d, e, f) <- choices k1 (l, h, g),
    c == 0 || f == 0, (a,b,c) <= (d,e,f), (c+f) <= g, (b+e) <= h, (a+d) <= l, (a+b+
    where
        k = (l+h+g) `div` 2

```

Choices function uses set comprehension with predicates to generate valid selections of  $k$  coins.

```

choices :: Int -> (Int, Int, Int) -> [(Int, Int, Int)]
choices k (l, h, g) = [(i,j,k-i-j) | i<-[0..l], j<-[0..h],
    (k-i-j) <= g,
    (k-i-j) >= 0]

```

Below code, is a case of manually set up an instance of type class. Typeclass `Ord` has two functions. This is special purpose ordering on `State`, which we use to determine whether state gives strictly more information about the coins.  $s < s'$

- “
- “

We need to implement those functions for type that derived `Ord` typeclass.

```

instance Ord State where
    (Pair _ _) < (Triple _ _ _) = False
    (Pair _ g1) < (Pair _ g2) = g2 < g1
    (Triple _ _ g1) < (Triple _ _ g2) = g2 < g1

    (Pair _ _) <= (Triple _ _ _) = False
    (Pair _ g1) <= (Pair _ g2) = g2 <= g1
    (Triple _ _ g1) <= (Triple _ _ g2) = g2 <= g1

```

Productive function checks if all outcomes making a progress, by using special purpose ordering on state  $s < s'$

```

productive :: State -> Test -> Bool
productive s t = all (s > ) (outcomes s t)

```

Test function uses two other functions. `weighings`, `productive` and `filter`. First two are defined by us. `Filter` is part of library. Which filters out an collection by provided predicate.

```

tests :: State -> [Test]
tests s = filter (productive s) (weighings s)

```

# Decision tree

Now we can introduce `Tree` data type that represents weighting process. It's a ternary tree. This datatype has two constructors, `Stop` that represents final state as a leaf of the tree. 'Node that represents weighting as a node of the tree.

```
data Tree = Stop State | Node Test [Tree]
  deriving (Show)
```

Final is a predicate that determine whether `State` is final.

```
final :: State -> Bool
final (Pair u g)
  | u == 0 = True
  | otherwise = False
final (Triple l h g)
  | l == 1 && h == 0 = True
  | l == 0 && h == 1 = True
  | otherwise = False
```

height function, case `(Stop s)` simply returns 0. `(Node _ xs)` recursively calculates height of a tree and then selects maximum value.

```
height :: Tree -> Int
height (Stop s) = 0
height (Node _ xs) = 1 + maximum (map height xs)
```

minHeight is a partial function that throws an error for empty set. Then it calculates height on elements and returns a tuple of `Tree` and its height. Then collection is sorted and selected first element.

```
minHeight :: [Tree] -> Tree
minHeight [] = error "Tree cannot be empty"
minHeight xs = snd
  $ head
  $ sortBy (compare `on` (\(y,_) -> y))
  $ map (\x -> (height x, x)) xs
```

mktree function generate tree recursively for each outcome `s t`.

```
mktree :: State -> Tree
mktree s
  | (final s) == True = Stop s
  | otherwise = minHeight
    $ map subTree
    $ productiveTests
  where
    productiveTests = tests s
    subTree = (\t -> (Node t (map mktree (getOutcomes s t))))
    getOutcomes = (\s t -> (outcomes s t))
```

## Caching heights

Program in the previous sections works but it is rather slow. One of the problems is that it is recomputing the heights of trees. Now we will try to introduce height on each Node so that we can compute it in constant time.

We define new datatype `TreeH`. As you can see it's very similar to previous `Tree` with one change. We introduce notion of height in the `NodeH` constructor.

```
data TreeH = StopH State | NodeH Int Test [TreeH]
  deriving Show
```

Function that extracts height out of `TreeH` type.

```
heightH :: TreeH -> Int
heightH (StopH s) = 0
heightH (NodeH h t ts) = h
```

`treeH2tree` that will map `TreeH` type to `Tree`. In this case `TreeH` loses direct access to its height.

```
treeH2tree :: TreeH -> Tree
treeH2tree (StopH s) = (Stop s)
treeH2tree (NodeH h t ts) = (Node t (map treeH2tree ts))
```

`nodeH` is a function that for given `Test` and list of tries, it will construct new `TreeH`.

```
nodeH :: Test -> [TreeH] -> TreeH
nodeH t ths = NodeH ((+) 1 $ maximum $ map heightH ths) t ths
```

`tree2treeH` is just an inverse of `treeH2tree`.

```
tree2treeH :: Tree -> TreeH
tree2treeH (Stop s) = (StopH s)
tree2treeH (Node t ts) = nodeH t (map tree2treeH ts)
```

As you can notice `heightH . tree2treeH = height`. This equality holds due to function composition law. Let's do quick type check.

`heightH` has a type `TreeH -> Int`, `tree2treeH` has a type `Tree -> TreeH`. Composition of those two functions has type `Tree -> TreeH -> TreeH -> Int` it can be simplified to `Tree -> Int` (composition law), which is a type signature of our `height` function.

We could also prove it by induction.

Finally we can implement function that constructs tree for given state.

```
mtreeH :: State -> TreeH
mtreeH s
  | (final s) == True = (StopH s)
  | otherwise = head $ sortBy (compare `on` heightH) $ subTree $ productiveTests
    where
      productiveTests = tests s
      subTree = map (\t -> nodeH t (map mtreeH (getOutcomes s t)))
      getOutcomes = (\s t -> (outcomes s t))
```



As it was stated in an assignment. This approach does not massively improve performance.

## Greedy solution

This function was copied from assignment description.

```
optimal :: State -> Test -> Bool
optimal (Pair u g) (TPair (a,b) (ab,0)) =
    (2 * a + b <= p) && (u - 2 * a - b <= q)
    where
        p = 3 ^ (t - 1)
        q = (p - 1) `div` 2
        t = ceiling (logBase 3 (fromIntegral (2 * u + k)))
        k = if g == 0 then 2 else 1
optimal (Triple l h g) (TTrip (a,b,c) (d,e,f)) =
    (a+e) `max` (b+d) `max` (l-a-d+h-b-e) <= p
    where
        p = 3 ^ (t - 1)
        t = ceiling (logBase 3 (fromIntegral (l+h)))
```

Function that filters unoptimal weighings, leaving just optimals.

```
bestTests :: State -> [Test]
bestTests s = filter (optimal s) (weighings s)
```

Function that builds tree out of the first optimal test.

```
mktreeG :: State -> TreeH
mktreeG s
    | (final s) == True = (StopH s)
    | otherwise = subTree $ bestTest
    where
        bestTest = head $ bestTests s
        subTree = (\t -> nodeH t (map mktreeG (getOutcomes s t)))
        getOutcomes = (\s t -> (outcomes s t))
```

Function that builds tries based on all optimal tests

```
mktreesG :: State -> [TreeH]
mktreesG s
    | (final s) == True = [StopH s]
    | otherwise = concat $ makeTree
    where
        optimalTests = bestTests s
        makeTree = map (\t -> map mktreeG (outcomes s t)) $ optimalTests
```

## Conclusion

Haskell is a perfect tool for mathematical puzzles. Code is much more compacted in compare with more popular languages like (C, C#, Java). That is because Haskell by default support features that other languages do not, like :

1. tail-recursion
2. lazy evaluation
3. high-orderism

This puzzle merly shows us power of functional paradigm and Haskell. There is whole separate field of study that concerns about patterns of behaviour in abstractions (Category Theory).

## What to improve, ideas ?

Error handling patter, by using Either bifunctor. pattern