产品详情

Product details

型号	电压	电流	功率	扬程	流量	启动电压	防水等级
JT-DC3W-3	3V	0.12	0.36	0.35	80	1	IP68
JT-DC3W*4.5	4.5V	0.18	0.91	0.55	100	1	IP68



型묵	电压	电流	功率	扬程	流量	启动电压	防水等级
JT-DC3L-3	3V	0.12	0.36	0.35	80	1	IP68
JT-DC3L-4.5	4.5V	0.18	0.91	0.55	100	1	IP68





	使	用方式	
Water	Box	水箱	~
		_	↑ Outlet
			出水口
			Dr
			Intake 进水口

使用范	围及材质说明
RETHER	等于-20度到60度
使用可染相 度	SOMBER F
REPARK.	年于-20度560度
REFE	s. Tambidehirben
ERGP (Operation place)	窓 庁、成果等
44 I Head	>200M(選集工作)
42	106
⊕ir (unglichet sourc)	<0.08
AGA LINE I PAR (NOLL BALANIA)	485
4.890	教気体水間
488091	2000年 創造130度
4.14世界	A35
n Award	PYC
48.004	140월 55033FW/XIH

	使用注意事项 (原、 表示一定要为直接改变 (如果)
	(多) 电统一元使对直接执电(即电电 (金) (1) 中国数),由东国在建设的电
	(电影、光热器)、电热自由规范的电 (特别、严禁起压特别)
 A B B B B B B B B B B B B B B B B B B B	
	1 被货给承货用。
	3500的杂质和导激现我的被保中使
用。如水质过度	要及时被使水原原宣布的杂质。
	In K page K without and to for K great
	ery, with IX gover magin, transporter).
	the preparated voltage marge, first can use
H. It to structly	problems without maker for a long time
	eministrat to used to scripty and algorithm
en in message	Recording to may be start and appropria
	manufactured to the Steam Securities and
	eter time v. 20 66 gert to be, such as the mose
	to the the one and chaker of the

接口说明

红线: 电机正极 黑线: 电机负极

适用水管:适用于内径6mm水管