

Commence Database API

This Guide documents the Commence Database API and the Automation objects that it supports. The Reference section details the properties and methods of each of the objects.

Reference

[ICommenceDB](#)

[ICommenceCursor](#)

[ICommenceConversation](#)

[ICommenceQueryRowset](#)

[ICommenceAddRowset](#)

[ICommenceEditRowset](#)

[ICommenceDeleteRowset](#)

[Constants](#)

[Developer Notes](#)

ICommenceDB Object

Represents a Commence Database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

Properties

String Name

(read-only) Name of the Commence database.

String Path

(read-only) Full path of the Commence database.

String RegisteredUser

(read-only) CR/LF delimited string with user name, company name and serial number.

Boolean Shared

(read-only) TRUE if database is enrolled in a workgroup.

String Version

(read-only) Version number in x.y format.

String VersionExt

(read-only) Version number in x.y.z.w format.

Methods

[ICommenceConversation](#) GetConversation

Create a conversation object.

[ICommenceCursor](#) GetCursor

Create a cursor object.

ICommenceDB::Name

Data Type

String

Description

(read-only) Name of the Commence database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::Path

Data Type

String

Description

(read-only) Full path of the Commence database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::RegisteredUser

Data Type

String

Description

(read-only) CR/LF delimited string with user name, company name and serial number.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::Shared

Data Type

Boolean

Description

(read-only) TRUE if database is enrolled in a workgroup.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::Version

Data Type

String

Description

(read-only) Version number in x.y format.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::VersionExt

Data Type

String

Description

(read-only) Version number in x.y.z.w format.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

See Also

[ICommenceDB](#)

ICommenceDB::GetConversation

ICommenceConversation **GetConversation**(String
pszApplicationName, **String** *pszTopic*)

Create a conversation object.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

Return Value

Returns a pointer to conversation object on success, NULL on error.

Parameters

pszApplicationName

DDE Application name.

The only valid value is "Commence".

pszTopic

DDE Topic name, must be a valid Commence topic name.

The DDE.HLP file contains a reference to the allowed DDE topic names.

Examples include "GetData", "ViewData", etc.

See Also

Related Methods and Objects

[ICommenceDB](#)

[ICommenceConversation](#)

[ICommenceConversation::Execute](#)

[ICommenceConversation::Request](#)

ICommenceDB::GetCursor

ICommenceCursor GetCursor(Long *nMode*, String *pName*, Long *nFlags*)

Create a cursor object.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DB.D

Return Value

Returns a pointer to cursor object on success, NULL on error.

Parameters

nMode

Type of Commence data to access with this cursor.

Valid values are:

0 - CMC_CURSOR_CATEGORY

Use the Commence category specified by *pName*.

1 - CMC_CURSOR_VIEW

Use the Commence view specified by *pName*.

2 - CMC_CURSOR_PILOTAB

Use the Commence category and fields defined from Preferences - Other Apps - 3Com Pilot Address Book

3 - CMC_CURSOR_PILOTMEMO

Use the Commence category and fields defined from Preferences - Other Apps - 3Com Pilot Memo Pad

5 - CMC_CURSOR_PILOTTODO

Use the Commence category and fields defined from Preferences - Other Apps - 3Com Pilot To Do List

6 - CMC_CURSOR_PILOTAPPT

Use the Commence category and fields defined from Preferences - Other Apps - 3Com Pilot Date Book

pName

Name of an object in the database.

Use determined by nMode:

For CMC_CURSOR_CATEGORY, pName is the category name.

For CMC_CURSOR_VIEW, pName is the view name.

For CMC_CURSOR_PILOTAB, pName is unused.

For CMC_CURSOR_PILOTMEMO, pName is unused.

For CMC_CURSOR_PILOTTODO, pName is unused.

For CMC_CURSOR_PILOTAPPT, pName is unused.

nFlags

Addition option flags.

Logical OR of following option flags:

CMC_FLAG_PILOT - Save Item agents defined for the Pilot

subsystem will fire.

CMC_FLAG_INTERNET - Save Itgem agents defined for the

Internet/intranet will fire.

Comments

For CMC_CURSOR_CATEGORY, the resulting cursor will have a column set composed of all supported fields in the category (in no particular order).

For CMC_CURSOR_VIEW, the resulting cursor will inherit the view's filter, sort and column set. ICommenceCursor methods can be used to change these attributes.

For CMC_CURSOR_PILOT*, the column set for the resulting cursor will only include fields defined by the Commence

preferences (in no particular order). It is not possible to change the filter, sort or column set.

See the Developer Notes for more information about the CMC_FLAG_PILOT and CMC_FLAG_INTERNET flags.

See Also

Related Methods and Objects

[ICommenceDB](#)

[ICommenceCursor](#)

[ICommenceCursor::SetFilter](#)

[ICommenceCursor::SetLogic](#)

[ICommenceCursor::SetSort](#)

[ICommenceCursor::SetColumn](#)

ICommenceCursor Object

Represents a cursor or query that is built to retrieve data

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Properties

String Category

(read-only) Name of the underlying Commence category.

Long ColumnCount

(read-only) Number of columns in this cursor (-1 on error).

Long RowCount

(read-only) Number of rows in this cursor (-1 on error).

Boolean Shared

(read-only) TRUE if category is shared in a workgroup.

Methods

Boolean SetColumn(Long nColumn, String pName, Long nFlags)

Defines the column set for the cursor.

Boolean SetFilter(String pFilter, Long nFlags)

Defines a filter clause for the cursor.

Boolean SetLogic(String pLogic, Long nFlags)

Defines the filter logic for the cursor.

Boolean SetSort(String pLogic, Long nFlags)

Defines the sort criteria for the cursor.

Long SeekRow(Long bkOrigin, Long nRows)

Seek to a particular row in the cursor.

Long SeekRowApprox(Long nNumerator, Long nDenom)

Seek to an approximate position in the cursor.

[ICommenceQueryRowSet](#) GetQueryRowSet(Long nCount, Long nFlags)

Create a rowset object with the results of a query.

[ICommenceQueryRowSet](#) **GetQueryRowSetByID(String pRowID, Long nFlags)**

Create a rowset object with a particular row loaded.

[ICommenceAddRowSet](#) **GetAddRowSet(Long nCount, Long nFlags)**

Create a rowset of new items to add to the database.

[ICommenceEditRowSet](#) **GetEditRowSet(Long nCount, Long nFlags)**

Create a rowset of existing items for editing.

[ICommenceEditRowSet](#) **GetEditRowSetByID(String pRowID, Long nFlags)**

Create a rowset for editing a particular row.

[ICommenceDeleteRowSet](#) **GetDeleteRowSet(Long nCount, Long nFlags)**

Create a rowset of existing items for deletion.

[ICommenceDeleteRowSet](#) **GetDeleteRowSetByID(String pRowID, Long nFlags)**

Create a rowset for deleting a particular row.

Boolean SetActiveItem

Set active item used for view cursors using a view linking filter.

Boolean SetActiveDate

Set active date used for view cursors using a view linking filter.

Boolean SetActiveDateRange

Set active date range used for view cursors using a view linking filter.

Boolean SetRelatedColumn

Adds a related (indirect/connected field) column to the cursor.

ICommenceCursor::Category

Data Type

String

Description

(read-only) Name of the underlying Commence category.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

See Also

[ICommenceCursor](#)

ICommenceCursor::ColumnCount

Data Type

Long

Description

(read-only) Number of columns in this cursor (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

See Also

[ICommenceCursor](#)

ICommenceCursor::RowCount

Data Type

Long

Description

(read-only) Number of rows in this cursor (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

See Also

[ICommenceCursor](#)

ICommenceCursor::Shared

Data Type

Boolean

Description

(read-only) TRUE if category is shared in a workgroup.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

See Also

[ICommenceCursor](#)

ICommenceCursor::SetFilter

Boolean SetFilter(String *pFilter*, Long *nFlags*)

Defines a filter clause for the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

pFilter

Text defining the new filter clause. Syntax is identical to the one used by the DDE ViewFilter request (qv).

nFlags

Unused at present, must be 0.

Comments

The *pFilter* string defines which filter clause is to be replaced. If the clause is already defined it will be overwritten.

If the cursor is opened in `CURSOR_VIEW` mode, the `SetFilter` only affects the cursor's secondary filter. That is, when building the rowset, the view's filter is first evaluated. Items that match are then passed through the cursor's secondary filter. The rowset only contains items that satisfy both filters.

See Also

[ICommenceCursor SetLogic](#)

ICommenceCursor::SetLogic

Boolean SetLogic(String *pLogic*, Long *nFlags*)

Defines the filter logic for the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

pLogic

Text defining the new filter logic. Syntax is identical to the one used by the DDE ViewConjunction request (qv).

nFlags

Unused at present, must be 0.

Comments

Unless otherwise specified, the default logic is AND, AND, AND.

See Also

[ICommenceCursor SetFilter](#)

ICommenceCursor::SetSort

Boolean SetSort(String *pSort*, Long *nFlags*)

Defines the sort criteria for the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

pSort

Text defining the new sort criteria. Syntax is identical to the one used by the DDE ViewSort request (qv).

nFlags

Unused at present, must be 0.

Comments

If the cursor is opened in CMC_CURSOR_VIEW mode, the sort defaults to the view's sort. All other cursor modes default to ascending sort by the Name field.

See Also

[ICommenceCursor](#)

ICommenceCursor::SetColumn

Boolean SetColumn(Long *nColumn*, String *pName*, Long *nFlags*)

Defines the column set for the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

nColumn

The (0-based) index of the column to set.

pName

Name of the field to use in this column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_ALL - create column set of all fields

Comments

When defining a column set, the columns must be defined in sequential order (0, 1, 2, etc.). This is to prevent problems with undefined columns (e.g. 0, 1, 3, ...).

Duplicate columns are not supported. Each column must map to a different field.

Not all Commence field types can be included in the cursor definition. The set of supported field types exactly matches those fields that can be displayed in a Commence report (minus combined fields and indirect fields).

See Also

[ICommenceCursor](#) [ICommenceDB::GetCursor](#)

ICommenceCursor::SeekRow

Long SeekRow(Long *bkOrigin*, Long *nRows*)

Seek to a particular row in the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Actual number of rows moved, -1 on error.

Parameters

bkOrigin

Position to move from.

Can be one of the following:

BOOKMARK_BEGINNING (0) - from first row

BOOKMARK_CURRENT (1) - from current row

BOOKMARK_END (2) - from last row

nRows

Number of rows to move the current row pointer.

Comments

For any cursor, there is a 'current row pointer'. When the cursor is created, this defaults to the first row. SeekRow will reposition the current row pointer. GetQueryRowSet, GetEditRowSet and GetDeleteRowSet will also advance the current row pointer.

See Also

[ICommenceCursor RowCount](#)

[SeekRowApprox](#)

[GetQueryRowSet](#)

[GetEditRowSet](#)

[GetDeleteRowSet](#)

ICommenceCursor::SeekRowApprox

Long SeekRowApprox(Long *nNumerator*, Long *nDenominator*)

Seek to an approximate position in the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Actual number of rows moved, -1 on error.

Parameters

nNumerator

Numerator for fractional position in the cursor.

nDenominator

Denominator for the fractional position in the cursor.

See Also

[ICommenceCursor RowCount](#)

[SeekRow](#)

[GetQueryRowSet](#)

[GetEditRowSet](#)

[GetDeleteRowSet](#)

ISCommenceCursor::GetQueryRowSet

ISCommenceQueryRowSet GetQueryRowSet(Long *nCount*, Long *nFlags*)

Create a rowset object with the results of a query.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

nCount

Maximum number of rows to retrieve.

nFlags

Unused at present, must be 0.

Comments

The rowset inherits to column set from the cursor.

The cursor's 'current row pointer' determines the first row to be included in the rowset.

The returned rowset can have fewer than *nCount* rows (e.g. if the current row pointer is near the end). Use ISCommenceXRowSet::RowCount to determine the actual row count.

GetQueryRowSet will advance the 'current row pointer' by the number of rows in the rowset.

See Also

[ISCommenceCursor](#)

[ISCommenceQueryRowSet](#)

[RowCount](#)

[SeekRow](#)

[SeekRowApprox](#)

ICommenceCursor::GetQueryRowSetByID

ICommenceQueryRowSet GetQueryRowSetByID(String *pRowID*, Long *nFlags*)

Create a rowset object with a particular row loaded.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

pRowID

Unique ID string obtained from GetRowID().

nFlags

Unused at present, must be 0.

Comments

The rowset inherits to column set from the cursor.

The cursor's 'current row pointer' is not advanced.

See Also

[ICommenceCursor](#) [ICommenceQueryRowSet::GetRowID](#)

ICommenceCursor::GetAddRowSet

ICommenceAddRowSet **GetAddRowSet**(Long *nCount*, Long *nFlags*)

Create a rowset of new items to add to the database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

(Long nCount, Long nFlags)

Parameters

nCount

Number of rows to create.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_SHARED - all rows default to shared

Comments

The rowset inherits the column set from the cursor.

When first created, each row is initialized to field default values.

See Also

[ICommenceCursor](#) [ICommenceAddRowSet](#)

ICommenceCursor::GetEditRowSet

ICommenceEditRowSet **GetEditRowSet**(Long *nCount*, Long *nFlags*)

Create a rowset of existing items for editing.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

nCount

Number of rows to retrieve.

nFlags

Unused at present, must be 0.

Comments

The rowset inherits the column set from the cursor.

See Also

[ICommenceCursor](#) [ICommenceEditRowSet](#)

ICommenceCursor::GetEditRowSetByID

ICommenceEditRowSet **GetEditRowSetByID**(String *pRowID*, Long *nFlags*)

Create a rowset for editing a particular row.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

pRowID

Unique ID string obtained from GetRowID().

nFlags

Unused at present, must be 0.

Comments

The rowset inherits the column set from the cursor.

The cursor's 'current row pointer' is not advanced.

See Also

[ICommenceCursor](#) [ICommenceQueryRowSet::GetRowID](#)

[ICommenceEditRowSet::GetRowID](#)

[ICommenceDeleteRowSet::GetRowID](#)

ISCommenceCursor::GetDeleteRowSet

ISCommenceDeleteRowSet **GetDeleteRowSet**(Long *nCount*, Long *nFlags*)

Create a rowset of existing items for deletion.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

nCount

Number of rows to retrieve.

nFlags

Unused at present, must be 0.

Comments

The rowset inherits the column set from the cursor.

See Also

[ISCommenceCursor](#) [ISCommenceDeleteRowSet](#)

ICommenceCursor::GetDeleteRowSetByID

ICommenceDeleteRowSet **GetDeleteRowSetByID**(String *pRowID*, Long *nFlags*)

Create a rowset for deleting a particular row.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns Pointer to rowset object on success, NULL on error.

Parameters

pRowID

Unique ID string obtained from GetRowID().

nFlags

Unused at present, must be 0.

Comments

The rowset inherits the column set from the cursor.

The cursor's 'current row pointer' is not advanced.

See Also

[ICommenceCursor](#) [ICommenceDeleteRowSet](#)

[ICommenceQueryRowSet::GetRowID](#)

[ICommenceEditRowSet::GetRowID](#)

[ICommenceDeleteRowSet::GetRowID](#)

ICommenceCursor::SetActiveItem

Boolean SetActiveItem(String *pCategoryName*, String *pRowID*, Long *flags*)

Set active item used for view cursors using a view linking filter.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, else FALSE on error

Parameters

pCategoryName

Category name of the active item used with view linking filter.

pRowID

Unique ID string obtained from GetRowID() indicating the active item used with view linking filter.

flags

Unused at present, must be 0.

Comments

This method is used with a view cursor using view linking by active item. This method enables the active item to be set via the API, separate from the active item in the Commence UI.

See Also

[ICommenceCursor SetActiveDate](#)

[SetActiveDateRange](#)

[ICommenceQueryRowSet::GetRowID](#)

ICommenceCursor::SetActiveDate

Boolean SetActiveDate(String *sDate*, Long *flags*)

Set active date used for view cursors using a view linking filter.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, else FALSE on error

Parameters

sDate

Date value used with view linking filter; supports AI date values such as 'today'.

flags

Unused at present, must be 0.

Comments

This method is used with a view cursor using view linking by active date. This method enables the active date to be set via the API, separate from the active date in the Commence UI.

See Also

[ICommenceCursor SetActiveItem](#)
[SetActiveDateRange](#)

ICommenceCursor::SetActiveDateRange

Boolean SetActiveDateRange(String *startDate*, String *endDate*, Long *flags*)

Set active date range used for view cursors using a view linking filter.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, else FALSE on error

Parameters

startDate

Date value of start date used with view linking filter; supports AI date values such as 'today'.

endDate

Date value of end date used with view linking filter; supports AI date values such as 'next monday'.

flags

Unused at present, must be 0.

Comments

This method is used with a view cursor using view linking by active date range. This method enables the active date range to be set via the API, separate from the active date range in the Commence UI.

See Also

[ICommenceCursor SetActiveItem](#)
[SetActiveDate](#)

ICommenceCursor::SetRelatedColumn

Boolean SetRelatedColumn(Long *nColumn*, String *pConnName*, String *pCatName*, String *pName*, Long *nFlags*)

Adds a related (indirect/connected field) column to the cursor.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CURSOR.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

nColumn

The (0-based) index of the column to set.

pConnName

Name of the connection to use in this column.

pCatName

Name of the connected Category to use in this column.

pName

Name of the field in the connected category to use in this column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_ALL - create column set of all fields

Comments

When defining a column set, the columns must be defined in sequential order (0, 1, 2, etc.). This is to prevent problems with undefined columns (e.g. 0, 1, 3, ...).

Duplicate columns are not supported. Each column must map to a different field.

Not all Commence field types can be included in the cursor definition. The set of supported field types exactly matches those fields that can be displayed in a Commence report (minus combined fields and indirect fields).

Sample call: `SetRelatedColumn("Relates To", "History", "Date", 0)`

This call will add the Date field to the cursor via the 'Relates to History' connection.

See Also

[ICommenceCursor](#) [ICommenceDB::GetCursor](#)

ICommenceConversation Object

Represents a DDE conversation.

Defined in:

E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CONVERSATION.D

Methods

Boolean Execute(String pDDECommand)

Executes the DDE Command.

String Request(String pDDECommand)

Processes the DDE Request.

ICommenceConversation::Execute

Boolean Execute(String *pDDECommand*)

Executes the DDE Command.

Defined in:

E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CONVERSATION.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

pDDECommand

Text with the DDE command. Syntax is identical to the commands used by the DDE API.

Comments

TBD.

See Also

[ICommenceConversation](#)

ICommenceConversation::Request

String Request(String *pDDECommand*)

Processes the DDE Request.

Defined in:

E:/DEV/PIM80/DOCS/DBAPI/PIMOA/CONVERSATION.D

Return Value

Returns String value on success.

Parameters

pDDECommand

Text with the DDE Request. Syntax is identical to the commands used by the DDE API.

Comments

TBD.

See Also

[ICommenceConversation](#)

ICommenceAddRowSet Object

Represents the set of new items to add to the database

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Properties

Long ColumnCount

(read-only) Number of columns in this rowset (-1 on error).

Long RowCount

(read-only) Number of rows in this rowset (-1 on error).

Methods

Long Commit

Make row modifications permanent (commit to disk).

[ICommenceCursor](#) **CommitGetCursor**

Make row modifications permanent (commit to disk) and return a cursor

Long GetColumnIndex

Search the column set and return the index of the column with the given label.

String GetColumnLabel

Return the label associated with a particular column.

String GetRow

Returns an entire row's field values.

String GetRowValue

Returns the field value at the given (row,column) in text form.

Long ModifyRow

Modify a field value in the rowset. for the newly added data.

Boolean SetShared

Mark a row to be shared.

Boolean GetShared

Return the row's current shared vs. local status.

ICommenceAddRowSet::ColumnCount

Data Type

Long

Description

(read-only) Number of columns in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

See Also

[ICommenceAddRowSet](#)

ICommenceAddRowSet::RowCount

Data Type

Long

Description

(read-only) Number of rows in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

See Also

[ICommenceAddRowSet](#)

ICommenceAddRowSet::GetRowValue

String GetRowValue(Long *nRow*, Long *nCol*, Long *nFlags*)

Returns the field value at the given (row,column) in text form.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns Field value in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in
canonical form

Comments

See the Developer Notes for more information about the canonical format.

See Also

[ICommenceAddRowSet RowCount](#)
[ColumnCount](#)
[GetRow](#)

ICommenceAddRowSet::GetColumnLabel

String GetColumnLabel(Long *nCol*, Long *nFlags*)

Return the label associated with a particular column.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns Column label in text form on success, NULL on error.

Parameters

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will return the labels used with the view. Specify the CMC_FLAG_FIELD_NAME to force the underlying Commence field name to be returned.

See Also

[ICommenceAddRowSet GetColumnIndex](#)

ICommenceAddRowSet::GetColumnIndex

Long GetColumnIndex(String *pLabel*, Long *nFlags*)

Search the column set and return the index of the column with the given label.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns 0-based column index on success, -1 on error.

Parameters

pLabel

The column label to map.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will first search the view labels for a possible match. If not found, the field labels will then be searched. Specify the CMC_FLAG_FIELD_NAME to force only the underlying Commence field name to be searched.

See Also

[ICommenceAddRowSet GetColumnLabel](#)

ICommenceAddRowSet::ModifyRow

Long ModifyRow(Long *nRow*, Long *nCol*, String *pBuf*, Long *nFlags*)

Modify a field value in the rowset.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

pBuf

New field value in text form.

nFlags

Unused at present, must be 0.

Comments

Modifications to the rowset will be reflected by GetRowValue() and GetRow() but changes are not permanent until Commit() is called.

See Also

[ICommenceAddRowSet Commit](#)
[CommitGetCursor](#)

ISCommenceAddRowSet::Commit

Long Commit(Long *nFlags*)

Make row modifications permanent (commit to disk).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nFlags

Unused at present, must be 0.

Comments

After Commit(), the ISCommenceAddRowSet is no longer valid and should be discarded.

See Also

[ISCommenceAddRowSet ModifyRow](#)
[CommitGetCursor](#)

ISCommenceAddRowSet::CommitGetCursor

ISCommenceCursor CommitGetCursor(Long *nFlags*)

Make row modifications permanent (commit to disk) and return a cursor for the newly added data.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns ISCommenceCursor object on success, NULL on error.

Parameters

nFlags

Unused at present, must be 0.

Comments

After Commit(), the ISCommenceAddRowSet is no longer valid and should be discarded.

See Also

[ISCommenceAddRowSet ModifyRow](#)
[Commit](#)

ICommenceAddRowSet::GetRow

String GetRow(Long *nRow*, String *pDelim*, Long *nFlags*)

Returns an entire row's field values.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns Row values in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

pDelim

Delimiter to use between field values.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

pDelim is used to separate field values. pDelim can be up to 20 chars.

Returned string is EOS terminated. Format is: <col1><delim><col2><delim>...<coln><EOS>

See Also

[ICommenceAddRowSet GetRowValue](#)

ICommenceAddRowSet::SetShared

Boolean SetShared(Long *nRow*)

Mark a row to be shared.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

nRow

The (0-based) index of the row.

Comments

By default, all rows are marked local. To create a rowset with all rows marked as shared, call GetAddRowSet with the CMC_FLAG_SHARED flag.

See Also

[ICommenceAddRowSet](#) [ICommenceCursor::GetAddRowSet](#)

ICommenceAddRowSet::GetShared

Boolean GetShared(Long *nRow*)

Return the row's current shared vs. local status.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/ADD.D

Return Value

Returns TRUE if row is shared, FALSE otherwise.

Parameters

nRow

The (0-based) index of the row.

See Also

[ICommenceAddRowSet](#)

ICommenceDeleteRowSet Object

Represents the set of items to delete from the database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Properties

Long ColumnCount

(read-only) Number of columns in this rowset (-1 on error).

Long RowCount

(read-only) Number of rows in this rowset (-1 on error).

Methods

String GetRowValue

Returns the field value at the given (row,column) in text form.

String GetColumnLabel

Return the label associated with a particular column.

Long GetColumnIndex

Search the column set and return the index of the column with the given label.

Long DeleteRow

Mark a row for deletion.

Long Commit

Make row modifications permanent (commit to disk).

String GetRow

Returns an entire row's field values.

String GetRowID

Returns a unique identifier for a row.

Boolean GetShared

Return the row's current shared vs. local status.

ICommenceDeleteRowSet::ColumnCount

Data Type

Long

Description

(read-only) Number of columns in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

See Also

[ICommenceDeleteRowSet](#)

ICommenceDeleteRowSet::RowCount

Data Type

Long

Description

(read-only) Number of rows in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

See Also

[ICommenceDeleteRowSet](#)

ICommenceDeleteRowSet::GetRowValue

String GetRowValue(Long *nRow*, Long *nCol*, Long *nFlags*)

Returns the field value at the given (row,column) in text form.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns Field value in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

nFlags

option flags.

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in
canonical form

Comments

See the Developer Notes for more information about the canonical format.

See Also

[ICommenceDeleteRowSet RowCount](#)
[ColumnCount](#)
[GetRow](#)

ICommenceDeleteRowSet::GetColumnLabel

String GetColumnLabel(Long *nCol*, Long *nFlags*)

Return the label associated with a particular column.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns Column label in text form on success, NULL on error.

Parameters

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will return the labels used with the view. Specify the CMC_FLAG_FIELD_NAME to force the underlying Commence field name to be returned.

See Also

[ICommenceDeleteRowSet GetColumnIndex](#)

ICommenceDeleteRowSet::GetColumnIndex

Long GetColumnIndex(String *pLabel*, Long *nFlags*)

Search the column set and return the index of the column with the given label.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns 0-based column index on success, -1 on error.

Parameters

pLabel

The column label to map.

nFlags

option flags.

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will first search the view labels for a possible match. If not found, the field labels will then be searched. Specify the CMC_FLAG_FIELD_NAME to force only the underlying Commence field name to be searched.

See Also

[ICommenceDeleteRowSet GetColumnLabel](#)

ICommenceDeleteRowSet::DeleteRow

Long DeleteRow(Long *nRow*, Long *nFlags*)

Mark a row for deletion.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nRow

The (0-based) index of the row.

nFlags

Unused at present, must be 0.

Comments

Deletion is not permanent until Commit() is called.

See Also

[ICommenceDeleteRowSet Commit](#)

ICommenceDeleteRowSet::Commit

Long Commit(Long *nFlags*)

Make row modifications permanent (commit to disk).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nFlags

Unused at present, must be 0.

Comments

After Commit(), the ICommenceDeleteRowSet is no longer valid and should be discarded.

See Also

[ICommenceDeleteRowSet DeleteRow](#)

ICommenceDeleteRowSet::GetRow

String GetRow(Long *nRow*, String *pDelim*, Long *nFlags*)

Returns an entire row's field values.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns Row values in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

pDelim

Delimiter to use between field values.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

pDelim is used to separate field values. pDelim can be up to 20 chars.

Returned string is EOS terminated. Format is: <col1><delim><col2><delim>...<coln><EOS>

See Developer Notes for more information on canonical format.

See Also

[ICommenceDeleteRowSet GetRowValue](#)

ICommenceDeleteRowSet::GetRowID

String GetRowID(Long *nRow*, Long *nFlags*)

Returns a unique identifier for a row.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns a unique ID string (less than 100 chars) on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nFlags

Unused at present, must be 0.

Comments

Unlike the row number, this ID value is valid across cursor sessions.

The 'scope' of the ID value is the Commence database from which it was retrieved. The ID value is not valid in other Commence databases, even if they are in the same workgroup and sync.

Do not make any assumptions about the contents of the returned ID string. Format may change in the future.

See Also

[ICommenceDeleteRowSet](#)

[ICommenceCursor::GetEditRowSetByID](#)

[ICommenceCursor::GetDeleteRowSetByID](#)

ISCommenceDeleteRowSet::GetShared

Boolean GetShared(Long *nRow*)

Return the row's current shared vs. local status.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/DELETE.D

Return Value

Returns TRUE if row is shared, FALSE otherwise.

Parameters

nRow

The (0-based) index of the row.

See Also

[ISCommenceDeleteRowSet](#)

ICommenceEditRowSet Object

Represents the set of items to edit in the database.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Properties

Long ColumnCount

(read-only) Number of columns in this rowset (-1 on error).

Long RowCount

(read-only) Number of rows in this rowset (-1 on error).

Methods

String GetRowValue

Returns the field value at the given (row,column) in text form.

String GetColumnLabel

Return the label associated with a particular column.

Long GetColumnIndex

Search the column set and return the index of the column with the given label.

Long ModifyRow

Modify a field value in the rowset.

Long Commit

Make row modifications permanent (commit to disk).

[ICommenceCursor](#) **CommitGetCursor**

Make row modifications permanent (commit to disk) and return a cursor for the newly added data.

String GetRow

Returns an entire row's field values.

Boolean GetShared

Return the row's current shared vs. local status.

Boolean SetShared

Mark a row to be shared.

String GetRowID

Returns a unique identifier for a row.

ICommenceEditRowSet::ColumnCount

Data Type

Long

Description

(read-only) Number of columns in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

See Also

[ICommenceEditRowSet](#)

ICommenceEditRowSet::RowCount

Data Type

Long

Description

(read-only) Number of rows in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

See Also

[ICommenceEditRowSet](#)

ICommenceEditRowSet::GetRowValue

String GetRowValue(Long *nRow*, Long *nCol*, Long *nFlags*)

Returns the field value at the given (row,column) in text form.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns Field value in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

See the Developer Notes for more information about the canonical format.

See Also

[ICommenceEditRowSet RowCount](#)
[ColumnCount](#)
[GetRow](#)

ICommenceEditRowSet::GetColumnLabel

String GetColumnLabel(Long *nCol*, Long *nFlags*)

Return the label associated with a particular column.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns Column label in text form on success, NULL on error.

Parameters

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will return the labels used with the view. Specify the CMC_FLAG_FIELD_NAME to force the underlying Commence field name to be returned.

See Also

[ICommenceEditRowSet GetColumnIndex](#)

ICommenceEditRowSet::GetColumnIndex

Long GetColumnIndex(String *pLabel*, Long *nFlags*)

Search the column set and return the index of the column with the given label.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns 0-based column index on success, -1 on error.

Parameters

pLabel

The column label to map.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will first search the view labels for a possible match. If not found, the field labels will then be searched. Specify the CMC_FLAG_FIELD_NAME to force only the underlying Commence field name to be searched.

See Also

[ICommenceEditRowSet GetColumnLabel](#)

ICommenceEditRowSet::ModifyRow

Long ModifyRow(Long *nRow*, Long *nCol*, String *pBuf*, Long *nFlags*)

Modify a field value in the rowset.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

pBuf

New field value in text form.

nFlags

Unused at present, must be 0.

Comments

Modifications to the rowset will be reflected by GetRowValue() and GetRow() but changes are not permanent until Commit() is called.

See Also

[ICommenceEditRowSet Commit](#)
[CommitGetCursor](#)

ISCommenceEditRowSet::Commit

Long Commit(Long *nFlags*)

Make row modifications permanent (commit to disk).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns 0 on success, -1 on error.

Parameters

nFlags

Unused at present, must be 0.

Comments

After Commit(), the ISCommenceEditRowSet is no longer valid and should be discarded.

See Also

[ISCommenceEditRowSet ModifyRow](#)
[CommitGetCursor](#)

ISCommenceEditRowSet::CommitGetCursor

ISCommenceCursor CommitGetCursor(Long *nFlags*)

Make row modifications permanent (commit to disk) and return a cursor for the newly added data.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns ISCommenceCursor object on success, NULL on error.

Parameters

nFlags

Unused at present, must be 0.

Comments

After Commit(), the ISCommenceEditRowSet is no longer valid and should be discarded.

See Also

[ISCommenceEditRowSet ModifyRow](#)
[Commit](#)

ICommenceEditRowSet::GetRow

String GetRow(Long *nRow*, String *pDelim*, Long *nFlags*)

Returns an entire row's field values.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns Row values in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

pDelim

Delimiter to use between field values.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

pDelim is used to separate field values. pDelim can be up to 20 chars.

Returned string is EOS terminated. Format is: <col1><delim><col2><delim>...<coln><EOS>

See the Developer Notes for more information about the canonical format.

See Also

[ICommenceEditRowSet GetRowValue](#)

ICommenceEditRowSet::GetShared

Boolean GetShared(Long *nRow*)

Return the row's current shared vs. local status.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns TRUE if row is shared, FALSE otherwise.

Parameters

nRow

The (0-based) index of the row.

See Also

[ICommenceEditRowSet SetShared](#)

ICommenceEditRowSet::SetShared

Boolean SetShared(Long *nRow*)

Mark a row to be shared.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns TRUE on success, FALSE on error.

Parameters

nRow

The (0-based) index of the row.

See Also

[ICommenceEditRowSet GetShared](#)

ICommenceEditRowSet::GetRowID

String GetRowID(Long *nRow*, Long *nFlags*)

Returns a unique identifier for a row.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/EDIT.D

Return Value

Returns a unique ID string (less than 100 chars) on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nFlags

Unused at present, must be 0.

Comments

Unlike the row number, this ID value is valid across cursor sessions.

The 'scope' of the ID value is the Commence database from which it was retrieved. The ID value is not valid in other Commence databases, even if they are in the same workgroup and sync.

Do not make any assumptions about the contents of the returned ID string. Format may change in the future.

See Also

[ICommenceEditRowSet](#)

[ICommenceCursor::GetQueryRowSetByID](#)

[ICommenceCursor::GetEditRowSetByID](#)

[ICommenceCursor::GetDeleteRowSetByID](#)

ICommenceQueryRowSet Object

Represents a result set from a query

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Properties

Long ColumnCount

(read-only) Number of columns in this rowset (-1 on error).

Long RowCount

(read-only) Number of rows in this rowset (-1 on error).

Methods

String GetRowValue

Returns the field value at the given (row,column) in text form.

String GetColumnLabel

Return the label associated with a particular column.

Long GetColumnIndex

Search the column set and return the index of the column with the given label.

String GetRow

Returns an entire row's field values.

String GetRowID

Returns a unique identifier for a row.

Boolean GetShared

Return the row's current shared vs. local status.

Long GetFieldToFile

Save the field value at the given (row,column) to a file.

ICommenceQueryRowSet::ColumnCount

Data Type

Long

Description

(read-only) Number of columns in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

See Also

[ICommenceQueryRowSet](#)

ICommenceQueryRowSet::RowCount

Data Type

Long

Description

(read-only) Number of rows in this rowset (-1 on error).

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

See Also

[ICommenceQueryRowSet](#)

ICommenceQueryRowSet::GetRowValue

String GetRowValue(Long *nRow*, Long *nCol*, Long *nFlags*)

Returns the field value at the given (row,column) in text form.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns Field value in text form on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

See the Developer Notes about canonical format.

See Also

[ICommenceQueryRowSet RowCount](#)

[ColumnCount](#)

[GetRow](#)

[GetFieldToFile](#)

ICommenceQueryRowSet::GetColumnLabel

String GetColumnLabel(Long *nCol*, Long *nFlags*)

Return the label associated with a particular column.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns Column label in text form on success, NULL on error.

Parameters

nCol

The (0-based) index of the column.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will return the labels used with the view. Specify the CMC_FLAG_FIELD_NAME to force the underlying Commence field name to be returned.

See Also

[ICommenceQueryRowSet GetColumnIndex](#)

ICommenceQueryRowSet::GetColumnIndex

Long GetColumnIndex(String *pLabel*, Long *nFlags*)

Search the column set and return the index of the column with the given label.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns 0-based column index on success, -1 on error.

Parameters

pLabel

The column label to map.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_FIELD_NAME - return field label (ignore view labels)

Comments

If the cursor is created with CMC_CURSOR_VIEW, this will first search the view labels for a possible match. If not found, the field labels will then be searched. Specify the CMC_FLAG_FIELD_NAME to force only the underlying Commence field name to be searched.

See Also

[ICommenceQueryRowSet GetColumnLabel](#)

ICommenceQueryRowSet::GetRow

String GetRow(Long *nRow*, String *pDelim*, Long *nFlags*)

Returns an entire row's field values.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns Row values in text form on success, NULL on error.

(Long *nRow*, String *pDelim*, Long *nFlags*)

Parameters

nRow

The (0-based) index of the row.

pDelim

Delimiter to use between field values.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

pDelim is used to separate field values. *pDelim* can be up to 20 chars.

Returned string is EOS terminated. Format is: <col1><delim><col2><delim>...<coln><EOS>

See Developer Notes for more information about the canonical format.

See Also

[ICommenceQueryRowSet GetRowValue](#)
[GetFieldToFile](#)

ICommenceQueryRowSet::GetRowID

String GetRowID(Long *nRow*, Long *nFlags*)

Returns a unique identifier for a row.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns a unique ID string (less than 100 chars) on success, NULL on error.

Parameters

nRow

The (0-based) index of the row.

nFlags

Unused at present, must be 0.

Comments

Unlike the row number, this ID value is valid across cursor sessions.

The 'scope' of the ID value is the Commence database from which it was retrieved. The ID value is not valid in other Commence databases, even if they are in the same workgroup and sync.

Do not make any assumptions about the contents of the returned ID string. Format may change in the future.

Not yet supported but the unique ID will be useful in the future to edit/delete a particular item.

See Also

[ICommenceQueryRowSet](#)

ICommenceQueryRowSet::GetShared

Boolean GetShared(Long *nRow*)

Return the row's current shared vs. local status.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns TRUE if row is shared, FALSE otherwise.

Parameters

nRow

The (0-based) index of the row.

See Also

[ICommenceQueryRowSet](#)

ICommenceQueryRowSet::GetFieldToFile

Long GetFieldToFile(Long *nRow*, Long *nCol*, String *filename*, Long *nFlags*)

Save the field value at the given (row,column) to a file.

Defined in: E:/DEV/PIM80/DOCS/DBAPI/PIMOA/QUERY.D

Return Value

Returns the file size in bytes, or -1 on error.

Parameters

nRow

The (0-based) index of the row.

nCol

The (0-based) index of the column.

filename

Filename and path where the field value is written.

nFlags

option flags

Logical OR of following option flags:

CMC_FLAG_CANONICAL - return field value in canonical form

Comments

If there is no data in the indicated column, the return code is 0 and a file is not written. Otherwise, a file is created with the field's data and the size of the data is returned.

See the Developer Notes about canonical format.

See Also

[ICommenceQueryRowSet GetRowValue](#)
[GetRow](#)

Constants

Flags used with GetCursor

CMC_CURSOR_CATEGORY = 0

open based on a category

CMC_CURSOR_VIEW = 1

open based on a view

CMC_CURSOR_PILOTAB = 2

3Com Pilot Address Book

CMC_CURSOR_PILOTMEMO= 3

3Com Pilot Memo

CMC_CURSOR_PILOTTODO= 5

3Com Pilot to-do list

CMC_CURSOR_PILOTAPPT= 6

3Com Pilot appt calendar

CMC_CURSOR_OUTLOOKAB= 7

MS Outlook contacts preference

CMC_CURSOR_OUTLOOKAPPT=8

MS Outlook calendar preference

CMC_CURSOR_EMAILLOG=9

MS Outlook Email Log preference

CMC_CURSOR_OUTLOOKTASK=10

MS Outlook Task preference

CMC_CURSOR_MERGE=11

open based on the view data used with the Send Letter command

Flags used with SeekRow

BOOKMARK_BEGINNING = 0

Offset from beginning of the rowset.

BOOKMARK_CURRENT = 1

Offset from current position.

BOOKMARK_END = 2

Offset from end of the rowset.

Option Flags

CMC_FLAG_FIELD_NAME = &H0001

return actual field name

CMC_FLAG_ALL = &H0002

include all fields

CMC_FLAG_SHARED = &H0004

init as shared

CMC_FLAG_PILOT = &H0008

changes from 3Com Pilot

CMC_FLAG_CANONICAL = &H0010

data in canonical format

CMC_FLAG_INTERNET = &H0020

changes from Internet

Developer Notes

The following topics contain technical notes about the Database API.

[3Com Pilot support](#)

[Canonical Format](#)

[CMC_FLAG_PILOT](#)

[CMC_FLAG_INTERNET](#)

Palm Pilot support

For CMC_CURSOR_PILOTx cursor modes, Commence will use the 'Sync Condition' field (which must be a checkbox or a connection to the "(-me-)" item) to determine which items appear in the cursor. The column set only includes fields for which mappings exist.

For example, if the user did not select a Fax Number field, then it will not appear in the column set. This means GetColumnIndex("Fax Number", 0) can and will fail.

If 'Sync Condition' is not mapped to a Commence field, then all items in the category will appear in the cursor.

Canonical Format

By default, data values are returned formatted according to the local Control Panel settings. Where applicable, specifying CMC_FLAG_CANONICAL will return data in a consistent format.

Data	Type	Format	Notes
------	------	--------	-------

Date	yyyymmdd		
------	----------	--	--

Time	hh:mm	military time,	24 hour clock
------	-------	----------------	---------------

Number	123456.78	no separator,	period for decimal delimiter
--------	-----------	---------------	---------------------------------

Checkbox	TRUE or FALSE	English	
----------	---------------	---------	--

CMC_FLAG_PILOT

The Save Item trigger can be configured to fire only if an item is added or edited by specific subsystems. As part of Pilot support, the Save Item Options dialog box will include a Pilot Link check box (SS_PILOT).

By default, a cursor in CMC_CURSOR_PILOTx mode will assume SS_PILOT mode. When using other cursor modes, specifying CMC_FLAG_PILOT will force SS_PILOT mode.

CMC_FLAG_INTERNET

The Save Item trigger can be configured to fire only if an item is added or edited by specific subsystems. As part of Commence Web support, the Save Item Options dialog box will include a Internet/Intranet check box (SS_INTERNET).

Specifying CMC_FLAG_INTERNET will allow SS_INTERNET agents to fire.