



```
FROM continuumio/miniconda3:4.9.2
```

```
ARG port=8888
```

```
ENV NOTEBOOK_PORT $port
```

```
RUN conda config --set auto_update_conda false \  
&& conda config --set notify_outdated_conda false \  
&& conda config --prepend channels conda-forge \  
&& conda config --set channel_priority strict \  
&& conda install -Sy \  
    python==3.8.5 \  
    pip==20.2.4 \  
    notebook=6.1.4 \  
    ipywidgets=7.5.1 \  
    jupyter_contrib_nbextensions=0.5.1 \  
    tini=0.18.0 \  
    numpy=1.19.1 \  
    pandas=1.1.2 \  
    matplotlib=3.2.2 \  
    seaborn=0.11.0 \  
&& conda clean -afy
```

```
COPY jupyter_notebook_config.py /root/.jupyter/
```

```
WORKDIR "/mnt"
```

```
ENTRYPOINT ["tini", "-g", "--"]
```

```
CMD ["jupyter", "notebook"]
```


Data analysis in Docker

1. Write a *Dockerfile*

2. Build an *image*

3. Run a *container*

Donkerfileinstreiding

RUN



Configureconda

• Disabled auto-updates and notification

• `useconda-freg channel to install packages`

• **Installation requirements**

- Python(checkexpectedversion)

• pip package manager

- Jupyter notebooks, interactive widgets, some handy notebook extensions

• **tininitmanager**

• Packages for analyses

- Clear cache to reduce image size























2. Build an *image*

1. Write a Dockerfile

3. *Run a container*

• Why all the &&'s?

handy notebook extensions

• Jupyter notebooks, interactive widgets, some

