DISCORD BOT ENGINEER

Discord bots that get used.

Hello, I am Eren. I’m 16, and I write Discord bots.

Most of my bots use Node.js and discord.js. I also write Python bots with discord.py. Outside bots I write C, C++, Rust, Zig and Java. I maintain a private bot for a community I’m in, and I’m building Pinx, an x86-64 kernel.

AVAILABILITY	AGE
20+ hrs/week	**16**
CURRENT	SETUP
Pinx kernel	**VPS · Docker**

GITHUB

github.com/paxxydevv

TOOLBOX

LANGUAGES

JavaScript / TypeScript
Python
C · C++ · Rust
Zig · Java

DISCORD

discord.js · discord.py
Bot architecture
Command handling
Moderation tooling

INFRASTRUCTURE

Linux VPS
Docker
Deployment
Maintenance

01 / SELECTED WORK

Private Community Bot

PRIVATE BOT · DEVELOPER & MAINTAINER

A private Discord bot for a community I’m in. It covers moderation and utility commands.

I run it on a Linux VPS with Docker. There’s no public invite because the bot is private.

NODE.JS / DISCORD.JS / DOCKER / LINUX

02 / SYSTEMS WORK

Pinx: x86-64 Kernel

BARE-METAL OS · C · X86 ASSEMBLY · RUST

A from-scratch x86-64 kernel that boots on UEFI via Limine. The long-term goal is to run Linux ELF and Windows PE binaries.

GDT / IDT · PMM / VMM · KERNEL HEAP · FRAMEBUFFER
LAPIC / X2APIC · UEFI BOOT

IN PROGRESS: FILESYSTEM · DEBUG SHELL · RUST MIGRATION

github.com/paxxydevv/pinx_kernel ↗

SRC/MAIN.RS · BOOT SEQUENCE

```
gdt::init_cpu(0);
idt::init();

mm::pmm_init();
mm::vmm_init();
mm::kheap_init();
```

03 / NOTES

Pinx boots in order: GDT, IDT, physical memory, virtual memory, kernel heap, APIC, keyboard. Each stage logs before the next one starts. If the machine resets, the last line tells you which stage failed.

The PMM is a bitmap over Limine's memory map. The VMM walks four-level page tables through the HHDM. The heap is a first-fit free list carved out of a fixed virtual window.

Let's invent something that will be used, not something that will just gather dust in your folders.

GITHUB ↗