

## POC-2 : POC 2 — ConfigMap: Mounting a Single Key (subPath)

Steps:

1 . Reuse ConfigMap app-config from POC 1.

```
POC > POC-1-ConfigMap-1 > ! configmap.yaml > {} data > abc APP_NAME
1  apiVersion: v1
2  kind: ConfigMap
3  metadata:
4    name: app-config
5  data:
6    APP_ENV: production
7    APP_NAME: inventory-service
```

2 . Create pod config-subpath (toolbox image) that mounts **only** the APP\_NAME key from app-config to the path /etc/app/name.txt, using subPath.

```
POC-2-ConfigMap-2 > ! pod.yaml > {} spec > {} containers > {} 0 > abc image
1  apiVersion: v1
2  kind: Pod
3  metadata:
4    name: config-subpath
5  spec:
6    containers:
7      - name: toolbox
8        image: docker.io/payal_kharat/kubernetes-toolbox:latest
9        volumeMounts:
10         - name: app-config-volume
11           mountPath: /etc/app/name.txt
12           subPath: APP_NAME
13       volumes:
14         - name: app-config-volume
15           configMap:
16             name: app-config
```

3 . Verify: kubectl exec config-subpath -- cat /etc/app/name.txt and kubectl exec config-subpath -- ls /etc/app.

```
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ ls
configmap.yaml pod.yaml
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl apply -f configmap.yaml
configmap/app-config created
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl get configmap
NAME      DATA  AGE
app-config 2      5s
kube-root-ca.crt 1      31h
special-config 1      28h
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl apply -f pod.yaml
pod/config-subpath created
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl get pods
NAME      READY  STATUS   RESTARTS  AGE
config-subpath 1/1    Running  0          7s
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl exec config-subpath -- cat /etc/app/name.txt
inventory-service
payal_kharat@LAPTOP-V1NV0QFT: /mnt/d/CloudEthix_Internship/Kubernetes/POC/POC-2-ConfigMap-2$ kubectl exec config-subpath -- ls /etc/app
name.txt
```

