

Question-1:

Create 2 Public Docker Hub registries named
cloudethix_master_nginx_yourname & cloudethix_release_nginx_yourname.

- Clone below repository on your system.
<https://github.com/zembutsu/docker-sample-nginx.git>
- Initialize a local repository & copy the code from above repo to your local repository in master branch and then create below branches.
release
main
hotfix
- Once code is copied to local repository,from master branch update the index.html and add word "Cloudethix Master Branch Nginx" and build the docker image & add meaningful tags and push to Docker Hub registry cloudethix_master_nginx_yourname.
- Also from release branch update the index.html and add word "Cloudethix Release Branch Nginx" and build the docker image & add meaningful tags and push to Docker Hub registry cloudethix_release_nginx_yourname.
- Once Images are copied to Docker hub registries, switch to the main branch.
- In main branch create directory named kube/clusterIP & inside kube directory create file named master_pod.yaml with pod name master_nginx & with label master_nginx & add image that you have pushed in Docker Hub registry cloudethix_master_nginx_yourname.
- Also create a file release_pod.yaml with pod name release_nginx & with label release_nginx & add image that you have pushed in Docker Hub registry cloudethix_release_nginx_yourname.
- Create a file called cluster_ip-service.yaml with service name cloudethix_clusterip and with Type clusterIP.
- Then, select the pod with label release_nginx in service.
- Create all these three resources in your k8s cluster.
- Now, access master_nginx pod shell & curl the master_nginx pod & check the result.
- Also try to curl release_nginx pod with DNS name & check the result.
- Then curl the clusterip service with its name and check the result.
- Finally, create a GITHUB remote repository named cloudethix-k8s-yourname and push all the branches to the remote repository.

=====

System / Terminal Output

```
payal_kharat@LAPTOP-# git clone https://github.com/zembutsu/docker-sample-nginx.git
Cloning into 'docker-sample-nginx'...
remote: Enumerating objects: 22, done.
remote: Counting objects: 100% (12/12), done.
remote: Compressing objects: 100% (6/6), done.
remote: Total 22 (delta 7), reused 6 (delta 6), pack-reused 10 (from 1)
Receiving objects: 100% (22/22), done.
Resolving deltas: 100% (7/7), done.
```

```
-----
payal_kharat@LAPTOP-# ls
docker-sample-nginx
payal_kharat@LAPTOP-# git init
hint: Using 'master' as the name for the initial branch. This default branch
name
hint: will change to "main" in Git 3.0. To configure the initial branch name
hint: to use in all of your new repositories, which will suppress this
warning,
hint: call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
hint:
hint: Disable this message with "git config set advice.defaultBranchName
false"
Initialized empty Git repository in
/mnt/d/CloudEthix_Internship/Kubernetes/Assignment-2/.git/
payal_kharat@LAPTOP-# cp -rf docker-sample-nginx/* .
payal_kharat@LAPTOP-# ls
Dockerfile  LICENSE  README.md  default.conf  docker-sample-nginx  index.html
payal_kharat@LAPTOP-# git checkout -b master
Switched to a new branch 'master'
payal_kharat@LAPTOP-# git add .
payal_kharat@LAPTOP-# git commit -m "Initial commit"
[master (root-commit) 620585d] Initial commit
 5 files changed, 46 insertions(+)
 create mode 100644 Dockerfile
 create mode 100644 LICENSE
 create mode 100644 README.md
 create mode 100644 default.conf
 create mode 100644 index.html
-----

payal_kharat@LAPTOP-# git branch main
payal_kharat@LAPTOP-# git branch release
payal_kharat@LAPTOP-# git branch hotfix
payal_kharat@LAPTOP-# git branch
  hotfix
  main
* master
  release
-----

payal_kharat@LAPTOP-# podman build -t cloudethix-master-nginx .
STEP 1/3: FROM nginx:alpine
STEP 2/3: COPY default.conf /etc/nginx/conf.d/
--> Using cache
bfba633494f51cc913622ffd1987833f35e1c8cff0ccf02885633eeca04dc5a0
--> bfba633494f5
STEP 3/3: COPY index.html /usr/share/nginx/html/
COMMIT cloudethix-master-nginx
--> caf1290ae9d7
Successfully tagged localhost/cloudethix-master-nginx:latest
caf1290ae9d7044437a1f170ab6b175cd1651fd93567fa10f5ef3bc2250d0b48
-----

payal_kharat@LAPTOP-# podman login docker.io
Username: payalkharat
```

Password:
Login Succeeded!

```
payal_kharat@LAPTOP-# podman tag localhost/cloudethix-master-nginx
docker.io/payalkharat/cloudethix_master_nginx_payal:master-v1
payal_kharat@LAPTOP-# podman push
docker.io/payalkharat/cloudethix_master_nginx_payal:master-v1
Getting image source signatures
Copying blob 0d62d88506ba skipped: already exists
Copying blob 1ed8e39a7434 skipped: already exists
Copying blob d94291c26261 skipped: already exists
Copying blob 8cdfef4f23778 skipped: already exists
Copying blob 55afa1ecc21d skipped: already exists
Copying blob 0ea935727878 skipped: already exists
Copying blob da4dea1b00af skipped: already exists
Copying blob e011cd894381 done    |
Copying blob 31ecba1cce22 done    |
Copying blob fb597529c916 skipped: already exists
Copying config caf1290ae9 done    |
Writing manifest to image destination
```

```
payal_kharat@LAPTOP-# git checkout release
Switched to branch 'release'
payal_kharat@LAPTOP-# vim index.html
payal_kharat@LAPTOP-# git add index.html
payal_kharat@LAPTOP-# git commit -m "Update nginx for Cloudethix release
branch"
[release c1fd64f] Update nginx for Cloudethix release branch
1 file changed, 1 insertion(+)
```

```
payal_kharat@LAPTOP-# podman build -t cloudethix-release-nginx .
STEP 1/3: FROM nginx:alpine
STEP 2/3: COPY default.conf /etc/nginx/conf.d/
--> Using cache
bfba633494f51cc913622ffd1987833f35e1c8cff0ccf02885633eeca04dc5a0
--> bfba633494f5
STEP 3/3: COPY index.html /usr/share/nginx/html/
COMMIT cloudethix-release-nginx
--> 611d02a8945b
Successfully tagged localhost/cloudethix-release-nginx:latest
611d02a8945b16a022f539e7a62688a4c0336161788c352834df9a57ca413e4a
```

```
payal_kharat@LAPTOP-# podman tag localhost/cloudethix-release-nginx
docker.io/payalkharat/cloudethix_release_nginx_payal:release-v1
payal_kharat@LAPTOP-# podman push
docker.io/payalkharat/cloudethix_release_nginx_payal:release-v1
Getting image source signatures
Copying blob 1ed8e39a7434 skipped: already exists
Copying blob d94291c26261 skipped: already exists
Copying blob 0d62d88506ba skipped: already exists
Copying blob 8cdfef4f23778 skipped: already exists
Copying blob 55afa1ecc21d skipped: already exists
Copying blob 0ea935727878 skipped: already exists
Copying blob e198772e16f4 done    |
Copying blob da4dea1b00af skipped: already exists
Copying blob fb597529c916 skipped: already exists
Copying blob b83fc70afc5e skipped: already exists
Copying config 611d02a894 done    |
```

Writing manifest to image destination

```
payal_kharat@LAPTOP-# git branch
```

```
hotfix
```

```
main
```

```
master
```

```
* release
```

```
payal_kharat@LAPTOP-# git checkout main
```

```
Switched to branch 'main'
```

```
payal_kharat@LAPTOP-# git branch
```

```
hotfix
```

```
* main
```

```
master
```

```
release
```

```
payal_kharat@LAPTOP-# mkdir -p kube/clusterIP
```

```
payal_kharat@LAPTOP-# ls
```

```
Assignment-2.txt  Dockerfile  LICENSE  README.md  default.conf  index.html
```

```
kube
```

```
payal_kharat@LAPTOP-# cat master-pod.yaml
```

```
apiVersion: v1
```

```
kind: Pod
```

```
metadata:
```

```
  name: master-nginx
```

```
  labels:
```

```
    app: master-nginx
```

```
spec:
```

```
  containers:
```

```
    - name: master-nginx
```

```
      image: docker.io/payalkharat/cloudethix_master_nginx_payal:master-v1
```

```
      ports:
```

```
        - containerPort: 80
```

```
payal_kharat@LAPTOP-# cat release-pod.yaml
```

```
apiVersion: v1
```

```
kind: Pod
```

```
metadata:
```

```
  name: release-nginx
```

```
  labels:
```

```
    app: release-nginx
```

```
spec:
```

```
  containers:
```

```
    - name: release-nginx
```

```
      image: docker.io/payalkharat/cloudethix_release_nginx_payal:release-v1
```

```
      ports:
```

```
        - containerPort: 80
```

```
payal_kharat@LAPTOP-# cat cluster-ip-service.yaml
```

```
apiVersion: v1
```

```
kind: Service
```

```
metadata:
```

```
  name: cloudethix-clusterip
```

```
spec:
```

```
  type: ClusterIP
```

```
  selector:
```

```
    app: release-nginx
```

```
  ports:
```

```
    - protocol: TCP
```

```
      port: 80
```

```
targetPort: 80
-----
payal_kharat@LAPTOP-# kubectl apply -f cluster-ip-service.yaml
service/cloudethix-clusterip created
payal_kharat@LAPTOP-# kubectl get svc
NAME                                TYPE                CLUSTER-IP      EXTERNAL-IP      PORT(S)          AGE
cloudethix-clusterip              ClusterIP           10.96.172.109   <none>           80/TCP           7s
kubernetes                        ClusterIP           10.96.0.1       <none>           443/TCP          34m
-----

payal_kharat@LAPTOP-# kubectl apply -f master-pod.yaml
pod/master-nginx created
payal_kharat@LAPTOP-# kubectl apply -f release-pod.yaml
pod/release-nginx created
payal_kharat@LAPTOP-# kubectl get pods
NAME                READY   STATUS    RESTARTS   AGE
master-nginx        1/1     Running   0           17s
release-nginx       1/1     Running   0           8s
-----

-payal_kharat@LAPTOP-# kubectl exec -it master-nginx -- /bin/sh
/ # curl localhost
<html>
<body>
    <h1>Host: master-nginx</h1>
    Version: 1.1
    <h1> Cloudethix Master Branch Nginx </h1>
</body>
</html>
/ #

/ # curl http://cloudethix-clusterip
<html>
<body>
    <h1>Host: release-nginx</h1>
    Version: 1.1
    <h1>Cloudethix Release Branch Nginx</h1>
</body>
</html>
-----

payal_kharat@LAPTOP-# kubectl exec -it master-nginx -- /bin/sh
/ # curl http://cloudethix-clusterip
<html>
<body>
    <h1>Host: release-nginx</h1>
    Version: 1.1
    <h1>Cloudethix Release Branch Nginx</h1>
</body>
</html>
-----

/ # curl http://10.96.172.109
<html>
<body>
    <h1>Host: release-nginx</h1>
    Version: 1.1
    <h1>Cloudethix Release Branch Nginx</h1>
</body>
</html>
/ #
```

Question-2:

In the main branch of your local repository create a directory kube/NodePort.

- Create below files from below url. Please make sure you will create NodePort service with port 30008 instead of loadbalancer.
<https://kubernetes.io/docs/tasks/access-application-cluster/connecting-front-end-backend/>.
backend-deployment.yaml
backend-service.yaml
frontend-deployment.yaml
frontend-NodePort-service.yaml
- Once files are created , create all the resources in your k8s cluster.
- Access all public ips with port 30008 in the browser and then check the result.
- Finally, push all the latest code to the remote repository.

- **Take all screenshots and create a well formatted document.**

System / Terminal Output

```
payal_kharat@LAPTOP-# mkdir -p kube/NodePort
payal_kharat@LAPTOP-# cat backend-deployment.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: backend
spec:
  selector:
    matchLabels:
      app: hello
      tier: backend
      track: stable
  replicas: 3
  template:
    metadata:
      labels:
        app: hello
        tier: backend
        track: stable
    spec:
      containers:
        - name: hello
          image: "gcr.io/google-samples/hello-go-gke:1.0"
          ports:
            - name: http
              containerPort: 80
```

```
payal_kharat@LAPTOP-# cat backend-service.yaml
```

```
apiVersion: v1
kind: Service
metadata:
  name: hello
spec:
  selector:
    app: hello
```

```
    tier: backend
  ports:
  - protocol: TCP
    port: 80
    targetPort: http
-----

payal_kharat@LAPTOP-# cat frontend-deployment.yaml

apiVersion: apps/v1
kind: Deployment
metadata:
  name: frontend
spec:
  selector:
    matchLabels:
      app: hello
      tier: frontend
      track: stable
  replicas: 1
  template:
    metadata:
      labels:
        app: hello
        tier: frontend
        track: stable
    spec:
      containers:
      - name: nginx
        image: "gcr.io/google-samples/hello-frontend:1.0"
        lifecycle:
          preStop:
            exec:
              command: ["/usr/sbin/nginx", "-s", "quit"]
-----

payal_kharat@LAPTOP-# cat frontend-service.yaml

apiVersion: v1
kind: Service
metadata:
  name: frontend
spec:
  selector:
    app: hello
    tier: frontend
  type: NodePort
  ports:
  - protocol: "TCP"
    port: 80
    targetPort: 80
    nodePort: 30008
-----

payal_kharat@LAPTOP-# kubectl apply -f frontend-service.yaml
service/frontend created
payal_kharat@LAPTOP-# kubectl apply -f backend-service.yaml
service/hello created
payal_kharat@LAPTOP-# kubectl get svc
NAME                                TYPE                CLUSTER-IP          EXTERNAL-IP          PORT(S)
AGE
cloudethix-clusterip               ClusterIP            10.96.172.109       <none>                80/TCP
55m
```

```
frontend                                LoadBalancer    10.96.153.35    <pending>
30008:30894/TCP    64s
hello                                ClusterIP        10.96.97.226    <none>        80/TCP
18s
kubernetes                                ClusterIP        10.96.0.1        <none>        443/TCP
90m
-----

payal_kharat@LAPTOP-# kubectl apply -f backend-deployment.yaml
deployment.apps/backend created
payal_kharat@LAPTOP-# kubectl apply -f frontend-deployment.yaml
deployment.apps/frontend created
payal_kharat@LAPTOP-# kubectl get pods
NAME                                READY    STATUS    RESTARTS    AGE
backend-5fd7c8c4d6-c46zm            1/1      Running   0            84s
backend-5fd7c8c4d6-h9hzx            1/1      Running   0            84s
backend-5fd7c8c4d6-lr69g            1/1      Running   0            84s
frontend-78cf647c59-ct97b           1/1      Running   0            77s
```

Question-3:

Create any 2 pods and assign them to different worker nodes with nodeName property.

=====

System / Terminal Output

```
payal_kharat@LAPTOP-V# kubectl get nodes
NAME                                STATUS    ROLES    AGE    VERSION
mycluster-control-plane            Ready     control-plane  116m   v1.34.0
mycluster-worker                   Ready     <none>      115m   v1.34.0
mycluster-worker2                  Ready     <none>      115m   v1.34.0
-----

payal_kharat@LAPTOP-# cat pod1.yaml
apiVersion: v1
kind: Pod
metadata:
  name: pod1
spec:
  nodeName: mycluster-worker
  containers:
    - name: nginx
      image: nginx:alpine
      ports:
        - containerPort: 80
-----

payal_kharat@LAPTOP-# cat pod2.yaml
apiVersion: v1
kind: Pod
metadata:
  name: pod2
spec:
  nodeName: mycluster-worker2
  containers:
    - name: nginx
      image: nginx:alpine
      ports:
        - containerPort: 80
-----
```



```
payal_kharat@LAPTOP-# kubectl apply -f pod1.yaml
pod/pod1 created
payal_kharat@LAPTOP-# kubectl apply -f pod2.yaml
pod/pod2 created
payal_kharat@LAPTOP-# kubectl get pod -o wide
NAME      READY   STATUS    RESTARTS   AGE   IP            NODE
NOMINATED NODE   READINESS GATES
pod1      1/1     Running   0           12s   10.244.1.7    mycluster-worker
<none>    <none>
pod2      1/1     Running   0           7s    10.244.2.10   mycluster-worker2
<none>    <none>
```

Question-4:

Label both worker nodes such as worker-0 node as cloudehix-k8s-00 & worker-1 node as cloudehix-k8s-01.

- Once nodes are labeled, create pod00.yaml file and schedule the pod on worker-0 node with nodeSelector property. Also create one more file named pod01.yaml & schedule the pod on worker-1 node.

=====

System / Terminal Output

```
payal_kharat@LAPTOP-# kubectl get nodes
NAME                                STATUS    ROLES          AGE   VERSION
mycluster-control-plane             Ready    control-plane  128m   v1.34.0
mycluster-worker                    Ready    <none>         127m   v1.34.0
mycluster-worker2                   Ready    <none>         127m   v1.34.0
-----

payal_kharat@LAPTOP-# kubectl label nodes mycluster-worker cloudehix-k8s-00=worker-0
node/mycluster-worker labeled
payal_kharat@LAPTOP-# kubectl label nodes mycluster-worker2 cloudehix-k8s-01=worker-1
node/mycluster-worker2 labeled
-----

payal_kharat@LAPTOP-# kubectl get nodes --show-labels
NAME                                STATUS    ROLES          AGE   VERSION   LABELS
mycluster-control-plane             Ready    control-plane  134m   v1.34.0   beta.kubernetes.io/arch=amd64,beta.kubernetes.io/os=linux,kubernetes.io/arch=amd64,kubernetes.io/hostname=mycluster-control-plane,kubernetes.io/os=linux,node-role.kubernetes.io/control-plane=,node.kubernetes.io/exclude-from-external-load-balancers=
mycluster-worker                    Ready    <none>         134m   v1.34.0   beta.kubernetes.io/arch=amd64,beta.kubernetes.io/os=linux,cloudehix-k8s-00=worker-0,kubernetes.io/arch=amd64,kubernetes.io/hostname=mycluster-worker,kubernetes.io/os=linux
mycluster-worker2                   Ready    <none>         134m   v1.34.0   beta.kubernetes.io/arch=amd64,beta.kubernetes.io/os=linux,cloudehix-k8s-01=worker-1,kubernetes.io/arch=amd64,kubernetes.io/hostname=mycluster-worker2,kubernetes.io/os=linux
-----

payal_kharat@LAPTOP-# cat pod00.yaml
apiVersion: v1
kind: Pod
metadata:
```

```
name: pod00
spec:
  nodeSelector:
    cloudethix-k8s-00: worker-0
  containers:
    - name: nginx
      image: nginx:alpine
      ports:
        - containerPort: 80
```

```
payal_kharat@LAPTOP-# cat pod01.yaml
apiVersion: v1
kind: Pod
metadata:
  name: pod01
spec:
  nodeSelector:
    cloudethix-k8s-01: worker-1
  containers:
    - name: nginx
      image: nginx:alpine
      ports:
        - containerPort: 80
```

```
payal_kharat@LAPTOP-# kubectl apply -f pod00.yaml
pod/pod00 created
payal_kharat@LAPTOP-# kubectl apply -f pod01.yaml
pod/pod01 created
payal_kharat@LAPTOP-# kubectl get pods -o wide
NAME      READY   STATUS    RESTARTS   AGE   IP            NODE
NOMINATED NODE   READINESS GATES
pod00     1/1     Running   0           13s   10.244.1.8    mycluster-worker
<none>    <none>
pod01     1/1     Running   0           9s    10.244.2.11   mycluster-worker2
<none>    <none>
```

Question-5:

Clone the below repo locally & create DaemonSet from directory DaemonSet101.

<https://github.com/collabnix/kubelabs>

System / Terminal Output

```
payal_kharat@LAPTOP-# git clone https://github.com/collabnix/kubelabs.git
Cloning into 'kubelabs'...
remote: Enumerating objects: 14031, done.
remote: Counting objects: 100% (707/707), done.
remote: Compressing objects: 100% (147/147), done.
remote: Total 14031 (delta 637), reused 560 (delta 560), pack-reused 13324 (from 5)
Receiving objects: 100% (14031/14031), 61.81 MiB | 4.37 MiB/s, done.
Resolving deltas: 100% (4181/4181), done.
Updating files: 100% (7374/7374), done

payal_kharat@LAPTOP-# ls
201                               Gemfile                          LICENSE
```

Secrets101	assets	kube101.md
AKS101	Gemfile.lock	LKE101
Security101	bluegreen	kubectl-for-docker.md
Autoscaler101	GitLab101	'Labels&Selectors'
ServiceCatalog101	bootstrap.sh	namespace.yaml
CONTRIBUTING.md	GitOps101	Labels-and-Selectors
ServiceMesh101	cka	nodejs.md
Chaos101	Helm101	Loft101
Services101	context	Pods101
'Cheat Sheets'	IOT	Logging101
Shipa101	detect.md	Pods101.png
ClusterNetworking101	Ingress101	ManagedKubernetes
SlidesReplicaSet101	dockertutorialformac	portainer
ConfigMaps101	InitContainers101	Monitoring101
Slides_Services101	dockervsk8s	portainer.yaml
Cronjobs101	JavaClient101	MultiTenant101
StatefulSets101	gke-setup.md	python
Cronjobs101.md	Jenkins101	Network_Policies101
Strimzi101	golang	replicaset101
DaemonSet101	Jobs101	Observability101
Terraform101	helm	scripts
Deployment101	Karpenter101	Pods101_slides
Weave-UI.png	images	secrets_configmaps101
Deployment101_slides	Keda101	RBAC101
_config.yml	img	weave-pwk.md
DevSpace101	KubeSphere	README.md
_config_dev.yml	install	weave-service.png
DisasterRecovery101	Kubernetes_Architecture.md	ReplicationController101
_layouts	intermediate	weave.jpg
EKS101	Kubernetes_Intro_slides-1	ResourceQuota101
_site	jekyll-theme-hacker.gemspec	weave.md
GKE101	Kubezoo	Rollouts101
ai	k3s	
Gateway101	Kyverno101	Scheduler101
api.md	k8sworkshop.png	

```
-----  
-  
payal_kharat@LAPTOP-# cd DaemonSet101/  
payal_kharat@LAPTOP-# ls  
README.md daemonset.yaml
```

```
-----  
payal_kharat@LAPTOP-# cat daemonset.yaml  
apiVersion: apps/v1  
kind: DaemonSet  
metadata:  
  name: prometheus-daemonset  
spec:  
  selector:  
    matchLabels:  
      tier: monitoring  
      name: prometheus-exporter  
  template:  
    metadata:  
      labels:  
        tier: monitoring  
        name: prometheus-exporter  
    spec:  
      containers:  
        - name: prometheus  
          image: prom/node-exporter
```

```
ports:
  - containerPort: 80

-----

payal_kharat@LAPTOP-# kubectl apply -f daemonset.yml
daemonset.apps/prometheus-daemonset created
payal_kharat@LAPTOP-# kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
prometheus-daemonset-ks8sc          1/1     Running   0           9s
prometheus-daemonset-r7ss8          1/1     Running   0           9s

-----

payal_kharat@LAPTOP-# kubectl get DaemonSet
NAME                                DESIRED   CURRENT   READY   UP-TO-DATE   AVAILABLE
NODE SELECTOR  AGE
prometheus-daemonset  2           2         2         2           2
<none>           3m7s
```

Question-6:

Create a static pod with name cloudethix-static in your k8s cluster. Refer below link.

<https://kubernetes.io/docs/tasks/configure-pod-container/static-pod/>

=====

System / Terminal Output

```
payal_kharat@LAPTOP-# cat static-pod.yaml
apiVersion: v1
kind: Pod
metadata:
  name: cloudethix-static
  labels:
    role: myrole
spec:
  containers:
    - name: web
      image: nginx
      ports:
        - name: web
          containerPort: 80
          protocol: TCP

-----

payal_kharat@LAPTOP-# kubectl get pod
NAME            READY   STATUS    RESTARTS   AGE
cloudethix-static  1/1     Running   0           15s

-----

payal_kharat@LAPTOP-# podman exec mycluster-control-plane ls -la
/etc/kubernetes/manifests/
total 28
drwxr-xr-x 1 root root 4096 Sep  2 07:54 .
drwxr-xr-x 1 root root 4096 Sep  2 07:39 ..
-rw----- 1 root root 2608 Sep  2 07:39 etcd.yaml
-rw----- 1 root root 4013 Sep  2 07:39 kube-apiserver.yaml
-rw----- 1 root root 3548 Sep  2 07:39 kube-controller-manager.yaml
-rw----- 1 root root 1776 Sep  2 07:39 kube-scheduler.yaml
-rwxrwxrwx 1 root root  228 Sep  2 07:33 static-pod.yaml
```

Question-7:

Install Kubectl & kubens in your k8s cluster

=====

System / Terminal Output

```
payal_kharat@LAPTOP-# kubectl
kind-mycluster
payal_kharat@LAPTOP-V# kubectl config current-context
kind-mycluster
-----

payal_kharat@LAPTOP-# kubens
cloudethix-payal
default
kube-node-lease
kube-public
kube-system
local-path-storage
-----

payal_kharat@LAPTOP-# kubens kube-system
✓ Active namespace is "kube-system"
-----

payal_kharat@LAPTOP-# kubens
cloudethix-payal
default
kube-node-lease
kube-public
kube-system
local-path-storage
-----

payal_kharat@LAPTOP-# kubens default
✓ Active namespace is "default"
```