2CEIT5PE5: MOBILE APPLICATION DEVELOPMENT

Practical: 9

AIM: What is Difference between ListView and RecyclerView? Create SMS Android Application that can receive SMS by BroadcastReceiver and Interface, Send SMS and read & display all SMS of Inbox by using RecyclerView.

Submitted By: Gondaliya Payal Enrollment number: 21012022013



Department of Computer Engineering/Information Technolog

Practical: 9

RecyclerView	ListView
The RecyclerView's adaptor forces us to use the ViewHolder pattern.	The ListView doesn't give that kind of protection by default.
 Supported Vertical Scrolling and Horizontal Scrolling 	Supported Only Vertical Scrolling
Use of less memory.	 More memory is used for a long list. Sometimes devices get hanged.
 Animations using ItemAnimator are easy and smooth. Animations like list appearance and disappearance, adding or removing particular views, and so on. 	It's complex to use Animation and hard to handle it.
Dividers between items are not shown by default.	 Dividers between items are shown by default.
Use ItemDecorations to add margins and draw on or under an item View.	ItemDecorations require customization
RecyclerView is a more flexible control for handling a "list of data"	 ListView is a less flexible control for handling a "list of data"

sms_item_view.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"</pre>
    android:layout width="match parent"
    android:layout_height="match_parent"
    android:orientation="horizontal"
    android:layout_marginHorizontal="10dp"
    android:padding="20dp">
    <ImageView</pre>
        android:id="@+id/icon"
        android:layout_width="40dp"
        android:layout_height="40dp"
        android:padding="5dp"
        android:background="@drawable/shape"
        android:src="@drawable/ic_baseline_person_24"
        />
    <LinearLayout</pre>
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:orientation="vertical">
        <TextView
            android:id="@+id/textViewPhoneNo"
            android:layout width="wrap content"
            android:layout_height="wrap_content"
            android:text="Medium Text"
            android:textSize="14dp"
            android:textStyle="bold"
            android:textAppearance="?android:attr/textAppearanceMedium"
            android:layout marginLeft="10dp"
            android:layout_marginTop="5dp"
            android:padding="2dp"
            android:textColor="#4d4d4d" />
        <TextView
            android:id="@+id/textViewMessage"
            android:layout width="wrap_content"
            android:layout_height="wrap_content"
            android:text="TextView"
            android:layout marginLeft="10dp"
            android:textSize="12dp"/>
    </LinearLayout>
</LinearLayout>
```

activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout</pre>
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".MainActivity">
    <com.google.android.material.appbar.AppBarLayout</pre>
        android:id="@+id/app bar"
        android:layout width="match parent"
        android:layout height="wrap content"
        app:layout_constraintTop_toTopOf="parent">
        <androidx.appcompat.widget.Toolbar</pre>
            android:layout_width="match_parent"
            android:layout_height="match_parent"
            app:title="Message Application"
            app:titleTextColor="@color/white"/>
    </com.google.android.material.appbar.AppBarLayout>
    <com.google.android.material.card.MaterialCardView</pre>
        android:id="@+id/card"
        android:layout_width="0dp"
        android:layout_height="0dp"
        app:layout_constraintEnd_toEndOf="parent"
        app:layout_constraintStart_toStartOf="parent"
        app:layout constraintBottom toTopOf="@id/l1"
        app:layout constraintTop toBottomOf="@id/app bar"
        android:layout margin="10dp"
        <ListView
            android:id="@+id/listView"
            android:layout width="match parent"
            android:layout height="wrap content"
            android:backgroundTint="@color/cardview shadow end color"
            android:layout margin="10dp"
            />
    </com.google.android.material.card.MaterialCardView>
    <LinearLayout</pre>
        android:id="@+id/l1"
        android:layout width="match parent"
        android:layout height="wrap content"
        android:weightSum="100"
        app:layout_constraintStart_toStartOf="parent"
        app:layout constraintEnd toEndOf="parent"
        app:layout_constraintBottom toBottomOf="parent"
        android:orientation="horizontal"
        android:layout margin="20dp">
        <LinearLayout
            android:layout_weight="90"
            android:layout width="match parent"
            android:layout_height="wrap_content"
            android:orientation="vertical">
            <com.google.android.material.textfield.TextInputLayout</pre>
```

```
android:id="@+id/phoneNoInput"
                android:layout_width="match_parent"
                android:layout_height="wrap_content"
                android:hint="Mobile No"
                app:endIconMode="custom"
                app:endIconDrawable="@drawable/ic baseline phone android 24"
                style="@style/Widget.MaterialComponents.TextInputLayout.OutlinedBox">
                <com.google.android.material.textfield.TextInputEditText</pre>
                    android:id="@+id/phoneNo"
                    android:layout width="match parent"
                    android:layout_height="match_parent"
                    android:inputType="phone"
                    />
            </com.google.android.material.textfield.TextInputLayout>
            <com.google.android.material.textfield.TextInputLayout</pre>
                android:id="@+id/msgInput"
                android:layout width="match parent"
                android:layout_height="wrap_content"
                android:hint="Message"
                app:endIconMode="custom"
                app:endIconDrawable="@drawable/ic baseline message 24"
                style="@style/Widget.MaterialComponents.TextInputLayout.OutlinedBox">
                <com.google.android.material.textfield.TextInputEditText</pre>
                    android:id="@+id/msg"
                    android:layout width="match parent"
                    android:layout height="match parent"
                    android:inputType="textLongMessage"
                    />
            </com.google.android.material.textfield.TextInputLayout>
        </LinearLayout>
        <com.google.android.material.button.MaterialButton</pre>
            android:id="@+id/sendButton"
            app:fabSize="normal"
            android:layout_width="50dp"
            android:layout height="50dp"
            android:layout_marginHorizontal="10dp"
            android:layout_marginTop="5dp"
            app:icon="@drawable/ic baseline send 24"
            app:iconSize="20dp"
            android:elevation="5dp"
            app:cornerRadius="15dp"
            />
    </LinearLayout>
</androidx.constraintlayout.widget.ConstraintLayout>
```

MainActivity.kt

```
package com.example.madpractical9 21012022013
import android.Manifest
import android.content.IntentFilter
import android.content.pm.PackageManager
import android.net.Uri
import androidx.appcompat.app.AppCompatActivity
import android.os.Bundle
import android.provider.Telephony
import android.telephonv.SmsManager
import android.widget.ListView
import androidx.appcompat.app.AlertDialog
import androidx.core.app.ActivityCompat
import androidx.core.content.ContextCompat
import com.example.madpractical9_21012022013.databinding.ActivityMainBinding
class MainActivity : AppCompatActivity() {
    private lateinit var binding : ActivityMainBinding
    private val SMS PERMISSION CODE = 100
    private lateinit var lv: ListView
    private lateinit var al: ArrayList<SMSView>
   private lateinit var smsReceiver:SMSBroadcastReceiver
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
       binding = ActivityMainBinding.inflate(layoutInflater)
       setContentView(binding.root)
       lv = binding.listView
       al = ArrayList()
       if(checkRequestPermission()){
            loadSMSInbox()
       smsReceiver = SMSBroadcastReceiver()
       registerReceiver(smsReceiver, IntentFilter(
       Telephony.Sms.Intents.SMS RECEIVED ACTION))
        smsReceiver.setListner(ListenerImplement())
       binding.sendButton.setOnClickListener{
            val phone = binding.phoneNo.text.toString()
            val msg = binding.msg.text.toString()
            sendSms(phone,msg)
            val builder : AlertDialog.Builder = AlertDialog.Builder(this@MainActivity)
            builder.setTitle("Sent SMS")
            builder.setMessage("SMS is sent.\nPhone No : $phone \n\n Message : $msg")
            builder.setCancelable(true)
            builder.setPositiveButton("OK", null);
            builder.show()
        }
    }
```

```
private fun sendSms(sPhoneNo: String?,sMsg: String?){
    if(!checkRequestPermission()){
        return
   val smsmanager = SmsManager.getDefault()
    if(smsmanager != null){
        smsmanager.sendTextMessage(sPhoneNo,null,sMsg,null,null)
   }
}
inner class ListenerImplement:SMSBroadcastReceiver.Listner{
   override fun onTextReceived(sPhoneNo: String?, sMsg: String?) {
        val builder : AlertDialog.Builder = AlertDialog.Builder(this@MainActivity)
        builder.setTitle("New SMS Received")
        builder.setMessage("From : $sPhoneNo\n\n Message : $sMsg")
        builder.setCancelable(true)
        builder.setPositiveButton("OK",null);
        builder.show()
        loadSMSInbox()
   }
}
private val isSMSReadPermission: Boolean
   get() = ContextCompat.checkSelfPermission(this, Manifest.permission.READ SMS) ==
    PackageManager.PERMISSION GRANTED
private val isSMSWritePermission: Boolean
   get() = ContextCompat.checkSelfPermission(this, Manifest.permission.SEND SMS) ==
    PackageManager.PERMISSION GRANTED
private fun requestSMSPermission() {
    if (ActivityCompat.shouldShowRequestPermissionRationale
       (this, Manifest.permission.READ SMS)) {
       // You may display a non-blocking explanation here,
        read more in the documentation:
        // https://developer.android.com/training/permissions/requesting.html
   }
   ActivityCompat.requestPermissions(this, arrayOf(Manifest.permission.READ SMS,
        Manifest.permission.SEND SMS,
        Manifest.permission.RECEIVE_SMS),
        SMS PERMISSION CODE)
}
private fun checkRequestPermission(): Boolean {
   return if (!isSMSReadPermission || !isSMSWritePermission) {
        requestSMSPermission()
        false
   } else true
private fun loadSMSInbox() {
    if (!checkRequestPermission()) return
   val uriSMS = Uri.parse("content://sms/inbox")
   val c = contentResolver.query(uriSMS, null, null, null, null)
   al.clear()
   while (c!!.moveToNext()) {
        al.add(SMSView(c.getString(2),c.getString(12)))
```

```
}
lv.adapter = SMSViewAdapter(this,al)

}

override fun onDestroy() {
    unregisterReceiver(smsReceiver)
    super.onDestroy()
}
```

SMSBroadcastReceiver.kt

```
package com.example.madpractical9_21012022013
import android.content.BroadcastReceiver
import android.content.Context
import android.content.Intent
import android.os.Build
import android.provider.Telephony
class SMSBroadcastReceiver : BroadcastReceiver() {
    interface Listner {
        fun onTextReceived(sPhoneNo: String?, sMsg: String?)
    private var listner: Listner? = null
    fun setListner(lis: Listner) {
        listner = lis
    override fun onReceive(context: Context, intent: Intent) {
        if (intent.action == Telephony.Sms.Intents.SMS_RECEIVED_ACTION) {
            var sPhoneNo = ""
            var sSMSBody = ""
            if (Build.VERSION.SDK_INT >= Build.VERSION_CODES.M) {
                for (smsMessage in Telephony.Sms.Intents.getMessagesFromIntent(intent)) {
                    sPhoneNo = smsMessage.displayOriginatingAddress
                    sSMSBody += smsMessage.messageBody
                if (listner != null) {
                    listner?.onTextReceived(sPhoneNo, sSMSBody)
            }
        }
    }
```

SMSView.kt

```
package com.example.madpractical9_21012022013

class SMSView(val phoneNo:String,val msg:String) {
}
```

Practical: 9

SMSViewAdapter.kt

```
package com.example.madpractical9_21012022013
import android.content.Context
import android.view.LayoutInflater
import android.view.View
import android.view.ViewGroup
import android.widget.ArrayAdapter
import com.example.madpractical9 21012022022.databinding.SmsItemViewBinding
class SMSViewAdapter(context: Context, private val array:ArrayList<SMSView>):
    ArrayAdapter<SMSView>(context,array.size,array) {
    override fun getView(position: Int, convertView: View?, parent: ViewGroup): View {
        //val currentItemView:View = LayoutInflater.from(context)
        .inflate(R.layout.sms_item_view, parent, false)
        // get the position of the view from the ArrayAdapter
        val currentSms: SMSView? = getItem(position)
        val binding = SmsItemViewBinding.inflate(LayoutInflater.from(context))
        binding.textViewPhoneNo.text = currentSms!!.phoneNo
        binding.textViewMessage.text = currentSms.msg
        return binding.root
        //return super.getView(position, convertView, parent)
    }
```

AndroidManifest.xml

```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"</pre>
   xmlns:tools="http://schemas.android.com/tools"
   package="com.example.madpractical9_21012022013" >
    <uses-permission android:name="android.permission.RECEIVE_SMS" />
    <uses-permission android:name="android.permission.READ_SMS" />
    <uses-permission android:name="android.permission.SEND_SMS" />
    <application
       android:allowBackup="true"
       android:dataExtractionRules="@xml/data_extraction_rules"
       android:fullBackupContent="@xml/backup_rules"
       android:icon="@mipmap/ic_launcher"
       android:label="Practical 9"
       android:roundIcon="@mipmap/ic_launcher_round"
       android:supportsRtl="true"
       android:theme="@style/Theme.MADPractical9_21012022013"
       tools:targetApi="31" >
       <receiver
            android:name=".SMSBroadcastReceiver"
            android:enabled="true"
            android:exported="true" >
       </receiver>
       <activity
            android:name=".MainActivity"
            android:exported="true" >
            <intent-filter>
                <action android:name="android.intent.action.MAIN" />
                <category android:name="android.intent.category.LAUNCHER" />
            </intent-filter>
        </activity>
    </application>
</manifest>
```

Resources:

```
drawable

c_baseline_message_24.xml

c_baseline_person_24.xml

c_baseline_phone_android_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml

c_baseline_send_24.xml
```

Output:







