

Problem_1

April 15, 2024

```
[ ]: '''  
Patrick Ballou  
ID: 801130521  
ECGR 4106  
Homework 4  
Problem 1  
'''
```

```
[ ]: '\nPatrick Ballou\nID: 801130521\nECGR 4106\nHomework 4\nProblem 1\n'
```

```
[ ]: import torch  
import torch.nn as nn  
import torch.optim as optim  
from torch import cuda  
from torch.utils.data import DataLoader, Dataset
```

```
[ ]: #check if GPU is available and set the device accordingly  
#device = 'torch.device("cuda:0" if torch.cuda.is_available() else "cpu")'  
device = 'cuda'  
print("Using GPU: ", cuda.get_device_name())  
  
gpu_info = !nvidia-smi  
gpu_info = '\n'.join(gpu_info)  
if gpu_info.find('failed') >= 0:  
    print('Not connected to a GPU')  
else:  
    print(gpu_info)
```

Using GPU: Quadro T2000

Mon Apr 15 11:57:51 2024

```
+-----+  
-----+  
| NVIDIA-SMI 551.86                Driver Version: 551.86          CUDA Version:  
12.4          |  
|-----+-----+-----+  
-----+  
| GPU   Name                               TCC/WDDM  | Bus-Id          Disp.A | Volatile  
Uncorr. ECC |
```

Fan	Temp	Perf	Pwr:Usage/Cap		Memory-Usage	GPU-Util
Compute M.						
MIG M.						
=====						
=====						
0	Quadro T2000		WDDM	00000000:01:00.0	On	
N/A						
N/A	46C	P5	8W / 30W	1561MiB / 4096MiB		14%
Default						
N/A						
+-----+-----+-----						
-----+						
+-----+-----+-----						
-----+						
Processes:						
GPU	GI	CI	PID	Type	Process name	
GPU Memory						
	ID	ID				
Usage						
=====						
=====						
0	N/A	N/A	1176	C	...ri\anaconda3\envs\dl_env\python.exe	
N/A						
0	N/A	N/A	2084	C+G	...t.LockApp_cw5n1h2txyewy\LockApp.exe	
N/A						
0	N/A	N/A	3148	C+G	...e Stream\89.0.2.0\GoogleDriveFS.exe	
N/A						
0	N/A	N/A	6212	C+G	...Programs\Microsoft VS Code\Code.exe	
N/A						
0	N/A	N/A	10052	C+G	...b3d8bbwe\Microsoft.Media.Player.exe	
N/A						
0	N/A	N/A	10604	C+G	...1300.0_x64__8j3eq9eme6ctt\IGCC.exe	
N/A						
0	N/A	N/A	12068	C+G	C:\Windows\explorer.exe	
N/A						
0	N/A	N/A	14436	C+G	...CBS_cw5n1h2txyewy\TextInputHost.exe	
N/A						
0	N/A	N/A	15644	C+G	...Search_cw5n1h2txyewy\SearchApp.exe	
N/A						
0	N/A	N/A	16524	C+G	...Brave-Browser\Application\brave.exe	
N/A						
0	N/A	N/A	17168	C+G	...aam7r\AcrobatNotificationClient.exe	
N/A						
0	N/A	N/A	18440	C+G	...ekyb3d8bbwe\PhoneExperienceHost.exe	

N/A						
	0	N/A	N/A	19164	C+G	...5n1h2txyewy\ShellExperienceHost.exe
N/A						
	0	N/A	N/A	19280	C+G	...ta\Local\Programs\Notion\Notion.exe
N/A						
	0	N/A	N/A	19304	C+G	...siveControlPanel\SystemSettings.exe
N/A						
	0	N/A	N/A	20356	C+G	...91.0_x64__8wekyb3d8bbwe\GameBar.exe
N/A						
	0	N/A	N/A	21180	C+G	...AppData\Roaming\Spotify\Spotify.exe
N/A						
	0	N/A	N/A	21636	C+G	...les\Microsoft OneDrive\OneDrive.exe
N/A						

+-----+
-----+

```
[ ]: text = [
    ("I am cold", "J'ai froid"),
    ("You are tired", "Tu es fatigué"),
    ("He is hungry", "Il a faim"),
    ("She is happy", "Elle est heureuse"),
    ("We are friends", "Nous sommes amis"),
    ("They are students", "Ils sont étudiants"),
    ("The cat is sleeping", "Le chat dort"),
    ("The sun is shining", "Le soleil brille"),
    ("We love music", "Nous aimons la musique"),
    ("She speaks French fluently", "Elle parle français couramment"),
    ("He enjoys reading books", "Il aime lire des livres"),
    ("They play soccer every weekend", "Ils jouent au football chaque
↪ week-end"),
    ("The movie starts at 7 PM", "Le film commence à 19 heures"),
    ("She wears a red dress", "Elle porte une robe rouge"),
    ("We cook dinner together", "Nous cuisinons le dîner ensemble"),
    ("He drives a blue car", "Il conduit une voiture bleue"),
    ("They visit museums often", "Ils visitent souvent des musées"),
    ("The restaurant serves delicious food", "Le restaurant sert une délicieuse
↪ cuisine"),
    ("She studies mathematics at university", "Elle étudie les mathématiques à
↪ l'université"),
    ("We watch movies on Fridays", "Nous regardons des films le vendredi"),
    ("He listens to music while jogging", "Il écoute de la musique en faisant
↪ du jogging"),
    ("They travel around the world", "Ils voyagent autour du monde"),
    ("The book is on the table", "Le livre est sur la table"),
    ("She dances gracefully", "Elle danse avec grâce"),
    ("We celebrate birthdays with cake", "Nous célébrons les anniversaires avec
↪ un gâteau"),
```

("He works hard every day", "Il travaille dur tous les jours"),
 ("They speak different languages", "Ils parlent différentes langues"),
 ("The flowers bloom in spring", "Les fleurs fleurissent au printemps"),
 ("She writes poetry in her free time", "Elle écrit de la poésie pendant son ↵
 ↵temps libre"),
 ("We learn something new every day", "Nous apprenons quelque chose de ↵
 ↵nouveau chaque jour"),
 ("The dog barks loudly", "Le chien aboie bruyamment"),
 ("He sings beautifully", "Il chante magnifiquement"),
 ("They swim in the pool", "Ils nagent dans la piscine"),
 ("The birds chirp in the morning", "Les oiseaux gazouillent le matin"),
 ("She teaches English at school", "Elle enseigne l'anglais à l'école"),
 ("We eat breakfast together", "Nous prenons le petit déjeuner ensemble"),
 ("He paints landscapes", "Il peint des paysages"),
 ("They laugh at the joke", "Ils rient de la blague"),
 ("The clock ticks loudly", "L'horloge tic-tac bruyamment"),
 ("She runs in the park", "Elle court dans le parc"),
 ("We travel by train", "Nous voyageons en train"),
 ("He writes a letter", "Il écrit une lettre"),
 ("They read books at the library", "Ils lisent des livres à la ↵
 ↵bibliothèque"),
 ("The baby cries", "Le bébé pleure"),
 ("She studies hard for exams", "Elle étudie dur pour les examens"),
 ("We plant flowers in the garden", "Nous plantons des fleurs dans le ↵
 ↵jardin"),
 ("He fixes the car", "Il répare la voiture"),
 ("They drink coffee in the morning", "Ils boivent du café le matin"),
 ("The sun sets in the evening", "Le soleil se couche le soir"),
 ("She dances at the party", "Elle danse à la fête"),
 ("We play music at the concert", "Nous jouons de la musique au concert"),
 ("He cooks dinner for his family", "Il cuisine le dîner pour sa famille"),
 ("They study French grammar", "Ils étudient la grammaire française"),
 ("The rain falls gently", "La pluie tombe doucement"),
 ("She sings a song", "Elle chante une chanson"),
 ("We watch a movie together", "Nous regardons un film ensemble"),
 ("He sleeps deeply", "Il dort profondément"),
 ("They travel to Paris", "Ils voyagent à Paris"),
 ("The children play in the park", "Les enfants jouent dans le parc"),
 ("She walks along the beach", "Elle se promène le long de la plage"),
 ("We talk on the phone", "Nous parlons au téléphone"),
 ("He waits for the bus", "Il attend le bus"),
 ("They visit the Eiffel Tower", "Ils visitent la tour Eiffel"),
 ("The stars twinkle at night", "Les étoiles scintillent la nuit"),
 ("She dreams of flying", "Elle rêve de voler"),
 ("We work in the office", "Nous travaillons au bureau"),
 ("He studies history", "Il étudie l'histoire"),
 ("They listen to the radio", "Ils écoutent la radio"),

```

("The wind blows gently", "Le vent souffle doucement"),
("She swims in the ocean", "Elle nage dans l'océan"),
("We dance at the wedding", "Nous dansons au mariage"),
("He climbs the mountain", "Il gravit la montagne"),
("They hike in the forest", "Ils font de la randonnée dans la forêt"),
("The cat meows loudly", "Le chat miaule bruyamment"),
("She paints a picture", "Elle peint un tableau"),
("We build a sandcastle", "Nous construisons un château de sable"),
("He sings in the choir", "Il chante dans le chœur")
]

SOS_token = 0
EOS_token = 1

```

```

[ ]: # Vocabulary class to handle mapping between words and numerical indices
class Vocabulary:
    def __init__(self):
        # Initialize dictionaries for word to index and index to word mappings
        self.word2index = {"<SOS>": SOS_token, "<EOS>": EOS_token}
        self.index2word = {SOS_token: "<SOS>", EOS_token: "<EOS>"}
        self.word_count = {} # Keep track of word frequencies
        self.n_words = 2 # Start counting from 2 to account for special tokens

    def add_sentence(self, sentence):
        # Add all words in a sentence to the vocabulary
        for word in sentence.split(' '):
            self.add_word(word)

    def add_word(self, word):
        # Add a word to the vocabulary
        if word not in self.word2index:
            # Assign a new index to the word and update mappings
            self.word2index[word] = self.n_words
            self.index2word[self.n_words] = word
            self.word_count[word] = 1
            self.n_words += 1
        else:
            # Increment word count if the word already exists in the vocabulary
            self.word_count[word] += 1

# Custom Dataset class for English to French sentences
class EngFrDataset(Dataset):
    def __init__(self, pairs):
        self.eng_vocab = Vocabulary()
        self.fr_vocab = Vocabulary()
        self.pairs = []

```

```

    # Process each English-French pair
    for eng, fr in pairs:
        self.eng_vocab.add_sentence(eng)
        self.fr_vocab.add_sentence(fr)
        self.pairs.append((eng, fr))

    # Separate English and French sentences
    self.eng_sentences = [pair[0] for pair in self.pairs]
    self.fr_sentences = [pair[1] for pair in self.pairs]

    # Returns the number of pairs
    def __len__(self):
        return len(self.pairs)

    # Get the sentences by index
    def __getitem__(self, idx):
        input_sentence = self.eng_sentences[idx]
        target_sentence = self.fr_sentences[idx]
        input_indices = [self.eng_vocab.word2index[word] for word in
↪input_sentence.split()] + [EOS_token]
        target_indices = [self.fr_vocab.word2index[word] for word in
↪target_sentence.split()] + [EOS_token]

        return torch.tensor(input_indices, dtype=torch.long), torch.
↪tensor(target_indices, dtype=torch.long)

# Initialize the dataset and DataLoader
e2f_dataset = EngFrDataset(text)
dataloader = DataLoader(e2f_dataset, batch_size=1, shuffle=True)

```

```

[ ]: class Encoder(nn.Module):
    """The Encoder part of the seq2seq model."""
    def __init__(self, input_size, hidden_size):
        super(Encoder, self).__init__()
        self.hidden_size = hidden_size
        self.embedding = nn.Embedding(input_size, hidden_size) # Embedding
↪layer
        self.gru = nn.GRU(hidden_size, hidden_size) # GRU layer

    def forward(self, input, hidden):
        embedded = self.embedding(input).view(1, 1, -1)
        output, hidden = self.gru(embedded, hidden)
        return output, hidden

    def initHidden(self):
        return torch.zeros(1, 1, self.hidden_size, device=device)

```

```

class Decoder(nn.Module):
    """The Decoder part of the seq2seq model."""
    def __init__(self, hidden_size, output_size):
        super(Decoder, self).__init__()
        self.hidden_size = hidden_size
        self.embedding = nn.Embedding(output_size, hidden_size)
        self.gru = nn.GRU(hidden_size, hidden_size)
        self.out = nn.Linear(hidden_size, output_size)
        self.softmax = nn.LogSoftmax(dim=1)

    def forward(self, input, hidden):
        embedded = self.embedding(input).view(1, 1, -1)
        output, hidden = self.gru(embedded, hidden)
        output = self.softmax(self.out(output[0]))
        return output, hidden

    def initHidden(self):
        return torch.zeros(1, 1, self.hidden_size, device=device)

```

```

[ ]: def train(input_tensor, target_tensor, encoder, decoder, encoder_optimizer,
↳decoder_optimizer, criterion):
    # Initialize encoder hidden state
    encoder_hidden = encoder.initHidden()

    encoder_optimizer.zero_grad()
    decoder_optimizer.zero_grad()

    input_length = input_tensor.size(0)
    target_length = target_tensor.size(0)

    loss = 0

    # Encoding each character in the input
    for ei in range(input_length):
        encoder_output, encoder_hidden = encoder(input_tensor[ei].unsqueeze(0),
↳encoder_hidden)

    # Decoder's first input is the SOS token
    decoder_input = torch.tensor([[SOS_token]], device=device)

    # Decoder starts with encoder's last hidden state
    decoder_hidden = encoder_hidden

    # Decoding loop
    for di in range(target_length):
        decoder_output, decoder_hidden = decoder(decoder_input, decoder_hidden)
        # Choose top1 word from decoder's output

```

```

        topv, topi = decoder_output.topk(1)
        decoder_input = topi.squeeze().detach() # Detach from history as input

        # Calculate loss
        loss += criterion(decoder_output, target_tensor[di].unsqueeze(0))
        if decoder_input.item() == EOS_token:
            break

    # Backpropagation
    loss.backward()

    # Update encoder and decoder
    encoder_optimizer.step()
    decoder_optimizer.step()

    # Return average loss
    return loss.item() / target_length

def train__loop(encoder, decoder, encoder_optimizer, decoder_optimizer,
    ↪criterion, dataloader, epochs):
    for epoch in range(epochs):
        total_loss = 0
        for input_tensor, target_tensor in dataloader:
            input_tensor = input_tensor[0].to(device)
            target_tensor = target_tensor[0].to(device)

            # Perform a single training step and update loss
            loss = train(input_tensor, target_tensor, encoder, decoder,
    ↪encoder_optimizer, decoder_optimizer, criterion)
            total_loss += loss

        # Print loss every 5 epochs
        if epoch % 5 == 0:
            print(f'Epoch {epoch}, Loss: {total_loss / len(dataloader)}')

```

```

[ ]: def evaluate_and_show_examples(encoder, decoder, dataloader, criterion,
    ↪n_examples=10):
    # Switch model to evaluation mode
    encoder.eval()
    decoder.eval()

    total_loss = 0
    correct_predictions = 0

    # No gradient calculation
    with torch.no_grad():
        for i, (input_tensor, target_tensor) in enumerate(dataloader):

```



```

# Move tensors to the correct device
input_tensor = input_tensor[0].to(device)
target_tensor = target_tensor[0].to(device)

encoder_hidden = encoder.initHidden()

input_length = input_tensor.size(0)
target_length = target_tensor.size(0)

loss = 0

# Encoding step
for ei in range(input_length):
    encoder_output, encoder_hidden = encoder(input_tensor[ei].
↪unsqueeze(0), encoder_hidden)

# Decoding step
decoder_input = torch.tensor([[SOS_token]], device=device)
decoder_hidden = encoder_hidden

predicted_indices = []

for di in range(target_length):
    decoder_output, decoder_hidden = decoder(decoder_input,
↪decoder_hidden)
    topv, topi = decoder_output.topk(1)
    predicted_indices.append(topi.item())
    decoder_input = topi.squeeze().detach()

    loss += criterion(decoder_output, target_tensor[di].
↪unsqueeze(0))
    if decoder_input.item() == EOS_token:
        break

# Calculate and print loss and accuracy for the evaluation
total_loss += loss.item() / target_length
if predicted_indices == target_tensor.tolist():
    correct_predictions += 1

# Print some examples
if i < n_examples:
    predicted_sentence = ' '.join([dataloader.dataset.fr_vocab.
↪index2word[index] for index in predicted_indices if index not in (SOS_token,
↪EOS_token)])
    target_sentence = ' '.join([dataloader.dataset.fr_vocab.
↪index2word[index.item()] for index in target_tensor if index.item() not in
↪(SOS_token, EOS_token)])

```

```

        input_sentence = ' '.join([dataloader.dataset.eng_vocab.
↪index2word[index.item()] for index in input_tensor if index.item() not in
↪(SOS_token, EOS_token)])

        print(f'Input: {input_sentence}, Target: {target_sentence},
↪Predicted: {predicted_sentence}')

        # Print overall evaluation results
        average_loss = total_loss / len(dataloader)
        accuracy = correct_predictions / len(dataloader)
        print(f'Evaluation Loss: {average_loss:.4f}, Accuracy: {100*accuracy:.
↪2f}%')

```

```

[ ]: # Params
epochs = 51
learning_rate = 0.01
hidden_size = 1028

```

```

[ ]: input_size = len(e2f_dataset.eng_vocab.word2index)
output_size = len(e2f_dataset.fr_vocab.word2index)
encoder = Encoder(input_size=input_size, hidden_size=hidden_size).to(device)
decoder = Decoder(hidden_size=hidden_size, output_size=output_size).to(device)

# Optimizers
encoder_optimizer = optim.SGD(encoder.parameters(), lr=learning_rate)
decoder_optimizer = optim.SGD(decoder.parameters(), lr=learning_rate)

criterion = nn.NLLLoss()

train_loop(encoder, decoder, encoder_optimizer, decoder_optimizer, criterion,
↪dataloader, epochs)

```

```

Epoch 0, Loss: 3.479523268251708
Epoch 5, Loss: 2.4761671150917617
Epoch 10, Loss: 1.34410981452728
Epoch 15, Loss: 0.4029710673511494
Epoch 20, Loss: 0.111238581571099
Epoch 25, Loss: 0.03839110464373709
Epoch 30, Loss: 0.02439764090154225
Epoch 35, Loss: 0.018448227389585636
Epoch 40, Loss: 0.014817427380048499
Epoch 45, Loss: 0.0123648420987615
Epoch 50, Loss: 0.010606209402207006

```

```

[ ]: evaluate_and_show_examples(encoder, decoder, dataloader, criterion)

```

```

Input: We love music, Target: Nous aimons la musique, Predicted: Nous aimons la
musique

```

Input: She dances at the party, Target: Elle danse à la fête, Predicted: Elle danse à la fête
Input: The movie starts at 7 PM, Target: Le film commence à 19 heures, Predicted: Le film commence à 19 heures
Input: We plant flowers in the garden, Target: Nous plantons des fleurs dans le jardin, Predicted: Nous plantons des fleurs dans le jardin
Input: He studies history, Target: Il étudie l'histoire, Predicted: Il étudie l'histoire
Input: She dreams of flying, Target: Elle rêve de voler, Predicted: Elle rêve de voler
Input: She teaches English at school, Target: Elle enseigne l'anglais à l'école, Predicted: Elle enseigne l'anglais à l'école
Input: We learn something new every day, Target: Nous apprenons quelque chose de nouveau chaque jour, Predicted: Nous apprenons quelque chose de nouveau chaque jour
Input: She paints a picture, Target: Elle peint un tableau, Predicted: Elle peint un tableau
Input: We cook dinner together, Target: Nous cuisinons le dîner ensemble, Predicted: Nous cuisinons le dîner ensemble
Evaluation Loss: 0.0102, Accuracy: 100.00%

```
[ ]: torch.save(encoder.state_dict(), '../Models/hw4_1_encoder.pth')  
      torch.save(decoder.state_dict(), '../Models/hw4_1_decoder.pth')
```