N-Channel Enhancement-Mode Vertical DMOS FETs

Ordering Information

BV_{DSS} / BV_{DGS}	$R_{DS(ON)}$ (max)	$I_{D(ON)}$ (min)	$V_{GS(th)}$ (max)	Order Number / Package	
				TO-92	SOW-20*
20V	0.75Ω	4.0A	1.6V	—	—
40V	0.75Ω	4.0A	1.6V	TN0604N3	—
40V	1.0Ω	4.0A	1.6V	—	TN0604WG

* Same as SO-20 with 300 mil wide body.

7

Features

- ☐ Low threshold — 1.6V max.
- ☐ High input impedance
- ☐ Low input capacitance — 140pF typical
- ☐ Fast switching speeds
- ☐ Low on resistance
- ☐ Free from secondary breakdown
- ☐ Low input and output leakage
- ☐ Complementary N- and P-channel devices

Low Threshold DMOS Technology

These low threshold enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Applications

- ☐ Logic level interfaces – ideal for TTL and CMOS
- ☐ Solid state relays
- ☐ Battery operated systems
- ☐ Photo voltaic drives
- ☐ Analog switches
- ☐ General purpose line drivers
- ☐ Telecom switches

Package Options



S G D

TO-92



SOW-20

Notes:
1. See Package Outline section for dimensions.
2. See Array section for quad pinouts.

Absolute Maximum Ratings

Drain-to-Source Voltage	BV_{DSS}
Drain-to-Gate Voltage	BV_{DGS}
Gate-to-Source Voltage	± 20V
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C

* Distance of 1.6 mm from case for 10 seconds.

Thermal Characteristics

Package	I_D (continuous)*	I_D (pulsed)	Power Dissipation @ T_C = 25°C	θ_{jc} °C/W	θ_{ja} °C/W	I_{DR}*	I_{DRM}
TO-92	1.0A	4.6A	1W	125	170	1.0A	4.6A
SOW-20	Refer to Arrays & Special Functions Section.						

* I_D (continuous) is limited by max rated T_j.

Electrical Characteristics (@ 25°C unless otherwise specified)

Symbol	Parameter		Min	Typ	Max	Unit	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	TN0604	40			V	V_{GS} = 0V, I_D = 2.0mA
		TN0602	20				
$V_{GS(th)}$	Gate Threshold Voltage		0.6		1.6	V	V_{GS} = V_{DS}, I_D = 1.0mA
$\Delta V_{GS(th)}$	Change in $V_{GS(th)}$ with Temperature			-3.8	-4.5	mV/°C	V_{GS} = V_{DS}, I_D = 2.5mA
I_{GSS}	Gate Body Leakage				100	nA	V_{GS} = ±20V, V_{DS} = 0V
I_{DSS}	Zero Gate Voltage Drain Current				10	µA	V_{GS} = 0V, V_{DS} = Max Rating
					1.0	mA	V_{GS} = 0V, V_{DS} = 0.8 Max Rating, T_A = 125°C
$I_{D(ON)}$	ON-State Drain Current		1.5	2.1		A	V_{GS} = 5V, V_{DS} = 20V
			4.0	7.0			V_{GS} = 10V, V_{DS} = 20V
$R_{DS(ON)}$	Static Drain-to-Source ON-State Resistance	TO-92/SOW-20		1.0	1.6	Ω	V_{GS} = 5V, I_D = 0.75A
		TO-92		0.6	0.75	Ω	V_{GS} = 10V, I_D = 1.5A
		SOW - 20			1.0		
$\Delta R_{DS(ON)}$	Change in $R_{DS(ON)}$ with Temperature			0.5	0.75	%/°C	V_{GS} = 10V, I_D = 1.5A
G_{FS}	Forward Transconductance		0.5	0.8		℧	V_{DS} = 20V, I_D = 1.5A
C_{ISS}	Input Capacitance			140	190	pF	V_{GS} = 0V, V_{DS} = 20V, f = 1 MHz
C_{OSS}	Common Source Output Capacitance			75	110		
C_{RSS}	Reverse Transfer Capacitance			25	50		
$t_{d(ON)}$	Turn-ON Delay Time				10	ns	V_{DD} = 20V, I_D = 0.5A, R_{GEN} = 25Ω
t_r	Rise Time				6.0		
$t_{d(OFF)}$	Turn-OFF Delay Time				25		
t_f	Fall Time				20		
V_{SD}	Diode Forward Voltage Drop			1.2	1.8	V	V_{GS} = 0V, I_{SD} = 1.5A
t_{rr}	Reverse Recovery Time			300		ns	V_{GS} = 0V, I_{SD} = 1A

Notes:
1: All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)
2: All A.C. parameters sample tested.

Switching Waveforms and Test Circuit





Typical Performance Curves

Output Characteristics



Saturation Characteristics



Transconductance vs. Drain Current



Power Dissipation vs. Case Temperature



Maximum Rated Safe Operating Area



Thermal Response Characteristics



7

Typical Performance Curves

BV_{DSS} Variation with Temperature



On-Resistance vs. Drain Current



Transfer Characteristics



$V_{(th)}$ and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics