

Android Concurrency: Java Synchronization & Scheduling Example (Part 2)



Douglas C. Schmidt

d.schmidt@vanderbilt.edu


www.dre.vanderbilt.edu/~schmidt

Institute for Software
Integrated Systems
Vanderbilt University
Nashville, Tennessee, USA



Learning Objectives in this Part of the Module

- Understand the implementation of our pattern-oriented & framework-based ping-pong program




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code

```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code

```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code

```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code

```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code

```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```



Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code


```
/**
 * Create the appropriate type of
 * threads with the designated
 * scheduling mechanism (e.g.,
 * "SEMA" for Semaphores, "COND"
 * for ConditionObjects, etc.).
 */
makePingPongThreads
    (mSyncMechanism,
     pingPongThreads);

/**
 * Start ping and pong threads,
 * which calls their run()
 * hook methods.
 */
pingPongThreads[PING_THREAD].start();
pingPongThreads[PONG_THREAD].start();
```

```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Pong!(1)
Ping!(2)
Pong!(2)
Ping!(3)
Pong!(3)
Ping!(4)
Pong!(4)
Ping!(5)
Pong!(5)
Ping!(6)
Pong!(6)
Ping!(7)
Pong!(7)
Ping!(8)
Pong!(8)
Ping!(9)
Pong!(9)
Ping!(10)
Pong!(10)
Done!
```



Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code
- Show how to program with Java synchronizers




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code
 - Show how to program with Java synchronizers
- Demonstrate benefits of patterns




Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code
 - Show how to program with Java synchronizers
 - Demonstrate benefits of patterns



Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code
 - Show how to program with Java synchronizers
 - Demonstrate benefits of patterns



ConditionObjects

These changes don't affect the ping-pong algorithm or the framework software

Analyzing Pattern-Oriented Framework Solution

- We walk through the pattern-oriented framework source code
- It's important to run/read the code & (re)watch the video carefully to understand how it works

USE THE
SOURCE LUKE



Implementation of the PlayPingPong Class

Implementation of the Ping-Pong Program


- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {
```

Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    ...
```



Provides a pattern-oriented framework
for varying certain aspects of the
ping/pong algorithm concurrently

Implementation of the Ping-Pong Program


- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    private static volatile int  
        mMaxIterations;  
  
    private static volatile int  
        mMaxTurns;  
  
    private static volatile  
        PlatformStrategy mPlatformStrategy;  
  
    private static String mSyncMechanism = "SEMA";  
    ...  
}
```

Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    private static volatile int  
        mMaxIterations;  
  
    private static volatile int  
        mMaxTurns;  
  
    private static volatile  
        PlatformStrategy mPlatformStrategy;  
  
    private static String mSyncMEchanism = "SEMA";  
    ...  
}
```



Number of iterations
to play ping/pong

Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    private static volatile int  
        mMaxIterations;  
  
    private static volatile int  
        mMaxTurns;  
  
    private static volatile  
        PlatformStrategy mPlatformStrategy;  
  
    private static String mSyncMEchanism = "SEMA";  
    ...  
}
```

Number of times to print either
"ping" & "pong" during each turn



Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    private static volatile int  
        mMaxIterations;
```

```
    private static volatile int  
        mMaxTurns;
```

```
    private static volatile  
        PlatformStrategy mPlatformStrategy;
```

```
    private static String mSyncMEchanism = "SEMA";  
    ...
```

Strategy object used to print
& synchronize completion of
the "ping" & "pong" output



Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    private static volatile int  
        mMaxIterations;  
  
    private static volatile int  
        mMaxTurns;  
  
    private static volatile  
        PlatformStrategy mPlatformStrategy;  
  
    private static String mSyncMechanism = "SEMA";  
    ...  
}
```



Synchronization mechanism to use,
e.g. Semaphore or ConditionObject

Implementation of the Ping-Pong Program

- Implementation of the PlayPingPong class

```
public class PlayPingPong implements Runnable {  
    ...  
  
    public PlayPingPong (PlatformStrategy platformStrategy,  
                        int maxIterations, int maxTurns,  
                        String syncMechanism) {  
        mPlatformStrategy = platformStrategy;  
        mMaxIterations = maxIterations;  
        mMaxTurns = maxTurns;  
        mSyncMechanism = syncMechanism;  
    }
```



Constructor stores
parameters used in the
ping/pong algorithm

Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {  
    ...  
    static abstract class PingPongThread  
                        extends Thread {  
  
        abstract void acquire();  
        abstract void release();  
  
        private String nStringToPrint;  
  
        PingPongThread(String stringToPrint)  
        { mStringToPrint = stringToPrint; }  
    }  
}
```

Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class


```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
                    extends Thread {
```

```
    abstract void acquire();
```

```
    abstract void release();
```



Plays role of "abstract
class" in Template
Method pattern

```
private String nStringToPrint;
```

```
PingPongThread(String stringToPrint)  
{ mStringToPrint = stringToPrint; }
```


Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {  
    ...  
    static abstract class PingPongThread  
                        extends Thread {
```

```
        abstract void acquire();  
        abstract void release();
```



Abstract methods overridden by subclasses to schedule the order of printing ping & pong in run() template method

```
        private String nStringToPrint;
```

```
        PingPongThread(String stringToPrint)  
        { mStringToPrint = stringToPrint; }
```

Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
                    extends Thread {
```

```
    abstract void acquire();
```

```
    abstract void release();
```

```
private String nStringToPrint;
```



Define/set common data member

```
PingPongThread(String stringToPrint)  
{ mStringToPrint = stringToPrint; }
```

Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
    extends Thread {
```

```
    public void run() {  
        for (int loopsDone = 1;  
            loopsDone <= mMaxIterations;  
            ++loopsDone) {  
            acquire();  
            mPlatformStrategy.print(mStringToPrint  
                                    + "(" + loopsDone + ")");  
            release();  
        }  
        mPlatformStrategy.done();  
    }
```

Executes in a separate thread & plays
role of the “template method” in the
Template Method pattern



Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
    extends Thread {
```

```
public void run() {
```

```
    for (int loopsDone = 1;
```

```
        loopsDone <= mMaxIterations;
```

```
        ++loopsDone) {
```

```
        acquire();
```

```
        mPlatformStrategy.print(mStringToPrint
```

```
                                + "(" + loopsDone + ")");
```


```
        release();
```

```
    }
```

```
    mPlatformStrategy.done();
```

```
}
```

Executes in a separate thread & plays
role of the “template method” in the
Template Method pattern



Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
    extends Thread {
```

```
    public void run() {  
        for (int loopsDone = 1;  
            loopsDone <= mMaxIterations;  
            ++loopsDone) {  
            acquire();  
            mPlatformStrategy.print(mStringToPrint  
                                    + "(" + loopsDone + ")");  
            release();  
        }  
        mPlatformStrategy.done();  
    }
```


Perform protocol
that alternates
printing "ping" or
"pong"



Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {  
    ...  
    static abstract class PingPongThread  
                        extends Thread {  
  
        public void run() {  
            for (int loopsDone = 1;  
                loopsDone <= mMaxIterations;  
                ++loopsDone) {  
                acquire();  
                mPlatformStrategy.print(mStringToPrint  
                                       + "(" + loopsDone + ")");  
                release();  
            }  
            mPlatformStrategy.done();  
        }  
    }  
}
```




Platform-independent print strategy

Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {  
    ...  
    static abstract class PingPongThread  
                        extends Thread {  
  
        public void run() {  
            for (int loopsDone = 1;  
                loopsDone <= mMaxIterations;  
                ++loopsDone) {  
                acquire();  
                mPlatformStrategy.print(mStringToPrint  
                                       + "(" + loopsDone + ")");  
                release();  
            }  
            mPlatformStrategy.done();  
        }  
    }  
}
```

Scheduling
hooks



Implementation of the Ping-Pong Program

- Implementation of the PingPongThread class

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
static abstract class PingPongThread  
    extends Thread {
```


```
public void run() {  
    for (int loopsDone = 1;  
        loopsDone <= mMaxIterations;  
        ++loopsDone) {  
        acquire();  
        mPlatformStrategy.print(mStringToPrint  
                                + "(" + loopsDone + ")");
```

```
        release();
```

```
    }
```

```
mPlatformStrategy.done();
```

```
}
```




Indicate thread is exiting when loop's done

The underlying CountdownLatch is used to shutdown the PlayPingPong thread

Semaphore Synchronizer Configuration


Ping-Pong Program Synchronizers

- The pattern-oriented ping-pong framework can be transparently configured with different synchronizers




Ping-Pong Program Synchronizers

- The pattern-oriented ping-pong framework can be transparently configured with different synchronizers
- e.g., Java Semaphores or Java ConditionObjects



Semaphore Synchronizer Configuration

- Behavior of the PingPongThreadSema class




```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Pong!(1)
Ping!(2)
Pong!(2)
Ping!(3)
Pong!(3)
Ping!(4)
Pong!(4)
Ping!(5)
Pong!(5)
Ping!(6)
Pong!(6)
Ping!(7)
Pong!(7)
Ping!(8)
Pong!(8)
Ping!(9)
Pong!(9)
Ping!(10)
Pong!(10)
Done!
```

Semaphore Synchronizer Configuration

- Implementation of the PingPongThreadSema class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadSema extends PingPongThread {
```



Plays role of “concrete class”
in Template Method pattern

```
        private Semaphore mSemas[] = new Semaphore[2];
```

```
        PingPongThreadSema(String stringToPrint,  
                            Semaphore firstSema, Semaphore secondSema) {  
            super(stringToPrint);  
            mSemas[FIRST_SEMA] = firstSema;  
            mSemas[SECOND_SEMA] = secondSema;  
        }
```

Semaphore Synchronizer Configuration

- Implementation of the PingPongThreadSema class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadSema extends PingPongThread {
```

```
        private Semaphore mSemas[] = new Semaphore[2];
```



Semaphores that schedule the
acquire() & release() hook methods

```
        PingPongThreadSema(String stringToPrint,  
                           Semaphore firstSema, Semaphore secondSema) {  
            super(stringToPrint);  
            mSemas[FIRST_SEMA] = firstSema;  
            mSemas[SECOND_SEMA] = secondSema;  
        }
```

Semaphore Synchronizer Configuration

- Implementation of the PingPongThreadSema class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadSema extends PingPongThread {  
  
        private Semaphore mSemas[] = new Semaphore[2];  
  
        PingPongThreadSema(String stringToPrint,  
                           Semaphore firstSema, Semaphore secondSema) {  
            super(stringToPrint);  
            mSemas[FIRST_SEMA] = firstSema;  
            mSemas[SECOND_SEMA] = secondSema;  
        }  
    }  
}
```





Pass parameter up to super class
& initialize the semaphores

Semaphore Synchronizer Configuration

- Implementation of the PingPongThreadSema class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadSema extends PingPongThread {  
  
        void acquire() {  
            mSemas[FIRST_SEMA].acquireUninterruptibly();  
        }  
  
        void release() {  
            mSemas[SECOND_SEMA].release(); }  
    }  
}
```


 Hook method for acquiring synchronizer

 Hook method for releasing synchronizer

ConditionObject Synchronizer Configuration

ConditionObject Synchronizer Configuration

- Behavior of the PingPongThreadCond class



ConditionObjects


Note multiple consecutive printings of "ping" or "pong" per turn

```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Ping!(2)
Pong!(1)
Pong!(2)
Ping!(3)
Ping!(4)
Pong!(3)
Pong!(4)
Ping!(5)
Ping!(6)
Pong!(5)
Pong!(6)
Ping!(7)
Ping!(8)
Pong!(7)
Pong!(8)
Ping!(9)
Ping!(10)
Pong!(9)
Pong!(10)
Done!
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {
```



Plays role of “concrete class”
in Template Method pattern

```
        private Condition mConds[] = new Condition[2];
```

```
        private ReentrantLock mLock = null;
```

```
        private int mTurnCountDown = 0;
```

```
        public long mOtherThreadId = 0;
```

```
        private static long mTurnOwner;
```

```
        ...
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        private Condition mConds[] = new Condition[2];  
  
        private ReentrantLock mLock = null;  
  
        private int mTurnCountDown = 0;  
  
        public long mOtherThreadId = 0;  
  
        private static long mTurnOwner;  
        ...  
    }  
}
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {
```

ConditionObjects that schedule the
acquire() & release() hook methods




```
        private Condition mConds[] = new Condition[2];  
  
        private ReentrantLock mLock = null;  
  
        private int mTurnCountDown = 0;  
  
        public long mOtherThreadId = 0;  
  
        private static long mTurnOwner;  
        ...
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        private Condition mConds[] = new Condition[2];  
  
        private ReentrantLock mLock = null;  
  
        private int mTurnCountDown = 0;  
  
        public long mOtherThreadId = 0;  
  
        private static long mTurnOwner;  
        ...  
    }  
}
```




Used together with
the ConditionObjects

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        private Condition mConds[] = new Condition[2];  
  
        private ReentrantLock mLock = null;  
  
        private int mTurnCountDown = 0;  
  
        public long mOtherThreadId = 0;  
  
        private static long mTurnOwner;  
        ...  
    }  
}
```




Controls number of
consecutive iterations
per turn

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        private Condition mConds[] = new Condition[2];  
  
        private ReentrantLock mLock = null;  
  
        private int mTurnCountDown = 0;  
  
        public long mOtherThreadId = 0;  
  
        private static long mTurnOwner;  
        ...  
    }  
}
```




Coordinate the passing
of control between ping
& pong Threads

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
        ...  
        private final static int FIRST_COND = 0;  
        private final static int SECOND_COND = 1;
```


```
        PingPongThreadCond(String stringToPrint,  
                            ReentrantLock lock, Condition firstCond,  
                            Condition secondCond, boolean isOwner) {  
            super(stringToPrint);  
            mTurnCountDown = mMaxTurns;  
            mLock = lock;  
            mConds[FIRST_COND] = firstCond;  
            mConds[SECOND_COND] = secondCond;  
            if (isOwner) mTurnOwner = this.getId();  
            ...
```



Pass parameter up to
super class & initialize
data members

ConditionObject Synchronizer Configuration


- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void acquire() {  Hook method for acquiring synchronizer  
            mLock.lock();  
  
            while (mTurnOwner != this.getId())  
                mConds[FIRST_COND].awaitUninterruptibly();  
  
            mLock.unlock();  
        }  
    }  
}
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void acquire() {  
            mLock.lock();  
  
            while (mTurnOwner != this.getId())  
                mConds[FIRST_COND].awaitUninterruptibly();  
  
            mLock.unlock();  
        }  
    }  
}
```




Acquire the ReentrantLock

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void acquire() {  
            mLock.lock();  
  
            while (mTurnOwner != this.getId())  
                mConds[FIRST_COND].awaitUninterruptibly();  
  
            mLock.unlock();  
        }  
    }  
}
```



Check to see if it's the turn owner

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class


```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void acquire() {  
            mLock.lock();  
  
            while (mTurnOwner != this.getId())  
                mConds[FIRST_COND].awaitUninterruptibly();  
  
            mLock.unlock();  
        }  
    }  
}
```



Wait to become the turn owner


ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  Hook method for releasing synchronizer  
            mLock.lock();  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```

ConditionObject Synchronizer Configuration


- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  Acquire the ReentrantLock  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```

ConditionObject Synchronizer Configuration


- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```

 Decrement each iteration of our "turn"

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  
  
            --mTurnCountDown;  Check whether our turn is over  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```

Make the other Thread
the turn owner & reset
the number of iterations
per turn



ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```



Signal the other Thread that its
turn can begin

ConditionObject Synchronizer Configuration

- Implementation of the PingPongThreadCond class

```
public class PlayPingPong implements Runnable {  
    ...  
    static class PingPongThreadCond extends PingPongThread {  
  
        void release() {  
            mLock.lock();  
  
            --mTurnCountDown;  
  
            if (mTurnCountDown == 0) {  
                mTurnOwner = mOtherThreadId;  
                mTurnCountDown = mMaxTurns;  
                mConds[SECOND_COND].signal();  
            }  
            mLock.unlock();  
        }  
    }  
}
```




Release the ReentrantLock

Putting All the Pieces Together

Putting All the Pieces Together




Putting All the Pieces Together



Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {  
    ...  
    public void run() {  Entry point into PlayPingPong  
        mPlatformStrategy.begin();  
        ...  
        PingPongThread pingPongThreads[] =  
            new PingPongThread[2];  
        ...  
  
        makePingPongThreads(mSyncMechanism,  
                            pingPongThreads);  
  
        pingPongThreads[PING_THREAD].start();  
        pingPongThreads[PONG_THREAD].start();  
  
        mPlatformStrategy.awaitDone();  
        ...  
}
```


Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {  
    ...  
    public void run() {  
        mPlatformStrategy.begin();  
        ...  
        PingPongThread pingPongThreads[] =  
            new PingPongThread[2];  
        ...  
  
        makePingPongThreads(mSyncMechanism,  
                            pingPongThreads);  
  
        pingPongThreads[PING_THREAD].start();  
        pingPongThreads[PONG_THREAD].start();  
  
        mPlatformStrategy.awaitDone();  
        ...  
    }  
}
```

← Indicate a new game is beginning

Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {
```

```
...
```

```
public void run() {
```

```
    mPlatformStrategy.begin();
```

```
...
```

```
    PingPongThread pingPongThreads[] =  
        new PingPongThread[2];
```


```
...
```

```
    makePingPongThreads(mSyncMechanism,  
                        pingPongThreads);
```

```
    pingPongThreads[PING_THREAD].start();  
    pingPongThreads[PONG_THREAD].start();
```

```
    mPlatformStrategy.awaitDone();
```

```
...
```




Create array of
PingPongThreads

Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {  
    ...  
    public void run() {  
        mPlatformStrategy.begin();  
        ...  
        PingPongThread pingPongThreads[] =  
            new PingPongThread[2];  
        ...  
  
        makePingPongThreads(mSyncMechanism,  
                           pingPongThreads);  
  
        pingPongThreads[PING_THREAD].start();  
        pingPongThreads[PONG_THREAD].start();  
  
        mPlatformStrategy.awaitDone();  
        ...  
    }  
}
```

Use a factory method
to initialize Semaphore
objects to control thread
alternation




Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {  
    ...  
    public void run() {  
        mPlatformStrategy.begin();  
        ...  
        PingPongThread pingPongThreads[] =  
            new PingPongThread[2];  
        ...  
  
        makePingPongThreads(mSyncMechanism,  
                            pingPongThreads);  
  
        pingPongThreads[PING_THREAD].start();  
        pingPongThreads[PONG_THREAD].start();  
  
        mPlatformStrategy.awaitDone();  
        ...  
    }  
}
```

Start ping & pong
threads, which calls
their run() methods



Putting All the Pieces Together

- Implementing the PlayPingPong run() method

```
public class PlayPingPong implements Runnable {  
    ...  
    public void run() {  
        mPlatformStrategy.begin();  
        ...  
        PingPongThread pingPongThreads[] =  
            new PingPongThread[2];  
        ...  
  
        makePingPongThreads(mSyncMechanism,  
                             pingPongThreads);  
  
        pingPongThreads[PING_THREAD].start();  
        pingPongThreads[PONG_THREAD].start();  
  
        mPlatformStrategy.awaitDone();  
        ...  
    }  
}
```


Wait for both threads to
exit before exiting run()

Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

Factory
method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```



Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```



Select semaphore
implementation

Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);
```




Create two binary semaphores

```
        pingPongThreads[PING_THREAD] =  
            new PingPongThreadSema("ping", pingSema, pongSema);  
        pingPongThreads[PONG_THREAD] =  
            new PingPongThreadSema("pong", pongSema, pingSema);  
    }  
    ...
```


Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```



Begin
unlocked

Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```



Create two thread objects
initialized for "ping" & "pong"

Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```



Create two thread objects
initialized for "ping" & "pong"

Putting All the Pieces Together

- Implementing the PlayPingPong makePingPongThreads() method

```
public class PlayPingPong implements Runnable {  
    ...  
    private void makePingPongThreads(String schedMechanism,  
                                     PingPongThread[] pingPongThreads) {  
        if (schedMechanism.equals("SEMA")) {  
            Semaphore pingSema = new Semaphore(1);  
            Semaphore pongSema = new Semaphore(0);  
  
            pingPongThreads[PING_THREAD] =  
                new PingPongThreadSema("ping", pingSema, pongSema);  
            pingPongThreads[PONG_THREAD] =  
                new PingPongThreadSema("pong", pongSema, pingSema);  
        }  
        ...  
    }  
}
```




Create two thread objects
initialized for "ping" & "pong"

Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
                (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                             Options.instance().maxIterations(),  
                             Options.instance().maxTurns(),  
                             Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```


 **main()** entry point into the ping/pong program

Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
             (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                             Options.instance().maxIterations(),  
                             Options.instance().maxTurns(),  
                             Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```


Initialize PlatformStrategy to ConsolePlatformStrategy



Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
                (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                            Options.instance().maxIterations(),  
                            Options.instance().maxTurns(),  
                            Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```




Initialize the Options

Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
                (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                            Options.instance().maxIterations(),  
                            Options.instance().maxTurns(),  
                            Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```

 Initialize PlayPingPong object
with designated parameters

Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
                (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                             Options.instance().maxIterations(),  
                             Options.instance().maxTurns(),  
                             Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```



Start a thread to play ping pong concurrently!

Putting All the Pieces Together

- Implementation of the Main class

```
public class Main {  
    ...  
    public void main(String[] args) {  
        PlatformStrategy.instance  
            (new PlatformStrategyFactory  
                (System.out, null).makePlatformStrategy());  
  
        Options.instance().parseArgs(args);  
  
        PlayPingPong playPingPong =  
            new PlayPingPong(PlatformStrategy.instance(),  
                             Options.instance().maxIterations(),  
                             Options.instance().maxTurns(),  
                             Options.instance().syncMechanism());  
  
        new Thread (playPingPong).start();  
        ...  
    }  
}
```




Start a thread to play ping pong concurrently!

Summary



Summary

- Pattern-oriented framework implements a concurrent ping/pong program



Summary

- Pattern-oriented framework implements a concurrent ping/pong program
 - Fixes problems with the PingPongWrong implementation

```
% java PingPongWrong
Ready...Set...Go!
Ping!(1)
Ping!(2)
Ping!(3)
Ping!(4)
Ping!(5)
Ping!(6)
Ping!(7)
Ping!(8)
Ping!(9)
Ping!(10)
Pong!(1)
Pong!(2)
Pong!(3)
Pong!(4)
Pong!(5)
Pong!(6)
Pong!(7)
Pong!(8)
Pong!(9)
Pong!(10)
Done!
```


Summary

- Pattern-oriented framework implements a concurrent ping/pong program
 - Fixes problems with the PingPongWrong implementation
- Output correctly alternates printing “ping” & “pong” to output since Java Semaphores, ConditionObjects, & CountdownLatches are used

```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Pong!(1)
Ping!(2)
Pong!(2)
Ping!(3)
Pong!(3)
Ping!(4)
Pong!(4)
Ping!(5)
Pong!(5)
Ping!(6)
Pong!(6)
Ping!(7)
Pong!(7)
Ping!(8)
Pong!(8)
Ping!(9)
Pong!(9)
Ping!(10)
Pong!(10)
Done!
```

Summary

- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits
 - *Template Method* & *Factory Method* simplify systematic reuse & flexibility



Summary



- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits
 - *Template Method* & *Factory Method* simplify systematic reuse & flexibility



```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Ping!(1)
Pong!(1)
Pong!(1)
Ping!(2)
Ping!(2)
Pong!(2)
Pong!(2)
Ping!(3)
Ping!(3)
Pong!(3)
Pong!(3)
Ping!(4)
Ping!(4)
Pong!(4)
Pong!(4)
Ping!(5)
Ping!(5)
Pong!(5)
Pong!(5)
Done!
```



Summary

- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits
 - *Template Method* & *Factory Method* simplify systematic reuse & flexibility
 - *Strategy* enhanced portability



Summary

- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits
 - *Template Method* & *Factory Method* simplify systematic reuse & flexibility
 - *Strategy* enhanced portability



Summary


- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits
 - *Template Method* & *Factory Method* simplify systematic reuse & flexibility
 - *Strategy* enhanced portability



```
% java PlayPingPong
Ready...Set...Go!
Ping!(1)
Ping!(1)
Pong!(1)
Pong!(1)
Ping!(2)
Ping!(2)
Pong!(2)
Pong!(2)
Ping!(3)
Ping!(3)
Pong!(3)
Pong!(3)
Ping!(4)
Ping!(4)
Pong!(4)
Pong!(4)
Ping!(5)
Ping!(5)
Pong!(5)
Pong!(5)
Done!
```

Summary

- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits



Summary

- Pattern-oriented framework implements a concurrent ping/pong program
- GoF patterns provide several benefits

