Parallel Fast Multipole

Paul Beckman, Mariya Savinov

NYU Courant

May 1, 2022

• Consider a collection of interacting particles with a potential

- Consider a collection of interacting particles with a potential
- Total potential at a point x due to particles x_j with charges q_j is

$$u(x) = \sum_{j=1}^{n} \frac{q_j}{|x - x_j|} = \sum_{j=1}^{n} q_j \phi(x - x_j)$$

- Consider a collection of interacting particles with a potential
- Total potential at a point x due to particles x_j with charges q_j is


$$u(x) = \sum_{j=1}^{n} \frac{q_j}{|x - x_j|} = \sum_{j=1}^{n} q_j \phi(x - x_j)$$

Separate sum into near-field and far-field contributions

- Consider a collection of interacting particles with a potential
- Total potential at a point x due to particles x_j with charges q_j is

$$u(x) = \sum_{j=1}^{n} \frac{q_j}{|x - x_j|} = \sum_{j=1}^{n} q_j \phi(x - x_j)$$

- Separate sum into near-field and far-field contributions
 - ► Take aggregate effect of far-field charges via Taylor series expansion




• For a set of points x_i , potential contribution can be approximated:

$$\sum_{j \in \mathsf{far}\text{-field}} q_j \phi(\mathsf{x} - \mathsf{x}_j) \approx \sum_{m=0}^p \underbrace{\left[\sum_{j \in \mathsf{far}\text{-field}} q_j a_m(\mathsf{x}_j - \mathsf{x}^*)\right]}_{\mathsf{weight} \ m} S_m(\mathsf{x}^* - \mathsf{x}) + O(\delta^{p+1})$$

• For a set of points x_i , potential contribution can be approximated:

$$\sum_{j \in \text{far-field}} q_j \phi(x - x_j) \approx \sum_{m=0}^p \underbrace{\left[\sum_{j \in \text{far-field}} q_j a_m(x_j - x^*) \right]}_{\text{weight } m} S_m(x^* - x) + O(\delta^{p+1})$$

• For N particles, partition [0,1] uniformly at $O(\log N)$ levels:



• For a set of points x_i , potential contribution can be approximated:

$$\sum_{j \in \text{far-field}} q_j \phi(x - x_j) \approx \sum_{m=0}^p \underbrace{\left[\sum_{j \in \text{far-field}} q_j a_m(x_j - x^*) \right]}_{\text{weight } m} S_m(x^* - x) + O(\delta^{p+1})$$


• For N particles, partition [0,1] uniformly at $O(\log N)$ levels:




ullet For each $T_{\ell,k}$ cell, compute weights $w_{\ell,k,m} \longrightarrow \operatorname{total} \operatorname{cost} O(N \log N)$

• At each level, only 'interact' with up to 3 far-field cells not already included at higher levels

• At each level, only 'interact' with up to 3 far-field cells not already included at higher levels




 At each level, only 'interact' with up to 3 far-field cells not already included at higher levels



Then for a point x, the potential is approximately

$$u(x) = \sum_{\ell=1}^{O(\log N)} \sum_{m=0}^{p} w_{\ell,k(\ell),m} S_m \left(x_{\ell,k(\ell)}^* - x \right) + O\left(2^{-p} \right)$$

 At each level, only 'interact' with up to 3 far-field cells not already included at higher levels



• Then for a point x, the potential is approximately

$$u(x) = \sum_{\ell=1}^{O(\log N)} \sum_{m=0}^{p} w_{\ell,k(\ell),m} S_m \left(x_{\ell,k(\ell)}^* - x \right) + O\left(2^{-p} \right)$$

Total cost is O(N log N)


Serial implementation

Serial implementation

 Successfully implemented the serial code for the algorithm, making use of a tree data type

Serial implementation

- Successfully implemented the serial code for the algorithm, making use of a tree data type
- Confirmation of $O(N \log N)$ cost:



Parallelizing with OpenMP

- Parallelizing with OpenMP
 - ► Challenge:

- Parallelizing with OpenMP
 - ► Challenge: Recursive tree code may prevent significant speedup

- Parallelizing with OpenMP
 - ► Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize

- Parallelizing with OpenMP
 - ► Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code

- Parallelizing with OpenMP
 - Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code
 - computing weights, adding near-field terms, and adding far-field terms

- Parallelizing with OpenMP
 - Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code
 - computing weights, adding near-field terms, and adding far-field terms
 - ▶ Potential Problem: Loops of varying sizes, possibly large overhead


- Parallelizing with OpenMP
 - Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code
 - computing weights, adding near-field terms, and adding far-field terms
 - ▶ Potential Problem: Loops of varying sizes, possibly large overhead
- OPTION 2: Distribute the work in the tree among threads

- Parallelizing with OpenMP
 - Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code
 - computing weights, adding near-field terms, and adding far-field terms
 - ▶ Potential Problem: Loops of varying sizes, possibly large overhead
- OPTION 2: Distribute the work in the tree among threads
 - ▶ At tree levels $\ell < O(\log p)$ for p threads, open a new section

- Parallelizing with OpenMP
 - Challenge: Recursive tree code may prevent significant speedup
- Two options of how to parallelize
- OPTION 1: Parallelize the loops in the code
 - computing weights, adding near-field terms, and adding far-field terms
 - ▶ Potential Problem: Loops of varying sizes, possibly large overhead
- OPTION 2: Distribute the work in the tree among threads
 - ▶ At tree levels $\ell < O(\log p)$ for p threads, open a new section
 - ▶ Potential Problem: Nested parallelism


Results: Comparing Parallel Options


Results: Comparing Parallel Options



Results: Strong Scalability

Results: Strong Scalability







Results: Weak Scalability

Results: Weak Scalability

$$n = 8192$$
, max pts = 2048, and $p = 5$





Supplemental Slides

Approximating far-field

• Use Taylor series expansion of $\phi(x-x_j)$ for small $\delta = \frac{x_j - x^*}{x^* - x}$:

$$\phi(x_{j} - x) = \phi((x^{*} - x)(1 + \delta)) = \phi(x^{*} - x)\phi(1 + \delta)$$

$$\approx \phi(x^{*} - x) \left[\sum_{m=0}^{p} \frac{\phi^{(m)}(1)}{m!} \delta^{m} + O(\delta^{p+1}) \right]$$


$$= \sum_{m=0}^{p} a_{m}(x_{j} - x^{*}) S_{m}(x^{*} - x) + O(\delta^{p+1})$$

• Then potential from $x_j \in \text{far-field is}$

$$\sum_{j \in \mathsf{far}\text{-field}} q_j \phi(x - x_j) \approx \sum_{m=0}^p \left[\sum_{j \in \mathsf{far}\text{-field}} q_j a_m(x_j - x^*) \right] S_m(x^* - x) + O(\delta^{p+1})$$

• Accuracy depends on choice of x^* and thus size of $\delta = \frac{x_j - x^*}{x^* - x}$

• For N particles, partition [0,1] uniformly at $O(\log N)$ levels:



- Let $T_{\ell,k}$ be the cell at level ℓ with index $k=1:2^\ell$ with center $x_{\ell,k}^*$.
- Compute weight at each cell, total cost $O(N \log N)$

$$w_{\ell,k,m} = \sum_{x_j \in T_{\ell,k}} q_j a_m(x_j - x_{\ell,k}^*)$$

• For a point x: far-field components added at increasingly coarse levels

$$u(x) = \sum_{\ell=1}^{O(\log N)} \sum_{m=0}^{p} w_{\ell,k(\ell),m} S_m \left(x_{\ell,k(\ell)}^* - x \right)$$