

Parallel Fast Multipole

Paul Beckman, Mariya Savinov

NYU Courant

April 26, 2022

Motivating Problem

Motivating Problem

- Consider a collection of interacting particles with a potential

Motivating Problem

- Consider a collection of interacting particles with a potential
- **Total potential** at a point x due to **particles** x_j with **charges** q_j is


$$u(x) = \sum_{j=1}^n \frac{q_j}{|x - x_j|} = \sum_{j=1}^n q_j \phi(x - x_j)$$

Motivating Problem

- Consider a collection of interacting particles with a potential
- Total potential** at a point x due to **particles** x_j with **charges** q_j is

$$u(x) = \sum_{j=1}^n \frac{q_j}{|x - x_j|} = \sum_{j=1}^n q_j \phi(x - x_j)$$

- Separate sum into **near-field** and **far-field** contributions
 - Take *aggregate* effect of far-field charges



Approximating far-field

Approximating far-field

- Use **Taylor series expansion** of $\phi(x - x_j)$ for small $\delta = \frac{x_j - x^*}{x^* - x}$:

$$\begin{aligned}\phi(x_j - x) &= \phi((x^* - x)(1 + \delta)) = \phi(x^* - x)\phi(1 + \delta) \\ &\approx \phi(x^* - x) \left[\sum_{k=0}^p \frac{\phi^{(k)}(1)}{k!} \delta^k + O(\delta^{p+1}) \right] \\ &= \sum_{k=0}^p a_k(x_j - x^*) S_k(x^* - x) + O(\delta^{p+1})\end{aligned}$$

Approximating far-field

- Use **Taylor series expansion** of $\phi(x - x_j)$ for small $\delta = \frac{x_j - x^*}{x^* - x}$:

$$\begin{aligned}\phi(x_j - x) &= \phi((x^* - x)(1 + \delta)) = \phi(x^* - x)\phi(1 + \delta) \\ &\approx \phi(x^* - x) \left[\sum_{k=0}^p \frac{\phi^{(k)}(1)}{k!} \delta^k + O(\delta^{p+1}) \right] \\ &= \sum_{k=0}^p a_k(x_j - x^*) S_k(x^* - x) + O(\delta^{p+1})\end{aligned}$$

- Then potential from $x_j \in \text{far-field}$ is

$$\sum_{j \in \text{far-field}} q_j \phi(x - x_j) \approx \sum_{k=0}^p \left[\sum_{j \in \text{far-field}} q_j a_k(x_j - x^*) \right] S_k(x^* - x) + O(\delta^{p+1})$$

Approximating far-field

- Use **Taylor series expansion** of $\phi(x - x_j)$ for small $\delta = \frac{x_j - x^*}{x^* - x}$:

$$\begin{aligned}\phi(x_j - x) &= \phi((x^* - x)(1 + \delta)) = \phi(x^* - x)\phi(1 + \delta) \\ &\approx \phi(x^* - x) \left[\sum_{k=0}^p \frac{\phi^{(k)}(1)}{k!} \delta^k + O(\delta^{p+1}) \right] \\ &= \sum_{k=0}^p a_k(x_j - x^*) S_k(x^* - x) + O(\delta^{p+1})\end{aligned}$$

- Then potential from $x_j \in \text{far-field}$ is


$$\sum_{j \in \text{far-field}} q_j \phi(x - x_j) \approx \sum_{k=0}^p \left[\sum_{j \in \text{far-field}} q_j a_k(x_j - x^*) \right] S_k(x^* - x) + O(\delta^{p+1})$$

- Accuracy depends on choice of x^* and thus size of $\delta = \frac{x_j - x^*}{x^* - x}$

Tree Algorithm by Barnes and Hut, complexity $O(N \log N)$


Tree Algorithm by Barnes and Hut, complexity $O(N \log N)$

- For N particles, partition $[0, 1]$ uniformly at $O(\log N)$ levels:



Tree Algorithm by Barnes and Hut, complexity $O(N \log N)$


- For N particles, partition $[0, 1]$ uniformly at $O(\log N)$ levels:



- Let $T_{\ell,m}$ be the cell at level ℓ with index $m = 1 : 2^\ell$ with center $x_{\ell,m}^*$.

Tree Algorithm by Barnes and Hut, complexity $O(N \log N)$

- For N particles, partition $[0, 1]$ uniformly at $O(\log N)$ levels:




- Let $T_{\ell,m}$ be the cell at level ℓ with index $m = 1 : 2^\ell$ with center $x_{\ell,m}^*$.
- Compute weight at each cell, total cost $O(N \log N)$

$$w_{\ell,m,k} = \sum_{x_j \in T_{\ell,m}} q_j a_k(x_j - x_{\ell,m}^*)$$

Tree Algorithm by Barnes and Hut, complexity $O(N \log N)$

- For N particles, partition $[0, 1]$ uniformly at $O(\log N)$ levels:



- Let $T_{\ell,m}$ be the cell at level ℓ with index $m = 1 : 2^\ell$ with center $x_{\ell,m}^*$.
- Compute weight at each cell, total cost $O(N \log N)$

$$w_{\ell,m,k} = \sum_{x_j \in T_{\ell,m}} q_j a_k(x_j - x_{\ell,m}^*)$$

- For a point x : far-field components added at increasingly *coarse* levels

$$u(x) = \sum_{\ell=1}^{O(\log N)} \sum_{k=0}^p w_{\ell,m(\ell),k} S_k(x_{\ell,m(\ell)}^* - x)$$


Interaction List

Interaction List

- At each level, only 'interact' with up to 4 far-field cells *not already included at higher levels*

Interaction List

- At each level, only 'interact' with up to 4 far-field cells *not already included at higher levels*



Parallelism

Parallelism

- Parallelize with OpenMP

Parallelism

- Parallelize with OpenMP
 - ▶ *Challenge:*

Parallelism

- Parallelize with OpenMP
 - ▶ *Challenge:* Recursive tree code may prevent significant speedup

Parallelism

- Parallelize with OpenMP
 - ▶ *Challenge:* Recursive tree code may prevent significant speedup
- Partition the memory and work with MPI

Parallelism

- Parallelize with OpenMP
 - ▶ *Challenge:* Recursive tree code may prevent significant speedup
- Partition the memory and work with MPI
 - ▶ *Challenge:*

Parallelism

- Parallelize with OpenMP
 - ▶ *Challenge:* Recursive tree code may prevent significant speedup
- Partition the memory and work with MPI
 - ▶ *Challenge:* Minimizing communication between cores

Results

Results

- Speed-up

Results

- Speed-up
- How we measured speed-up

Results

- Speed-up
- How we measured speed-up
- What did we expect? Is there some unavoidable overhead?