Lista09_Blumtritt

Lista 09

1. Crie um banco de dados SQLite utilizando os 3 arquivos acima. O banco de dados deve conter as seguintes tabelas: basics, ratings e principals

```
library(tidyverse)
```

```
-- Attaching core tidyverse packages ------------------------ tidyverse 2.0.0 --
v dplyr     1.2.1     v readr     2.2.0
v forcats   1.0.1     v stringr   1.6.0
v ggplot2   4.0.3     v tibble    3.3.1
v lubridate 1.9.5     v tidyr     1.3.2
v purrr     1.2.2
-- Conflicts ------------------------------------------ tidyverse_conflicts() --
x dplyr::filter() masks stats::filter()
x dplyr::lag()    masks stats::lag()
i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to beco
```

```
library(DBI)
library(RSQLite)

con <- dbConnect(RSQLite::SQLite(), "banco_lista09.sqlite")
dbWriteTable(con, "basics", read_tsv("title.basics0.tsv.gz"), overwrite = TRUE)
```

```
Rows: 11144942 Columns: 9
-- Column specification --------------------------------------------------------
Delimiter: "\t"
chr (8): tconst, titleType, primaryTitle, originalTitle, startYear, endYear,...
dbl (1): isAdult

i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```r
dbWriteTable(con, "ratings", read_tsv("title.ratings.tsv.gz"), overwrite = TRUE)
```

```
Rows: 1484615 Columns: 3
-- Column specification --------------------------------------------------------
Delimiter: "\t"
chr (1): tconst
dbl (2): averageRating, numVotes

i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```r
dbWriteTable(con, "principals", read_tsv("title.principals0.tsv.gz"), overwrite = TRUE)
```

```
Rows: 88359622 Columns: 6
-- Column specification --------------------------------------------------------
Delimiter: "\t"
chr (5): tconst, nconst, category, job, characters
dbl (1): ordering

i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

2. (Utilizando SQL, responda): Quais são os 5 filmes com as maiores notas (averageRating)? Apresente uma solução capaz de desempatar os filmes baseando-se no número de votos recebidos.

```sql
SELECT primaryTitle AS Filme, averageRating AS Nota_Media, numVotes AS Votos FROM basics B
JOIN ratings R ON B.tconst = R.tconst
WHERE titleType LIKE "movie"
ORDER BY averageRating DESC, numVotes DESC
LIMIT 5
```

Table 1: 5 records

Filme	Nota_Media	Votos
Kaveri	10	1023
Kurukku	10	451
Jedal Dar Omghe 30 Metri	10	142
Sargashte	10	134
Gorgeous Rascal	10	115

Filme	Nota_Media	Votos

3. (Utilizando SQL, responda): Qual é o gênero mais frequente entre os filmes com nota maior que 8?

```
SELECT TRIM(j.value) AS Genero, COUNT(*) AS Frequencia FROM basics B
JOIN ratings R ON B.tconst = R.tconst
JOIN json_each('["' || REPLACE(b.genres, ',', '","') || '"]') j
WHERE averageRating > 8 AND titleType LIKE "movie" AND b.genres != "\N"
GROUP BY genero
ORDER BY frequencia DESC
LIMIT 1
```

Table 2: 1 records

Genero	Frequencia
Documentary	10564

4. (Utilizando SQL, responda): Quais são os 3 atores/atrizes que mais participaram de filmes com nota maior que 7.5?

```
SELECT nconst AS Artista, COUNT(*) AS Quantidade FROM basics B
JOIN ratings R ON B.tconst = R.tconst
JOIN principals P ON B.tconst = P.tconst
WHERE B.titleType = "movie" AND averageRating > 7.5 AND P.category IN ("actor", "actress")
GROUP BY Artista
ORDER BY Quantidade DESC
LIMIT 3
```

Table 3: 3 records

Artista	Quantidade
nm0004660	231
nm0595934	155
nm3183374	124

```
dbDisconnect(con)
Sys.setenv(TZ = "America/Sao_Paulo")
Sys.time()
```

```
[1] "2026-10-15 11:46:34 -03"
```