

Configuration Web Services API

5 May 2026

About Five9

Five9 is the leading provider of cloud contact center software, bringing the power of the cloud to thousands of customers and facilitating more than three billion customer interactions annually. Since 2001, Five9 has led the cloud revolution in contact centers, delivering software to help organizations of every size transition from premise-based software to the cloud. With its extensive expertise, technology, and ecosystem of partners, Five9 delivers secure, reliable, scalable cloud contact center software to help businesses create exceptional customer experiences, increase agent productivity and deliver tangible results. For more information visit www.five9.com.

Trademarks

Five9®

Five9 Logo

Five9® SoCoCare™

Five9® Connect™

Five9 and the Five9 logo are registered trademarks of Five9 and its subsidiaries in the United States and other countries. Other marks and brands may be claimed as the property of others. The product plans, specifications, and descriptions herein are provided for information only and subject to change without notice, and are provided without warranty of any kind, express or implied. Copyright © 2026 Five9, Inc.

Contents

About the Five9 Configuration Web Services API.....	4
Web Services Platform.....	5
Differences Among Versions 4, 3, 2, and Default.....	6
Basic Access Authentication	11

About the Five9 Configuration Web Services API

The Five9 Configuration Web Services enable you to build secure applications to access, configure, manage, and synchronize call center information with work flow-management systems, such as lead management, CRM, and ERP systems.

This guide is intended for developers who understand these technologies and protocols:

- Client-server architecture and Web services
- SOAP, HTTP, and XML
- JSP, ASP, CGI, or Perl
- Computer-telephony integration concepts, processes, events, and call routing
- Overall call center integration and configuration

Note:

Five9 Configuration Web Services uses the swaRef.xsd to include binary content for types that are used to `upload` greetings in WAV format.

If you use Apache CXF, be aware that it does not support swaRef.xsd types. Before the SOAP envelope, it inserts text for which Five9 returns this exception:

```
Exception=javax.xml.ws.soap.SOAPFaultException: org.xml.sax.SAXParse
```

To prevent this issue, remove the SwaOutputInterceptor Apache CXF proxy class. However, with this fix, you cannot use Five9 methods that uses the

swaRef types.

Web Services Platform

Your client sends Web service requests that are acknowledged by Five9 with a Web services response. Your client needs to check periodically for the status and outcome of the operations requested. The Web services API contains the XML-encoded SOAP methods used to communicate with your client application.

Five9 recommends that you use the latest version. Previous versions are still supported but are not recommended because they do not contain all the features. `Five9username` is the user name of the administrator:

Note:

In the rest of this guide, the features that apply to these versions are highlighted. Release 13 supports SOAP web services but adds no new features.

Use the appropriate data center for your location:

US: `api.five9.com`

UK: `api.five9.eu`

Canada: `api.five9.ca`

Frankfurt: `api.eu.five9.com`

- **Version 13:** `https://api.five9.com/wsadmin/v13/AdminWebService?wsdl&user=<Five9username>`
- **Version 12:** `https://api.five9.com/wsadmin/v12/AdminWebService?wsdl&user=<Five9username>`
- **Version 11:** `https://api.five9.com/wsadmin/v11/AdminWebService?wsdl&user=<Five9username>`
- **Version 10.2:** `https://api.five9.com/wsadmin/v10_2/AdminWebService?wsdl&user=<Five9username>`

- **Version 10:** `https://api.five9.com/wsadmin/v10/AdminWebService?wsdl&user=<Five9username>`
- **Version 9.5:** `https://api.five9.com/wsadmin/v9_5/AdminWebService?wsdl&user=<Five9username>`
- **Version 9.3:** `https://api.five9.com/wsadmin/v9_3/AdminWebService?wsdl&user=<Five9username>`
- **Version 4:** `https://api.five9.com/wsadmin/v4/AdminWebService?wsdl&user=<Five9username>`
- **Version 3:** `https://api.five9.com/wsadmin/v3/AdminWebService?wsdl&user=<Five9username>`
- **Version 2:** `https://api.five9.com/wsadmin/v2/AdminWebService?wsdl&user=<Five9username>`
- **Default version (common to all versions):** `https://api.five9.com/wsadmin/AdminWebService?wsdl&user=<Five9username>`

To ensure that connections are secure, send all requests by Transport Layer Security protocol (HTTPS) or VPN (IPSec or SSH) to the URL for your version, for example:

```
https://api.five9.com/
wsadmin[/<version>]/AdminWebService
```

Differences Among Versions 4, 3, 2, and Default

The differences between API versions 4, 3, 2, and the default are listed in this table.

	Version 4	Version 3	Version 2	Default
Data Types				
<code>adminPermissionType</code>	Added	Added		

	Version 4	Version 3	Version 2	Default
e				
apiOperationType (VIVRCreat eSession Version 3)		Added		
basicImportResult (importTrou bles , keyFields Version 3)		Added		
basicImportSetting s (countryCo de , failOnFie ldParseErr or)	Added	Added		
campaignS trategies	New			
campaignS trategy	New			
campaignS trategyFil	New			

	Version 4	Version 3	Version 2	Default
<code>ter</code>				
<code>campaignStrategyPeriod</code>	New			
<code>contactFieldRestriction(isEnabled)</code>		Deleted	Added	
<code>importTrouble</code>		New		
<code>importTroubleKind</code>		New		
<code>listDialingMode(chatEnabled, visualModeEnabled)</code>		Added		
<code>listDialingMode(EXTENDED_STRATEGY)</code>	Added			

	Version 4	Version 3	Version 2	Default
<code>listUpdateSimpleSettings (countryCode)</code>	Added	New		
<code>passwordPolicies (entryValues)</code>		Modified	Added	Modified
<code>passwordPolicyEntries</code>		Removed	Added	Removed
<code>passwordPolicyEntryValue</code>		Removed	Added	Removed
<code>supervisorPermissionType (CanViewTextDetailsTab</code> Version 3 <code>, CanAccessShowFields</code>		Added		

	Version 4	Version 3	Version 2	Default
Version 3				
Methods				
<code>addRecordToSimpleList</code>		New		
<code>createContactField</code>		Modified	Modified	Modified
<code>getCampaignStrategies</code>	New			
<code>getContactFields</code>		Modified	Modified	Modified
<code>modifyContactField</code>		Modified	Modified	Modified
<code>setCampaignStrategies</code>	New			
<code>setDefaultIVRSchedule</code>		Added		

	Version 4	Version 3	Version 2	Default
<pre>(isVisualM odeEnabled Version 3 Version 3 , isChatEna bled)</pre>				
Exceptions				
<pre>AddRecord ToListFaul t</pre>		New		
<pre>CommonCam paignFaul t Version 3</pre>		New		
<pre>WrongList DialingMod eFault</pre>	New			

Basic Access Authentication

Your HTTPS requests must provide valid Five9 credentials for basic access authentication, which is used by the Web services API to enforce access control.

The credentials included in the header should be those of an administrator.

Five9 recommends that you create several administrator users reserved for the Web Services if you plan to send multiple concurrent requests. Otherwise, if you try to use the same user name and password for multiple concurrent requests, your requests are denied, and you receive an exception. The administrator user must have the VCC Administrator role. Be sure to set the appropriate permissions for each administrator.

With HTTP basic authentication, the user name and password are encoded in base 64. In your client, construct your authorization header as follows:

1. Concatenate the user name and password, for example:

```
ExampleUsername:ExamplePassword
```

2. Encode the string in base 64, for example:

```
RXhhbXBsZVVzZXJOYW1lOkV4YW1wbGVQYXNzd29yZA==
```

3. In your client, include the `Authorization` header with the value `Basic <base64-encoded string>`.

Example:

Web services header with encoded user name and password.

Copy

```
POST https://api.five9.com/wsadmin/AdminWebService HTTP/1.1
Accept-Encoding: gzip, deflate
Content-Type: text/xml; charset=UTF-8
SOAPAction: ""
Authorization: Basic RXhhbXBsZVVzZXJOYW1lOkV4YW1wbGVQYXNzd29yZA==
```