Scoring Workbook and Calculator Validation Guide

v1.1 (production documentation release in package v3.22) | Scorekeepers, workbook maintainer and calculator validator

PRODUCTION DOCUMENTATION RELEASE (v3.22) — USER-DIRECTED GATE WAIVER; TECHNICAL TESTS REMAIN UNVERIFIED

Defines how to accept individual performance inputs, calculate the match outcome under the published scoring method, interpret participant-level dblns outputs, and produce repeatable validation evidence. It is a procedure and target specification, not proof that the unavailable canonical workbook implements it.

Prepared 29 October 2026 • Policy version v3.15

1. Authority and safety boundary

⚓ **Quick hint:** Make changes only through the stated authority and change process; preserve the prior decision trail.

Documentation release disposition — RELEASED UNDER USER-DIRECTED GATE WAIVER. The designated workbook test27xlsm_detailed_audit_polished_regression.xlsm was not available in the accessible files. The accessible test27xlsm.xlsm and its formula-repaired copy are historical evidence only. Formula parity and desktop Excel behavior remain unverified; this guide is a procedural reference, not a score certification.

Never overwrite the source evidence to make an output match. Keep original workbook, test copy, raw input fixture, accepted output, and formula-repair experiments separate.

2. Approved purpose of outputs

⚓ **Quick hint:** Check the stated authority, required evidence, and completion criteria before acting; do not infer an approval that is not recorded.

Record	Meaning	Must not be confused with
Match result	Verified outcome for a specific recurring match, calculated from individual performance across the applicable published metrics (including	Individual Damage/Kills/dblns or a calculator display.

	Damage and Kills) under the approved scoring method; published forfeit/void rules apply where performance scoring does not.	
Individual dblns	A participant-level calculated performance output from the validated scoring system. Its contribution to the match outcome is governed by the approved formula; preserve it for audit, and use it for an additional award or seeding purpose only when the format settings expressly authorize that use.	A standalone substitute for the full match-outcome calculation, unless that formula expressly specifies it.
Overview averages	Descriptive aggregate fields, not substitutes for the approved performance-based match-outcome calculation.	Score, prize guarantee or bracket outcome.
H12 dollar estimate	Historical display based on 0.54 × dblns / 100.	Cash, official store price, prize valuation or obligation.

3. Selected scoring policies

⚓ **Quick hint:** Use the designated source of truth; compare identical inputs and formulas, and do not certify untested parity.

C01 — Round 3 Race: store positive elapsed seconds; the target per-game metric is 1 / elapsed_seconds. Lower elapsed time therefore produces a larger metric. Blank, nonnumeric, zero, negative, and non-finite times block score certification until corrected. Historical formula behavior contradicts this target.

C02 — Class mapping: use DD = 4, CA = 3, BB = 2 in both implementations. Unknown/blank classes are invalid—not weight zero. The implementation must derive the coefficient from the class code or enforce paired label/weight validation.

C03 — S10:S12 class-preference controls: retire/hide them from participant-facing scoring controls because the historical score formulas do not use them. Do not alter old sample cells to simulate an effect.

C04 — Round 4 pool: retire/hide the visible pool control because the historical formula does not reference it. Do not claim Round 4 score or payout changes when it is moved.

C05 — Dollar estimate: OFF by default in participant-facing views. Keep H12 only as an internal historical diagnostic because 0.54 × dblns / 100 has no verified conversion basis. Any later public display requires a verified basis, separate organizer approval, and the exact label: “Illustrative estimate only—not cash value, official store price/conversion, award valuation, or prize obligation.”

C06 — After event start: ordinary changes apply to future/unplayed games only. Never retroactively change completed results. Emergency safety/security/platform actions require a written, timestamped, scoped and reviewed record; data corrections preserve old and new values.

4. Archived equation shape (reference only)

⚓ **Quick hint:** Use the designated source of truth; compare identical inputs and formulas, and do not certify untested parity.

Rounds 1–3 archived shape: Score = 2 × OverallMultiplier × Pool × Σgames[ClassWeight × (PlayerMetric ÷ AllPlayersMetricTotal) ÷ Tier^TierPower]. Target PlayerMetric: Damage for Round 1; Kills for Round 2; 1 / elapsed_seconds for Round 3. The formula shape is not proof of canonical implementation or a guarantee that weighted totals sum to the displayed pool.

Round 4 historical shape: Score = OverallMultiplier ÷ 3 × Σgames[ClassWeight × DamageShare × (100/Tier × TierWeight + Damage/(Tier × 1,000) × DamageWeight + Kills × 10/Tier × KillsWeight + 5,000/Time × TimeWeight)]. DamageShare is player Round-4 damage divided by all players' Round-4 damage. The visible Round-4 pool control is not part of this archived expression. Verify against the designated workbook before certification.

Formula caution — The historical sample has missing formulas in per-player totals and summary cells. A separate repaired copy is not the designated workbook and was not tested in desktop Excel here. Use the equations above as a target/review reference only, not as a declaration of the live spreadsheet's behavior.

5. Mandatory regression matrix

⚓ **Quick hint:** Use the designated source of truth; compare identical inputs and formulas, and do not certify untested parity.

Area	Case(s)	Pass criterion
Round 1	Double one player's Damage while holding others fixed; verify numerator and shared denominator.	Exact formula outputs match canonical workbook and calculator within predeclared numeric tolerance.
Round 2	Change kills; test zero total kills and invalid/blank input.	Valid inputs calculate consistently; invalid/zero-denominator case is handled explicitly, not silently.
Round 3 / C01	Compare time 70 vs 140; also blank, text, 0, negative, and non-finite.	With other inputs fixed, 70 seconds gives higher metric than 140; invalid values block certification.
Class / C02	DD→CA→BB; blank, unknown, whitespace, case variants, and changing label without weight.	DD=4, CA=3, BB=2 in both systems; invalid class blocks score; label and numeric weight cannot diverge.
C03 / C04	Change legacy S10:S12 and Round-4 pool F8.	Retired controls hidden/inert; no UI advertises an unimplemented scoring effect.
Round 4	Change each term separately; zero total DamageShare; invalid Time; alter Damage and denominator.	Formula, error handling, aggregation and boundaries match the validated spec.
Totals / H12	All participant rows; missing-row fixtures; seed display; dollar label.	No stale formulas; values recompute; H12 label clearly says illustrative-only.
Defaults / interaction	First use, each 0.1 step, individual reset,	Expected settings persist/reset correctly

	site reset, save/reload, legacy migration.	in actual browser.
Runtime	Desktop Excel and Office 2010 if still a required target.	VBA compiles, formulas recalculate on open/edit/save, no broken references, fixed tests pass.

6. Run sequence and evidence

⚓ **Quick hint:** Preserve the original evidence and distinguish an observed fact from an OCR, bot, or calculator interpretation.

1. Obtain the exact designated workbook. Record filename, version, file size, and SHA-256; ensure it is the one named in the approved settings record.
2. Preserve a read-only copy. Create a separate test copy and never modify the source as part of testing.
3. Run the untouched default fixture, then one-variable mutations and invalid-input boundaries. Record exact input cells, expected result source, unrounded value, displayed value, formula, and tolerance.
4. Run workbook and calculator with identical accepted individual-performance inputs. Compare row outputs, round totals, participant-level dblns, aggregation, rounding, and H12. Verify that the match outcome is calculated from the approved metrics and formula, follows the published tie-break rules, and matches the saved official result record.
5. Open/compile/recalculate in the actual required Excel environment, including Office 2010 if it remains a target. Test save/reopen and UI/macro paths.
6. Archive raw fixtures, logs, version/hash, discrepancies, corrections and reviewer sign-off. A formula engine or browser result is not a substitute for the target-runtime test.

7. Current status

⚓ **Quick hint:** A polished document is not release approval; keep blockers visible until the required evidence exists.

Open / blocking — No certification is possible until the designated workbook is provided. Historical source tests showed missing formulas in Event1-Damage!AE17:AE23, Event2-Kills!AE16:AE23, Event3-Race!AE16:AE23, Event4-GrandYolo!AS18:AS23, Tourney Totals!H4:H11 and E5:E11. The repaired copy matched four controlled mutations in a formula engine but has not passed desktop Excel/Office 2010 acceptance.

8. Definition of done

⚓ **Quick hint:** Use the defined term consistently; if two documents differ, follow the explicitly named governing source.

Scoring gate passes when — The exact designated workbook is fingerprinted; all formula and invalid-input tests, C01–C05 behavior, resets and H12 tests pass; workbook and calculator match on the full suite; target Excel/VBA runtime succeeds; independent reviewer signs the evidence; and the approved event settings record names the accepted version.