


WAAS CH 93637 W12A	APP CRS 119°	Rwy Idg 3300 TDZE 813 Apt Elev 813
--	------------------------	---

RNAV (GPS) RWY 12

MEMPHIS MEML (Ø3D)

RNP APCH.	MISSED APPROACH: Climb to 4500 direct OPATE and hold, continue climb-in-hold to 4500.
<div><div>▼</div><div>NA</div></div> Rwy 12 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA. Use Kirksville altimeter setting.	

IRK ASOS 121.125	KANSAS CITY CENTER 126.225 317.775	CTAF 122.90
----------------------------	--	-----------------------



5 NM Holding Pattern		IDIXE		MEPME		RW12	
6000 ← 299°		4500 → 119°		2600		3300 X 60	
GP 3.00°		TCH 40		6.2 NM		5.5 NM	
CATEGORY	A	B	C	D			
LPV DA	1144-1 331 (400-1)			NA			
LNAV/VNAV DA	1144-1 331 (400-1)			NA			
LNAV MDA	1360-1	547 (600-1)	1360-1⅜ 547 (600-1⅜)	NA			
CIRCLING	1360-1	547 (600-1)	1500-2 687 (700-2)	NA			

ELEV 813

TDZE 813

4500

OPATE

119° to RWY 12

3300 X 60

MIRL Rwy 12-30