

WAAS CH 62834 W09A	APP CRS 092°	Rwy Idg TDZE Apt Elev	5000 856 861
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 9

FRANKFORT CLINTON COUNTY RGNL (F'KR)


▼

NA

Baro-VNAV NA when using Indianapolis Exec altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Indianapolis Exec altimeter setting. When local altimeter setting not received, use Indianapolis Exec altimeter setting: increase LPV DA to 1162 feet and visibility 1⁄8 SM all Cats; increase LNAV/VNAV DA to 1245 feet and visibility 1⁄8 SM all Cats; increase all MDAs 60 feet and LNAV and Circling Cats C/D visibilities 1⁄4 SM.

MISSED APPROACH:
Climb to 2500 direct
CAXEV and hold.

AWOS-3 124.325	GRISCOM APP CON ★ 123.85 291.675	UNICOM 123.0 (CTAF) 0
--------------------------	--	---------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).

4 NM Holding Pattern

2500

GP 3.00° TCH 40

HULOL

OSWAB

ZITUD

2500

2500

2500

7 NM

2.5 NM

1.4

1.1

CAXEV

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	1106-7⁄8 250 (300-7⁄8)			
LNAV/VNAV DA	1189-1 333 (400-1)			
LNAV MDA	1260-1 404 (400-1)	1260-1 1⁄8 404 (400-1 1⁄8)		
CIRCLING	1460-1 599 (600-1)	1520-1 3⁄4 659 (700-1 3⁄4)	1520-2 659 (700-2)	

MIRL Rwy 4-22 and 9-27 0

REIL Rwy 9 and 27 0