

WAAS CH 63026 W25A	APP CRS 251°	Rwy Idg TDZE 86 Apt Elev 86	4001
--	------------------------	---	-------------



RNAV (GPS) RWY 25
HERLONG RECREATIONAL (HE'G)


Baro-VNAV NA when using Cecil altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

NA When local altimeter setting not received, use Cecil altimeter setting: increase all DA 13 feet and all MDA 20 feet; increase LNAV Cat C and D visibility 1/8 mile. Procedure NA at night for Cat C/D aircraft. Night landing: Rwy 7, 11, 29 NA. Helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH: Climb to 2000 direct WODKU and on track 304° to REDIE and hold.

AWOS-3 119.275	JACKSONVILLE APP CON 127.775 377.075	GCO 121.725	UNICOM 123.0 (CTAF) 0
--------------------------	--	-----------------------	---------------------------------



2000	WODKU	tr 304°	REDIE		
*LNAV only.					
					
CATEGORY	A		B	C	D
LPV DA	378-1 292 (300-1)				
LNAV/VNAV DA	612-1½ 526 (600-1½)				
LNAV MDA	600-1 514 (600-1)		600-1½ 514 (600-1½)		
CIRCLING	600-1 514 (600-1)		980-2¾ 894 (900-2¾)		980-3 894 (900-3)

SE-3, 13 JUL 2023 to 10 AUG 2023

SE-3, 13 JUL 2023 to 10 AUG 2023