

WAAS CH <b>45508</b> <b>W36A</b>	APP CRS <b>002°</b>	Rwy Idg TDZE Apt Elev	<b>8000</b> <b>401</b> <b>407</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 36

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Evansville altimeter setting. When local altimeter setting not received, use Evansville altimeter setting: increase LPV DA to 656 feet; increase LNAV/VNAV DA to 720 feet and all Cats visibility 1/8 mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cats C/D visibility 1/4 mile.

MALSR

MISSED APPROACH:

Climb to 3000 direct HUMAD and hold.

AWOS-3PT <b>119.025</b>	EVANSVILLE APP CON ★ <b>124.025 290.9</b>	OWENSBORO TOWER ★ <b>120.7 (CTAF) 0 251.15</b>	GND CON <b>121.7</b>	UNICOM <b>122.95</b>
----------------------------	--	---	-------------------------	-------------------------

MISSED APCH FIX

4 NM Holding Pattern

ECOCO

COPOM

XIXIH 2.5 NM to RW36

\* 1 NM to RW36

RW36

GP 3.00° TCH 56

3000

182°

002°

002°

2100

\* 1240

6.1 NM

2.7 NM

1.5 NM

1 NM

3000

HUMAD

\* LNAV only.

CATEGORY	A	B	C	D
LPV DA	601-1/2 200 (200-1/2)			
LNAV/VNAV DA	665-1/2 264 (300-1/2)			
LNAV MDA	780-1/2 379 (400-1/2)	780-5/8 379 (400-5/8)		
CIRCLING	860-1 453 (500-1)	1120-1 713 (800-1)	1140-2 733 (800-2)	1140-2 1/4 733 (800-2 1/4)

ELEV 407

D

TDZE 401

MIRL Rwy 6-24

HIRL Rwy 18-36

REIL Rws 6, 18, and 24

OWENSBORO, KENTUCKY

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

Amdt 4B 25MAR21

37°44'N-87°10'W

RNAV (GPS) RWY 36