

WAAS
CH **57927**
W12A

APP CRS
118°

Rwy Idg
TDZE **2609**
Apt Elev **2615**

RNAV (GPS) RWY 12
ROY HURD MEML (E01)

▼

DME/DME RNP-0.30 NA. Obtain local altimeter setting on CTAF; when not received, use Wink altimeter setting. Night landing: Rwy 12 NA. Helicopter visibility reduction below 1 SM NA.

▲

NA

MISSED APPROACH: Climb to 3200 then climbing left turn to 6000 direct INK VORTAC and hold.

FORT WORTH CENTER
133.1 298.95

UNICOM
122.8 (CTAF) 0

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 24).

3200

6000

INK

5000

4000

118°

3.00° TCH 45

RW12

6.4 NM

4.2 NM

61

4268 X 75

2922 X 75

30

CATEGORY	A	B	C	D
LP MDA	3100-1	491 (500-1)	3100-1 $\frac{3}{8}$ 491 (500-1 $\frac{3}{8}$)	NA
LNAV MDA	3120-1	511 (600-1)	3120-1 $\frac{3}{8}$ 511 (600-1 $\frac{3}{8}$)	NA
CIRCLING	3280-1	665 (700-1)	3280-1 $\frac{3}{4}$ 665 (700-1 $\frac{3}{4}$)	NA
WINK ALTIMETER SETTING MINIMUMS				
LP MDA	3180-1	571 (600-1)	3180-1 $\frac{5}{8}$ 571 (600-1 $\frac{5}{8}$)	NA
LNAV MDA	3200-1	591 (600-1)	3200-1 $\frac{3}{4}$ 591 (600-1 $\frac{3}{4}$)	NA
CIRCLING	3360-1	745 (800-1)	3360-2 $\frac{1}{4}$ 745 (800-2 $\frac{1}{4}$)	NA

MIRL Rwy 1-19 and 12-30 0

MONAHANS, TEXAS

Orig-A 02APR15

31°35' N-102°55' W

ROY HURD MEML (E01)

RNAV (GPS) RWY 12