

WAAS
CH **82221**
W26A

APP CRS
259°

Rwy Idg
TDZE **564**

Apt Elev **564**

RNAV (GPS) RWY 26

HOPKINSVILLE-CHRISTIAN COUNTY (HVC)

RNP APCH - GPS.

▼

▲NA

Circling Rwy 8 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using Clarksville altimeter setting. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Clarksville altimeter setting and increase LPV DA to 851 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1033 feet and all visibilities ⅓ SM; increase all MDAs 40 feet and Circling visibility Cat C ¼ SM.

MISSED APPROACH:
Climb to 1100 then climbing right turn to 3000 direct WASMO and hold.

AWOS-3 132.575	CAMPBELL APP CON 118.1 269.525	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

The chart displays the RNAV (GPS) RWY 26 approach. Key features include:

- Waypoints:** WASMO (4.00 NM), ZITVI (2.2 NM to RW26), YAYUP (FAF), and UYURI (IF/IAF).
- Altitudes:** 1249, 1056, 883, 776, 668, 779, 817, 950, 1268, 2500, 259°.
- Navigation Aids:** GNSHP, ZITVI, YAYUP, UYURI.
- Obstacles:** 1249, 1056, 883, 776, 668, 779, 817, 950, 1268.
- MSA:** MSA RW26 25 NM, 2700.
- Chart Scale:** 1:100,000.

ELEV 564 TDZE 564

1100

3000

WASMO

VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 34).

*LNAV only

YAYUP

UYURI

2500

259°

079°

2500

GP 3.00° TCH 40

1 NM

1.2 NM

3.8 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	814-¾		250 (300-¾)	
LNAV/VNAV DA	996-1¼		432 (500-1¼)	
LNAV MDA	1040-1 476 (500-1)		1040-1¾ 476 (500-1¾)	
CIRCLING	1140-1 576 (600-1)		1280-2 716 (800-2) 1320-2½ 756 (800-2½)	

MIRL Rwy 8-26

REIL Rws 8 and 26

HOPKINSVILLE, KENTUCKY

Amdt 2A 08SEP22

HOPKINSVILLE-CHRISTIAN COUNTY (HVC)

36°51'N-87°27'W

RNAV (GPS) RWY 26