



WAAS CH 78144	APP CRS 053°	Rwy Idg TDZE 716	7543
W05A		Apt Elev	716

RNAV (GPS) RWY 5

WILLOW RUN (YIP)

RNP APCH - GPS.	MALSR	MISSED APPROACH: Climb to 1200 then climbing left turn to 3000 direct SVM VORTAC and hold.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000, LNAV Cats C/D visibility to 1½ SM.		

ATIS 127.425	DETROIT APP CON 118.95 284.0	WILLOW RUN TOWER 125.275 256.9	GND CON 119.975
------------------------	--	--	---------------------------



4 NM Holding Pattern	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).	1200	3000	SVM
ICADE	TABUY	1200	3000	SVM
6000	3000	1200	3000	SVM
GP 3.00°	TCH 59	1200	3000	SVM
8 NM	3.9 NM	1.2 NM	1.2 NM	1.2 NM
CATEGORY	A	B	C	D
LPV DA	916/18	200 (200-½)		
LNAV/VNAV DA	1121/40	405 (500-¾)		
LNAV MDA	1200/24	484 (500-½)	1200/50	484 (500-1)
CIRCLING	1220-1	504 (600-1)	1220-1½	1400-2¼
		504 (600-½)	684 (700-2¼)	